



DPC: 18/30369338 DC

BSI Group Headquarters

389 Chiswick High Road London W4 4AL

Tel: +44 (0)20 8996 9000

Fax: +44 (0)20 8996 7400

www.bsigroup.com

Date: 05 June 2018

Origin: International

Latest date for receipt of comments: 27 June 2018

Project No. 2017/03609

Responsible committee: CPL/61/7 Safety of electrical appliances - Heated appliance group

Interested committees:

Title: Draft BS IEC 60335-2-96 Household and similar electrical appliances - Safety. Part 2-96: Particular requirements for flexible sheet heating elements for room heating.

Please notify the secretary if you are aware of any keywords that might assist in classifying or identifying the standard or if the content of this standard

- i) has any issues related to 3rd party IPR, patent or copyright
- ii) affects other national standard(s)
- iii) requires additional national guidance or information

WARNING: THIS IS A DRAFT AND MUST NOT BE REGARDED OR USED AS A BRITISH STANDARD. THIS DRAFT IS NOT CURRENT BEYOND 27 June 2018

This draft is issued to allow comments from interested parties; all comments will be given consideration prior to publication. No acknowledgement will normally be sent. **See overleaf for information on the submission of comments.**

No copying is allowed, in any form, without prior written permission from BSI except as permitted under the Copyright, Designs and Patent Act 1988 or for circulation within a nominating organization for briefing purposes. Electronic circulation is limited to dissemination by e-mail within such an organization by committee members.

Further copies of this draft may be purchased from BSI Shop <http://shop.bsigroup.com> or from BSI Customer Services, Tel: +44(0) 20 8996 9001 or email cservices@bsigroup.com. British, International and foreign standards are also available from BSI Customer Services.

Information on the co-operating organizations represented on the committees referenced above may be obtained from <https://standardsdevelopment.bsigroup.com/>.

Responsible Committee Secretary: Mrs Geraldine D Salt (BSI)
Direct tel: 020 8996 7273
E-mail: geraldine.salt@bsigroup.com

Full document details: 18/30369338 DC

Introduction

This draft standard is based on national and international discussions. Your comments on this draft are invited and will assist in the preparation of the consequent standard.

For international standards, comments will be reviewed by the relevant UK national committee before sending the consensus UK vote and comments to the international committee, which will then decide appropriate action. If the international standard is approved, it is usual for the text to be published as a British Standard.

For national standards, comments will be reviewed by the relevant UK national committee and the resulting standards published as a British Standard.

UK Vote

Please indicate whether you consider the UK should submit a negative (with supporting technical reasons) or positive vote on this draft. Please indicate if you are aware of any reason why this draft standard should not be published as a British Standard.

Submission of Comments

- **Annotated drafts are not acceptable and will be rejected.**
- All comments should be submitted online at <https://standardsdevelopment.bsigroup.com/>. You will need to register in order to comment.

Template for comments and secretariat observations

Date: xx/xx/20xx	Document: ISO/DIS xxxx
------------------	------------------------

1	2	(3)	4	5	(6)	7
MB	Clause No./ Subclause No./Annex (e.g. 3.1)	Paragraph/Figure/ Table/Note	Type of comment	Commend (justification for change) by the MB	Proposed change by the MB	Secretariat observations on each comment submitted
	3.1	Definition 1	ed	Definition is ambiguous and needs clarifying.	Amend to read '...so that the mains connector to which no connection...'	
	6.4	Paragraph 2	te	The use of the UV photometer as an alternative cannot be supported as serious problems have been encountered in its use in the UK.	Delete reference to UV photometer.	



61/5573/CDV

COMMITTEE DRAFT FOR VOTE (CDV)

PROJECT NUMBER:

IEC 60335-2-96 ED2

DATE OF CIRCULATION:

2017-12-22

CLOSING DATE FOR VOTING:

2018-03-16

SUPERSEDES DOCUMENTS:

61/5558/RR

IEC TC 61 : SAFETY OF HOUSEHOLD AND SIMILAR ELECTRICAL APPLIANCES

SECRETARIAT:

United States of America

SECRETARY:

Ms Randi Myers

OF INTEREST TO THE FOLLOWING COMMITTEES:

PROPOSED HORIZONTAL STANDARD:



Other TC/SCs are requested to indicate their interest, if any, in this CDV to the secretary.

FUNCTIONS CONCERNED:

☐ EMC

☐ ENVIRONMENT

☐ QUALITY ASSURANCE

☒ SAFETY

☐ SUBMITTED FOR CENELEC PARALLEL VOTING

☒ NOT SUBMITTED FOR CENELEC PARALLEL VOTING

This document is still under study and subject to change. It should not be used for reference purposes.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

TITLE:

Household and similar electrical appliances - Safety - Part 2-96: Particular requirements for flexible sheet heating elements for room heating

NOTE FROM TC/SC OFFICERS:

This document is circulated according to the decisions taken at the meeting of TC 61 in Vladivostok.

Refer to 61/5476/DC and 61/5528/INF and item 25a in Vladivostok

Refer to 61/5478/DC and 61/5530/INF and item 25b in Vladivostok

Copyright © 2017 International Electrotechnical Commission, IEC. All rights reserved. It is permitted to download this electronic file, to make a copy and to print out the content for the sole purpose of preparing National Committee positions. You may not copy or "mirror" the file or printed version of the document, or any part of it, for any other purpose without permission in writing from IEC.

CONTENTS

FOREWORD	4
INTRODUCTION	7
1 Scope	8
2 Normative references	8
3 Terms and definitions	9
4 General requirement	10
5 General conditions for the tests	10
6 Classification	11
7 Marking and instructions	11
8 Protection against access to live parts	15
9 Starting of motor-operated appliances	15
10 Power input and current	16
11 Heating	16
12 Void	19
13 Leakage current and electric strength at operating temperature	19
14 Transient overvoltages	20
15 Moisture resistance	20
16 Leakage current and electric strength	20
17 Overload protection of transformers and associated circuits	21
18 Endurance	21
19 Abnormal operation	23
20 Stability and mechanical hazards	24
21 Mechanical strength	24
22 Construction	25
23 Internal wiring	27
24 Components	27
25 Supply connection and external flexible cords	28
26 Terminals for external conductors	28
27 Provision for earthing	28
28 Screws and connections	28
29 Clearances, creepage distances and solid insulation	28
30 Resistance to heat and fire	29
31 Resistance to rusting	29
32 Radiation, toxicity and similar hazards	29
Annexes	43
Annex AA (informative) Summary of installation instructions	44
Bibliography	46

Figure 101 – Arrangement for testing heating units in timber ceilings	30
Figure 102 – Arrangement for testing modular heating units.....	31
Figure 103 – Arrangement for testing heating units in timber floors	32
Figure 104 – Arrangement for testing heating units below concrete	33
Figure 105 – Arrangement for testing heating units in timber floors and ceilings in combination 34	
Figure 106 – Jig for locating the contact needle	35
Figure 107 – Arrangement for testing heating units above timber floors.....	36
Figure 108 – Arrangement for testing heating units above concrete floors	37
Figure 109 – Arrangement for measuring capacitive currents	38
Figure 110 – Arrangement for testing heating units in timber walls	39
Figure 111 – Arrangement for testing heating units in both sides of timber wall applications	40
Figure 112 – Arrangement for testing heating units intended to be installed in a wall of concrete or similar material	41
Figure 113 – Arrangement for testing heating units against wall of concrete or similar material 42	
Table 101 – Temperature rise limits for surfaces	19

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**HOUSEHOLD AND SIMILAR ELECTRICAL APPLIANCES –
SAFETY –****Part 2-96: Particular requirements for flexible sheet heating elements
for room heating**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

1

2 International Standard IEC 60335-2-96 has been prepared by IEC technical committee 61:
3 Safety of household and similar electrical appliances.

4 This second edition cancels and replaces the first edition published in 2002 including its
5 Amendment 1 (2003) and its Amendment 2 (2008). It constitutes a technical revision.

6 This edition includes the following significant technical changes with respect to the first
7 edition:

8 – aligns the text with IEC 60335-1, Ed 5, and its Amendments 1 and 2;

9 – some notes have been converted to normative text or deleted (5.6, 7.12.1, 10.1, 11.2.103,
10 13.1, 13.2, 16.2, 16.3, 18.101, 18.102.5, 21.1, 22.103, 22.105)).

- the strength test for heating units incorporating insulated wires intended to be installed in floors has been modified a (21.103);
- specific requirements have been added for heating units installed in walls below a height of 1,2 m (6.2, 7.1, 7.12.1, 7.12.6, 7.101, 11.2, 19.2, 22.106, 24.102, Annex AA).

The text of this International Standard is based on the following documents:

FDIS	Report on voting
61/XX/FDIS	61/5381/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 60335 series, under the general title: *Household and similar electrical appliances – Safety*, can be found on the IEC website.

This part 2 is to be used in conjunction with the latest edition of IEC 60335-1 and its amendments. It was established on the basis of the fifth edition (2010) of that standard.

NOTE 1 When "Part 1" is mentioned in this standard, it refers to IEC 60335-1.

This part 2 supplements or modifies the corresponding clauses in IEC 60335-1, so as to convert that publication into the IEC standard: Safety requirements for tumble dryers.

When a particular subclause of Part 1 is not mentioned in this part 2, that subclause applies as far as is reasonable. When this standard states "addition", "modification" or "replacement", the relevant text in Part 1 is to be adapted accordingly.

NOTE 2 The following numbering system is used:

- subclauses, tables and figures that are numbered starting from 101 are additional to those in Part 1;
- unless notes are in a new subclause or involve notes in Part 1, they are numbered starting from 101, including those in a replaced clause or subclause;
- additional annexes are lettered AA, BB, etc.

NOTE 3 The following print types are used:

- requirements: in roman type;
- *test specifications: in italic type;*
- notes: in small roman type.

Words in **bold** in the text are defined in Clause 3. When a definition concerns an adjective, the adjective and the associated noun are also in bold.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

The National Committees are requested to note that for this document the stability date is 2022.

This text is included for the information of the National Committees and will be deleted at the publication stage.

NOTE 4 The attention of National Committees is drawn to the fact that equipment manufacturers and testing organizations may need a transitional period following publication of a new, amended or revised IEC publication in

which to make products in accordance with the new requirements and to equip themselves for conducting new or revised tests.

It is the recommendation of the committee that the content of this publication be adopted for implementation nationally not earlier than 12 months or later than 36 months from the date of publication.

The following additional differences exist in the countries indicated below.

- Clause 1: Flexible sheet heating elements that are cut on site are not allowed (France, Germany and Israel).
- 6.1: The installation is to be of class II construction (Germany).
- 6.1: Heating units are to be class II (Israel).
- 7.1: The intended installation is not to include walls (Canada and USA).
- 7.12.1 c): The instructions in timber floors shall state that the heating unit is to be covered with additional insulation, be supplied through an isolating transformer, or be class II (Sweden).
- 7.12.1 c): The instructions need not refer to residual current devices (USA).
- 7.12.101 a): The size of the terminals fitted to the grid may be smaller (Canada).
- Clause 18: The tests are different (USA).
- 22.102: The test is different (USA).
- 22.103: The test is different (USA).
- 25.3: Heating units are not allowed to incorporate supply cords (Canada and USA).

Note of the Secretary: National Committees are asked to reconfirm their in some countries notes. Unless they are reconfirmed, they will be deleted.

INTRODUCTION

It has been assumed in the drafting of this International Standard that the execution of its provisions is entrusted to appropriately qualified and experienced persons.

This standard recognizes the internationally accepted level of protection against hazards such as electrical, mechanical, thermal, fire and radiation of appliances when operated as in normal use taking into account the manufacturer's instructions. It also covers abnormal situations that can be expected in practice and takes into account the way in which electromagnetic phenomena can affect the safe operation of appliances.

This standard takes into account the requirements of IEC 60364 as far as possible so that there is compatibility with the wiring rules when the appliance is connected to the supply mains. However, national wiring rules may differ.

If an appliance within the scope of this standard also incorporates functions that are covered by another part 2 of IEC 60335, the relevant part 2 is applied to each function separately, as far as is reasonable. If applicable, the influence of one function on the other is taken into account.

When a part 2 standard does not include additional requirements to cover hazards dealt with in Part 1, Part 1 applies.

NOTE 1 This means that the technical committees responsible for the part 2 standards have determined that it is not necessary to specify particular requirements for the appliance in question over and above the general requirements.

This standard is a product family standard dealing with the safety of appliances and takes precedence over horizontal and generic standards covering the same subject.

NOTE 2 Horizontal and generic standards covering a hazard are not applicable since they have been taken into consideration when developing the general and particular requirements for the IEC 60335 series of standards. For example, in the case of temperature requirements for surfaces on many appliances, generic standards, such as ISO 13732-1 for hot surfaces, are not applicable in addition to Part 1 or part 2 standards.

An appliance that complies with the text of this standard will not necessarily be considered to comply with the safety principles of the standard if, when examined and tested, it is found to have other features which impair the level of safety covered by these requirements.

An appliance employing materials or having forms of construction differing from those detailed in the requirements of this standard may be examined and tested according to the intent of the requirements and, if found to be substantially equivalent, may be considered to comply with the standard.

HOUSEHOLD AND SIMILAR ELECTRICAL APPLIANCES – SAFETY –

Part 2-96: Particular requirements for flexible sheet heating elements for room heating

1 Scope

This clause of Part 1 is replaced by the following.

This International Standard deals with the safety of **flexible sheet heating elements** intended to be incorporated into the building to heat the room in which they are located, their **rated voltage** being not more than 250 V for single-phase installations and 480 V for other installations.

Flexible sheet heating elements are converted into **heating units** that are incorporated in the building in accordance with the instructions after which the required level of protection against hazards is achieved.

NOTE 101 Attention is drawn to the fact that

- in many countries different wiring rules apply;
- for **heating units** intended to be used in vehicles or on board ships or aircraft, additional requirements may be necessary;
- in many countries additional requirements are specified by the national authorities for fire protection, the national authorities for building regulations, the national health authorities, the national authorities responsible for the protection of labour and similar authorities.

NOTE 102 This standard does not apply to

- **heating units** intended exclusively for industrial purposes;
- **heating units** intended to be used in locations where special conditions prevail, such as the presence of a corrosive or explosive atmosphere (dust, vapour or gas);
- blankets, pads and similar flexible heating appliances (IEC 60335-2-17);
- heated mats and foot warmers (IEC 60335-2-81);
- heated carpets and for heating units for room heating installed under removable floor coverings (IEC 60335-2-6 106);
- **flexible sheet heating elements** incorporated in other appliances.

2 Normative references

This clause of Part 1 is applicable except as follows.

Addition:

IEC 60364-7-701, *Electrical installations of buildings – Part 7: Requirements for special installations or locations – Section 701: Electrical installations in bathrooms*

IEC 60884-1:2002, *Plugs and socket-outlets for household and similar purposes – Part 1: General requirement*
AMD 1:2006
AMD 2:2013¹

ISO 3864-1, *Graphical symbols – Safety colours and safety signs – Part 1: Design principles for safety signs in workplaces and public areas*

¹ There exists a consolidated edition 3.2 (2013) that includes edition 3 and its Amendment 1 and its Amendment 2

3 Terms and definitions

This clause of Part 1 is applicable except as follows.

3.1 Definitions relating to physical characteristics

Replacement:

3.1.9

normal operation

operation of the **heating unit** after incorporation into the building in accordance with the instructions.

Flexible sheet heating elements, the current of which can vary depending on the length of the **flexible sheet heating elements** and those that can supply other **flexible sheet heating elements** are loaded so that the current marked on the **flexible sheet heating elements** flows through the **heating unit**.

Heating units for **storage heating applications** are charged for 75 % of the **rated charging period**.

Addition:

3.1.101

rated charging period

longest uninterrupted charging period assigned to the **heating unit** by the manufacturer

3.2 Definitions relating to means of connection

Replacement:

3.2.7

supply leads

set of wires intended for connecting the appliance to fixed wiring

3.5 Definitions relating to types of appliances

Addition:

3.5.4 Addition:

Heating units are considered to be **fixed appliances**.

3.5.101

flexible sheet heating element

heating element consisting of sheets of electrical insulation laminated with electrical resistance material, or a base material on which electrically insulated heating wires are fixed

Note 1 to entry: This definition does not preclude other methods of combining the insulation and resistance materials.

3.5.102

heating unit

flexible sheet heating element equipped with means of connection to the supply and with insulation surrounding **live parts**

Note 1 to entry: The **heating unit** can be partly or completely prefabricated.

3.5.103

modular heating unit

prefabricated assembly consisting of a **heating unit** and other materials to form a rigid construction for mounting on a ceiling

3.5.104

storage heating application

use of **heating units** to heat thermal accumulating material

Note 1 to entry: The heat is discharged naturally, the heat output being varied by adjusting the energy input.

3.6 Definitions relating to parts of an appliance

Addition:

3.6.101

electrode

conductive part incorporated in a **flexible sheet heating element** for supplying the heating material

4 General requirement

This clause of Part 1 is applicable.

5 General conditions for the tests

This clause of Part 1 is applicable except as follows.

5.2 Replacement:

In general, eight samples are required for the tests.

The tests of 13.3 and of Clauses 15 and 16 are carried out on one sample.

The tests of 18.101 and of Clause 30 are carried out on one sample.

The test of 21.102 is carried out on two samples. One of these samples is also used for the test of 22.101.

The test of 22.103 is carried out on one sample.

The remaining tests are carried out on the sixth sample. The other two samples are required for incorporating into the test arrangement to create the necessary thermal environment.

NOTE 101 Additional samples may be necessary if tests have to be repeated.

Nine samples of **modular heating units** are necessary for the tests of 11.2.102.

Additional samples are necessary if the tests of 18.102 are carried out.

Additional samples may be necessary for testing different sizes of **heating units**.

The test of 22.105 is carried out on the same sample as that used for the test of 13.2.

*Two samples of the additional layer of material, of sufficient size to cover the **heating unit**, are required if the test of 21.104 is carried out.*

5.3 Addition:

The test of 22.105 is carried out after the test of 13.2.

5.6 Addition:

Thermostats sensitive to room air temperature or outdoor air temperature are short circuited. However, the **thermostat** is not short circuited if it can be set so that it does not cycle.

5.10 Addition:

*However, for **flexible sheet heating elements** that are cut on site, the tests are carried out after connecting the **supply leads** and protecting the edges in accordance with the instructions.*

5.101 Heating units intended to be installed in walls above a height of 2,3 m are subjected to the tests for installation in ceilings.

6 Classification

This clause of Part 1 is applicable except as follows.

6.1 Addition:

Heating units need not be classified. However, if a **heating unit** is classified, the relevant requirements apply.

6.2 Addition:

Heating units for installation in concrete or similar material shall be at least IPX7.

Other **heating units** shall be at least IPX1.

7 Marking and instructions

This clause of Part 1 is applicable except as follows.

7.1 Modification:

Instead of the marking of **rated power input** or **rated current** the following applies:

- **heating units** shall be marked with their **rated power input**;
- **flexible sheet heating elements** without connection between adjacent elements shall be individually marked with their **rated power input**;
- other **flexible sheet heating elements** shall be marked with their **rated power input** per metre length.

Flexible sheet heating elements shall be marked with their maximum current if

- the current can vary depending on the length of the **flexible sheet heating element**;
- other **flexible sheet heating elements** can be supplied through them.

Addition:

Flexible sheet heating elements shall be marked with

- the indication of orientation, unless **heating units** are symmetrical;
- the intended installation (ceilings, walls between 0,2m and 1,2m and/or above 2,3m, or floors);
- the heating mode (direct heating or storage heating), unless intended for both modes.


If the **heating unit** is only intended for application in floors of concrete or similar materials, it shall be marked with the symbol for installation in concrete.

The marking shall be repeated at least once every 0,5 m of the **flexible sheet heating element** or on every section that can be cut to form a heating unit.

Flexible sheet heating elements that can be cut on site and have to be cut at specified places shall be marked appropriately.

Appliances with **detachable controls** shall be marked with the reference number or by other means of identification of the control

7.6 Addition:




Direct ceiling heating



Direct floor heating



Floor storage heating



Installation in concrete

273

274 These symbols are information signs and, except for the colours, the rules of ISO 3864-1
 275 apply.

276 7.12.1 Addition:

277 Instructions shall be provided. They shall include

278 a) explanation of the marking and symbols, if necessary;

279 b) information for incorporating the **heating units** into the building, in particular the following:

280 – precautions to be taken to avoid damage during installation, such as dropping sharp
 281 objects or stepping on the **heating unit**, or careless pouring of concrete;

282 – dimensions and distances to be taken into account;

283 – a statement that the **heating units** have to be separated from other heat sources such
 284 as luminaires and chimneys;

285 – description of the fixing areas of the **heating unit** and the separate screen, if
 286 applicable;

287 – guidance on how to avoid air gaps between the **flexible sheet heating element** and
 288 the screed of concrete floors;

289 – guidance on how to avoid damage to a **flexible sheet heating element** and its
 290 terminations in timber constructions due to relative movement after installation;

291 – the lowest ambient temperature at which **heating units** may be installed;

292 – the minimum radius for bending the **flexible sheet heating element**, if applicable;

293 – a statement that **heating units** shall not cross expansion joints of the building or
 294 structure;

295 – a statement to ensure that attachment of room fittings does not restrict heat emission
 296 from heated areas.

297 Except for **modular heating units**, the instructions shall include the following:

298 – precautions to be taken to avoid creasing the **flexible sheet heating element**;

299 – a statement that the **heating unit** is not to be installed on irregular surfaces;

300 – a description of the intended orientation and a statement that the heating unit is to be
 301 installed in this way (for heating units having non-symmetric construction);

302 c) a statement that the installation is to be in accordance with the national wiring rules. The
 303 substance of the following information shall be included:

304 – the **heating units** are to be supplied through a residual current device (RCD) having a
 305 rated residual operating current not exceeding 30 mA. The RCD shall not be of the
 306 time delayed type. Alternatively, except for installations in floors surrounding swimming
 307 pools or walls below a height of 2,3 m, they may be supplied through an isolating
 308 transformer. This statement is not required for **class III heating units** and for
 309 applications in

- timber floors provided that the instructions for installation state that there is to be an air gap between the **heating unit** and the floor;
 - timber ceilings;
 - floors of concrete or similar material in dry locations (dry locations are areas outside zone 3 as defined in IEC 60364-7-701) as long as the **basic insulation** and additional electrical insulation each withstand the electric strength test of 16.3 for **reinforced insulation**;
 - how to connect **heating units** to the supply, giving the cross-sectional area of the leads, if applicable;
 - how to interconnect the **heating units**, giving the cross-sectional area of the leads, if applicable;
 - **heating units** shall be installed to avoid increasing the ambient temperature of any existing electrical installation
 - d) the maximum current allowed to flow through one **heating unit** when other units are supplied through it or when the current can vary depending on its length;
 - e) list of controls, unless they are incorporated into the **heating unit**;
 - f) the maximum thermal resistance between the **heating unit** and the room;
 - g) the type of covering materials that are allowed to be used in conjunction with the **heating units** with a statement that the advice of the manufacturer is to be requested before materials other than those recommended are used; the thickness of covering materials, which for floors shall be at least 5 mm;
 - h) characteristics of the thermal insulation that is to be inserted between separate **heating units** installed to heat a floor and the ceiling below it;
 - i) characteristics of the thermal insulation that is to be inserted between separate **heating units** installed to heat both sides of a wall;
 - j) specification of any adhesive to be used;
 - k) a statement that a label is to be fixed adjacent to the distribution board and that it has to contain the locations of the **heating units**;
 - l) if the **heating units** are installed in a suspended ceiling, or are accessible from the roof space, a statement that a label giving this information is to be fixed to the access point of the ceiling.
 - m) in applications in timber floors, a statement indicating that heating units having basic insulation only shall be covered by additional electrical insulation or supplied through an isolating transformer.
- NOTE A summary of particular installation requirements for different applications is given in Annex AA.
- 7.12.101** The instructions for applications in floors of concrete or similar material or under tiles shall state that
- a) a grid is to be installed above the heating unit. The grid is to
 - be protected against corrosion but not electrically insulated;
 - be electrically and mechanically equivalent to a steel grid having a mesh not more than 50 mm x 50 mm and a wire diameter of 1 mm, unless the grid covers
 - class II heating units;
 - heating units installed with additional electrical insulation;
 - fully cover the heating unit including the fixing areas. It may cover several heating units;
 - be connected to earth;
 - be fitted with terminals suitable for the connection of two conductors each having a nominal cross-sectional area of 2,5 mm²;
 - be checked for electrical continuity during installation.