



DPC: 20/30416454 DC

BSI Group Headquarters

389 Chiswick High Road London W4 4AL

Tel: +44 (0)20 8996 9000

Fax: +44 (0)20 8996 7400

www.bsigroup.com

Date: 03 April 2020

Origin: International

Latest date for receipt of comments: 27 May 2020

Project No. 2020/00878

Responsible committee: CPL/59/6 Floor treatment appliances

Interested committees:

Title: Draft BS IEC/ASTM 62885-6 Surface cleaning appliances. Part 6: Wet hard floor cleaning appliances for household or similar use – Methods for measuring the performance.

Please notify the secretary if you are aware of any keywords that might assist in classifying or identifying the standard or if the content of this standard

- i) has any issues related to 3rd party IPR, patent or copyright
- ii) affects other national standard(s)
- iii) requires additional national guidance or information

WARNING: THIS IS A DRAFT AND MUST NOT BE REGARDED OR USED AS A BRITISH STANDARD. THIS DRAFT IS NOT CURRENT BEYOND 27 May 2020

This draft is issued to allow comments from interested parties; all comments will be given consideration prior to publication. No acknowledgement will normally be sent. **See overleaf for information on the submission of comments.**

No copying is allowed, in any form, without prior written permission from BSI except as permitted under the Copyright, Designs and Patent Act 1988 or for circulation within a nominating organization for briefing purposes. Electronic circulation is limited to dissemination by e-mail within such an organization by committee members.

Further copies of this draft may be purchased from BSI Shop <http://shop.bsigroup.com> or from BSI Customer Services, Tel: +44(0) 20 8996 9001 or email cservices@bsigroup.com. British, International and foreign standards are also available from BSI Customer Services.

Information on the co-operating organizations represented on the committees referenced above may be obtained from <https://standardsdevelopment.bsigroup.com/>.

Responsible Committee Secretary: Ms Nicola Young (BSI)

Direct tel:

E-mail: nicola.young@bsigroup.com

Full document details: 20/30416454 DC

Introduction

This draft standard is based on national and international discussions. Your comments on this draft are invited and will assist in the preparation of the consequent standard.

For international standards, comments will be reviewed by the relevant UK national committee before sending the consensus UK vote and comments to the international committee, which will then decide appropriate action. If the international standard is approved, it is usual for the text to be published as a British Standard.

For national standards, comments will be reviewed by the relevant UK national committee and the resulting standards published as a British Standard.

UK Vote

Please indicate whether you consider the UK should submit a negative (with supporting technical reasons) or positive vote on this draft. Please indicate if you are aware of any reason why this draft standard should not be published as a British Standard.

Submission of Comments

- **Annotated drafts are not acceptable and will be rejected.**
- All comments should be submitted online at <https://standardsdevelopment.bsigroup.com/>. You will need to register in order to comment.

Template for comments and secretariat observations

Date: xx/xx/20xx	Document: ISO/DIS xxxx
------------------	------------------------

1	2	(3)	4	5	(6)	7
MB	Clause No./ Subclause No./Annex (e.g. 3.1)	Paragraph/Figure/ Table/Note	Type of comment	Commend (justification for change) by the MB	Proposed change by the MB	Secretariat observations on each comment submitted
	3.1	Definition 1	ed	Definition is ambiguous and needs clarifying.	Amend to read '...so that the mains connector to which no connection...'	
	6.4	Paragraph 2	te	The use of the UV photometer as an alternative cannot be supported as serious problems have been encountered in its use in the UK.	Delete reference to UV photometer.	

PROJECT NUMBER: IEC/ASTM 62885-6 ED2	
DATE OF CIRCULATION: 2020-04-03	CLOSING DATE FOR COMMENTS: 2020-06-26
SUPERSEDES DOCUMENTS: 59F/392/RR	

IEC SC 59F : SURFACE CLEANING APPLIANCES	
SECRETARIAT: Sweden	SECRETARY: Mr Hans Erik Rundqvist
OF INTEREST TO THE FOLLOWING COMMITTEES:	PROPOSED HORIZONTAL STANDARD: ☐ Other TC/SCs are requested to indicate their interest, if any, in this CD to the secretary.
FUNCTIONS CONCERNED: ☐ EMC ☒ ENVIRONMENT ☒ QUALITY ASSURANCE ☐ SAFETY	

This document is still under study and subject to change. It should not be used for reference purposes.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

TITLE:

Surface cleaning appliances – Part 6: Wet hard floor cleaning appliances for household or similar use – Methods for measuring the performance

NOTE FROM TC/SC OFFICERS:

CONTENTS

FOREWORD	4
1 Scope	6
2 Normative references	6
3 Terms and definitions	6
4 General conditions for testing	8
4.1 Atmospheric conditions	8
4.2 Test equipment and materials	8
4.3 Voltage and frequency	8
4.4 Running-in of wet hard floor cleaners	9
4.5 Equipment of the wet hard floor cleaner	9
4.6 Operation of the wet hard floor cleaner	9
4.7 Conditioning prior to each test	10
4.7.1 General	10
4.7.2 Preparations specific to steam cleaners	10
4.7.3 Preparations for other wet hard floor cleaners	10
4.8 Mechanical operator	10
4.9 Number of samples	10
5 Wet hard floor cleaning tests	11
5.1 Stain cleaning efficiency of hard flat floors	11
5.1.1 General	11
5.1.2 Apparatus	11
5.1.3 Materials	12
5.1.4 Sampling and test trials	13
5.1.5 Method	13
5.2 Soil cleaning efficacy of hard flat floors	19
5.2.1 General	19
5.2.2 Apparatus	19
5.2.3 Materials	19
5.2.4 Sampling and test trials	19
5.2.5 Method	19
5.3 Floor wetness (<i>future development</i>)	26
5.4 Soil removal along walls (<i>future development</i>)	26
5.5 Pad loading test for steam cleaners (<i>future development</i>)	26
5.6 Air data (<i>future development</i>)	26
6 Miscellaneous tests	26
6.1 General	26
6.2 Motion resistance (<i>future development</i>)	26
6.3 Cleaning under furniture (<i>future development</i>)	26
6.4 Radius of operation	26
6.4.1 Purpose	26
6.4.2 Conditions for measurement	26
6.4.3 Determination of radius of operation	26
6.5 Impact resistance for floor cleaning heads	26
6.5.1 Purpose	26
6.5.2 Test equipment	26

6.5.3	Determination of impact resistance	27
6.6	Mass	27
6.7	Weight in hand	27
6.8	Specific cleaning time	27
6.9	Dimensions	28
6.10	Noise level (<i>future development</i>)	28
6.11	Energy consumption (<i>future development</i>)	28
6.12	Operational life-time test (<i>future development</i>)	28
6.13	Rated input power	28
7	Test material and equipment	28
7.1	General	28
7.2	Material for tests	28
7.2.1	Test surfaces	28
7.2.2	Test soils	29
7.2.3	Demineralized water	30
7.3	Equipment for tests	30
7.3.1	Mechanical operator	30
7.3.2	Tile floor cleaning fixture	31
7.3.3	Adjustable pipette	31
7.3.4	Stain & Soil application templates (type A & B)	32
7.3.5	Device for impact test	33
7.3.6	Magnetic stirring device	34
7.3.7	475 ml glass mixing jar (example)	34
8	Instructions for use	35
Annex A (informative)	Information on materials	36
Annex B (informative)	Information at the point of sale	37
Bibliography		38
Figure 1	– Photo of spoon and spatula	11
Figure 2	– Electronic scale for weighing of tiles	12
Figure 3	– Tile drying rack for preparing and drying soil stains	12
Figure 4	– Marking of tile	13
Figure 5	– Soiling with coffee	14
Figure 6	– Food strainer	15
Figure 7	– Application of pasty soil	15
Figure 8	– Removal of excess soil	16
Figure 9	– Cleaning stroke starting position	17
Figure 10	– End position after first stroke	18
Figure 11	– Jar with magnetic spinner (tare weighted)	20
Figure 12	– Properly mixed soil grime	21
Figure 13	– Soil grime settling results after 12 h	21
Figure 14	– Location of type B soiling template on porcelain tile	22
Figure 15	– Soiling a porcelain tile with pipette	22
Figure 16	– Soiled tile after 4 h drying	23
Figure 17	– Tile placement & cleaning stroke starting position	24

Figure 18 – End position after forward cleaning stroke	24
Figure 19 – Example of zigzag cleaning pattern	28
Figure 20 – Mechanical operator for executing cleaning tests	30
Figure 21 – Tile floor cleaning fixture with guides and stroke pacing device	31
Figure 22 – Adjustable pipette	31
Figure 23 – Stain application template (type A)	32
Figure 24 – Soil grime application template (type B)	33
Figure 25 – Drum for impact tests	34
Figure 26 – Magnetic stirring device (example)	35
Figure 27 – 475 ml glass mixing jar (example)	35
Table 1 – Example of results	19
Table 2 – Soils, composition, tools	29
Table 3 – Distance between holes	32
Table 4 – Inside dimension (b)	33

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SURFACE CLEANING APPLIANCES –

**Part 6: Wet hard floor cleaning appliances for household or similar use –
Methods for measuring the performance**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC/ASTM 62885-6 has been prepared by a Joint Working Group of subcommittee 59F: Surface cleaning appliances, of IEC technical committee 59: Performance of household and similar electrical appliances and ASTM Committee F11: Vacuum cleaners.

This second edition of IEC/ASTM 62885-6 cancels and replace the first edition published in 2018.

This edition constitutes a technical revision.

It is published as a dual logo standard.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
59F/XXX/FDIS	59F/XXX/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 62885 series, under the general title *Surface cleaning appliances*, can be found on the IEC website.

In this standard, the following print types are used:

- terms defined in Clause 3: **bold type**.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

SURFACE CLEANING APPLIANCES –

Part 6: Wet hard floor cleaning appliances for household or similar use – Methods for measuring the performance

1 Scope

This part of IEC 62885 is applicable for measurements of the performance of **wet hard floor cleaning appliances** for household use in or under conditions similar to those in households. In the case of appliances with combined functionality, this document only addresses the wet cleaning functionality.

The purpose of this document is to specify essential performance characteristics of **wet hard floor cleaning appliances** that are of interest to users and to describe methods for measuring these characteristics.

NOTE This document is not intended for cordless and robotic wet hard floor cleaning appliances.

For safety requirements, reference is made to IEC 60335-1, IEC 60335-2-2, IEC 60335-2-10, and IEC 60335-2-54.

A recommendation on information for the consumer at the point of sale is given in Annex B.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60335-1, *Household and similar electrical appliances – Safety – Part 1: General requirements*

IEC 60335-2-2, *Household and similar electrical appliances – Safety – Part 2-2: Particular requirements for vacuum cleaners and water-suction cleaning appliances*

IEC 60335-2-10, *Household and similar electrical appliances – Safety – Part 2-10: Particular requirements for floor treatment machines and wet scrubbing machines*

IEC 60335-2-54, *Household and similar electrical appliances – Safety – Part 2-54: Particular requirements for surface-cleaning appliances for household use employing liquids or steam*

IEC 60688, *Electrical measuring transducers for converting A.C. and D.C. electrical quantities to analogue or digital signals*

IEC 60734:2012, *Household electrical appliances – Performance – Water for testing*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

38 ISO and IEC maintain terminological databases for use in standardization at the following
39 addresses:

- 40 • IEC Electropedia: available at <http://www.electropedia.org/>
- 41 • ISO Online browsing platform: available at <http://www.iso.org/obp>

42 3.1

43 **wet hard floor cleaner**

44 electrically operated appliance that removes wet or dry stains and soils (e.g. beverage & food
45 stains, floor grime, etc.) from a hard floor surface to be cleaned by use of water alone, a
46 detergent solution mix, or use of steam, and can employ an air flow created by a vacuum
47 developed within the unit, the removed material being separated in the appliance and the
48 cleaned suction air being returned to the ambient air

49 3.2

50 **steam cleaner**

51 **wet hard floor cleaner** that uses steam, and generally employs a soft absorbent pad to transfer
52 hot moisture to the floor surface and to absorb and remove the stains and soils

53 3.3

54 **cleaning head**

55 plain nozzle, pad, or brush attached to a wet hard floor cleaner that is applied to a surface to
56 be cleaned

57 3.4

58 **active nozzle**

59 cleaning head provided with a driven agitation device to assist stain or soil removal

60 3.5

61 **passive nozzle**

62 **cleaning head** without any driven agitation device

63 3.6

64 **floor cleaning head width**

65 **W**

66 external maximum width of the **cleaning head** with pad

67 Note 1 to entry: **Floor cleaning head width** is expressed in metres.

68 3.7

69 **cleaning cycle**

70 execution of one **double stroke** to be carried out at a specified **stroke speed** over the test area

71 3.8

72 **stroke pattern**

73 arrangement of the **forward strokes** and **return strokes** on the surface to be cleaned

74 3.9

75 **parallel pattern**

76 stroke pattern where the **forward strokes** and the **return strokes** are congruent

77 3.10

78 **stroke speed**

79 speed of the **cleaning head**, moved as uniformly as possible, during a **forward stroke** or a
80 **return stroke**

3.11**stroke length**

distance between the two parallel lines defining the limits of a stroke pattern

3.12**double stroke**

one forward and one backward movement of the **cleaning head** performed in a **parallel pattern**

3.13**forward stroke**

forward movement of a stroke pattern

3.14**return stroke**

backward movement of a stroke pattern

4 General conditions for testing**4.1 Atmospheric conditions**

Unless otherwise specified, the test procedures and measurements shall be carried out under the following conditions:

Standard atmosphere 23/50

Temperature: $(23 \pm 2) ^\circ\text{C}$

Relative humidity: $(50 \pm 5) \%$

Air pressure: 86 kPa to 106 kPa

Temperature and humidity conditions within the specified ranges are required for good repeatability and reproducibility. Care should be taken to avoid changes during a test.

For test procedures and measurements, which may be carried out at conditions other than standard atmospheric conditions, the ambient temperature shall be maintained at $(23 \pm 5) ^\circ\text{C}$.

NOTE Due to the influence of environmental conditions, variations in time, origin of test materials and proficiency of the operator, most of the described test methods will give more reliable results when applied for comparative testing of a number of appliances at the same time, in the same laboratory and by the same operator.

4.2 Test equipment and materials

Equipment and materials for measurements (devices, test surfaces, stains, soils, etc.) to be used in a test shall, prior to the test, be stored for at least 16 h at standard atmospheric conditions in accordance with 4.1.

4.3 Voltage and frequency

Unless otherwise stated, measurements shall be carried out at rated voltage with a tolerance of $\pm 1 \%$ and, if applicable, at rated frequency.

Wet hard floor cleaners designed for DC only shall be operated at DC. **Wet hard floor cleaners** designed for both AC and DC shall be operated at AC. **Wet hard floor cleaners** not marked with rated frequency shall be operated at either $(50 \pm 1) \text{ Hz}$ or $(60 \pm 1) \text{ Hz}$ with a total harmonic distortion of $< 3 \%$, as is common in the country of use.

For **wet hard floor cleaners** with a rated voltage range, measurements shall be carried out at the mean value of the voltage range if the difference between the limits of the range does not

exceed 10 % of the mean value. If the difference exceeds 10 % of the mean value, measurements shall be carried out at both the upper and lower limits of the voltage range.

If the rated voltage differs from the nominal system voltage of the country concerned, measurements carried out at rated voltage can give test results misleading for the consumer, and additional measurements could be required. If the test voltage differs from the rated voltage, this shall be reported.

4.4 Running-in of wet hard floor cleaners

Prior to the first test of a new **wet hard floor cleaner**, the appliance shall be kept operating for at least 30 min while dispensing cleaning liquid, steam, etc. to ensure adequate running-in. If the appliance employs a pad, the pad shall be removed. If the appliance employs a vacuum, the run-in time shall be 2 h, and the appliance shall be operated with unrestricted air flow during the run-in period. If the appliance employs an **active nozzle**, the agitation device shall be running but not in contact with the floor.

Prior to conducting any series of tests, the age, condition, and history of the product shall be recorded.

4.5 Equipment of the wet hard floor cleaner

If the **wet hard floor cleaner** is provided with a reusable pad(s) or brush that is removable without the aid of tools, it shall be cleaned and prepared according to the manufacturer's instructions prior to each measurement.

Wet hard floor cleaners with receptacles to collect dirty cleaning solutions shall be cleaned and/or maintained in accordance with relevant clauses and carried out according to the manufacturer's instructions.

4.6 Operation of the wet hard floor cleaner

The **wet hard floor cleaner** shall be used and adjusted in accordance with the manufacturer's instructions for normal operation for the test to be carried out. Height adjustment controls (if any) for the cleaning head shall be set as appropriate and the position noted. Any safety-related device shall be allowed to operate.

For a **wet hard floor cleaner** with more than one cleaning head, the **cleaning head** recommended by the manufacturer in the user instructions for cleaning tasks corresponding to the cleaning tests described in 5.1 to 5.5 shall be used. If no instructions are provided, contact the manufacturer or the **wet hard floor cleaner** shall be tested with the **cleaning head** with the largest head width for the appropriate purpose. The **cleaning head** used for each test shall be reported.

For a **cleaning head** with more than one setting, the setting recommended by the manufacturer in the user manual for cleaning tasks corresponding with the cleaning tests described in 5.1 to 5.5 shall be used. If no instructions are provided in the user manual, contact the manufacturer to determine the correct setting. If the manufacturer cannot provide the correct setting, the **cleaning head** shall be tested in its default delivery setting. The setting used for each test shall be reported.

Any electrical controls shall be set for maximum continuous operation and air flow. Unless the manufacturer's instruction states otherwise, any manually operated air by-pass openings for reduction of the suction power shall be closed, and if open, it shall be reported.

4.7 Conditioning prior to each test

4.7.1 General

If the **wet hard floor cleaner** is unused and de-energized for more than 1 h, then the **wet hard floor cleaner** shall be kept running for at least 10 min under the provisions given in 4.4 to allow it to stabilize.

4.7.2 Preparations specific to steam cleaners

Follow the manufacturer's instructions to prepare the steam cleaner for use. When the steam cleaner is ready for operation (after the heating-up phase), produce steam for 15 s to remove any air and/or condensed water from the steam conduits in the appliance to ensure proper priming of the system. Prior to any test, a clean pad is to be installed on the **cleaning head**, which has been washed and thoroughly dried in accordance with the manufacturer's instructions. This step is necessary to ensure no foreign substances on a new or used pad will affect the test results. Place the **cleaning head** on a clean floor surface and produce steam for 15 s to moisten the pad.

4.7.3 Preparations for other wet hard floor cleaners

Follow the manufacturer's instructions for preparing and priming the product for floor cleaning use.

4.8 Mechanical operator

In order to achieve reliable results, certain tests require the **cleaning head** to be moved at uniform speed over the test area and without exerting an additional force pressing the **cleaning head** against the test surface.

It is recommended to simulate the handling of the **wet hard floor cleaner** by using a mechanical operator such as that described in 7.3.1. The handle of the cleaner shall be attached to the linear drive so that its centre pivots at a height of (800 ± 50) mm above the test surface. For nozzles without pivoting connectors, it shall be ensured that the bottom of the **cleaning head** be made parallel with the test surface by adjusting the handle height within the tolerances. Any adjustment shall be reported.

The linear drive may be motorized or operated by hand. The method of operation shall be reported.

4.9 Number of samples

All measurements of performance shall be carried out on the same sample(s) of the **wet hard floor cleaner**.

For increased confidence in the test results, a minimum of three samples of a **wet hard floor cleaner** should be tested.

Tests carried out to simulate stresses that a **wet hard floor cleaner** can be exposed to during normal use, possibly causing impairment of the cleaner's performance, can require additional samples of replaceable parts. Such tests shall be carried out at the end of the test programme.