



DPC: 20/30423331 DC

BSI Group Headquarters

389 Chiswick High Road London W4 4AL

Tel: +44 (0)20 8996 9000

Fax: +44 (0)20 8996 7400

www.bsigroup.com

Date: 07 July 2020

Origin: International

Latest date for receipt of comments: 22 July 2020

Project No. 2017/02254

Responsible committee: EPL/47 Semiconductors

Interested committees:

Title: Draft BS EN IEC 62906-5-5 Laser displays. Part 5-5: Optical measuring methods of raster-scanning retina direct projection laser displays.

Please notify the secretary if you are aware of any keywords that might assist in classifying or identifying the standard or if the content of this standard

- i) has any issues related to 3rd party IPR, patent or copyright
- ii) affects other national standard(s)
- iii) requires additional national guidance or information

WARNING: THIS IS A DRAFT AND MUST NOT BE REGARDED OR USED AS A BRITISH STANDARD. THIS DRAFT IS NOT CURRENT BEYOND 22 July 2020

This draft is issued to allow comments from interested parties; all comments will be given consideration prior to publication. No acknowledgement will normally be sent. **See overleaf for information on the submission of comments.**

No copying is allowed, in any form, without prior written permission from BSI except as permitted under the Copyright, Designs and Patent Act 1988 or for circulation within a nominating organization for briefing purposes. Electronic circulation is limited to dissemination by e-mail within such an organization by committee members.

Further copies of this draft may be purchased from BSI Shop <http://shop.bsigroup.com> or from BSI Customer Services, Tel: +44(0) 20 8996 9001 or email cservices@bsigroup.com. British, International and foreign standards are also available from BSI Customer Services.

Information on the co-operating organizations represented on the committees referenced above may be obtained from <https://standardsdevelopment.bsigroup.com/>.

Introduction

This draft standard is based on national and international discussions. Your comments on this draft are invited and will assist in the preparation of the consequent standard.

For international standards, comments will be reviewed by the relevant UK national committee before sending the consensus UK vote and comments to the international committee, which will then decide appropriate action. If the international standard is approved, it is usual for the text to be published as a British Standard.

For national standards, comments will be reviewed by the relevant UK national committee and the resulting standards published as a British Standard.

UK Vote

Please indicate whether you consider the UK should submit a negative (with supporting technical reasons) or positive vote on this draft. Please indicate if you are aware of any reason why this draft standard should not be published as a British Standard.

Submission of Comments

- **Annotated drafts are not acceptable and will be rejected.**
- All comments should be submitted online at <https://standardsdevelopment.bsigroup.com/>. You will need to register in order to comment.

Template for comments and secretariat observations

Date: xx/xx/20xx	Document: ISO/DIS xxxx
------------------	------------------------

1	2	(3)	4	5	(6)	7
MB	Clause No./ Subclause No./Annex (e.g. 3.1)	Paragraph/Figure/ Table/Note	Type of comment	Comment (justification for change) by the MB	Proposed change by the MB	Secretariat observations on each comment submitted
	3.1	Definition 1	ed	Definition is ambiguous and needs clarifying.	Amend to read '...so that the mains connector to which no connection...'	
	6.4	Paragraph 2	te	The use of the UV photometer as an alternative cannot be supported as serious problems have been encountered in its use in the UK.	Delete reference to UV photometer.	



110/981/CD

COMMITTEE DRAFT (CD)

PROJECT NUMBER:
IEC 62906-5-5 ED1

DATE OF CIRCULATION:
2018-05-04

CLOSING DATE FOR COMMENTS:
2018-06-29

SUPERSEDES DOCUMENTS:
110/857/NP, 110/875A/RVN

IEC TC 110 : ELECTRONIC DISPLAY DEVICES			
SECRETARIAT: Japan		SECRETARY: Mr Yoshi SHIBAHARA	
OF INTEREST TO THE FOLLOWING COMMITTEES: TC 76, TC 100		PROPOSED HORIZONTAL STANDARD: ☐ Other TC/SCs are requested to indicate their interest, if any, in this CD to the secretary.	
FUNCTIONS CONCERNED: ☐ EMC ☐ ENVIRONMENT ☐ QUALITY ASSURANCE ☐ SAFETY			

This document is still under study and subject to change. It should not be used for reference purposes.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

TITLE:

Laser display devices – Part 5-5: Optical measuring methods of raster-scanning retina direct projection devices

NOTE FROM TC/SC OFFICERS:

As the adHoc meeting of IEC TC 110 WG 10 will be held on May 18th, 2018 at LA, CA USA, all NCs are invited to submit their comments by that date to allow discussion during that meeting. Kindly submit the comments to the IEC TC 110 secretary in parallel with the submission through the IEC voting system.

Copyright © 2018 International Electrotechnical Commission, IEC. All rights reserved. It is permitted to download this electronic file, to make a copy and to print out the content for the sole purpose of preparing National Committee positions. You may not copy or "mirror" the file or printed version of the document, or any part of it, for any other purpose without permission in writing from IEC.

CONTENTS

1		
2		
3	FOREWORD.....	4
4	1 Scope.....	6
5	2 Normative references	6
6	3 Terms, definitions and abbreviations	6
7	3.1 Terms and definitions.....	6
8	3.2 Abbreviations.....	7
9	4 Standard measuring conditions.....	7
10	4.1 Standard measuring environmental conditions	7
11	4.2 Coordinate systems	7
12	4.3 Standard conditions of RS-RDP LDD (DUT) and measuring equipment	
13	(LMD)	8
14	4.4 Eye-safety requirements	9
15	5 Optical measuring methods	9
16	5.1 General.....	9
17	5.2 Optical power considering the biological safety of laser beams	9
18	5.3 Fundamental optical properties	10
19	5.4 Scanning properties.....	12
20	5.5 Image quality	13
21	6 Report	17
22	Annex A.....	18
23	A.1 General.....	18
24	A.2 Example of mechanical structure	18
25	A.3 Example of fundamental electro-optical structure of RS-RDP LDD	18
26	Annex B.....	20
27	B.1 General.....	20
28	B.2 Maxwellian View	20
29	B.3 Pinhole Image on the Retina in the Maxwellian View.....	20
30	B.4 Laser Image on the Retina in the Maxwellian View.....	21
31	Annex C.....	22
32	C.1 Eyeball screen model.....	22
33	Annex D.....	24
34	D.1 Spatial frequency response measurement.....	24
35	Annex E.....	26
36	E.1 Conversion from retinal illuminance to luminance.....	26
37	Bibliography.....	28
38		
39	Figure 1 – Planar measurement coordinate system for measurement.....	8
40	Figure 2 – Measurement points of light power of RS-RDP LDD	10
41	Figure 3 – Measurement geometry of eyebox.....	11
42	Figure 4 – Measurement geometry of FOV.....	12
43	Figure 5 – Measurement geometry of scanning property	12
44	Figure 6 – Example of plots of frame rate	13
45	Figure 7 – Example of measurement points for image quality.....	13
46	Figure 8 – Test patterns for resolution measurement	14
47	Figure 9 – Measurement result example	15

48	Figure 10 - Measurement geometry of illuminance	16
49	Figure 11 – Measurement geometry of colour gamut.....	17
50	Figure A.1 – Example of mechanical structure of RS-RDP LDD (a) eyewear	
51	configuration for both eyes, and (b) relative position of the reflector and the eye.	18
52	Figure A.2 –Example of electro-optical structure of RS-RDP LDD	19
53	Figure B.1 – (a) Maxwellian view (b) viewing	20
54	Figure B.2 – (a) Pinhole (b) Laser beam in the Maxwellian view.....	21
55	Figure C.1 – Schematic structure of eyeball screen model	22
56	Figure C.2 – Comparison between eyeball screen model and flat screen	22
57	Figure C.3 – Coordinate system for measurement with eyeball model.....	23
58	Figure D 1 - Determination of the spatial frequency response (SFR)	24
59	Figure E 1- Model of the display observation	26
60		
61		

INTERNATIONAL ELECTROTECHNICAL COMMISSION

LASER DISPLAY DEVICES –**Part 5-5: Optical measuring methods of raster-scanning
retina direct projection laser display devices –**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62906-5-5 has been prepared by IEC technical committee 110: Electronic display devices.

The text of this standard is based on the following documents:

NP	Report on voting
110/XX/NP	110/XX/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

Future standards in this series will carry the new general title as cited above. Titles of existing standards in this series will be updated at the time of the next edition.

A list of all parts of the IEC 62906 series, under the general title *Laser display devices*, can be found on the IEC website.

116 The committee has decided that the contents of this publication will remain unchanged until
117 the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data
118 related to the specific publication. At this date, the publication will be

- 119 • reconfirmed,
- 120 • withdrawn,
- 121 • replaced by a revised edition, or
- 122 • amended.

123

124 The National Committees are requested to note that for this publication the stability date
125 is 20XX.

126 THIS TEXT IS INCLUDED FOR THE INFORMATION OF THE NATIONAL COMMITTEES AND WILL BE
127 DELETED AT THE PUBLICATION STAGE.

128

129

LASER DISPLAY DEVICES –

Part 5-5: Optical measuring methods of raster-scanning retina direct projection laser display devices –

1 Scope

This part of IEC 62906 specifies the standard measurement conditions and optical measuring methods for raster-scanning retina direct projection laser display devices.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC61906-1-2: *Laser display devices – Part 1-2: Vocabulary and letter symbols*

IEC 60825-1 Ed.3.0: *Safety of laser products – Part 1: Equipment classification and requirements*

IEC 60050: *International Electrotechnical Vocabulary*

ICNIRP. Guidelines on limits of exposure to laser radiation of wavelengths between 180 nm and 1000 nm, Health Phys. 105(3) pp. 271 - 295 (2013).

3 Terms, definitions and abbreviations

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply. ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>

- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1.1

raster-scanning retina direct projection laser display device

RS-RDP LDD

direct laser projection system to retina, that the display does not need actual or virtual screen for observation

Note 1 to entry: For examples, see Annex A

3.1.2

retinal imaging

projection and observation of image by the Maxwellian view

Note 1 to entry: The Maxwellian view is a method of observation in which a converging lens forms an image of the light source in the plane of the eye's pupil of the observer, instead of looking at the source directly. For examples, see Annex B

3.1.3

Effective angular resolution, <of a RS-RDP LDD>

resolution of the projected image on human retina expressed as the pixel per degree

3.1.4

focal point

smallest beam spot point in the vicinity of the exit of the optical system of RS-RDP LDD

3.1.5

pupil offset

distance between focal point and the centre of pupil

3.1.6**differential image resolution**

$\Delta R/\Delta f$

derivative of image resolution R with respect to the focal length f of lens in the pupil of eyeball model

3.1.7**eyebox**

three-dimensional volume that the full displayed image can be observed

3.2 Abbreviations

CW continuous wave

(a term widely used in the laser industry from a viewpoint of light output.

Equivalent to DC: direct current from a viewpoint of driving electrical current

← → pulse)

DUT device under test

FOV field of view

LD laser diode

LDD laser display devices

LMD light measuring device

MEMS microelectromechanical system

IPD inter-pupillary distance

RGB red, green, and blue

SFR spatial frequency response

2D two-dimension, two-dimensional

4 Standard measuring conditions**4.1 Standard measuring environmental conditions**

Optical measurements related to RS-RDP LDD shall be carried out under the standard environmental conditions:

- Temperature: 25 °C ± 3 °C,
- Relative humidity: 25% to 85% RH,
- Atmospheric pressure: 86 kPa to 106 kPa.

when different environmental conditions are used, they shall be noted in the measurement report.

The darkroom luminance contribution from the background light shall be $\leq 0,01$ lx.

4.2 Coordinate systems

The measurement coordinate systems are shown in Figure 1. The origin of the coordinate systems is placed at the focal point of the RS-RDP LDD. In the Cartesian system, the horizontal x axis and the vertical y axis are parallel and normal to the line between the two eyes, respectively. The z axis is normal to the x - y plane. In the polar coordinate system, zenith angle θ and azimuth angle ϕ are also defined in Figure 1.

The optical measurements shall be carried out either on a planar sensor parallel to the x - y plane. The coordinate conversion between the retinal screen and the planar screen is shown in Annex C.3. It should be noted that the focal point usually does not coincide exactly with the centre surface of the pupil.

The length from the focal point to the planar screen L_{screen} shall be 22 mm because of the retina position of human eye.