



DPC: 24/30493808 DC

BSI Group Headquarters

389 Chiswick High Road London W4 4AL

Tel: +44 (0)20 8996 9000

Fax: +44 (0)20 8996 7400

www.bsigroup.com

Date: 19 September 2024

Origin: European

Latest date for receipt of comments: 12 November 2024

Project No. 2024/01567

Responsible committee: RAE/2 Railway Applications - Track

Interested committees:

Title: Draft BS EN 13848-6 BS Railway applications - Track - Track geometry quality. Part 6: Characterisation of track geometry quality.

Please notify the secretary if you are aware of any keywords that might assist in classifying or identifying the standard or if the content of this standard

- i) has any issues related to 3rd party IPR, patent or copyright
- ii) affects other national standard(s)
- iii) requires additional national guidance or information

WARNING: THIS IS A DRAFT AND MUST NOT BE REGARDED OR USED AS A BRITISH STANDARD. THIS DRAFT IS NOT CURRENT BEYOND 12 November 2024

This draft is issued to allow comments from interested parties; all comments will be given consideration prior to publication. No acknowledgement will normally be sent. **See overleaf for information on the submission of comments.**

No copying is allowed, in any form, without prior written permission from BSI except as permitted under the Copyright, Designs and Patent Act 1988 or for circulation within a nominating organization for briefing purposes. Electronic circulation is limited to dissemination by e-mail within such an organization by committee members.

Further copies of this draft may be purchased from BSI Shop <http://shop.bsigroup.com> or from BSI Customer Services, Tel: +44(0) 20 8996 9001 or email cservices@bsigroup.com. British, International and foreign standards are also available from BSI Customer Services.

Information on the co-operating organizations represented on the committees referenced above may be obtained from <https://standardsdevelopment.bsigroup.com/>.

Introduction

This draft standard is based on national and international discussions. Your comments on this draft are invited and will assist in the preparation of the consequent standard.

For international standards, comments will be reviewed by the relevant UK national committee before sending the consensus UK vote and comments to the international committee, which will then decide appropriate action. If the international standard is approved, it is usual for the text to be published as a British Standard.

For national standards, comments will be reviewed by the relevant UK national committee and the resulting standards published as a British Standard.

UK Vote

Please indicate whether you consider the UK should submit a negative (with supporting technical reasons) or positive vote on this draft. Please indicate if you are aware of any reason why this draft standard should not be published as a British Standard.

Submission of Comments

- **Annotated drafts are not acceptable and will be rejected.**
- All comments should be submitted online at <https://standardsdevelopment.bsigroup.com/>. You will need to register in order to comment.

Template for comments and secretariat observations

Date: xx/xx/20xx	Document: ISO/DIS xxxx
------------------	------------------------

1	2	(3)	4	5	(6)	7
MB	Clause No./ Subclause No./Annex (e.g. 3.1)	Paragraph/ Figure/Table/Note	Type of comment	Comment (justification for change) by the MB	Proposed change by the MB	Secretariat observations on each comment submitted
	3.1	Definition 1	ed	Definition is ambiguous and needs clarifying.	Amend to read '...so that the mains connector to which no connection...'	
	6.4	Paragraph 2	te	The use of the UV photometer as an alternative cannot be supported as serious problems have been encountered in its use in the UK.	Delete reference to UV photometer.	

English Version

Railway applications - Track - Track geometry quality - Part 6: Characterisation of track geometry quality

Applications ferroviaires - Voie - Qualité géométrique
de la voie - Partie 6 : Caractérisation de la qualité
géométrique de la voie

Bahnanwendungen - Oberbau - Gleislagequalität - Teil
6: Charakterisierung der geometrischen
Gleislagequalität

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee CEN/TC 256.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents	Page
European foreword	4
1 Scope.....	5
2 Normative references.....	5
3 Terms, definitions, symbols and abbreviations.....	5
3.1 Terms and definitions	5
3.2 Symbols and abbreviations	6
4 General principles	7
4.1 Introduction.....	7
4.2 Parameters for track geometry quality assessment	7
4.3 Transparency	7
4.4 Complexity.....	7
4.5 Track-vehicle interaction	7
5 Methods of assessment of track geometry quality	7
5.1 General.....	7
5.2 Reference method: TQI_{ref} - Standard deviation (SD)	8
5.3 Other methods	9
5.3.1 General.....	9
5.3.2 Number of isolated defects.....	9
5.3.2 Combined standard deviation ($CoSD$)	9
5.3.3 Standard deviation of the combinations of parameters	10
5.3.4 Point mass acceleration method (PMA)	11
5.3.5 Methods based on vehicle response.....	12
5.3.6 Power Spectral Density (PSD)	13
6 Levels of aggregation and calculation methods.....	14
7 Classes of track geometry quality	14
7.1 General.....	14
7.2 Description of track quality classes (TQC)	15
7.3 Values of track quality classes	16
7.4 Assignment of $TQCs$	17
7.5 Possible application of $TQCs$	17
Annex A (informative) Point mass acceleration method (PMA)	19
A.1 Introduction.....	19
A.2 Calculation of the PMA-assessment figure.....	19
Annex B (informative) Vehicle Response Analysis methods (VRA).....	21
B.1 Introduction.....	21
B.2 Determination of the assessment tables	21
B.3 Application of the assessment tables.....	24
Annex C (normative) Method for calculating reference $TQIs$ (TQI_{ref})	27
C.1 Introduction.....	27
C.2 Description of the method	27
Annex D (informative) Method of classification of alternative TQI using the $TQCs$	28
D.1 Introduction.....	28

D.2	Description of the conversion method.....	28
Bibliography		30

European foreword

This document (prEN 13848-6:2024) has been prepared by Technical Committee CEN/TC 256 “Railway applications”, the secretariat of which is held by DIN.

This document is currently submitted to the CEN Enquiry.

This document will supersede EN 13848-6:2014+A1:2020.

The main changes compared to EN 13848-6:2014+A1:2020 are listed below:

- *change of the structure of the document;*
- *revision of Annex A;*
- *revision of Annex B.*

In this document, the Annex C is normative and the Annexes A, B and D are informative.

This document is one of the series EN 13848 “Railway applications — Track — Track geometry quality” as listed below:

- *Part 1: Characterisation of track geometry;*
- *Part 2: Measuring systems — Track recording vehicles;*
- *Part 3: Measuring systems — Track construction and maintenance machines;*
- *Part 4: Measuring systems — Manual and lightweight devices;*
- *Part 5: Geometric quality levels — Plain line, switches and crossings;*
- *Part 6: Characterisation of track geometry quality.*

1 Scope

This document provides the method to characterize and classify the quality of track geometry based on parameters defined in EN 13848-1.

This document also specifies different track geometry classes.

This document does not:

- apply to lines with a nominal gauge less than 1 435 mm;
- specify requirements for Urban Rail Systems.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 13848-1:2019, *Railway applications — Track — Track geometry quality — Part 1: Characterization of track geometry*

EN 17343, *Railway applications — General terms and definitions*

3 Terms, definitions, symbols and abbreviations

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 17343 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp/>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1.1

decolouring

algorithm which modifies the spectral content of a signal aimed to compensate or apply the characteristics of a specific measuring system

Note 1 to entry: The decolouring is used in EN 13848 series to convert a chord measurement signal into a *D1* or *D2* measurement signal.

3.1.2

track quality index (TQI)

value that characterises track geometry quality of a track section based on parameters and measuring methods compliant with EN 13848 series

3.1.3

track quality class (TQC)

characterization of track geometry quality as a function of speed and expressed as a range of TQIs

3.2 Symbols and abbreviations

For the purposes of this document, the symbols and abbreviations given in Table 1 apply.

Table 1 — Symbols and abbreviations

Symbol	Designation	Unit
<i>AL</i>	Alignment	mm
<i>ATQI</i>	Alternative Track Quality Index	
<i>CL</i>	Cross level	mm
<i>CoSD</i>	Combined standard deviation	mm
<i>cr</i>	Curvature	1/m
<i>D0</i>	Wavelength range $1 < \lambda \leq 5$	m
<i>D1</i>	Wavelength range $3 < \lambda \leq 25$	m
<i>D2</i>	Wavelength range $25 < \lambda \leq 70$	m
<i>D3</i>	Wavelength range $70 < \lambda \leq 150$ for longitudinal level Wavelength range $70 < \lambda \leq 200$ for alignment	m
λ	Wavelength	m
<i>G</i>	Track gauge	mm
<i>LL</i>	Longitudinal level	mm
<i>MBS</i>	Multi Body System	
<i>PMA</i>	Point Mass Acceleration (method)	
<i>PSD</i>	Power Spectral Density	$\text{m}^2/(\text{1/m})$
<i>SD</i>	Standard deviation	mm
<i>SD_{LL}</i>	Standard deviation longitudinal level	mm
<i>SD_{AL}</i>	Standard deviation alignment	mm
<i>TQI</i>	Track Quality Index	
<i>TQI_{ref}</i>	Reference Track Quality Index	
<i>TQC</i>	Track Quality Class	
<i>V</i>	Speed	km/h
<i>VRA</i>	Vehicle Response Analysis (method)	

NOTE In this document, *AL* stands for “alignment” and is not to be confused with *AL* standing for “alert limit” as defined in EN 13848-5.

4 General principles

4.1 Introduction

In order to provide a sufficient level of safety, ride quality and cost-effective railway traffic, track geometry quality is assessed.

This document deals with track geometry quality classification regarding ride quality through TQIs. The safety aspect on the other hand is covered in EN 13848-5.

TQIs can be calculated using different methods. The ones described in Clause 5 are applied by at least one European network. The reference method for calculating comparable TQIs is detailed in Clause 7.

4.2 Parameters for track geometry quality assessment

As track geometry measurement, vehicles present their outputs in accordance with the parameters specified in EN 13848-1, any standardized assessment method shall be based on these parameters.

4.3 Transparency

Any algorithm for track geometry quality assessment complying with this document shall be fully documented, reproducible and available in the public domain.

4.4 Complexity

Track geometry quality should be assessed by as few *TQIs* as possible and the algorithm should be understandable by the user.

4.5 Track-vehicle interaction

Track quality assessment should reflect the principles of track-vehicle interaction. For example, the track geometry defects of the same amplitude but different wavelengths lead to different vehicle responses and the required wavelength range will be different depending on the track-vehicle interaction parameters to be assessed.

5 Methods of assessment of track geometry quality

5.1 General

Considering their wide use across European Railway Networks and the need to have a single, easily understandable *TQI*, standard deviation (*SD*) of longitudinal level and alignment defined in 5.2 is taken as the reference method to describe track geometry quality. It will be referred to as *TQI_{ref}* in the following and is specified in Annex C.

Establishing a TQI by other means may be used providing that complete documentation is available about the method and how it relates to the reference method as described in Annex D.

The methods described in the following sub-clauses can be applied to any track geometry data of interest. Switches may be included.

5.2 Reference method: TQI_{ref} - Standard deviation (SD)

The standard deviation is the most commonly used aggregation method to calculate TQI by European railway networks. It represents the dispersion of a signal over a given track section, in relation to the mean value of this signal over the considered section.

$$SD = \sqrt{\frac{\sum_{i=1}^N (x_i - \bar{x})^2}{N - 1}}$$

where

- N is the number of values in the sample;
- x_i is the current value of a signal;
- $\bar{x}$ is the mean value of a signal;
- SD is the standard deviation.

NOTE 1 Standard deviation is linked to the energy of the signal in a given wavelength range $[\lambda 1, \lambda 2]$ according to the following relationship: $SD^2 = 2 \int_{\lambda 1}^{\lambda 2} S_{xx}(\nu) d\nu$, where S_{xx} is the PSD described in 5.3.8 below.

SD is commonly calculated for the following parameters:

- longitudinal level $D1$;
- alignment $D1$.

It is also calculated for other parameters such as:

- twist;
- track gauge;
- cross level;
- longitudinal level $D2$;
- alignment $D2$.

When calculating SD , attention should be paid to the possible influence of the quasi-static part (e.g. track design) of the signals especially for twist, track gauge and cross level.

For longitudinal level and alignment it is recommended to calculate SD separately for each rail. It may also be calculated differently (for example: mean of both rails, worst or best of either rail or outer rail in curves).

Length of track section used for standard deviation has influence on the result. If comparable results are expected, only one length should be used. Commonly, for maintenance reasons standard deviation is calculated over a length of 200 m. It may be calculated either at fixed distances without overlap or with overlap, as a sliding standard deviation. Calculation of standard deviation is also done over longer distances such as 1 km, an entire line or an entire network.

NOTE 2 Distinction between specific track sections, such as plain lines, stations and switches and crossings, can also be made.