



DPC: 24 / 30500174 DC

BSI Group Headquarters

389 Chiswick High Road London W4 4AL

Tel: +44 (0)20 8996 9000

Fax: +44 (0)20 8996 7400

www.bsigroup.com

Date: 16 September 2024

Origin: International

Latest date for receipt of comments: 2 October 2024

Project No. 2024/02595

Responsible committee: EPL/100 Audio-visual and Electronic equipment

Interested committees:

Title: BS IEC 63145-30 ED1 Eyewear display

Part 30: Durability test methods

Please notify the secretary if you are aware of any keywords that might assist in classifying or identifying the standard or if the content of this standard

- i) has any issues related to 3rd party IPR, patent or copyright
- ii) affects other national standard(s)
- iii) requires additional national guidance or information

**WARNING: THIS IS A DRAFT AND MUST NOT BE REGARDED OR USED AS A BRITISH STANDARD.
THIS DRAFT IS NOT CURRENT BEYOND 2 October 2024**

This draft is issued to allow comments from interested parties; all comments will be given consideration prior to publication. No acknowledgement will normally be sent. **See overleaf for information on the submission of comments.**

No copying is allowed, in any form, without prior written permission from BSI except as permitted under the Copyright, Designs and Patent Act 1988 or for circulation within a nominating organization for briefing purposes. Electronic circulation is limited to dissemination by e-mail within such an organization by committee members.

Further copies of this draft may be purchased from BSI Shop <http://shop.bsigroup.com> or from BSI Customer Services, Tel: +44(0) 20 8996 9001 or email cservices@bsigroup.com. British, International and foreign standards are also available from BSI Customer Services.

Information on the co-operating organizations represented on the committees referenced above may be obtained from <http://standardsdevelopment.bsigroup.com>

Responsible Committee Secretary: **Committee Service Centre (BSI)**
Direct tel: **020 8996 7009**
E-mail: csc@bsigroup.com

Introduction

This draft standard is based on national and international discussions. Your comments on this draft are invited and will assist in the preparation of the consequent standard.

For international standards, comments will be reviewed by the relevant UK national committee before sending the consensus UK vote and comments to the international committee, which will then decide appropriate action. If the international standard is approved, it is usual for the text to be published as a British Standard.

For national standards, comments will be reviewed by the relevant UK national committee and the resulting standards published as a British Standard.

UK Vote

Please indicate whether you consider the UK should submit a negative (with supporting technical reasons) or positive vote on this draft. Please indicate if you are aware of any reason why this draft standard should not be published as a British Standard.

Submission of Comments

- **Annotated drafts are not acceptable and will be rejected.**
- All comments should be submitted online at <https://standardsdevelopment.bsigroup.com/>. You will need to register in order to comment.

Template for comments and secretariat observations

Date: xx/xx/20xx	Document: ISO/DIS xxxx
------------------	------------------------

1	2	(3)	4	5	(6)	7
MB	Clause No./ Subclause No./Annex (e.g. 3.1)	Paragraph/Figure/ Table/Note	Type of comment	Commend (justification for change) by the MB	Proposed change by the MB	Secretariat observations on each comment submitted
	3.1	Definition 1	ed	Definition is ambiguous and needs clarifying.	Amend to read '...so that the mains connector to which no connection...'	
	6.4	Paragraph 2	te	The use of the UV photometer as an alternative cannot be supported as serious problems have been encountered in its use in the UK.	Delete reference to UV photometer.	



110/1685/CD

COMMITTEE DRAFT (CD)

PROJECT NUMBER: IEC 63145-30 ED1	
DATE OF CIRCULATION: 2024-09-06	CLOSING DATE FOR COMMENTS: 2024-11-01
SUPERSEDES DOCUMENTS: 110/1598/NP, 110/1621A/RVN	

IEC TC 110 : ELECTRONIC DISPLAYS		
SECRETARIAT: Japan	SECRETARY: Mr Yoshi SHIBAHARA	
OF INTEREST TO THE FOLLOWING COMMITTEES: TC 100	HORIZONTAL FUNCTION(S):	
ASPECTS CONCERNED:		

This document is still under study and subject to change. It should not be used for reference purposes.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Recipients of this document are invited to submit, with their comments, notification of any local regulations or technical reasons that may exist and should be considered should this proposal proceed, recognizing that failure to address such requirements could result in the need for new or existing "In Some Countries" clauses. (See [AC/22/2007](#) or [NEW GUIDANCE DOC](#)).

TITLE: Eyewear display – Part 30: Durability test methods

NOTE FROM TC/SC OFFICERS:

Copyright © 2024 International Electrotechnical Commission, IEC. All rights reserved. It is permitted to download this electronic file, to make a copy and to print out the content for the sole purpose of preparing National Committee positions. You may not copy or "mirror" the file or printed version of the document, or any part of it, for any other purpose without permission in writing from IEC.

CONTENTS

FOREWORD.....	3
INTRODUCTION.....	1
1 Scope.....	2
2 Normative references	2
3 Terms, definitions and abbreviated terms	2
3.1 Terms and definitions.....	2
3.2 Abbreviated terms.....	3
4 Standard ambient conditions	3
5 Environmental test conditions	3
5.1 General.....	3
5.1.1 Standard environmental conditions	3
5.1.2 Recovery conditions	3
5.1.3 Operational control points for temperature and humidity	3
5.1.4 Operational fluctuations of temperature and humidity	3
5.2 Stressed environmental conditions during operation (performed after completion of the environmental durability test in the operational state).....	4
5.2.1 Purpose	4
5.2.2 Test conditions	4
5.3 Stressed storage/transport conditions (performed after completion of the environmental durability test in the non-operational state).....	6
5.3.1 Purpose	6
5.3.2 Test conditions	6
6 Mechanical test conditions.....	7
6.1 General.....	7
6.2 Vibration (sinusoidal)	8
6.2.1 Test Fc	8
6.2.2 Transverse motion	8
6.2.3 Distortion.....	8
6.2.4 Vibration amplitude tolerance	8
6.2.5 Severities	8
6.2.6 Vibration amplitude.....	9
6.2.7 Duration of endurance	9
6.3 Shock	10
7 Environmental test methods.....	10
7.1 General.....	10
7.2 Test procedure.....	10
7.3 Optical performance test.....	11
7.3.1 General	11
7.3.2 Luminance and luminance uniformity (non-uniformity).....	11
7.3.3 Chromaticity and chromaticity uniformity.....	11
7.3.4 Field of view (FOV).....	11
7.3.5 Eye-box based on luminance	11
7.3.6 Michelson contrast.....	12
8 Mechanical test methods	12

8.1	General.....	12
8.2	Test procedure.....	12
8.3	Optical performance test.....	12
Figure 1 – Temperature profile.....		6
Table 1 – Examples of the stressed environmental durability test conditions for use during the operational state		5
Table 2 – Examples of the environmental durability test conditions for use in the non- operational state		7
Table 3 – Frequency range – Lower end		8
Table 4 – Frequency range – Upper end		8
Table 5 – Recommended frequency ranges		9
Table 6 – Recommended vibration amplitudes		9
Table 7 – Conditions for shock test		10
Table 8 – Optical performance test		11