



DPC: 24/30501161 DC

**BSI Group Headquarters**

389 Chiswick High Road London W4 4AL

Tel: +44 (0)20 8996 9000

Fax: +44 (0)20 8996 7400

www.bsigroup.com

Date: 28 November 2024

Origin: International

**Latest date for receipt of comments: 21 January 2025**

Project No. 2024/02805

Responsible committee: MCE/12 Plain bearings

Interested committees:

Title: Draft BS ISO 31657-1 Plain bearings - Hydrodynamic plain journal bearings under steady-state conditions. Part 1: Calculation of multi-lobed and tilting pad journal bearings.

Please notify [admin.start@bsigroup.com](mailto:admin.start@bsigroup.com) if you are aware of any keywords that might assist in clarifying or identifying the standard or of the content of this standard:

- i) has any issues related to 3rd party IPR, patent or copyright
- ii) affects other national standard(s)
- iii) requires additional national guidance or information

**WARNING: THIS IS A DRAFT AND MUST NOT BE REGARDED OR USED AS A BRITISH STANDARD. THIS DRAFT IS NOT CURRENT BEYOND 21 January 2025**

This draft is issued to allow comments from interested parties; all comments will be given consideration prior to publication. No acknowledgement will normally be sent. **See overleaf for information on the submission of comments.**

No copying is allowed, in any form, without prior written permission from BSI except as permitted under the Copyright, Designs and Patent Act 1988 or for circulation within a nominating organization for briefing purposes. Electronic circulation is limited to dissemination by e-mail within such an organization by committee members.

Further copies of this draft may be purchased from BSI Shop <http://shop.bsigroup.com> or from BSI Customer Services, Tel: +44(0) 20 8996 9001 or email [cservices@bsigroup.com](mailto:cservices@bsigroup.com). British, International and foreign standards are also available from BSI Customer Services.

Information on the co-operating organizations represented on the committees referenced above may be obtained from <https://standardsdevelopment.bsigroup.com/>.

E-mail: [admin.start@bsigroup.com](mailto:admin.start@bsigroup.com)

## Introduction

This draft standard is based on national and international discussions. Your comments on this draft are invited and will assist in the preparation of the consequent standard.

For international standards, comments will be reviewed by the relevant UK national committee before sending the consensus UK vote and comments to the international committee, which will then decide appropriate action. If the international standard is approved, it is usual for the text to be published as a British Standard.

For national standards, comments will be reviewed by the relevant UK national committee and the resulting standards published as a British Standard.

## UK Vote

Please indicate whether you consider the UK should submit a negative (with supporting technical reasons) or positive vote on this draft. Please indicate if you are aware of any reason why this draft standard should not be published as a British Standard.

## Submission of Comments

- **Annotated drafts are not acceptable and will be rejected.**
- All comments should be submitted online at <https://standardsdevelopment.bsigroup.com/>. You will need to register in order to comment.

## Template for comments and secretariat observations

|                  |                        |
|------------------|------------------------|
| Date: xx/xx/20xx | Document: ISO/DIS xxxx |
|------------------|------------------------|

| 1  | 2                                          | (3)                          | 4               | 5                                                                                                                                  | (6)                                                                      | 7                                                  |
|----|--------------------------------------------|------------------------------|-----------------|------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|----------------------------------------------------|
| MB | Clause No./ Subclause No./Annex (e.g. 3.1) | Paragraph/ Figure/Table/Note | Type of comment | Comment (justification for change) by the MB                                                                                       | Proposed change by the MB                                                | Secretariat observations on each comment submitted |
|    | 3.1                                        | Definition 1                 | ed              | Definition is ambiguous and needs clarifying.                                                                                      | Amend to read '...so that the mains connector to which no connection...' |                                                    |
|    | 6.4                                        | Paragraph 2                  | te              | The use of the UV photometer as an alternative cannot be supported as serious problems have been encountered in its use in the UK. | Delete reference to UV photometer.                                       |                                                    |



# DRAFT International Standard

## ISO/DIS 31657-1

### Plain bearings — Hydrodynamic plain journal bearings under steady-state conditions —

#### Part 1: Calculation of multi-lobed and tilting pad journal bearings

ICS: 21.100.10

ISO/TC 123/SC 8

Secretariat: JISC

Voting begins on:  
**2024-11-28**

Voting terminates on:  
**2025-02-20**

This document is circulated as received from the committee secretariat.

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENTS AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

Reference number  
ISO/DIS 31657-1:2024(en)

© ISO 2024



**Documents**

Document Sharing Hub



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

|                                                            |           |
|------------------------------------------------------------|-----------|
| <b>Foreword</b>                                            | <b>iv</b> |
| <b>Introduction</b>                                        | <b>v</b>  |
| <b>1 Scope</b>                                             | <b>1</b>  |
| <b>2 Normative references</b>                              | <b>1</b>  |
| <b>3 Terms and definitions</b>                             | <b>1</b>  |
| <b>4 Symbols and units</b>                                 | <b>1</b>  |
| <b>5 General principles, assumptions and preconditions</b> | <b>6</b>  |
| <b>6 Calculation method</b>                                | <b>9</b>  |
| 6.1 General                                                | 9         |
| 6.2 Load-carrying capacity                                 | 11        |
| 6.3 Frictional power                                       | 11        |
| 6.4 Lubricant flow rate                                    | 11        |
| 6.5 Heat balance                                           | 12        |
| 6.6 Maximum lubricant film temperature                     | 14        |
| 6.7 Maximum lubricant film pressure                        | 15        |
| 6.8 Operating states                                       | 15        |
| 6.9 Further influencing parameters                         | 15        |
| 6.10 Stiffness and damping coefficients                    | 16        |
| <b>7 Figures</b>                                           | <b>17</b> |
| <b>Annex A (informative) Calculation examples</b>          | <b>23</b> |
| <b>Bibliography</b>                                        | <b>37</b> |

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO [had/had not] received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at [www.iso.org/patents](http://www.iso.org/patents). ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 123, *Plain bearings*, Subcommittee SC 8, *Calculation methods for plain bearings and their applications*.

A list of all parts in the ISO 31657 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

The aim of this document is the operationally-safe design of plain journal bearings for medium or high journal circumferential velocities,  $U_j$ , up to approximately 90 m/s by applying a calculation method for oil-lubricated hydrodynamic plain bearings with complete separation of journal and bearing sliding surfaces by a lubricating film.

For low circumferential velocities up to approximately 30 m/s usually circular cylindrical bearings are applied. For these bearings a similar calculation method is given in ISO 7902-1, ISO 7902-2 and ISO 7902-3.

Based on practical experience the calculation procedure is usable for application cases where specific bearing load times circumferential speed,  $\bar{p} \cdot U_j$ , does not exceed approximately 200 MPa·m/s.

This document discusses multi-lobed journal bearings with two, three and four equal, symmetrical sliding surfaces, which are separated by laterally-closed lubrication pockets, and symmetrically-loaded tilting-pad journal bearings with four and five pads. Here, the curvature radii,  $R_B$ , of the sliding surfaces are usually chosen larger than half the bearing diameter,  $D$ , so that an increased bearing clearance results at the pad ends.

The calculation method described here can also be used for other gap forms, for example asymmetrical multi-lobed journal bearings like offset-halves bearings, pressure-dam bearings or other tilting-pad journal bearing designs, if the numerical solutions of the basic formulas are available for these designs.



# Plain bearings — Hydrodynamic plain journal bearings under steady-state conditions —

## Part 1: Calculation of multi-lobed and tilting pad journal bearings

### 1 Scope

This document specifies the general principles, assumptions and preconditions for the calculation of multi-lobed and tilting-pad journal bearings by means of an easy-to-use calculation procedure based on numerous simplifying assumptions. For a reliable evaluation of the results of this calculation method, it is indispensable to consider the physical implications of these assumptions as well as practical experiences for instance from temperature measurements carried out on real machinery under typical operating conditions. Applied in this sense, this document presents a simple way to predict the approximate performance of plain journal bearings for those unable to access more complex and accurate calculation techniques.

The calculation method serves for the design and optimisation of plain bearings, for example in turbines, compressors, generators, electric motors, gears and pumps. It is restricted to steady-state operation, i.e. in continuous operating states the load according to size and direction and the angular velocity of the rotor are constant.

Unsteady operating states are not recorded. The stiffness and damping coefficients of the plain journal bearings required for the linear vibration and stability investigations are indicated in ISO 31657-2 and ISO 31657-3.

**NOTE** Equivalent calculation procedures exist that enable operating conditions to be estimated and checked against acceptable conditions. The use of them is equally admissible.

### 2 Normative references

There are no normative references in this document.

### 3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

### 4 Symbols and units

[Table 1](#) contains the symbols used in the ISO 31657 series.

**Table 1 — Symbols and units**

| Symbol   | Description   | Unit |
|----------|---------------|------|
| <i>B</i> | Bearing width | m    |

Table 1 (continued)

| Symbol         | Description                                                                                                                                                                              | Unit     |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| $B^*$          | Relative bearing width, width ratio as given by: $B^* = \frac{B}{D}$                                                                                                                     | 1        |
| $b_p$          | Width of lubricant pocket                                                                                                                                                                | m        |
| $b_p^*$        | Relative width of lubricant pocket, as given by: $b_p^* = \frac{b_p}{B}$                                                                                                                 | 1        |
| $C_R$          | Bearing radial clearance, as given by: $C_R = R - R_j$                                                                                                                                   | m        |
| $C_{R,eff}$    | Effective radial bearing clearance                                                                                                                                                       | m        |
| $c_{ik}$       | Stiffness coefficient of lubricant film ( $i, k = 1, 2$ )                                                                                                                                | N/m      |
| $c_{ik}^*$     | Non-dimensional stiffness coefficient of lubricant film, as given by:<br>$c_{ik}^* = \frac{\psi_{eff}^3}{2 \cdot B \cdot \eta_{eff} \cdot \omega} \cdot c_{ik} (i, k = 1, 2)$            | 1        |
| $c_p$          | Specific heat capacity ( $p = \text{constant}$ )                                                                                                                                         | J/(kg K) |
| $D$            | Nominal bearing diameter (inside diameter of journal bearing)                                                                                                                            | m        |
| $D_{max}$      | Maximum value of $D$                                                                                                                                                                     | m        |
| $D_{min}$      | Minimum value of $D$                                                                                                                                                                     | m        |
| $D_j$          | Journal diameter (diameter of the shaft section located inside of a journal bearing)                                                                                                     | m        |
| $D_{j,max}$    | Maximum value of $D_j$                                                                                                                                                                   | m        |
| $D_{j,min}$    | Minimum value of $D_j$                                                                                                                                                                   | m        |
| $d_{ik}$       | Damping coefficient of lubricant film ( $i, k = 1, 2$ )                                                                                                                                  | N s/m    |
| $d_{ik}^*$     | Non-dimensional damping coefficient of lubricant film, as given by:<br>$d_{ik}^* = \frac{\psi_{eff}^3}{2 \cdot B \cdot \eta_{eff} \cdot \omega} \cdot \omega \cdot d_{ik} (i, k = 1, 2)$ | 1        |
| $e$            | Eccentricity (distance between journal and bearing axis)                                                                                                                                 | m        |
| $e_B$          | Eccentricity of the bearing sliding surfaces (pads) of a multi-lobed or tilting-pad journal bearing                                                                                      | m        |
| $F$            | Bearing force, bearing load, nominal bearing load, load-carrying capacity                                                                                                                | N        |
| $\Delta F_x$   | Component of additional dynamic force in $x$ -direction                                                                                                                                  | N        |
| $\Delta F_y$   | Component of additional dynamic force in $y$ -direction                                                                                                                                  | N        |
| $\Delta F_x^*$ | Component of additional dynamic force parameter in $x$ -direction, as given by:<br>$\Delta F_x^* = \frac{\Delta F_x \cdot \psi_{eff}^2}{B \cdot D \cdot \eta_{eff} \cdot \omega}$        | 1        |
| $\Delta F_y^*$ | Component of additional dynamic force parameter in $y$ -direction, as given by:<br>$\Delta F_y^* = \frac{\Delta F_y \cdot \psi_{eff}^2}{B \cdot D \cdot \eta_{eff} \cdot \omega}$        | 1        |
| $F_f$          | Friction force, as given by: $F_f = f \cdot F$                                                                                                                                           | N        |
| $F_f^*$        | Friction force parameter, as given by: $F_f^* = \frac{f}{\psi_{eff}} \cdot So$                                                                                                           | 1        |
| $F_{tr}$       | Bearing force at transition to mixed friction                                                                                                                                            | N        |
| $f$            | Coefficient of friction                                                                                                                                                                  | 1        |
| $f_j$          | Journal deflection                                                                                                                                                                       | m        |
| $h(\varphi)$   | Local lubricant film thickness                                                                                                                                                           | m        |

Table 1 (continued)

| Symbol                | Description                                                                                                                                                           | Unit            |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| $h^*(\varphi)$        | Relative local lubricant film thickness, as given by: $h^*(\varphi) = \frac{h(\varphi)}{C_R}$                                                                         | 1               |
| $h_{\text{lim,tr}}$   | Minimum admissible lubricant film thickness at transition to mixed friction                                                                                           | m               |
| $h_{\text{lim,tr}}^*$ | Minimum admissible relative lubricant film thickness at transition to mixed friction, as given by: $h_{\text{lim,tr}}^* = \frac{h_{\text{lim,tr}}}{C_{R,\text{eff}}}$ | 1               |
| $h_{\text{min}}$      | Minimum lubricant film thickness, minimum gap                                                                                                                         | m               |
| $h_{\text{min}}^*$    | Minimum relative lubricant film thickness, minimum relative gap, as given by: $h_{\text{min}}^* = \frac{h_{\text{min}}}{C_{R,\text{eff}}}$                            | 1               |
| $h_{\text{min,tr}}$   | Minimum lubricant film thickness at transition to mixed friction                                                                                                      | m               |
| $h_{\text{min,tr}}^*$ | Minimum relative lubricant film thickness at transition to mixed friction, as given by: $h_{\text{min,tr}}^* = \frac{h_{\text{min,tr}}}{C_{R,\text{eff}}}$            | 1               |
| $h_0(\varphi)$        | Local gap at $\varepsilon = 0$ , gap function                                                                                                                         | m               |
| $h_0^*(\varphi)$      | Relative local gap at $\varepsilon = 0$ , profile function, as given by: $h_0^*(\varphi) = \frac{h_0(\varphi)}{C_R}$                                                  | 1               |
| $h_{0,\text{max}}$    | Maximum gap at $\varepsilon = 0$                                                                                                                                      | m               |
| $h_{0,\text{max}}^*$  | Maximum relative gap at $\varepsilon = 0$ , gap ratio, as given by: $h_{0,\text{max}}^* = \frac{h_{0,\text{max}}}{C_R}$                                               | 1               |
| $K_P$                 | Profile factor (relative difference between lobe or pad bore radius and journal radius), as given by: $K_P = \frac{\Delta R_B}{C_R} = \frac{1}{1-m}$                  | 1               |
| $K_{P,\text{eff}}$    | Effective profile factor                                                                                                                                              | 1               |
| $K_{P,20}$            | Profile factor at 20 °C                                                                                                                                               | 1               |
| $M$                   | Mixing factor                                                                                                                                                         | 1               |
| $m$                   | Preload factor, preload of bearing or pad sliding surface                                                                                                             | 1               |
| $N$                   | Rotational speed (rotational frequency) of the rotor (revolutions per time unit)                                                                                      | s <sup>-1</sup> |
| $N_{\text{cr}}$       | Critical speed (critical rotational frequency)                                                                                                                        | s <sup>-1</sup> |
| $N_{\text{lim}}$      | Rotational speed (rotational frequency) at the stability speed limit of the rotor supported by plain bearings                                                         | s <sup>-1</sup> |
| $N_{\text{rsn}}$      | Resonance speed (resonance rotational frequency) of the rotor supported by plain bearings                                                                             | s <sup>-1</sup> |
| $N_{\text{tr}}$       | Rotational speed (rotational frequency) at transition to mixed friction, transition rotational speed, transition rotational frequency                                 | s <sup>-1</sup> |
| $O_B$                 | Centreline of plain bearing                                                                                                                                           | 1               |
| $O_i$                 | Centreline of sliding surface No. $i$                                                                                                                                 | 1               |
| $O_J$                 | Centreline of journal                                                                                                                                                 | 1               |
| $P_f$                 | Frictional power, as given by: $P_f = F_f \cdot U_J$                                                                                                                  | W               |
| $P_{\text{th,L}}$     | Heat flow via the lubricant                                                                                                                                           | W               |
| $p$                   | Lubricant film pressure, local lubricant film pressure                                                                                                                | Pa              |

Table 1 (continued)

| Symbol                     | Description                                                                                                                                          | Unit              |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| $\bar{p}$                  | Specific bearing load, as given by: $\bar{p} = \frac{F}{B \cdot D}$                                                                                  | Pa                |
| $p_{\text{en}}$            | Lubricant supply pressure                                                                                                                            | Pa                |
| $p_{\text{en}}^*$          | Lubricant supply pressure parameter, as given by: $p_{\text{en}}^* = \frac{p_{\text{en}} \cdot \psi_{\text{eff}}^2}{\eta_{\text{eff}} \cdot \omega}$ | 1                 |
| $p_{\text{lim}}$           | Maximum admissible lubricant film pressure                                                                                                           | Pa                |
| $\bar{p}_{\text{lim, tr}}$ | Maximum admissible specific bearing load at transition to mixed friction                                                                             | Pa                |
| $p_{\text{max}}$           | Maximum lubricant film pressure                                                                                                                      | Pa                |
| $p_{\text{max}}^*$         | Maximum lubricant film pressure parameter, as given by: $p_{\text{max}}^* = \frac{p_{\text{max}}}{\bar{p}}$                                          | 1                 |
| $\bar{p}_{\text{tr}}$      | Specific bearing load at transition to mixed friction, as given by: $\bar{p}_{\text{tr}} = \frac{F_{\text{tr}}}{B \cdot D}$                          | Pa                |
| $Q$                        | Lubricant flow rate, as given by: $Q = Q_3 + Q_p$                                                                                                    | m <sup>3</sup> /s |
| $Q_{\text{lim}}$           | Minimum admissible lubricant flow rate                                                                                                               | m <sup>3</sup> /s |
| $Q_p$                      | Lubricant flow rate due to supply pressure                                                                                                           | m <sup>3</sup> /s |
| $Q_p^*$                    | Lubricant flow rate parameter due to supply pressure, as given by: $Q_p^* = \frac{Q_p}{p_{\text{en}}^* \cdot Q_0}$                                   | 1                 |
| $Q_0$                      | Reference value of $Q$ , as given by: $Q_0 = R^3 \cdot \omega \cdot \psi_{\text{eff}}$                                                               | m <sup>3</sup> /s |
| $Q_1$                      | Lubricant flow rate at the entrance into the lubrication gap (circumferential direction)                                                             | m <sup>3</sup> /s |
| $Q_2$                      | Lubricant flow rate at the exit of the lubrication gap (circumferential direction), as given by: $Q_2 = Q_1 - Q_3$                                   | m <sup>3</sup> /s |
| $Q_2^*$                    | Lubricant flow rate parameter at the exit of the lubrication gap (circumferential direction), as given by: $Q_2^* = \frac{Q_2}{Q_0}$                 | 1                 |
| $Q_3$                      | Lubricant flow rate due to hydrodynamic pressure build-up (side flow rate)                                                                           | m <sup>3</sup> /s |
| $Q_3^*$                    | Lubricant flow rate parameter due to hydrodynamic pressure build-up (side flow parameter), as given by: $Q_3^* = \frac{Q_3}{Q_0}$                    | 1                 |
| $R$                        | Journal bearing inside radius, as given by: $R = \frac{D}{2}$                                                                                        | m                 |
| $R_B$                      | Lobe or pad bore radius of a multi-lobed or tilting-pad journal bearing                                                                              | m                 |
| $\Delta R_B$               | Difference between lobe or pad bore radius and journal radius, as given by: $\Delta R_B = R_B - R_j$                                                 | m                 |
| $R_j$                      | Journal radius (radius of the shaft section located inside of a journal bearing), as given by: $R_j = \frac{D_j}{2}$                                 | m                 |
| $Rz_B$                     | Surface finish ten-point average of bearing sliding surface                                                                                          | m                 |
| $Rz_j$                     | Surface finish ten-point average of journal sliding surface                                                                                          | m                 |
| $Re$                       | Reynolds number, as given by: $Re = \frac{\rho \cdot \omega \cdot R \cdot C_{R, \text{eff}}}{\eta_{\text{eff}}}$                                     | 1                 |
| $Re_{\text{cr}}$           | Critical Reynolds number                                                                                                                             | 1                 |
| $So$                       | Sommerfeld number, as given by: $So = \frac{F \cdot \psi_{\text{eff}}^2}{B \cdot D \cdot \eta_{\text{eff}} \cdot \omega}$                            | 1                 |

Table 1 (continued)

| Symbol             | Description                                                                                                                                                                                                                                | Unit |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| $So_{tr}$          | Sommerfeld number at transition to mixed friction                                                                                                                                                                                          | 1    |
| $S$                | Displacement amplitude of the rotor (mechanical oscillation)                                                                                                                                                                               | m    |
| $T$                | Temperature                                                                                                                                                                                                                                | °C   |
| $\Delta T$         | Heating of lubricant between bearing entrance and exit, as given by: $\Delta T = T_{ex} - T_{en}$                                                                                                                                          | K    |
| $\Delta T_{lim}$   | Maximum admissible heating of lubricant between bearing entrance and exit                                                                                                                                                                  | K    |
| $T_B$              | Bearing temperature                                                                                                                                                                                                                        | °C   |
| $T_{eff}$          | Effective temperature of lubricant film                                                                                                                                                                                                    | °C   |
| $T_{en}$           | Lubricant temperature at the bearing entrance                                                                                                                                                                                              | °C   |
| $T_{ex}$           | Lubricant temperature at the bearing exit                                                                                                                                                                                                  | °C   |
| $T_j$              | Journal temperature                                                                                                                                                                                                                        | °C   |
| $T_{lim}$          | Maximum admissible bearing temperature                                                                                                                                                                                                     | °C   |
| $T_{max}$          | Maximum temperature of lubricant film                                                                                                                                                                                                      | °C   |
| $\Delta T_{max}$   | Difference between maximum temperature of lubricant film and lubricant temperature in the lubricant pocket, as given by: $\Delta T_{max} = T_{max} - T_1$                                                                                  | K    |
| $\Delta T_{max}^*$ | Non-dimensional difference between maximum temperature of lubricant film and lubricant temperature in the lubricant pocket, as given by: $\Delta T_{max}^* = \frac{\rho \cdot c_p \cdot \psi_{eff}}{\bar{p} \cdot f} \cdot \Delta T_{max}$ | 1    |
| $T_1$              | Lubricant temperature at the entrance into the lubrication gap (circumferential direction)                                                                                                                                                 | °C   |
| $\Delta T_1$       | Difference between lubricant temperature at the entrance into the lubrication gap and lubricant temperature at the bearing entrance, as given by: $\Delta T_1 = T_1 - T_{en}$                                                              | K    |
| $T_2$              | Lubricant temperature at pressure profile trailing edge (circumferential direction)                                                                                                                                                        | °C   |
| $\Delta T_2$       | Difference between lubricant temperature at pressure profile trailing edge and lubricant temperature at the entrance into the lubrication gap, as given by: $\Delta T_2 = T_2 - T_1$                                                       | K    |
| $t$                | Time                                                                                                                                                                                                                                       | s    |
| $U_j$              | Circumferential speed of the journal, sliding velocity<br>$U_j = \omega \cdot R_j$                                                                                                                                                         | m/s  |
| $U_{tr}$           | Circumferential speed at transition to mixed friction                                                                                                                                                                                      | m/s  |
| $U_{lim, tr}$      | Minimum admissible circumferential speed at transition to mixed friction                                                                                                                                                                   | m/s  |
| $u$                | Velocity component in the $\varphi$ -direction                                                                                                                                                                                             | m/s  |
| $\bar{u}$          | Average velocity component in the $\varphi$ -direction                                                                                                                                                                                     | m/s  |
| $w$                | Velocity component in the z- direction                                                                                                                                                                                                     | m/s  |
| $\bar{w}$          | Average velocity component in the z-direction                                                                                                                                                                                              | m/s  |
| $x$                | Coordinate of journal radial motion, normal to direction of load                                                                                                                                                                           | m    |
| $x^*$              | Relative coordinate of journal radial motion, normal to direction of load, as given by:<br>$x^* = \frac{x}{C_R}$                                                                                                                           | 1    |
| $y$                | Coordinate normal to sliding surface (across the lubricant film, in the radial direction); coordinate of journal radial motion, in direction of load                                                                                       | m    |
| $y^*$              | Relative coordinate of journal radial motion, in direction of load, as given by: $y^* = \frac{y}{C_R}$                                                                                                                                     | 1    |
| $y_h$              | Coordinate normal to sliding surface (across the lubricant film)                                                                                                                                                                           | m    |
| $Z$                | Number of sliding surfaces (pads), number of pockets per bearing                                                                                                                                                                           | 1    |
| $z$                | Coordinate parallel to the sliding surface, normal to direction of motion (normal to circumferential direction, in the axial direction)                                                                                                    | m    |

Table 1 (continued)

| Symbol            | Description                                                                                                                                                                       | Unit              |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| $\alpha_{l,B}$    | Linear thermal expansion coefficient of bearing material                                                                                                                          | K <sup>-1</sup>   |
| $\alpha_{l,J}$    | Linear thermal expansion coefficient of journal material                                                                                                                          | K <sup>-1</sup>   |
| $\beta$           | Attitude angle (angular position of journal eccentricity related to the direction of load)                                                                                        | °                 |
| $\beta_{h,min}$   | Angle between direction of load and position of minimum lubricant film thickness                                                                                                  | °                 |
| $\delta_j$        | Journal misalignment angle (angular deviation of journal)                                                                                                                         | °                 |
| $\varepsilon$     | Relative eccentricity: $\varepsilon = \frac{e}{C_{R,eff}}$                                                                                                                        | 1                 |
| $\eta$            | Dynamic viscosity of the lubricant                                                                                                                                                | Pa s              |
| $\eta_{eff}$      | Effective dynamic viscosity in the lubricant film                                                                                                                                 | Pa s              |
| $\rho$            | Density of the lubricant                                                                                                                                                          | kg/m <sup>3</sup> |
| $\varphi$         | Angular coordinate in circumferential direction                                                                                                                                   | °                 |
| $\varphi_F$       | Angular coordinate of pivot position of pad (tilting-pad bearing)                                                                                                                 | °                 |
| $\varphi_P$       | Angular coordinate of lubricant pocket centreline                                                                                                                                 | °                 |
| $\varphi_0$       | Angular coordinate of bearing sliding surface (segment or pad) centreline at multi-lobed or tilting-pad journal bearings (with non-tilted pads), see <a href="#">Figure 1, a)</a> | °                 |
| $\varphi_1$       | Angular coordinate at the entrance into the gap                                                                                                                                   | °                 |
| $\varphi_2$       | Angular coordinate at the end of the hydrodynamic pressure build-up                                                                                                               | °                 |
| $\varphi_3$       | Angular coordinate at the exit of the gap                                                                                                                                         | °                 |
| $\psi$            | Relative bearing clearance, as given by: $\psi = \frac{C_R}{R}$                                                                                                                   | ‰                 |
| $\Delta\psi$      | Tolerance of $\psi$ , as given by: $\Delta\psi = \psi_{max} - \psi_{min}$                                                                                                         | ‰                 |
| $\psi_{eff}$      | Effective relative bearing clearance                                                                                                                                              | ‰                 |
| $\psi_{max}$      | Maximum value of $\psi$                                                                                                                                                           | ‰                 |
| $\psi_{min}$      | Minimum value of $\psi$                                                                                                                                                           | ‰                 |
| $\Delta\psi_{th}$ | Thermal change of $\psi$                                                                                                                                                          | ‰                 |
| $\psi_{20}$       | Relative bearing clearance at 20 °C                                                                                                                                               | ‰                 |
| $\Omega$          | Angular span of bearing sliding surface (segment or pad), as given by: $\Omega = \varphi_3 - \varphi_1$                                                                           | °                 |
| $\Omega_F$        | Angular distance between leading edge and pivot position of pad (tilting-pad bearing), as given by: $\Omega_F = \varphi_F - \varphi_1$                                            | °                 |
| $\Omega_F^*$      | Relative angular distance between leading edge and pivot position of pad (tilting-pad bearing), as given by: $\Omega_F^* = \Omega_F / \Omega$                                     | 1                 |
| $\Omega_P$        | Angular span of lubricant pocket, as given by: $\Omega_P = \frac{360^\circ}{Z} - \Omega$                                                                                          | °                 |
| $\omega$          | Angular speed of the rotor, as given by: $\omega = 2 \cdot \pi \cdot N$                                                                                                           | s <sup>-1</sup>   |
| $\omega_{tr}$     | Angular speed at transition to mixed friction                                                                                                                                     | s <sup>-1</sup>   |

## 5 General principles, assumptions and preconditions

The bearing bore form of multi-lobed journal bearings [see [Figure 1, a\)](#)] and tilting-pad journal bearings [with non-tilted pads according to [Figure 1, b\)](#)] is described by the profile function  $h_0^*(\varphi) = \frac{h_0(\varphi)}{C_R}$  in the