



DPC: 25/30475278 DC

BSI Group Headquarters

389 Chiswick High Road London W4 4AL

Tel: +44 (0)20 8996 9000

Fax: +44 (0)20 8996 7400

www.bsigroup.com

Date: 17 July 2025

Origin: International

Latest date for receipt of comments: 09 September 2025

Project No. 2023/01295

Responsible committee: NCE/3

Interested committees:

Title: Draft BS ISO 18075 Reactor technology - Power reactor analysis - Steady-state neutronics methods.

Please notify admin.start@bsigroup.com if you are aware of any keywords that might assist in clarifying or identifying the standard or of the content of this standard:

- i) has any issues related to 3rd party IPR, patent or copyright
- ii) affects other national standard(s)
- iii) requires additional national guidance or information

WARNING: THIS IS A DRAFT AND MUST NOT BE REGARDED OR USED AS A BRITISH STANDARD. THIS DRAFT IS NOT CURRENT BEYOND 09 September 2025

This draft is issued to allow comments from interested parties; all comments will be given consideration prior to publication. No acknowledgement will normally be sent. **See overleaf for information on the submission of comments.**

No copying is allowed, in any form, without prior written permission from BSI except as permitted under the Copyright, Designs and Patent Act 1988 or for circulation within a nominating organization for briefing purposes. Electronic circulation is limited to dissemination by e-mail within such an organization by committee members.

Further copies of this draft may be purchased from BSI Shop <http://shop.bsigroup.com> or from BSI Customer Services, Tel: +44(0) 20 8996 9001 or email cservices@bsigroup.com. British, International and foreign standards are also available from BSI Customer Services.

Information on the co-operating organizations represented on the committees referenced above may be obtained from <https://standardsdevelopment.bsigroup.com/>.

E-mail: admin.start@bsigroup.com

Introduction

This draft standard is based on national and international discussions. Your comments on this draft are invited and will assist in the preparation of the consequent standard.

For international standards, comments will be reviewed by the relevant UK national committee before sending the consensus UK vote and comments to the international committee, which will then decide appropriate action. If the international standard is approved, it is usual for the text to be published as a British Standard.

For national standards, comments will be reviewed by the relevant UK national committee and the resulting standards published as a British Standard.

UK Vote

Please indicate whether you consider the UK should submit a negative (with supporting technical reasons) or positive vote on this draft. Please indicate if you are aware of any reason why this draft standard should not be published as a British Standard.

Submission of Comments

- **Annotated drafts are not acceptable and will be rejected.**
- All comments should be submitted online at <https://standardsdevelopment.bsigroup.com/>. You will need to register in order to comment.

Template for comments and secretariat observations

Date: xx/xx/20xx	Document: ISO/DIS xxxx
------------------	------------------------

1	2	(3)	4	5	(6)	7
MB	Clause No./ Subclause No./Annex (e.g. 3.1)	Paragraph/ Figure/Table/Note	Type of comment	Comment (justification for change) by the MB	Proposed change by the MB	Secretariat observations on each comment submitted
	3.1	Definition 1	ed	Definition is ambiguous and needs clarifying.	Amend to read '...so that the mains connector to which no connection...'	
	6.4	Paragraph 2	te	The use of the UV photometer as an alternative cannot be supported as serious problems have been encountered in its use in the UK.	Delete reference to UV photometer.	



DRAFT International Standard

ISO/DIS 18075

Reactor technology - Power reactor analysis - Steady-state neutronics methods

ICS: 27.120.10

ISO/TC 85/SC 6

Secretariat: **DIN**

Voting begins on:
2025-07-17

Voting terminates on:
2025-10-09

This document is circulated as received from the committee secretariat.

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENTS AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

Reference number
ISO/DIS 18075:2025(en)

Full document details: 25/30475278 DC

© ISO 2025  **Documents**
Document Sharing Hub



COPYRIGHT PROTECTED DOCUMENT

© ISO 2025

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms, definitions and abbreviations	1
3.1 Terms	1
3.2 Abbreviations	5
4 Relation to other standards	5
5 Methods of calculation	6
5.1 General	6
5.2 Conditions to be considered	6
5.3 Multi-group cross sections	7
5.3.1 Basic data	7
5.3.2 Preparation of multi-group constants	7
5.3.3 System dependent spectrum calculations	7
5.3.4 Choice of cell and supercell	7
5.3.5 Cell environment	8
5.3.6 Calculation model	8
5.4 Collapse to few-groups and spatial homogenization	8
5.5 Calculation of reactivity, reaction rates, and neutron flux distributions	9
5.5.1 Models	9
5.5.2 Uncertainties and assumptions	9
5.6 Calculation of reaction rates in reactor components	10
5.7 Depletion calculations	10
5.8 Common practices	12
5.8.1 General	12
5.8.2 PWR core physics methods	12
5.8.3 BWR core physics methods	13
5.8.4 LMR core physics methods	15
5.8.5 PHWR core physics methods	17
5.8.6 HTGR core physics methods	19
6 Verification and validation of the calculation system	20
6.1 Overview	20
6.2 Verification	20
6.2.1 General	20
6.2.2 Unit testing	20
6.2.3 Integral testing	21
6.3 Validation	21
6.3.1 Overview	21
6.3.2 Unit Testing	21
6.3.3 Integral testing	22
6.3.4 Code to code comparisons	22
6.4 Biases and uncertainties	23
7 Documentation	23
8 Summary of requirements	24
Annex A (informative) Computer Codes in Common Use	25
Bibliography	32

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 85, *Nuclear Energy, Nuclear Technologies, and Radiological Protection*, Subcommittee SC 6, *Reactor Technology*. This document is based on a standard developed by the American Nuclear Society (ANS) of which the current version is ANSI/ANS-19.3-2022^[2].

The main changes compared to the previous edition are as follows:

- addition of new terms in [Clause 3](#);
- figures slightly revised;
- [5.8.5](#) was amended so that CANDU is only an example;
- Correction of internal references;
- [Table A.1](#) corrected;
- editorial amendments in the whole document;

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The design and operation of nuclear reactors require knowledge of the conditions under which a reactor will be critical, as well as the degree of subcriticality or supercriticality when these conditions change. In addition, knowledge is required of the spatial distribution of neutron reaction rates in reactor components as a prerequisite, for example, for inferring proper power and temperature distributions to ensure the satisfaction of thermal-limit and safety-limit requirements. Both reaction-rate spatial distributions and reactivity can be and have been measured by suitable experimental techniques, either in mock-ups or in the operating reactors themselves. These quantities can also be calculated by various techniques. Available reactor experimental data have been used to validate the steady-state neutronic calculations within reasonable margins. As more accurate nuclear cross sections and improved calculation methods have become available, steady-state neutronic calculations have been utilized extensively for nuclear fuel and core designs and analyses and thus have become increasingly important.

Reactor technology - Power reactor analysis - Steady-state neutronics methods

1 Scope

This document provides guidance for performing and validating the sequence of steady-state calculations leading to prediction in all types of operating commercial nuclear reactors, of the following:

- reaction-rate spatial distributions;
- reactivity;
- change of nuclide compositions with time.

The document provides the following:

- a) guidance for the selection of computational methods;
- b) criteria for verification and validation of calculation methods used by reactor core analysts;
- c) criteria for evaluation of accuracy and range of applicability of data and methods;
- d) requirements for documentation of the preceding.

2 Normative references

There are no normative references in this document.

3 Terms, definitions and abbreviations

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1 Terms

3.1.1

application-dependent multigroup

discrete energy-group structure that is intermediate between the application-independent multigroup structure and a few-group structure

Note 1 to entry: The application-dependent multigroup structure can be such that the group constants are dependent on reactor composition through an estimated neutron energy spectrum. An application dependent multigroup data set is one type of averaged data set.

3.1.2

application-independent multigroup

discrete energy-group structure that is sufficiently detailed that the group constants may be considered as being independent of reactor composition, geometry, or spectrum for a wide range of reactor analysis

Note 1 to entry: The application-independent multigroup structure can be employed directly in reactor-design spectrum calculations, or it can be employed to generate group constants in an application-dependent multigroup structure. An application-independent multigroup data set is one type of averaged data set.

3.1.3**averaged data set**

data set prepared by averaging an evaluated data set or a processed continuous-energy data set with a specified weighting function over a specified energy group structure

Note 1 to entry: The group structure and weighting functions may be selected to be application dependent or application independent, e.g. light water reactors (LWRs), are dealt with in ANSI/ANS 19.1 2019^[1]

3.1.4**cell****supercell**

one or more reactor components with associated coolant (and possibly additional moderator and structural material) that, for computational purposes, are assumed to form a spatially repeating array in the reactor

Note 1 to entry: The simplest example of a cell is the “pin cell” in which a single fuel rod or pin is surrounded by coolant (e.g. light water, heavy water, or sodium). Another example is a bundle of fuel rods cooled by heavy water within a housing, surrounded by a heavy water moderator space.

Note 2 to entry: More complex geometric configurations are also used for some applications. These are often referred to as “supercells”, or sometimes “(fuel) assembly cells”, although the exact definition of the term varies greatly between reactor types and is even somewhat subjectively defined for a particular reactor type. Supercells, in the context of this document, represent more complex “cell” configurations that involve a collection of contiguous cells forming an assumed repeating array within the reactor, or augmented cells incorporating additional regions to serve as a computational artifice, e.g. to account for significant spectrum effects due to compositions outside the cell, or cell configurations including a reactivity device in addition to fuel, coolant, moderator and poison.

3.1.5**collapse**

method by which a many energy group set of cross sections is reduced to fewer energy groups

3.1.6**data set (or dataset)**

collection of microscopic cross sections and nuclear constants encompassing the range of materials and reaction processes needed for the application area of interest.

3.1.7**dilution cross section**

cross section, which refers to a background cross section that represents the effects of other isotopes in a material, particularly in the context of self-shielding in nuclear reactions

3.1.8**evaluated data set**

data set that is completely and uniquely specified over the ranges of energy and angles important to reactor calculations

Note 1 to entry: Such a data set is based upon available information (experimental measurement results and nuclear theories) and employs a judgment as to the best physical description of the interaction processes. An evaluated data set is intended to be independent of reactor composition, geometries, energy group structures, and spectra.

3.1.9**experimental data**

any experimentally measured quantity or quantities

Note 1 to entry: As such it is applied herein to both differential cross-section measurements and integral measurements (e.g. control-rod worth) obtained from reactor experiments or operations.

3.1.10**few-group**

energy-group (typically two-group) structure that is adopted for a particular application

Note 1 to entry: The few-group constants for a region are dependent on a specific reactor composition and geometry through a calculated energy spectrum, and are also dependent on other conditions such as pressure, temperature, Xenon concentration, void fraction, etc.

3.1.11

fine group

energy group structure (typically hundreds of groups for LWR, thousands for LFMR) that is adopted for a particular application.

Note 1 to entry: The fine-group constants are dependent on temperature.

3.1.12

lattice

normally refers to an array of cells

3.1.13

lumped pseudo fission product

fictitious fission product that is used in depletion calculations to represent a combination of certain minor fission products that are not tracked in an explicit fission product model

Note 1 to entry: A lumped pseudo fission product is characterized by effective neutron cross sections and decay constants.

3.1.14

methods of calculation

mathematical equations, approximations, assumptions, associated numerical parameters, and calculational procedures that yield the calculated results

Note 1 to entry: When more than one step is involved in the calculation, the entire sequence of steps comprises the "calculation method".

3.1.15

multigroup

more than a few groups, can be hundreds or thousands of energy groups

3.1.16

probability table parameters

parameters for a probability table that is used to process cross sections in the unresolved resonance energy range

3.1.17

processed continuous-energy data set

data set prepared by expansion or compaction of an evaluated data set using specified algorithms

Note 1 to entry: Such a data set is intended to be independent of reactor composition, geometries, and spectra.

3.1.18

quasi-steady state condition

evolution of reactivity and flux is sufficiently low between two time intervals such that we can consider that the core is under a succession of static states.

3.1.19

reaction rate

rate at which neutrons interact with nuclei at a point in the reactor, a volume of the phase space or as an integral over the reactor, according to the context

EXAMPLE The reaction rate for absorption, scattering, and fission.

3.1.20**reactivity**

reactivity means the quantity (1 minus the eigenvalue, λ , of the steady-state neutron balance equation), written as

$$M\Phi = \lambda F\Phi$$

where

- Φ is the neutron flux;
- F is the neutron fission yield operator; and
- M is the scattering, absorption, and leakage operator.

Note 1 to entry: The effective multiplication factor k_{eff} is the inverse of λ . Reactivity is a unitless, pure number. It is, however, often written in terms of smaller “units”, such as milli-k = 0,001, pcm = 0,000 01 = 10^{-5} or “dollars” (and cents), where 1 dollar is taken as the value of the delayed neutron fraction in the system of interest.

3.1.21**time-average model (CANDU)**

time-average cell-homogenized few-group macroscopic cross sections at each bundle location in the core are calculated as flux-weighted quantities over the fluence range experienced by the fuel during its residence at that specific location

Note 1 to entry: Consequently, the flux, fluence range, and macroscopic cross sections at each location are linked together and depend on the individual refueling rate of the channel in which the fuel bundle resides. The resulting self-consistency problem is solved iteratively to determine all the results of the time-average model.

Note 2 to entry: The CANada Deuterium Uranium (CANDU) reactor time-average model is also known as the equilibrium-core model.

3.1.22**ultrafine group**

energy group structure (typically ten thousand energy groups) that may allow to explicitly describe the resolved resonances

Note 1 to entry: The ultrafine-group constants can be dependent on temperature when they include narrow-resonance reactions.

3.1.23**experimental validation**

process of determining the degree to which a model is an accurate representation of the real world from the perspective of the intended uses of the model

3.1.24**numerical validation**

process of determining the degree to which a model is accurate by comparison to a previously validated code system

3.1.25**verification**

process of determining that a model implementation accurately represents the developer's conceptual description of the model and the solution to the model

3.2 Abbreviations

BWR	boiling water reactor
CANDU	CANada Deuterium Uranium (reactor)
HTGR	high temperature gas cooled reactor
LMR	liquid metal reactor
LWR	light water reactor
PHWR	pressurized heavy water reactor
PWR	pressurized water reactor

4 Relation to other standards

The following American National Standards are related to this document:

- *Nuclear Data Sets for Reactor Design Calculations*, ANSI/ANS-19.1-2019,^[1] defines the criteria to be employed in the preparation of application-independent cross-section data files from experimental data and theoretical models. This document covers subsequent space and energy averaging processes that may be employed to prepare cross sections for use in the representation of the core and its environment, and the subsequent calculation of the spatial distribution of neutron reaction rates in the core and of the core reactivity. There may be many ways of carrying out the space and energy averaging to obtain few-group cross sections, and no unique path for the preparation or use of cross sections employed in design calculations is defined, required, or recommended by this standard.
- *A Guide for Acquisition and Documentation of Reference Power Reactor Physics Measurements for Nuclear Analysis Verification*, ANSI/ANS-19.4–2017 (R2022) ^[3]; and *Requirements for Reference Reactor Physics Measurements*, ANSI/ANS 19.5-1995; W2005^[4].

Validation of calculation systems requires comparison with available experimental results. The preceding standards contain criteria for performing and documenting such experiments, in order to be most useful for this purpose.

- *Determination of Thermal Energy Deposition Rates in Nuclear Reactors*, ANSI/ANS 19.3.4–2002 R2017,^[5] provides criteria for the establishment of the thermal energy deposition rate distribution within a nuclear reactor core. Since the accuracy with which this can be done is dominated by the accuracy with which neutron reaction rates can be calculated, ANSI/ANS-19.3.4–2002; R2017 is closely related to ANSI/ANS-19.3–2022.
- *Quality Assurance Program Requirements for Nuclear Facility Applications*, ANSI/ASME-NQA 1 2022.^[6] This standard deals with quality assurance, including that for computer programs.
- *Verification and Validation of Non-Safety Related Scientific and Engineering Computer Programs for the Nuclear Industry*, ANSI/ANS-10.4–2008 (R2021).^[9] This standard deals with requirements for verifying and validating computer codes, such as those used for neutronics calculations.
- *Accommodating User Needs in Scientific and Engineering Computer Software*, ANSI/ANS-10.5–2006; R2021.^[10] This standard deals with methods to respond to users' requirements in computer programs.