



ANSI/ABMA 22.2:1988 (Stabilized Maintenance 2010)
AMERICAN NATIONAL STANDARD

*Accredited Standards
Committee B3*



Spherical Plain Radial Bearings, Joint Type Inch Design



Secretariat

**American Bearing
Manufacturers Association**

ANSI/ABMA 22.2:1988

Stabilized Maintenance 2010



ABMA
2025 M Street, NW
Suite 800
Washington, DC 20036
Ph: 202-367-1155
Fax: 202-367-2155
E-mail: info@americanbearings.org
www.americanbearings.org

AMERICAN NATIONAL STANDARD

(This is not an approved part of the standard)

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus means substantial agreement has been reached by directly and materially affected interests. This signifies the concurrence of more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that an effort be made toward their resolution.

The use of an American National Standard is completely voluntary; their existence does not in any respect preclude anyone, whether they approved the standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standard.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat of the sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time.

This standard is maintained under stabilized maintenance and will be reviewed by Accredited Standards Committee B3 on a 10-year cycle. Any materially affected and interested party that feels this standard should be revised or withdrawn should submit their rationale for revision or withdrawal to the B3 Secretariat at the address below.

Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute or online at www.ANSI.org.

Published by

American Bearing Manufacturers Association
2025 M Street, N.W., Suite 800
Washington, DC 20036
Copyright © 2011 by American Bearing Manufacturers Association

All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

SPHERICAL PLAIN RADIAL BEARINGS, JOINT TYPE Inch Design

CONTENTS

Section	Page
1. Scope	1
2. Reference ANSI/ABMA Standards.....	1
3. Terminology	1
4. Symbols	3
5. Boundary Dimensions	4
6. Tolerances	8

LIST OF TABLES

Table No.	Page
BOUNDARY DIMENSIONS	
1	Series 1, Swaged Style—Narrow
	Chamfered Outer Ring—Dimensions shown in mm & inches 4
	Face Groove Outer Ring—Dimensions shown in mm & inches 4
2	Series 2, Swaged Style—Wide
	Chamfered Outer Ring—Dimensions shown in mm & inches 5
	Face Grooved Outer Ring—Dimensions shown in mm & inches 5
3	Series 3, Fractured Style
	Part I—Dimensions shown in mm 6
	Part 2—Dimensions shown in inches.....7
BEARING TOLERANCES	
4	Series 1 & 2, Swaged Style—Narrow & Wide 8
	Series 3, Fractured Style 9

SPHERICAL RADIAL PLAIN BEARINGS, JOINT TYPE

Inch Design

1. SCOPE

1.1 General. This standard for spherical bearings, joint type (without rolling elements) has been established for the purpose of defining the characteristics of these bearings such as boundary dimensions, tolerances and terminology. This style of bearing consists of an outer ring having an inner concave sphered sliding contact surface and an inner ring having a matched outer convex sphered sliding contact surface. Two general styles, related to manufacturing method are included, swaged (1.2) and fractured (1.3).

1.2 Swaged. This style of bearing is manufactured utilizing a "swaging" or forming of the outer ring over the inner ring (ball). These bearings are Series 1 and 2 in this Standard.

1.3 Fractured. This style of bearing has the outer ring split or fractured in one position to facilitate manufacturing assembly of the rings. These bearings are Series 3 in this Standard.

2. REFERENCE ANSI/AFBMA STANDARDS

2.1 ANSI/ABMA Std. 4, Tolerance Definitions and Gaging Practices for Ball and Roller Bearings.

3. TERMINOLOGY

3.1 Types of Bearings

3.1.1 Spherical Plain Bearing, Joint Type. A spherical plain bearing designed primarily to accommodate oscillatory, tilting and low speed rotational movements. Sliding motion is accommodate at the spherical contact surface and/or at the inner ring bore.

3.1.1.1 Spherical Plain Radial Bearings. A spherical plain bearing intended to support radial load.

3.1.1.2 Spherical Plain Angular Contact Bearing. A spherical plain bearing intended to support a combination of radial and axial loads. (Not covered by this Standard at this time.)

3.1.1.3 Spherical Plain Thrust Bearing. A spherical plain bearing intended to support primarily axial loads. (Not covered by this Standard at this time.)

3.2 Bearing Components

3.2.1 Inner Ring. That part of a spherical plain bearing, joint type, having a convex sphered outer surface and a cylindrical inside surface.

3.2.2 Outer Ring. That part of a spherical plain bearing, joint type, having a concave sphered inner surface and a cylindrical outside surface.

3.2.2.1 One Piece Outer Ring. An outer ring manufactured and assembled in one piece., i.e., not divided or split in anyway.

3.2.2.2 Swaged Outer Ring. A one piece outer ring manufactured by deformation of the outer ring material around the inner ring to obtain the sphered inner surface.

3.2.2.3 Single Fractured Outer Ring. An outer ring manufactured in one piece and subsequently split or fractured in one position in an axial plane, to facilitate manufacturing assembly.

3.3 Features

3.3.1 Bore Cylindrical Surface. The inside surface of an inner ring having a basically cylindrical form.

3.3.2 Outside Cylindrical Surface. The outside surface of an outer ring having a basically cylindrical form.

3.3.3 Sphered Outer Surface. That surface of an inner ring intended to make sliding contact with an outer ring and having the form of part of the outside surface of a sphere whose center lies on the bearing axis.

3.3.4 Sphered Inner Surface. That surface of an outer ring intended to make sliding contact with an inner ring and having the form of part of the inside surface of a hollow sphere whose center lies on the bearing axis.