

Orifice Metering of Natural Gas and Other Related Hydrocarbon Fluids— Concentric, Square-edged Orifice Meters

Part 1: General Equations and Uncertainty Guidelines



American Gas Association

AGA Report No. 3
Part 1



AMERICAN PETROLEUM INSTITUTE

Manual of Petroleum
Measurement Standards
Chapter 14.3.1

American Gas Association
400 North Capitol Street, NW
Washington, DC 20001

American Petroleum Institute
1220 L Street, NW
Washington, DC 20005

FOURTH EDITION, SEPTEMBER 2012

An American National Standard
ANSI/API MPMS Ch. 14.3.1/AGA Report No. 3, Part 1

Special Notes

This AGA/API publication necessarily addresses problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither AGA and API nor any of AGA's or API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither AGA and API nor any of AGA's or API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

This AGA/API publication may be used by anyone desiring to do so. Every effort has been made by AGA/API to assure the accuracy and reliability of the data contained in it; however, AGA/API makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

This AGA/API publication is published to facilitate the broad availability of proven, sound engineering and operating practices. It is not intended to obviate the need for applying sound engineering judgment regarding when and where this publication should be utilized. The formulation and publication of this AGA/API publication is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from either the American Gas Association, 400 N. Capitol St., NW, Washington, DC 20001 or API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

Copyright © 2012 American Gas Association and American Petroleum Institute

Foreword

Nothing contained in this AGA/API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as API *Manual of Petroleum Measurement Standard (MPMS)* Chapter 14.3.1 and AGA Report No. 3, Part 1. Questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Questions concerning the interpretation of the content of this publication should be directed to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005 and to the Vice President, Operations and Engineering, American Gas Association, 400 N. Capitol Street, NW, Washington, DC 20001, and shall be handled in accordance with API's *Procedures for Standards Development*. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the Director of Standards, American Petroleum Institute (as above) or the Vice President, Operations and Engineering, American Gas Association (as above).

This AGA/API publication is reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

A catalog of AGA Operations and Engineering publications, which is published and updated as needed and can be obtained by contacting AGA Operations and Engineering Department, phone (202) 824-7000 or web site http://www.aga.org/Pages/contact_us.aspx.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org or Operations and Engineering Department, American Gas Association, 400 North Capitol Street, NW, Washington, DC 20001, http://www.aga.org/Pages/contact_us.aspx.

Contents

	Page
1 Introduction	1
1.1 Scope	1
1.2 Organization of Standard	1
2 Normative References	2
3 Terms, Definitions, and Symbols	3
3.1 Terms and Definitions	3
3.2 Symbols	7
4 Field of Application	8
4.1 Applicable Fluids	8
4.2 Types of Meters	9
4.3 Uncertainty of Measurement	10
5 Method of Calculation	10
6 Orifice Flow Equation	10
6.1 Velocity of Approach Factor (E_v)	12
6.2 Orifice Plate Bore Diameter (d)	12
6.3 Meter Tube Internal Diameter (D)	12
7 Empirical Coefficient of Discharge	13
7.1 Regression Database	14
7.2 Empirical Coefficient of Discharge Equation for Flange-tapped Orifice Meters	15
7.3 Reynolds Number (Re_D)	16
7.4 Flow Conditions	16
7.5 Pulsating Flow	17
8 Empirical Expansion Factor (Y) for Flange-tapped Orifice Meters	19
8.1 Upstream Expansion Factor (Y_1)	20
8.2 Downstream Expansion Factor (Y_2)	21
9 In-situ Calibration	22
9.1 General	22
9.2 Meter Factor (MF)	22
10 Fluid Physical Properties	23
10.1 Viscosity (μ)	23
10.2 Density ($\rho_{t,p}$, ρ_b)	23
10.3 Isentropic Exponent (κ)	24
11 Unit Conversion Factors	24
11.1 Orifice Flow Equation	24
11.2 Reynolds Number Equation	25
11.3 Expansion Factor Equation	25
11.4 Flow Rate per Unit of Time Conversion	25
12 Practical Uncertainty Guidelines	28
12.1 General	28
12.2 Uncertainty Over a Flow Range	28
12.3 Uncertainty of Flow Rate	28
12.4 Typical Uncertainties	31
12.5 Example Uncertainty Calculations	37

Contents

Page

Annex A (informative) Discharge Coefficients for Flange-tapped Orifice Meters	40
Annex B (informative) Adjustments for Instrument Calibration and Use	51
Annex C (informative) Buckingham and Bean Empirical Expansion Factor (Y) for Flange-tapped Orifice Meters	52
Bibliography	56

Figures

1 Orifice Tapping Location	5
2 Orifice Meter Elements	9
3 Contribution to Flow Error Due to Differential Pressure Instrumentation	29
4 Empirical Coefficient of Discharge: Uncertainty at Infinite Reynolds Number	32
5 Relative Change in Uncertainty: Dependence on Reynolds Number	32
6 Practical Uncertainty Levels.	34

Tables

1 Linear Coefficient of Thermal Expansion	13
2 Orifice Flow Rate Equation: Unit Conversion Factor (N_1).	26
3 Reynolds Number Equation: Unit Conversion Factor (N_2).	27
4 Empirical Expansion Factor Equation: Unit Conversion Factor (N_3)	27
5 Uncertainty Statement for Empirical Expansion Factor	33
6 Example Uncertainty Estimate for Liquid Flow Calculation.	38
7 Example Uncertainty Estimate for Natural Gas Flow Calculation	39
A.1 Discharge Coefficients for Flange-tapped Orifice Meters: Nominal 2-in. (50-mm) Meter [$D = 1.939$ in. (49.25 mm)]	40
A.2 Discharge Coefficients for Flange-tapped Orifice Meters: Nominal 3-in. (75-mm) Meter [$D = 2.900$ in. (73.66 mm)]	41
A.3 Discharge Coefficients for Flange-tapped Orifice Meters: Nominal 4-in. (100-mm) Meter [$D = 3.826$ in. (97.18 mm)]	42
A.4 Discharge Coefficients for Flange-tapped Orifice Meters: Nominal 6-in. (150-mm) Meter [$D = 5.761$ in. (146.33 mm)]	43
A.5 Discharge Coefficients for Flange-tapped Orifice Meters: Nominal 8-in. (200-mm) Meter [$D = 7.625$ in. (193.68 mm)]	44
A.6 Discharge Coefficients for Flange-tapped Orifice Meters: Nominal 10-in. (250-mm) Meter [$D = 9.562$ in. (242.87 mm)]	45
A.7 Discharge Coefficients for Flange-tapped Orifice Meters: Nominal 12-in. (300 mm) Meter [$D = 11.374$ in. (288.90 mm)]	46
A.8 Discharge Coefficients for Flange-tapped Orifice Meters: Nominal 16-in. (400-mm) Meter [$D = 14.688$ in. (373.08 mm)]	47
A.9 Discharge Coefficients for Flange-tapped Orifice Meters: Nominal 20-in. (500-mm) Meter [$D = 19.000$ in. (482.60 mm)]	48
A.10 Discharge Coefficients for Flange-tapped Orifice Meters: Nominal 24-in. (600-mm) Meter [$D = 23.000$ in. (584.20 mm)]	49
A.11 Discharge Coefficients for Flange-tapped Orifice Meters: Nominal 30-in. (750-mm) Meter [$D = 29.000$ in. (736.60 mm)]	50

Orifice Metering of Natural Gas and Other Related Hydrocarbon Fluids— Concentric, Square-edged Orifice Meters Part 1: General Equations and Uncertainty Guidelines

1 Introduction

1.1 Scope

This standard provides a single reference for engineering equations, uncertainty estimations, construction and installation requirements, and standardized implementation recommendations for the calculation of flow rate through concentric, square-edged, flange-tapped orifice meters. Both U.S. customary (USC), and international system of units (SI) units are included.

1.2 Organization of Standard

The standard is organized into four parts. Parts 1, 2, and 4 apply to the measurement of any Newtonian fluid in the petroleum and chemical industries. Part 3 focuses on the application of Parts 1, 2, and 4 to the measurement of natural gas.

1.2.1 Part 1—General Equations and Uncertainty Guidelines

The mass flow rate and base (or standard) volumetric flow rate equations are discussed, along with the terms required for solution of the flow equation.

The empirical equations for the coefficient of discharge and expansion factor are presented. However, the basis for the empirical equations are contained in other sections of this standard or the appropriate reference document.

In several sections of this revision of Part 1, identified errata have been changed relative to previous editions. In addition, this revision includes a change to the empirical expansion factor (Y) calculation for the flange-tapped orifice meters.

For all existing installations, the decision as to which expansion factor equation to use shall be at the discretion of the parties involved. However, the parties should be cognizant of the following:

- 1) If the calculated difference between previous revision (1990) Buckingham and Bean expansion factor equation (Annex C or API *MPMS* Ch. 14.3.3/AGA Report No. 3, Part 3, Annex G) and the new revised expansion factor equation is less than or equal to 0.25 %, then the expansion factor values produced by either expansion factor equation will be within the uncertainty of the new expansion factor database and the existence of any flow bias will be uncertain.
- 2) However, if the calculated difference between expansion factor equations exceeds 0.25 %, then a variable flow bias, which is a function of diameter ratio (β), isentropic exponent (κ), and $\Delta P/P_{f1}$ ratio (x_1), will be experienced unless the new expansion factor equation is utilized.

For the proper use of this standard, a discussion is presented on the prediction (or determination) of the fluid's properties at flowing conditions. The fluid's physical properties shall be determined by direct measurements, appropriate technical standards, or equations of state.

Uncertainty guidelines are presented for determining the possible error associated with the use of this standard for any fluid application. User-defined uncertainties for the fluid's physical properties and auxiliary (secondary) devices are required to solve the practical working formula for the estimated uncertainty.

1.2.2 Part 2—Specifications and Installation Requirements

Specifications are presented for orifice meters; in particular, orifice plates, orifice plate holders, sensing taps, meter tubes, and flow conditioners.

Installation requirements for orifice plates, meter tubes, thermometer wells, flow conditioners, and upstream/downstream meter tube lengths are presented.

1.2.3 Part 3—Natural Gas Applications

The application of this standard to natural gas is presented, along with practical guidelines. Mass flow rate and base (or standard) volumetric flow rate methods are presented in conformance with North American industry practices.

1.2.4 Part 4—Background, Development, and Implementation Procedure and Subroutine Documentation

The coefficient of discharge database for flange-tapped orifice meters and its background, development, and limitations are presented.

Implementation procedures for flange-tapped orifice meters are presented, along with a set of example calculations. The examples are designed to aid in checkout procedures for any routines that are developed using the implementation procedures.

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API MPMS Ch. 12.2.1, *Calculation of Petroleum Quantities Using Dynamic Measurement Methods and Volumetric Correction Factors*, Part 1—Introduction

API MPMS Ch. 14.3.2/AGA Report No. 3, Part 2/GPA 8185, Part 2, *Concentric, Square-Edged Orifice Meters*, Part 2—Specification and Installation Requirements (2000 edition)

API MPMS Ch. 14.3.3/AGA Report No. 3, Part 3, *Concentric, Square-Edged Orifice Meters*, Part 3—Natural Gas Applications

API MPMS Ch. 14.3.4/AGA Report No. 3, Part 4, *Concentric, Square-Edged Orifice Meters*, Part 4—Background, Development, Implementation Procedures and Subroutine Documentation

API MPMS Ch. 14.6, *Continuous Density Measurement*

API Technical Data Book—Petroleum Refining

AGA Report No. 8¹, *Compressibility Factors of Natural Gas and Other Related Hydrocarbon Gases*

¹ American Gas Association, 400 N. Capitol St., NW, Suite 450, Washington, DC 20001, www.aga.org.

3 Terms, Definitions, and Symbols

3.1 Terms and Definitions

This standard reflects orifice meter application to fluid flow measurement. The definitions are given to emphasize the particular meaning of the terms as used in this standard.

3.1.1 Primary Element

The primary element is defined as the orifice plate, the orifice plate holder with its associated differential pressure sensing taps, and the meter tube.

3.1.1.1

orifice plate

The orifice plate is defined as a thin plate in which a circular concentric aperture (bore) has been machined. The orifice plate is described as a thin plate with a sharp, square edge because the thickness of the plate material is small, compared with the internal diameter of the measuring aperture (bore), and because the upstream edge of the measuring aperture is sharp and square.

3.1.1.2

orifice plate bore diameter (d , d_m , d_r)

The calculated orifice plate bore diameter (d) is the internal diameter of the orifice plate measuring aperture (bore) computed at flowing temperature (T_f), as specified in 6.2. The calculated orifice plate bore diameter (d) is used in the flow equation for the determination of flow rate.

The measured orifice plate bore diameter (d_m) is the measured internal diameter of the orifice plate measuring aperture at the temperature of the orifice plate (T_m) at the time of bore diameter measurements, determined as specified in API *MPMS* Ch. 14.3, Part 2/AGA Report No. 3, Part 2.

The reference orifice plate bore diameter (d_r) is the internal diameter of the orifice plate measuring aperture at reference temperature (T_r), calculated as specified in API *MPMS* Ch. 14.3, Part 2/AGA Report No. 3, Part 2. The reference orifice plate bore diameter is the certified or stamped orifice plate bore diameter.

3.1.1.3

orifice plate holder

The orifice plate holder is defined as a pressure-containing piping element, such as a set of orifice flanges or an orifice fitting, used to contain and position the orifice plate in the piping system.

3.1.1.4

meter tube

The meter tube is defined as the straight sections of pipe, including all segments that are integral to the orifice plate holder, upstream and downstream of the orifice plate, as specified in API *MPMS* Ch. 14.3, Part 2/AGA Report No. 3, Part 2.

3.1.1.5

meter tube internal diameter (D , D_m , D_r)

The calculated meter tube internal diameter (D) is the inside diameter of the upstream section of the meter tube computed at flowing temperature (T_f), as specified in 6.3. The calculated meter tube internal diameter (D) is used in the diameter ratio and Reynolds number equations.

The measured meter tube internal diameter (D_m) is the inside diameter of the upstream section of the meter tube at the temperature of the meter tube (T_m) at the time of internal diameter measurements, determined as specified in API *MPMS* Ch. 14.3, Part 2/AGA Report No. 3, Part 2.

The reference meter tube internal diameter (D_r) is the inside diameter of the upstream section of the meter tube at the reference temperature (T_r), calculated as specified in API MPMS 14.3, Part 2/AGA Report No. 3, Part 2. The reference meter tube internal diameter is the certified or stamped meter tube internal diameter.

3.1.1.6

diameter ratio (β)

The diameter ratio (β) is defined as the calculated orifice plate bore diameter (d) divided by the calculated meter tube internal diameter (D).

3.1.2 Pressure Measurement

3.1.2.1

tap hole

A tap hole is a hole drilled radially in the wall of the meter tube or orifice plate holder, the inside edge of which is flush and without any burrs.

3.1.2.2

flange taps

Flange taps are a pair of tap holes positioned as follows (see Figure 1):

- a) the upstream tap center is located 1 in. (25.4 mm) upstream of the nearest plate face,
- b) the downstream tap center is located 1 in. (25.4 mm) downstream of the nearest plate face.

3.1.2.3

differential pressure (ΔP)

The differential pressure (ΔP) is the static pressure difference measured between the upstream and downstream flange taps.

3.1.2.4

static pressure (P_f)

The static pressure (P_f) is the absolute flowing fluid pressure measured at one of the flange tap holes. The absolute pressure may be measured directly or can be obtained by adding local barometric pressure to measured gauge pressure:

$$\text{absolute static pressure} = \text{gauge static pressure} + \text{local barometric pressure}$$

3.1.3 Temperature Measurement (T_f)

The temperature is the flowing fluid temperature (T_f) measured at the designated upstream or downstream location, as specified in API MPMS Ch. 14.3, Part 2/AGA Report No. 3, Part 2.

In flow measurement applications where the fluid velocity is well below sonic, it is common practice to insert a temperature sensing device in the middle of the flowing stream to obtain the flowing temperature. For practical applications, the sensed temperature is assumed to be the static temperature of the flowing fluid.

The use of flowing temperature in this part of the standard requires the temperature to be measured in degrees Fahrenheit or degrees Celsius. However, if the flowing temperature is used in an equation of state to determine the density of the flowing fluid, it may require that the Fahrenheit or Celsius values be converted to absolute temperature values of degrees Rankine or Kelvin through the following relationships:

$$^{\circ}\text{R} = ^{\circ}\text{F} + 459.67$$

$$\text{K} = ^{\circ}\text{C} + 273.15$$




Figure 1—Orifice Tapping Location

3.1.4 Flow Rate Determination

3.1.4.1

orifice flow rate (q_m , q_v , Q_v)

The orifice flow rate is the mass or volume flow through an orifice meter per unit of time.

3.1.4.2

orifice plate coefficient of discharge (C_d)

The orifice plate coefficient of discharge (C_d) is the ratio of the actual flow to the theoretical flow and is applied to the theoretical flow equation to obtain the actual flow.

3.1.4.3

velocity of approach (E_v)

The velocity of approach factor (E_v) is a mathematical expression that relates the velocity of the flowing fluid in the orifice meter approach section (upstream meter tube) to the fluid velocity in the orifice plate bore.

3.1.4.4

expansion factor (Y)

The expansion factor (Y) is an empirical expression used to correct the flow rate for the reduction in fluid density that a compressible fluid experiences when it passes through the orifice plate bore.

3.1.4.5

pipe Reynolds number (Re_D)

The pipe Reynolds number is a dimensionless ratio of forces used to correlate the variations in the orifice plate coefficient of discharge (C_d) with changes in the fluid's properties, flow rate, and orifice meter geometry.

3.1.5 Fluid Physical Properties

3.1.5.1

density ($\rho_{t,p}$, ρ_b)

The flowing fluid density ($\rho_{t,p}$) is the mass per unit volume of the fluid being measured at flowing conditions (T_f , P_f).

The base fluid density (ρ_b) is the mass per unit volume of the fluid being measured at base conditions (T_b , P_b).

3.1.5.2

absolute viscosity (μ)

The absolute viscosity (μ) is the measure of a fluid's intermolecular cohesive force's resistance to shear per unit of time.

3.1.5.3

compressibility (Z)

The compressibility (Z) is an adjustment factor used to account for the deviation from the ideal gas law.

3.1.5.4

isentropic exponent (κ)

The isentropic exponent (κ) is a thermodynamic state property that establishes the relationship between an expanding fluid's pressure and density as the fluid flows through the orifice plate bore. See 10.3 for further information on isentropic exponent as it applies to this standard.

3.1.6 Base Conditions (P_b , T_b)

Historically, the flow measurement of some fluids, such as custody transfer and process control, has been stated in volume units at base conditions of pressure and temperature. Base conditions are reference conditions of pressure and temperature for the calculation of volumes, generally defined by contract or regulation. Often base conditions are set as standard conditions and the terms are sometimes used interchangeably.

The base conditions for the flow measurement of fluids, such as crude petroleum and its liquid products, whose vapor pressure is equal to or less than atmospheric at base temperature are often designated as a pressure of 14.696 psia (101.325 kPa) at a temperature of 60.0 °F (15.56 °C) in the United States (U.S.) and 59.00 °F (15.00 °C) for ISO.

For fluids, such as liquid hydrocarbons, whose vapor pressure is greater than atmospheric pressure at base temperature, the base pressure is customarily designated as the equilibrium vapor pressure at base temperature.

Base conditions are normally defined by contract or government regulation. For interstate commerce, the base conditions for the flow measurement of natural gases are defined in the U.S. as a pressure of 14.73 psia (101.560 kPa) at a temperature of 60.0 °F (15.56 °C). Note, according to ISO, base conditions are defined as a pressure of 14.696 psia (101.325 kPa) at a temperature of 59.00 °F (15.00 °C).

For both liquid and gas applications, these base conditions can change from one country to the next, one state to the next, or one industry to the next. Therefore, it is necessary that the base conditions be identified for standard volumetric flow measurement.

3.1.7 Sensitivity Coefficient (S)

In estimating the uncertainty associated with the metering facility, a number of variables must be combined. The mathematical relationships among the variables establish the sensitivity of the metered quantities to each of these variables. As such, each variable that may influence the flow equation has a specific sensitivity coefficient. The derivation of this coefficient is based on a mathematical relationship or estimated from calculations, tables, or curves.

3.1.8 Meter Factor (MF)

The MF is a number obtained by dividing the quantity of fluid measured by the reference flow system by the quantity indicated by the orifice meter during calibration. See 9.2 for further information on meter factor as it applies to this standard.

3.1.9 In-situ Calibration

An in-situ calibration is defined as a calibration conducted under normal operating conditions, with the actual approach piping configuration, using the actual fluid with the actual orifice plate and recording system in place.

3.2 Symbols

This standard reflects orifice meter application to fluid flow measurement with symbols in general technical use.

C_d	orifice plate coefficient of discharge
$C_d(FT)$	coefficient of discharge at a specified pipe Reynolds number for flange-tapped orifice meter
C_i	coefficient of discharge at infinite pipe Reynolds number
$C_i(CT)$	coefficient of discharge at infinite pipe Reynolds number for corner-tapped orifice meter
$C_i(FT)$	coefficient of discharge at infinite pipe Reynolds number for flange-tapped orifice meter
c_p	specific heat at constant pressure
c_v	specific heat at constant volume
d	orifice plate bore diameter calculated at flowing temperature, T_f
d_m	orifice plate bore diameter measured at T_m
d_r	orifice plate bore diameter at reference temperature, T_r
D	meter tube internal diameter calculated at flowing temperature, T_f
D_m	meter tube internal diameter measured at T_m
D_r	meter tube internal diameter at reference temperature, T_r
ΔP	orifice differential pressure
$^{\circ}\text{C}$	temperature, in degrees Celsius
$^{\circ}\text{F}$	temperature, in degrees Fahrenheit
K	temperature, in Kelvin
$^{\circ}\text{R}$	temperature, in degrees Rankine
E_v	velocity of approach factor
g_c	dimensional conversion constant
G_i	ideal gas relative density (specific gravity)
κ	isentropic exponent
κ_i	ideal gas isentropic exponent
κ_p	perfect gas isentropic exponent
κ_r	real gas isentropic exponent
MF	calibration meter factor
Mr_{air}	molar mass of air
Mr_{gas}	molar mass of gas
N_1	unit conversion factor (orifice flow)
N_2	unit conversion factor (Reynolds number)
N_3	unit conversion factor (expansion factor)
N_4	unit conversion factor (discharge coefficient)
P	pressure
P_b	base (reference or standard) pressure
P_f	static pressure of fluid at the pressure tap
P_{f_1}	absolute static pressure at the orifice upstream differential pressure tap
P_{f_2}	absolute static pressure at the orifice downstream differential pressure tap



q_m	mass flow rate
q_{m_i}	mass flow rate indicated by the orifice meter being calibrated
q_{m_p}	mass flow rate determined by the reference flow system (or master meter)
q_v	volume flow rate at flowing (actual) conditions
q_{v_i}	volume flow rate indicated by the orifice meter being calibrated
Q_v	volume flow rate at base (standard) conditions
R	universal gas constant
R_a	roughness average value from continuously averaging meter readings
Re_D	pipe Reynolds number
T	temperature
T_b	base (reference or standard) temperature
T_f	temperature of fluid at flowing conditions
T_m	temperature of the orifice plate or meter tube at time of diameter measurements
T_r	reference temperature of orifice plate bore diameter and/or meter tube inside diameter
x	ratio of differential pressure to absolute static pressure
x_1	ratio of differential pressure to absolute static pressure at the upstream pressure tap
S	sensitivity coefficient (influence coefficient)
Y	expansion factor
Y_1	expansion factor based on upstream absolute static pressure
Y_2	expansion factor based on downstream absolute static pressure
Z	fluid compressibility
Z_f	fluid compressibility at flowing conditions
Z_{f_1}	compressibility of the fluid flowing at the upstream pressure tap location
Z_{f_2}	compressibility of the fluid flowing at the downstream pressure tap location
α	linear coefficient of thermal expansion
α_1	linear coefficient of thermal expansion of the orifice plate material
α_2	linear coefficient of thermal expansion of the meter tube material
β	ratio of orifice diameter to meter tube diameter calculated at flowing conditions
μ	absolute viscosity of fluid flowing
π	universal constant rounded to six significant figures
ρ	density of the fluid
ρ_b	density of the fluid at base conditions (P_b, T_b)
$\rho_{t,p}$	density of the fluid at flowing conditions (P_f, T_f)

4 Field of Application

4.1 Applicable Fluids

This standard applies to steady-state mass flow conditions for fluids that, for all practical purposes, are considered to be clean, single phase, homogeneous, and Newtonian and have pipe Reynolds numbers of 4,000 or greater. All gases, most liquids, and most dense phase fluids associated with the petroleum, petrochemical, and natural gas industries are usually considered Newtonian fluids.

4.2 Types of Meters

This standard provides design, construction, and installation specifications for flange-tapped, concentric, square-edged orifice meters of nominal 2-in. Schedule 160 and larger pipe diameters.

An orifice meter is a fluid flow measuring device that produces a differential pressure to infer flow rate. The meter consists of the following elements (see Figure 2):

- a thin, concentric, square-edged orifice plate;
- an orifice plate holder consisting of a set of orifice flanges (or an orifice fitting) equipped with the appropriate differential pressure sensing taps;
- a meter tube consisting of the adjacent piping sections (with or without flow conditioners).

The auxiliary (secondary) devices necessary for the precise determination of flow rate are not included in the scope of this standard. These devices are usually instruments that sense the differential and static pressure, fluid temperature, and fluid density and/or relative density (specific gravity), and either mechanical recording devices or electronic calculators. A review of the publications of AGA, API, GPA, and others that address the specifications and installations of these auxiliary(secondary) devices is encouraged.




Figure 2—Orifice Meter Elements

4.3 Uncertainty of Measurement

Many factors influence the overall measurement uncertainty associated with a metering application. Major contributors include construction tolerances in the meter components, tolerances of empirical coefficient of discharge databases or in-situ flow calibrations, predictability of and variations in the fluid's physical properties, and uncertainties associated with the auxiliary (secondary and tertiary) devices.

Using the guidelines contained in this standard and other relevant industry standards in combination with the associated uncertainty tolerances for the fluid's physical properties, in-situ calibrations, or coefficient of discharge databases, and the appropriate auxiliary (secondary and tertiary) devices, the user can estimate the overall measurement uncertainty associated with a properly designed, installed, and maintained thin plate, concentric, square-edged orifice metering application.

5 Method of Calculation

This standard provides recommended standardized calculation implementation methods for the quantification of fluid flow under defined conditions, regardless of the point of origin or destination or the units of measure required by governmental customs or statute. The recommended implementation procedures provided in API MPMS Ch. 14.3, Part 4/AGA Report No. 3, Part 4 allow different entities using various computer languages on different computing hardware to arrive at nearly identical results using the same standardized input data.

The following two recommended implementation procedures have been prepared to illustrate the standardized set of mathematical expressions and sequencing, including iteration/rounding techniques:

- a) mass flow rate,
- b) standard volumetric flow rate.

The procedures presented address only the solution of the flow rate equation and require specific inputs (fixed and variable). Typical fixed inputs include meter tube internal diameter, orifice plate bore diameter, and linear coefficient of expansion for steels (pipe and orifice plate). Typical variable inputs may include differential and static pressure, temperature, fluid density, isentropic exponent for compressible fluids, and fluid viscosity.

The fluid's physical properties shall be determined by direct measurements, appropriate technical standards, or equations of state. If multiple parties are involved in the measurement, the appropriate technical method selected for determining the fluid's physical properties shall be mutually agreed upon.

6 Orifice Flow Equation

The accepted one-dimensional equation for mass flow through a concentric, square-edged orifice meter is stated in Equation (1) or Equation (2). The derivation is based on conservation of mass and energy, one-dimensional fluid dynamics, and empirical functions such as equations of state and thermodynamic process statements. Any derivation is accurate when all the assumptions used to develop it are valid. As a result, an empirical orifice plate coefficient of discharge is applied to the theoretical equation to adjust for multidimensional viscous fluid dynamic effects. In addition, an empirical expansion factor is applied to the theoretical equation to adjust for the reduction in fluid density that a compressible fluid experiences when it passes through an orifice plate.

The fundamental orifice meter mass flow equation is as follows:

$$q_m = C_d E_v Y (\pi/4) d^2 \sqrt{2 g_c \rho_{t,p} \Delta P} \quad (1)$$

where

C_d is the orifice plate coefficient of discharge;

d is the orifice plate bore diameter calculated at flowing temperature (T_f);

ΔP is the orifice differential pressure;

E_v is the velocity of approach factor;

g_c is the dimensional conversion constant;

π is the universal constant = 3.14159;

q_m is the mass flow rate;

$\rho_{t,p}$ is the density of the fluid at flowing conditions (P_f , T_f);

Y is the expansion factor.

The practical orifice meter flow equation used in this standard is a simplified form that combines the numerical constants and unit conversion constants in a unit conversion factor (N_1):

$$q_m = N_1 C_d E_v Y d^2 \sqrt{\rho_{t,p} \Delta P} \quad (2)$$

where

C_d is the orifice plate coefficient of discharge;

d is the orifice plate bore diameter calculated at flowing temperature (T_f);

ΔP is the orifice differential pressure;

E_v is the velocity of approach factor;

N_1 is the unit conversion factor;

q_m is the mass flow rate;

$\rho_{t,p}$ is the density of the fluid at flowing conditions (P_f , T_f);

Y is the expansion factor.

The expansion factor, Y , is included in Equation (1) and Equation (2) because it is applicable to all single-phase, homogeneous Newtonian fluids. For incompressible fluids, such as water at 60 °F (15.56 °C) and atmospheric pressure, the empirical expansion factor is defined as 1.0000.

The orifice plate coefficient of discharge, C_d , and the expansion factor, Y , are empirical functions derived from experimental data.

The orifice meter is a mass meter from which a differential pressure signal is developed as a function of the velocity of the fluid as it passes through the orifice plate bore. Manipulation of the density variable in the equation permits calculation of flow rate in either mass or volume units. The volumetric flow rate at flowing (actual) conditions can be calculated using the following equation:

$$q_v = q_m / \rho_{t,p} \quad (3)$$

The volumetric flow rate at base (standard) conditions can be calculated using the following equation:

$$Q_v = q_m / \rho_b \quad (4)$$

The mass flow rate (q_m) can be converted to a volumetric flow rate at base (standard) conditions (Q_v) if the fluid density at the base conditions (ρ_b) can be determined or is specified.

The unit conversion factor (N_1), is defined and presented in 11.1.

6.1 Velocity of Approach Factor (E_v)

The velocity of approach factor (E_v), is calculated as follows:

$$E_v = \frac{1}{\sqrt{1 - \beta^4}} \quad (5)$$

and

$$\beta = d/D \quad (6)$$

where

d is the orifice plate bore diameter calculated at flowing temperature (T_f);

D is the meter tube internal diameter calculated at flowing temperature (T_f).

6.2 Orifice Plate Bore Diameter (d)

The orifice plate bore diameter (d) is defined as the diameter at flowing conditions and can be calculated using the following equation:

$$d = d_r [1 + \alpha_1 (T_f - T_r)] \quad (7)$$

where

α_1 is the linear coefficient of thermal expansion for the orifice plate material (see Table 1);

d is the orifice plate bore diameter calculated at flowing temperature (T_f);

d_r is the reference orifice plate bore diameter at reference temperature (T_r);

T_f is the temperature of the fluid at flowing conditions;

T_r is the reference temperature of the orifice plate bore diameter.

NOTE α , T_f and T_r must be in consistent units. For the purpose of this standard, T_r is assumed to be 68 °F (20 °C).

The orifice plate bore diameter (d_r) calculated at T_r is the diameter determined in accordance with the requirements contained in API MPMS Ch. 14.3, Part 2/AGA Report No. 3, Part 2.

6.3 Meter Tube Internal Diameter (D)

The meter tube internal diameter (D) is defined as the diameter at flowing conditions and can be calculated using the following equation:

$$D = D_r [1 + \alpha_2 (T_f - T_r)] \quad (8)$$

where

α_2 is the linear coefficient of thermal expansion for the meter tube material (see Table 1);

D is the meter tube internal diameter calculated at flowing temperature (T_f);

D_r is the reference meter tube internal diameter at T_r ;

T_f is the temperature of the fluid at flowing conditions;

T_r is the reference temperature of the meter tube internal diameter.

NOTE α , T_f , and T_r must be in consistent units. For the purpose of this standard, T_r is assumed to be 68 °F (20 °C).

The meter tube internal diameter (D_r) calculated at T_r is the diameter determined in accordance with the requirements contained in API MPMS 14.3, Part 2/AGA Report No. 3, Part 2.

Table 1—Linear Coefficient of Thermal Expansion

Material	Linear Coefficient of Thermal Expansion (α)	
	USC (in./in. °F)	Metric Units (mm/mm °C)
Type 304/316 stainless steel ^c	0.00000925	0.0000167
Type 304 stainless steel ^a	0.00000961	0.0000173
Type 316 stainless steel ^a	0.00000889	0.0000160
Monel 400 ^a	0.00000772	0.0000139
Carbon steel ^b	0.00000620	0.0000112
NOTE For flowing temperature limits or other materials, refer to the American Society for Metals (ASM) <i>Metals Handbook</i> , <i>Engineering Properties of Steel</i> , and <i>Handbook of Stainless Steels</i> .		
^a For flowing conditions between +32 °F and +212 °F for stainless steels and +68 °F and +212 °F for Monel.		
^b For flowing conditions between –7 °F and +154 °F, refer to API MPMS Ch. 12.2.1.		
^c Type 304/316 stainless steel linear coefficient of thermal expansion is the average of the type 304 and type 316 stainless steel coefficients.		
NOTE Over a temperature range from 32 °F to 130 °F the maximum difference in calculated flow between use of the 304/316 average coefficient and either the 304 or 316 coefficient is less than 0.005 % (50 ppm).		

7 Empirical Coefficient of Discharge

Empirical coefficients of discharge for flange-tapped orifice meters have been determined from experimental data by comparing the measured and theoretical flow rates. A major factor in the definition of the experimental patterns for this orifice research was dynamic similarity. Using Reynolds' Law of Similarity, experimental correlations can be applied to dynamically similar meters.

To accurately predict the coefficient of discharge, C_d (FT), for a flange-tapped orifice meter manufactured to the specifications of this standard, certain parameters concerning the orifice meter and the fluid must be known. The relationships between these functions can be simplified for application to commercial use. In fact, the coefficient of discharge can be shown to depend on a number of parameters, the major ones being the Reynolds number (Re_D), sensing tap location, meter tube diameter (D), and β ratio:

$$C_d = f(Re_D, \text{Sensing tap location}, D, \beta)$$