

Memorandum from

CSA America

8501 East Pleasant Valley Rd.
Cleveland, OH 44131

May 23, 2007

Erratum to

**American National Standard/CSA Standard for
Outdoor Cooking Gas Appliances, Z21.58-2007/CSA 1.6-2007**

The third edition of the American National Standard/CSA Standard for Outdoor Cooking Gas Appliances, Z21.58-2007/CSA 1.6-2007, was recently released. There are errors in Section 1.6, Self-Contained LP-Gas Supply Systems.

On page 9 through page 14, Section 1.6, Self-Contained LP-Gas Supply Systems, does not contain the revisions shown in the previous Addenda "a" Z21.58a-2006/CSA 1.6a-2006.

The attached Erratum, marked in the bottom right hand corner with the date May 23, 2007, contains the corrected Section 1.6 in its entirety.



Documents
Document Sharing Hub

Downloaded by [University of Alberta] on 01/13/2015 23:23:10 MST

1.6 Self-Contained LP-Gas Supply Systems

1.6.1

Integral mounting means shall be provided on the outdoor cooking gas appliance for mounting the LPgas supply cylinder(s).

Integral retention means shall be provided on the outdoor cooking gas appliance to limit the movement of the LP-gas cylinder(s). Lateral movement shall not exceed 1 in (25.4 mm) at the retention means, and the cylinder(s) or any portion thereof shall not become dislodged from its (their) retention means when a lateral force equal to the full weight of the cylinder(s) is applied in any direction at the center of the vertical height of the cylinder(s).

If the means is for attachment to the protective collar of the cylinder(s) it shall not interfere with the operation of the cylinder(s) valve(s). Any movement shall not transmit strain to rigid tubing or pipe connections.

Mounting and retention means shall incorporate adequate adjustments to accommodate the size cylinder(s) specified by the manufacturer.

1.6.2

Integral retention means shall be provided on the outdoor cooking gas appliance to limit the movement of the LPgas cylinder. With the cylinder installed per the manufacturers instructions, lateral movement shall not exceed 1 in (25.4 mm) at the retention means, and the cylinder or any portion thereof shall not become dislodged from its retention means when a lateral force equal to the full weight of the cylinder is applied in any direction at the center of the vertical height of the cylinder. This test shall be conducted with the installed cylinder empty and full.

If the means is for attachment to the protective collar of the cylinder, it shall not interfere with the operation of the cylinder valve. Any movement shall not transmit strain to rigid tubing or pipe connections.

Retention means shall not depend on openings in either the cylinder's protective collar or foot ring unless the appliance manufacturer specifies the following information:

1. The cylinder manufacturer(s) identity (symbol, trade name, etc.) as marked on the cylinder;
2. The marked cylinder water capacity or LPG capacity (in pounds) as stated by the cylinder manufacturer(s); and
3. Cylinder(s) that are to be approved for use with the appliance shall be provided by the appliance manufacturer for test.

1.6.3

Mounting and retention means shall incorporate adequate adjustments to accommodate the size cylinder specified by the manufacturer.

1.6.4

All gas handling components from the appliance portion of the cylinder(s) connection device up to and including the orifice shall be complete assembled. Portions of the assembly may b shipped separately if those portions are separated by a factory-installed device complying with: