



American
Gear Manufacturers
Association

Technical Resources

ANSI/AGMA 9103-B08

Metric Edition of ANSI/AGMA 9003-B08

American National Standard

Flexible Couplings – Keyless Fits (Metric Edition)

ANSI/AGMA 9103-B08

American National Standard

Flexible Couplings – Keyless Fits (Metric Edition) ANSI/AGMA 9103-B08

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretation of this standard should be addressed to the American Gear Manufacturers Association.

CAUTION NOTICE: AGMA technical publications are subject to constant improvement, revision, or withdrawal as dictated by experience. Any person who refers to any AGMA technical publication should be sure that the publication is the latest available from the Association on the subject matter.

[Tables or other self-supporting sections may be referenced. Citations should read: See ANSI/AGMA 9103-B08, *Flexible Couplings – Keyless Fits (Metric Edition)*, published by the American Gear Manufacturers Association, 500 Montgomery Street, Suite 350, Alexandria, Virginia 22314, <http://www.agma.org>.]

Approved May 20, 2008

ABSTRACT

This standard presents information on design, dimensions, tolerances, inspection, mounting, removal, and equipment that is in common use with keyless tapered and keyless straight (cylindrical) bore hubs for flexible couplings.

Published by

American Gear Manufacturers Association
500 Montgomery Street, Suite 350, Alexandria, Virginia 22314

Copyright © 2008 by American Gear Manufacturers Association
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

ISBN: 978-1-55589-925-7

Contents

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and symbols	1
4 Responsibility	1
5 Design considerations	2
6 Configurations for hydraulic installation or removal of hubs	5
7 Tapers, interference rate, and advance	6
8 Hydraulic mounting and removal equipment	7
9 Hub inspection, mounting and removal procedures for taper bores	8
10 Hub inspection, mounting and removal procedures for straight cylindrical bores	11
Bibliography	22

Annexes

A Derivation of constants	13
B Typical designs and dimensions for grooving and hydraulic fitting holes ...	15
C Mounting and dismounting equipment	17
D Example calculations	20

Figures

1 Hub with multiple sections	3
2 Flexible hub, gear tooth section influencing torque capacity and pressure ...	3
3 Rigid hub, flange not influencing torque capacity and pressure	3
4 Rigid hub, flange influencing torque capacity and pressure	3
5 Bore configurations	3
6 Oil port in shaft	6
7 Oil ports in hub	6
8 O-ring groove locations	6
9 O-rings with back-up rings	6
10 Typical mechanism for hydraulic mounting and removal	8
11 Initial position measurement	9
12 Measurement of hub advance	9
13 Retaining mechanisms	10
14 Relief groove	11
15 Hub retainer plate and stress relief groove	12

Tables

1 Symbols and definitions	2
2 Hub advance per millimeter of shaft diameter, S_d , vs. interference rate, i , for specified diametral tapers	7

Foreword

[The foreword, footnotes and annexes, if any, in this document are provided for informational purposes only and are not to be construed as a part of ANSI/AGMA 9103-B08, *Flexible Couplings – Keyless Fits (Metric Edition)*.]

This standard was developed after intensive study of existing practices, standards and literature. The intent of this document is to offer to rotating equipment designers and users a standard for design practice and dimensions regarding keyless fits for flexible couplings. In general, the information in this standard is a consolidation of the most common practices and standards currently in existence.

This AGMA standard and related publications are based on typical or average data, conditions, or applications.

Work was begun on ANSI/AGMA 9003-A91 in 1985 and was approved by the AGMA membership in February 1991. It was approved as an American National Standard on May 20, 1991.

ANSI/AGMA 9103-B08 split the original standard into inch (ANSI/AGMA 9003-B08) and metric versions, updated annex B and added an example calculation as annex D.

The first draft of ANSI/AGMA 9103-B08 was made in October, 2004. It was approved by the AGMA membership in October, 2007. It was approved as an American National Standard on May 20, 2008.

Suggestions for improvement of this standard will be welcome. They should be sent to the American Gear Manufacturers Association, 500 Montgomery Street, Suite 350, Alexandria, Virginia 22314.

PERSONNEL of the AGMA Flexible Couplings Committee

Chairman: Glenn Pokrandt Rexnord Industries Coupling Operations
Vice Chairman: James Paluh Ameridrives Gear Coupling Operations

ACTIVE MEMBERS

T. Hewitt Lord Corporation
D. Hindman Rexnord Industries Coupling Operations
D. Lyle Ameridrives Gear Coupling Operations
H.A. Lynn, III Rexnord Industries Coupling Operations
J.W. Mahan Lovejoy, Inc.
J.R. Mancuso Kop-Flex/Emerson Power Transmission
G.E. Saunders Ameridrives Gear Coupling Operations
T. Schatzka Rexnord Industries, Inc.
J. Sherred Ameridrives Gear Coupling Operations
J. Smihal T.B. Woods, Inc.
R. Whitney Riverhawk Company

(This page is intentionally blank)

.....

American National Standard –

Flexible Couplings – Keyless Fits (Metric Edition)

1 Scope

This standard presents information on design, dimensions, tolerances, inspection, mounting, removal, and equipment that is in common use with keyless tapered and keyless straight (cylindrical) bore hubs for flexible couplings. Calculated hub stress values and hub to shaft torque capacities are nominal values. This standard does not present a rigorous analysis of the components.

1.1 Applicability

This standard applies only to hubs and solid shafts made of steel, which generally have material properties of modulus of elasticity equal to 2.07×10^5 MPa, density equal to 7830 kg/m^3 , and thermal expansion coefficient equal to $11.4 \times 10^{-6} \text{ mm/mm/}^\circ\text{C}$.

1.2 Exclusions

This standard does not apply to couplings attached to shafts with keyways, splines, split hubs or polygon bores.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this American National Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this American National Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below.

ANSI/AGMA 9112-A04, *Bores and Keyways for Flexible Couplings (Metric Series)*

ANSI/AGMA 9009-D02, *Flexible Couplings – Nomenclature for Flexible Couplings*

3 Terms and symbols

3.1 Terms

The terms used, wherever applicable, conform to the following Standards:

ANSI Y10.3-1968, *Letter Symbols for Quantities Used in Mechanics of Solids*

ANSI/AGMA 1012-G05, *Gear Nomenclature, Definition of Terms with Symbols*

3.2 Symbols

The symbols used in the formulas are shown in table 1.

NOTE: The symbols and definitions used in this standard may differ from other AGMA standards. The user should not assume that familiar symbols can be used without a careful study of these definitions.

4 Responsibility

The purchaser has the sole responsibility for specifying the peak torque and all other pertinent loading and operating information affecting the hub-to-shaft juncture. The machine designer is totally responsible for the design of the hub-to-shaft juncture. The sole responsibility of the coupling manufacturer is to provide hubs designed and manufactured according to the purchaser's specifications.

Compliance with this standard does not constitute a warranty of the rating of the hub to shaft juncture under installed conditions. This standard only applies to the hub design. There can be personal injury or catastrophic failure of the shaft or hub-to-shaft juncture as a result of incorrect design, installation, or removal error, or other factors unrelated to the hub design.

WARNING: When working with hydraulic mounting and removal equipment **EXTREME** care and caution must be used to prevent personal injury and damage to equipment due to explosive axial movement at the time of hub release.

Table 1 - Symbols and definitions^{1), 2)}

Symbol	Definition	Units ²⁾	First used
C_e	Ratio of average bore diameter of section to outside diameter of section under consideration, $C_e = D_b / D_o$	- -	Eq 2
D	Shaft diameter at largest end of bore	mm	Eq 13
D_b	Average bore diameter of section	mm	Eq 1
D_o	Outside diameter of section	mm	Eq 2
E	Modulus of elasticity	MPa	Eq 2
I	Diametral interference	mm	Eq 13
I_c	Loss of interference when rotating	mm	5.1.4
I_{max}	Maximum diametral interference when not rotating	mm	Eq 4
I_{min}	Minimum diametral interference fit required to transmit the design torque at specified speed	mm	5.1.4
i	Interference rate	mm/mm	7.2
L	Length of hub engagement	mm	Eq 1
N	Specified rotational speed	1/min	Eq 3
p_1	Calculated pressure at hub bore to mount or dismount hub due to maximum interference fit	MPa	5.2.1
p_2	Maximum recommended pressure at hub bore when mounting or dismounting	MPa	5.2.2
p_{min}	Minimum pressure at hub bore for design torque calculation	MPa	5.1.3
Ra	Arithmetic average of surface finish	μm	5.1.1
S	Advance	mm	7.3
S_d	Advance per millimeter of shaft diameter	mm/mm	7.3
S_y	Tensile yield strength of the selected hub material	MPa	5.3.1
T	Design torque capacity of hub-to-shaft connection	Nm	5.1.2
t	Taper, rate of change of diameter per unit length	mm/mm	Eq 14
α	Thermal expansion coefficient	mm/mm/°C	Eq 17
ΔT	Required temperature difference between hub and shaft for mounting hub	°C	Eq 17
σ_H	Maximum hoop stress in mounted hub when rotating	MPa	Eq 7
σ_{max}	Maximum hub stress at hub bore due to hydraulic pressure when mounting or dismounting	MPa	5.3.1
σ_R	Radial stress at hub bore due to interference fit of mounted hub while rotating	MPa	Eq 7
σ_{Rv}	Radial stress in hub due to rotational speed	MPa	Eq 7
σ_{rot}	Combined stress in hub when rotating	MPa	Eq 7
σ_v	Hoop stress in hub due to rotational speed	MPa	Eq 7
μ	Apparent coefficient of friction	- -	5.1.1

NOTES:

1) Equations in this standard require the use of consistent units.

2) For this standard, pressure is noted in megapascals (MPa) to be consistent with hydraulic gages. 1 MPa = 1 N/mm².

5 Design considerations

The design of keyless fits in power transmission couplings is based on the calculations required for the safe transmission of the specified torque through the coupling hub-to-shaft juncture. These calculations consist of the following:

- The interference fit required to transmit the specified torque;
- The pressures involved in mounting and dismounting the hub;
- The stresses in the hub during mounting or dismounting and during operation.

The equations in the following sections for hub pressures and stresses account for hubs of substantially uniform cross sections. The equation for torque capacity of the hub-to-shaft junction assumes the hub outside diameter is uniform and equal to the outside diameter of the minimum hub section. The torque as calculated is conservatively low.

When a hub has multiple outside diameters such as shown in figure 1, the hub can be split into sections and the torque capacity of each section calculated separately. The total capacity is the sum of the separate section capacities. Hub configuration must be considered when performing stress and mounting pressure calculations (see figures 1, 2, 3, and 4).

Shrink or interference fit analysis is generally based on Lamé's equations for a thick walled cylinder under internal pressure.




Figure 1 - Hub with multiple sections




Figure 2 - Flexible hub, gear tooth section influencing torque capacity and pressure




Figure 3 - Rigid hub, flange not influencing torque capacity and pressure






Figure 4 - Rigid hub, flange influencing torque capacity and pressure


The bore used in the determination of the pressure for tapered and cylindrical bore configurations is as shown in figure 5. The following equations are based on the assumption that the shaft and hub have substantially equal surface finish, hardness, and modulus of elasticity.



(a) Tapered



(b) Cylindrical



(c) Grooved

Figure 5 - Bore configurations