


AEROSPACE INDUSTRIES ASSOCIATION OF AMERICA, INC.
1250 EYE STREET, N.W.
WASHINGTON, D.C. 20005

THIS DRAWING SUPERSEDES ALL ANTECEDENT STANDARD DRAWINGS FOR THE SAME PRODUCT
AND SHALL BECOME EFFECTIVE NO LATER THAN SIX MONTHS FROM THE LAST DATE OF
APPROVAL SHOWN HEREON.



BASIC PART NUMBER	NOM SIZE	D SHANK DIA	A (a) MAX DIA	A ₁ (a) MIN DIA	B (a) MAX	C MAX	GAGE			J DIA.	K	R RAD	V (c) HEAD MARKING
							E (b) DIA +.0002 -.0000	H (b) PROTRUSION					
								NOM	±TOL				
NAS2315	.164	.1640 .1635	.292	.263	.055	.008	.2558	.0130	.0018	.158 .150	.012 .008	.020 .010	2315V
NAS2316	.190	.1895 .1890	.357	.316	.071	.013	.2980	.0224	.0019	.185 .175	.015 .011	.030 .020	2316V
NAS231b	.250	.2495 .2490	.480	.428	.098	.017	.4048	.0290	.0020	.242 .231	.018 .014	.030 .020	2318V
NAS2320	.312	.3120 .3115	.568	.508	.109	.020	.4789	.0346	.0021	.305 .293	.023 .017	.040 .030	2320V
NAS2322	.375	.3745 .3740	.698	.629	.137	.023	.5940	.0404	.0024	.368 .354	.027 .021	.040 .030	NAS2322V

- (a) DIMENSIONS A, A₁ & B: INCLUDED FOR ENGINEERING REFERENCE PURPOSES ONLY, NOT FOR INSPECTION PURPOSES.
VALUES A, A₁ & B: CALCULATED LIMITS RESULTING FROM TOLERANCES ON C, D, E, H & HEAD ANGLE.
- (b) GAGE PROTRUSION (H): SEE NAS621 FOR THE RECOMMENDED PRACTICE FOR INSPECTING HEAD CHARACTERISTICS.
- (c) HEAD MARKING: "NAS" MAY BE INCLUDED IN HEAD MARKING AT OPTION OF FASTENER MANUFACTURER.
- (d) CHAMFER OR RADIUS PERMISSIBLE, .06 MAX.

MATERIAL: 6AL-4V TITANIUM ALLOY PER PROCUREMENT SPECIFICATION.

HEAT TREATMENT: MINIMUM SHEAR STRENGTH 95,000 PSI.

FINISH: NO PROTECTIVE FINISH REQUIRED.

LUBRICATION: CHLORINE FREE CETYL ALCOHOL.

CODE: DASH NUMBER DESIGNATES NOMINAL GRIP IN .0625 INCREMENTS.
ADD "V" AFTER BASIC PART NUMBER FOR 6AL-4V TITANIUM ALLOY.
ADD "H" AFTER BASIC NUMBER WHEN SEALANT ESCAPE GROOVE IS REQUIRED.

LIST OF CURRENT SHEETS

① INACTIVE FOR DESIGN AFTER OCT. 30, 1981.

SHT.	REV.
1	1
2	1

CUSTODIAN **NATIONAL AEROSPACE STANDARDS COMMITTEE**


PROCUREMENT
SPECIFICATION

NAS621

TITLE

**BOLT-LOCK, TENSION, 100° HEAD (MS20426),
STUMP -TYPE, TITANIUM ALLOY**

THIRD
ANGLE
PROJECTION



CLASSIFICATION

STANDARD PART

NAS2315 THRU 2322

SHEET 1 OF 2

USE OF OR RELIANCE UPON THIS DOCUMENT OR ANY NATIONAL AEROSPACE STANDARD IS ENTIRELY VOLUNTARY. AIA DOES NOT QUALIFY SUPPLIERS OR
CERTIFY CONFORMANCE OF ITEMS PROCURED UNDER NATIONAL AEROSPACE STANDARDS. AIA MAKES NO REPRESENTATION OR CLAIM RESPECTING (1) THE
Copyright Aerospace Industries Association of America Inc. S FOR ANY PARTICULAR APPLICATION, OR (2) THE EXISTENCE OF OR APPLICABILITY THERETO OF PATENT OR TRADEMARK RIGHTS.

NATIONAL AEROSPACE STANDARD

AEROSPACE INDUSTRIES ASSOCIATION OF AMERICA, INC., 1725 DE SALES STREET, N. W. WASHINGTON, D. C. 20036

EXAMPLES OF PART NUMBERS:

NAS2316V08 = .190 DIA 6AL-4V TITANIUM ALLOY PIN, 100° FLUSH HEAD, (MS20426), STUMP TYPE, .500 GRIP.

NAS2316VH08 = .190 DIA 6AL-4V TITANIUM ALLOY PIN, 100° FLUSH HEAD, (MS20426), SEALANT ESCAPE GROOVE, STUMP TYPE, .500 GRIP.

- NOTES: 1. DIMENSIONS IN INCHES.
 2. FOR RECOMMENDED HOLE SIZES, SEE NAS618.
 3. FOR COLLAR SELECTION, MINIMUM TENSILE STRENGTH, AND INSPECTION GAGE, SEE NAS1080.

GRIP DASH NUMBER	NOM GRIP	GRIP RANGE		+.015 G-.010	L + .015, -.005				
		MIN	MAX		.164 DIA	.190 DIA	.250 DIA	.312 DIA	.375 DIA
02	.125	.095	.156	.125	.324	.373	.456		
03	.188	.157	.219	.188	.387	.435	.519	.602	.697
04	.250	.220	.281	.250	.449	.498	.581	.664	.760
05	.312	.282	.344	.312	.512	.560	.644	.727	.822
06	.375	.345	.406	.375	.574	.623	.706	.789	.885
07	.438	.407	.469	.438	.637	.685	.769	.852	.947
08	.500	.470	.531	.500	.699	.748	.831	.914	1.010
09	.562	.532	.594	.562	.762	.810	.894	.976	1.072
10	.625	.595	.656	.625	.824	.873	.956	1.039	1.135
11	.688	.657	.719	.688	.887	.935	1.019	1.101	1.197
12	.750	.720	.781	.750	.949	.998	1.081	1.164	1.260
13	.812	.782	.844	.812	1.012	1.060	1.144	1.226	1.322
14	.875	.845	.906	.875	1.074	1.123	1.206	1.289	1.385
15	.938	.907	.969	.938	1.137	1.185	1.269	1.351	1.447
16	1.000	.970	1.031	1.000	1.199	1.248	1.331	1.414	1.510
17	1.062	1.032	1.094	1.062	1.262	1.310	1.394	1.476	1.572
18	1.125	1.095	1.156	1.125	1.324	1.373	1.456	1.539	1.635
19	1.188	1.157	1.219	1.188	1.387	1.435	1.519	1.602	1.697
20	1.250	1.220	1.281	1.250	1.449	1.498	1.581	1.664	1.760
21	1.312	1.282	1.344	1.312	1.512	1.560	1.644	1.727	1.822
22	1.375	1.345	1.406	1.375	1.574	1.623	1.706	1.789	1.885
23	1.438	1.407	1.469	1.438	1.637	1.685	1.769	1.852	1.947
24	1.500	1.470	1.531	1.500	1.699	1.748	1.831	1.914	2.010
25	1.562	1.532	1.594	1.562	1.762	1.810	1.894	1.976	2.072
26	1.625	1.595	1.656	1.625	1.824	1.873	1.956	2.039	2.135
27	1.688	1.657	1.719	1.688	1.887	1.935	2.019	2.101	2.197
28	1.750	1.720	1.781	1.750	1.949	1.998	2.081	2.164	2.260
29	1.812	1.782	1.844	1.812	2.012	2.060	2.144	2.226	2.322
30	1.875	1.845	1.906	1.875	2.074	2.123	2.206	2.289	2.385
31	1.938	1.907	1.969	1.938	2.137	2.185	2.269	2.351	2.447
32	2.000	1.970	2.031	2.000	2.199	2.248	2.331	2.414	2.510

① INACTIVE FOR DESIGN AFTER OCT. 30, 1981.

Published and distributed by: National Standards Association, Inc.

5161 River Road
Bethesda, Md. 20816Copyright Aerospace Industries Association of America Inc.
Provided by IHS under license with AIA/NAS
No reproduction or networking permitted without license from IHS

Full document details: AIA NAS2315-2322 1981

© Copyright 1981, Aerospace Industries Association of America, Inc.
All rights reserved.Licensee= www.sepana.ir/5991803002, User=sam, albert
Not for Resale, 01/09/2016 03:39:02 MSTNAS2315-2322
SHEET 2

APPROVAL DATE Dec. 1973 REVISION ① 30 Oct. 1981

AIA AND ITS COMMITTEES WILL NOT INVESTIGATE THE APPLICABILITY OF PATENTS TO THE SUBJECT MATTER OF NAS STANDARDS AND IN RESPECT THEREOF DO NOT ASSUME ANY LIABILITY TO PATENT OWNERS OR TO PROSPECTIVE USERS.

THIS DRAWING SUPERSEDES ALL ANTECEDENT STANDARD DRAWINGS FOR THE SAME PRODUCT AND SHALL BECOME EFFECTIVE NO LATER THAN SIX MONTHS FROM THE LAST DATE OF APPROVAL SHOWN HEREON.