

FED. SUPPLY CLASS

5325

TAPE ALLOWANCE

1 1/4 MIN

LENGTH
NOMINAL

1 1/4 MIN

TYPE A

LENGTH
NOMINAL

TYPE B

LENGTH
NOMINAL

TYPE C

LENGTH
NOMINAL

TYPE D

LENGTH
NOMINAL


TYPE E

LENGTH
NOMINAL

TYPE F

LENGTH
NOMINAL

TYPE G



SHORT TAB PULL

FINISH:


TAPE COLOR SHADE NO. 613 OF ANA BULLETIN NO. 157 34088 PER FED-STD-595, NATURAL FINISH ON CHAIN.

CODE:

SIZE 00 = EXTRA LIGHT SERVICE /1/
SIZE 0 = LIGHT SERVICE
SIZE 1 = LIGHT-MEDIUM SERVICE
SIZE 2 = MEDIUM SERVICE
SIZE 3 = MEDIUM-HEAVY SERVICE
SIZE 4 = HEAVY SERVICE

THE INITIAL RELEASE OF THIS DOCUMENT SUPERSEDES AN229, REVISION 5. PART NUMBERS REMAIN AN229.

THIRD
ANGLE
PROJECTION



CUSTODIAN

NATIONAL AEROSPACE STANDARDS COMMITTEE

REVISION

2

PROCUREMENT
SPECIFICATION

A-A-55634

EXCEPT AS NOTED

TITLE

FASTENERS, INTERLOCKING SLIDE

CLASSIFICATION
PART STANDARD

NASM229
SHEET 1 OF 2



Document Sharing Hub

TYPE A = NON-SEPARATING, SINGLE ACTION.
TYPE B = SEPARATING, SINGLE ACTION.
TYPE C = NON-SEPARATING, SINGLE ACTION WITH BRIDGE STOP.
TYPE D = SEPARATING, SINGLE ACTION, QUICK DETACHING.
TYPE E = NON-SEPARATING, DOUBLE ACTION, CENTER OPENING.
TYPE F = NON-SEPARATING, DOUBLE ACTION WITH BRIDGE STOP.
TYPE G = SEPARATING, DOUBLE ACTION, END OPENING.

STYLE S = STANDARD NON-LOCKING.
STYLE L = LOCKING.

GRADE I = BRASS.
~~GRADE II = ZINC-ALLOY. /2/~~

FIRST DASH NO. SHALL INCLUDE SIZE, TYPE, AND LENGTH EXPRESSED IN 1/4 INCH INCREMENTS.

EXAMPLES OF PART NO:

AN229-2AL25-I = MEDIUM SERVICE, NON-SEPARATING, SINGLE ACTION, LOCKING, 6-1/4 LONG, GRADE I.
~~AN229-1BS35-II = LIGHT MEDIUM SERVICE, SEPARATING, SINGLE ACTION, NON-LOCKING, 8-3/4 LONG, GRADE II.~~

NOTES:

- /1/ INACTIVE FOR NEW DESIGN AFTER 16 DEC 1949. USE SIZE 0.
- /2/ INACTIVE FOR NEW DESIGN AFTER 15 AUGUST 1968. USE GRADE I.
- (3) AN229 GRADE II CANCELLED AFTER 1 AUGUST 1968.
- (4) INTERCHANGEABILITY RELATIONSHIP, AN229 GRADE I IS UNIVERSALLY SUBSTITUTABLE WHEREVER GRADE II IS SPECIFIED.
- (5) DIMENSIONS IN INCHES AND APPLY AFTER FINISH UNLESS OTHERWISE SPECIFIED.
- (6) UNLESS OTHERWISE SPECIFIED, ALL FASTENERS TO BE CLASS A, SHORT TAB PULL WITH HOLE AS SHOWN.
- (7) RIGHT HAND SLIDE ASSEMBLY IS STANDARD FOR QUICK DETACHING FASTENERS: SPECIFY LEFT SLIDE ASSEMBLY WHEN REQUIRED.
- (8) THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.
- (9) UNLESS OTHERWISE SPECIFIED, PART INVENTORY MANUFACTURED TO PREVIOUS REVISIONS OF THE APPLICABLE DRAWING OR SPECIFICATION MAY BE PROCURED AND USED UNTIL STOCK IS DEPLETED.
- (2) (10) UNLESS OTHERWISE SPECIFIED HEREIN, REFERENCED DOCUMENTS SHALL BE THE ISSUE IN EFFECT ON DATE OF MANUFACTURE. HOWEVER, EXISTING MATERIAL INVENTORY CERTIFIED TO A PREVIOUS REVISION OF THE APPLICABLE MATERIAL SPECIFICATION(S) IS ACCEPTABLE FOR USE UNTIL DEPLETION.
- (11) DIMENSIONING AND TOLERANCING PER ANSI Y14.5M-1982.

REVISION
2
NAS229
SHEET 2

