
AMERICAN NATIONAL STANDARD

Quantities and Procedures for Description and Measurement of Environmental Sound, Part 7: Measurement of Low-frequency Noise and Infrasound Outdoors and in the Presence of Wind and Indoors in Occupied Spaces

ANSI/ASA S12.9-2016/Part 7

Accredited Standards Committee S12, Noise

Standards Secretariat
Acoustical Society of America
1305 Walt Whitman Road, Suite 300
Melville, NY 11747

The American National Standards Institute, Inc. (ANSI) is the national coordinator of voluntary standards development and the clearinghouse in the U.S.A. for information on national and international standards.

The Acoustical Society of America (ASA) is an organization of scientists and engineers formed in 1929 to increase and diffuse the knowledge of acoustics and to promote its practical applications.



AMERICAN NATIONAL STANDARD

**Quantities and Procedures for Description and
Measurement of Environmental Sound, Part 7:
Measurement of Low-frequency Noise and Infrasound
Outdoors in the Presence of Wind and Indoors in
Occupied Spaces**

Secretariat:

Acoustical Society of America

Approved on April 25, 2016, by:

American National Standards Institute, Inc.

Abstract

Part 7 of the ANSI/ASA S12.9 series describes cautions and unique techniques for measuring low-frequency noise (LFN) outdoors in the presence of wind. It is necessary to measure in wind for wind turbine projects and for countless other industrial power and facilities where environmental wind speed cannot be controlled or levels are specified under downwind conditions. The standard also describes a uniform and repeatable methodology for documenting LFN levels and spectra indoors in occupied spaces where modal considerations are important. The principal concern outdoors is wind-induced noise (WIN) created by wind sources alone. The best estimates for WIN versus wind speed are presented herein based on the literature and special testing conducted by the working group for this standard. The standard is intended to define methods for routinely observed or monitored measurements of infrasound and LFN (ILFN) with standard off-the-shelf instrumentation, commercially available or special windscreens, and microphones appropriate to the task at hand. Following the standard methods should promote uniform, repeatable, and comparable data from site to site.

AMERICAN NATIONAL STANDARDS ON ACOUSTICS

The Acoustical Society of America (ASA) provides the Secretariat for Accredited Standards Committees S1 on Acoustics, S2 on Mechanical Vibration and Shock, S3 on Bioacoustics, S3/SC 1 on Animal Bioacoustics, and S12 on Noise. These committees have wide representation from the technical community (manufacturers, consumers, trade associations, organizations with a general interest, and government representatives). The standards are published by the Acoustical Society of America as American National Standards after approval by their respective Standards Committees and the American National Standards Institute (ANSI).


These standards are developed and published as a public service to provide standards useful to the public, industry, and consumers, and to Federal, State, and local governments.

Each of the Accredited Standards Committees (operating in accordance with procedures approved by ANSI) is responsible for developing, voting upon, and maintaining or revising its own Standards. The ASA Standards Secretariat administers Committee organization and activity and provides liaison between the Accredited Standards Committees and ANSI. After the Standards have been produced and adopted by the Accredited Standards Committees, and approved as American National Standards by ANSI, the ASA Standards Secretariat arranges for their publication and distribution.

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered and that a concerted effort be made towards their resolution.

The use of an American National Standard is completely voluntary. Their existence does not in any respect preclude anyone, whether he or she has approved the Standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the Standards.

NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this Standard.



Acoustical Society of America
ASA Secretariat
1305 Walt Whitman Road, Suite 300
Melville, New York 11747
Telephone: 1 (631) 390-0215
Fax: 1 (631) 923-2875
E-mail: asastds@acousticalsociety.org

© 2016 by Acoustical Society of America. This standard may not be reproduced in whole or in part in any form for sale, promotion, or any commercial purpose, or any purpose not falling within the provisions of the U.S. Copyright Act of 1976, without prior written permission of the publisher. For permission, address a request to the Standards Secretariat of the Acoustical Society of America.

Contents

1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Instrumentation	3
4.1	Instrumentation sets and measurement grades	3
4.2	Survey-grade LFN	3
4.3	Survey-grade ILFN	3
4.4	Precision-grade LFN	3
4.5	Precision-grade ILFN	4
5	Measurement metric	4
5.1	Basic metric	4
5.2	Supplemental metric	4
6	Outdoor measurements	4
6.1	Measurement types	4
6.2	Windscreen selection	5
6.3	Estimation of lowest measurable frequency band	8
6.4	Reporting	9
7	Indoor measurements	10
7.1	General	10
7.2	Winds	10
7.3	Measurement locations and descriptions	10
7.4	Windscreen selection	11
7.5	Analysis results	11
7.6	Reporting	12
8	Signal processing techniques	13
Annex A	(informative) Examples of outdoor/indoor measurement testing – unsteady source	14
A.1	Introduction	14
A.2	Possible deviations	14
A.3	Test results	16
Annex B	(informative) Development of wind-induced noise (WIN) estimates	19
Annex C	(informative) Estimation of sound level spectra at normal above-grade microphone height from ground-plane results	23
Annex D	(informative) Advanced signal processing techniques	25
D.1	Introduction	25
D.2	Low-frequency wind turbine noise	25
D.3	Signal acquisition and analysis options	28

Figures

Figure 1 – Wind-induced noise (WIN) measurement setup; in the Mojave Desert (upper image) in California and western Oregon (lower image)	5
Figure 2a – Measured A- and C- weighted wind-induced noise levels for a 175 mm 20 ppi windscreen	6
Figure 2b – Measured G-weighted wind-induced noise levels for a 175 mm 20 ppi windscreen.....	6
Figure 3 – Measured C- and G-weighted levels in the 6-7 m/s wind speed bin for the seven microphone setups in the Mohave Desert (see Annex B)	7
Figure 4 – Example of measured wind turbine generator (WTG) spectra for low and high wind conditions compared to wind-induced noise (WIN)	9
Figure 5 – Indoor test setup	11
Figure A.1 – Depiction of measurement locations from inside interior space.....	14
Figure A.2 – Depiction of measurement locations on exterior of interior space	15
Figure A.3 – Raw measurement data normalized to free field.....	15
Figure A.4 – Noise reduction (NR_e) for each of two trials	16
Figure A.5 – 5-min duration Leq for outdoor and indoor measurement locations	17
Figure A.6 – 5-min duration Leq summary.....	18
Figure C.1 – Theoretical and measured corrections to convert from a ground-plane measurement to one at 1.5 m above grade to include ground-reflected wave	24

Tables

Table B.1 Measured spectral wind-induced noise (WIN) at site W (Mojave Desert) for seven windscreen designs (continued on next page)	20
Table B.1 - Measured spectral wind-induced noise (WIN) at site W (Mojave Desert) for seven windscreen designs (page 2).....	21
Table B.2 – Windscreen insertion loss.....	22

Foreword

[This Foreword is for information only, and is not a part of the American National Standard ANSI/ASA S12.9-2016/Part 7 American National Standard Quantities and Procedures for Description and Measurement of Environmental Sound, Part 7: Measurement of Low-frequency Noise and Infrasound Outdoors in the Presence of Wind and Indoors in Occupied Spaces. As such, this Foreword may contain material that has not been subjected to public review or a consensus process. In addition, it does not contain requirements necessary for conformance to the standard.]

This standard comprises a part of a group of definitions, standards, and specifications for use in noise. It was developed and approved by Accredited Standards Committee S12 Noise, under its approved operating procedures. Those procedures have been accredited by the American National Standards Institute (ANSI). The Scope of Accredited Standards Committee S12 is as follows:

Standards, specifications, and terminology in the field of acoustical noise pertaining to methods of measurement, evaluation, and control, including biological safety, tolerance, and comfort, and physical acoustics as related to environmental and occupational noise.

This standard is a new part of the ANSI/ASA S12.9 series *American National Standard Quantities and Procedures for Description and Measurement of Environmental Sound*.

This standard is not comparable to any existing ISO Standard.

At the time this Standard was submitted to Accredited Standards Committee S12 - Noise for approval, the membership was as follows:

S.J. Lind, *Chair*
D.F. Winker, *Vice-Chair*

S.B. Blaeser, *Secretary*

3M Occupational Health & Environmental Safety Division	E.H. Berger
Acoustical Society of America	R.D. Hellweg
.....	D. Lubman (Alt.)
Air-Conditioning, Heating and Refrigeration Institute	S.J. Lind
.....	D. Abbate (Alt.)
Air Movement & Control Association, Inc.	J.A. Brooks
.....	M. Stevens (Alt.)
American Academy of Audiology	T. Ricketts
.....	C. Schweitzer (Alt.)
American Academy of Otolaryngology - Head and Neck Surgery	R.A. Dobie
.....	A. Kim (Alt.)
American Industrial Hygiene Association	D. Driscoll
.....	M. Kram (Alt.)
American Speech-Language-Hearing Association	L.A. Wilber
.....	N. DiSarno (Alt.)
Boeing Commercial Airplanes, Noise, Vibration & Emissions	K. Lai
.....	M. Kosanchick (Alt.)
Caterpillar, Inc.	K.G. Meitl

Compressed Air and Gas Institute	R.C. Johnson
.....	D.R. Bookshar (Alt.)
Council for Accreditation in Occupational Hearing Conservation	C. Moritz
.....	C. Achutan (Alt.)
Emerson Electric – Copeland Corporation	A.T. Herfat
.....	G. Williamson (Alt.)
ESI Group	S. McGregor
ETS – Lindgren Acoustic Systems	D.F. Winker
.....	M. Black (Alt.)
ExxonMobil	B. Moulton
G.R.A.S. Sound & Vibration	B. Schustrich
.....	J. Soendergaard (Alt.)
GE Aviation	R. Majjigi
.....	R. Babbitt (Alt.)
General Motors	D.B. Moore
Honeywell Safety Products	R. Ghent
.....	B. Witt (Alt.)
Information Technology Industry Council	W.M. Beltman
.....	J. Rosenberg (Alt.)
Institute of Noise Control Engineering	J.M. Cuschieri
.....	B. Tinianov (Alt.)
International Safety Equipment Association	J. Birkner
.....	C.Z. Fargo (Alt.)
John Deere	S. Suh
National Council of Acoustical Consultants	B.M. Brooks
.....	G.E. Winzer (Alt.)
National Hearing Conservation Association	T. Thunder
.....	R. Paulsen (Alt.)
National Institute for Occupational Safety and Health	W.J. Murphy
.....	E. Zechmann (Alt.)
National Institute of Standards and Technology – National Voluntary Laboratory Accreditation Program	K Harper
National Park Service	M. McKenna
.....	K. Frstrup (Alt.)
Noise Control Engineering, Inc.	M.A. Bahtiarian
.....	R. Fischer (Alt.)
Noise Pollution Clearinghouse	L. Blomberg
Power Tool Institute, Inc.	W.D. Spencer
.....	M. Hickok (Alt.)

Schomer and Associates, Inc.	P.D. Schomer
U.S. Air Force	R.L. McKinley
.....	H. Gallagher (Alt.)
U.S. Army Aeromedical Research Laboratory	W.A. Ahroon
U.S. Army Construction Engineering Research Laboratory	M.J. White
.....	M. Swearingen (Alt.)
U.S. Army Public Health Command	C. Stewart
.....	M. Robinette (Alt.)
.....	C. Jokel (Alt.)
U.S. Army Research Laboratory, Human Research and Engineering Directorate	J. Gaston
.....	P. Fedeale (Alt.)
U.S. Department of Transportation	C. Mittleholtz
.....	C. Roof (Alt.)
U.S. Naval Surface Warfare Center - Carderock	S. Anderson
.....	W. Martin (Alt.)
Université du Québec ETS	J. Voix
.....	F. Laville (Alt.)

Individual Experts of Accredited Standards Committee S12, Noise, were:

B.M. Brooks	D. Lubman	J.G. Schmitt
A.J. Campanella	D.S. Michaud	P.D. Schomer
L.S. Finegold	N.P. Miller	L.C. Sutherland
R.D. Hellweg	W.J. Murphy	W.R. Thornton
A. Konheim	M.A. Nobile	L.A. Wilber
S.J. Lind	R.J. Peppin	G.E. Winzer

Working Group S12/WG 54, which assisted Accredited Standards Committee S12, Noise, in the development of this standard, had the following membership.

G.F. Hessler, Chair
P.D. Schomer, Vice Chair

J. Anderson	R.D. Horonjeff	R.A. Putnam
M. Bastasch	A. Huskey	R. Raspet
V. Buzduga	K. Kaliski	G. Sanchez
A.J. Campanella	K.W. Kinzie	M. Storm
M. Hankard	N.L. Lewis	B. Thorne
R.D. Hellweg	C. Long	B.E. Walker
D.M. Hessler	R.D. O'Neal	E.T. Watson
	R.J. Peppin	

Suggestions for improvements to this standard will be welcomed. They should be sent to Accredited Standards Committee S12, Noise, in care of the Standards Secretariat of the Acoustical Society of America, 1305 Walt Whitman Road, Suite 300, Melville, New York 11747-4300. Telephone: 631-390-0215; FAX: 631-923-2875; E-mail: asastds@acousticalsociety.org.

Introduction

Measuring outdoor sound pressure levels and spectra can be difficult in the presence of wind, even at very low wind speeds often defined as “acceptable” in many measurement standards. Wind-induced noise (WIN) is the principal problem and can produce a false indicator of sound pressure at low frequencies mistaken for actual low-frequency noise when in fact no such low-frequency noise is present. WIN is the sound that can be measured in remote quiet environments essentially free of all anthropogenic and natural sources of sound, except for wind-generated noise such as leaf noise and pseudo microphone noise. Experience shows that accurate outdoor measurements down to conventional frequency range limits (i.e., the 16 Hz or 31.5 Hz octave band) can only be made under nearly ideal “calm and still” conditions when using standard relatively small windscreens. Conditions are calm and still when there is no measurable wind speed at microphone height and no observable grass or tree leaf movement or audible sound.

Note that this experience and statement applies to precision type 1 instrumentation while using the windscreen (60 to 90 mm diameter) furnished by the instrument supplier. Measuring the overall A-weighted outdoor level is much less of a problem due to the severe weighting of the A scale filter, but measuring the C- or G-weighted levels usually requires calm and still conditions or improved wind protection. The A-weighting filter may not be appropriate for evaluating low-frequency noise (LFN) or infrasonic-plus-low-frequency noise (ILFN).

The procedures contained herein allow WIN to be estimated yielding the lowest levels for valid measurements in each frequency band in the presence of low to high wind speeds. WIN for seven improved windscreen designs have been measured and are tabulated herein. Using these data, one can separate true acoustic ILFN from wind-induced noise. This information is also informative to instrumentation suppliers in the development of commercial products.

Measurement of indoor sound at low frequencies is addressed, and a standard test measurement methodology is developed that should yield repeatable data from site to site and from one investigator to another.

Acknowledgement

The working group of volunteers for this standard has expended much time and effort in designing, fabricating, and testing improved windscreen devices to lower the valid frequency for which sound can be measured in the presence of wind. The results are contained in the standard and annexes. The chair would like to especially acknowledge the contribution of Dr. Bruce Walker of Channel Islands Acoustics for an extraordinary effort that far surpassed the considerable efforts of other members.

American National Standard

Quantities and Procedures for Description and Measurement of Environmental Sound, Part 7: Measurement of Low-frequency Noise and Infrasound Outdoors In the Presence of Wind and Indoors in Occupied Spaces

1 Scope

This standard provides requirements and methods for measuring low-frequency sound and noise levels outdoors in the presence of wind and indoors in occupied spaces. The most common application anticipated is the measurement of outdoor immission levels either near or far from sound emission sources or emission levels near a source.

A repeatable method for measuring low-frequency levels and spectra indoors is given so that results can be compared from site to site or for repeated measurements at the same site under differing operating scenarios or time periods.

The value of this method to indoor measurements is that wind effects on the microphone are eliminated. However, two new variables are introduced: wind impinging on a structure creates significant low-frequency noise that is difficult to quantify, and measuring indoors with room sizes comparable to or smaller than low-frequency wavelengths requires an accounting of room resonance modes. Nevertheless, following the prescribed measurement technique in low-wind conditions should give a uniform repeatable method of measurement that accounts for differing room modes from space to space.

The standard does not address all factors to be considered when measuring the emissions of sources or background sound levels in the environment that are covered in other standards. Such factors may be measurement metrics, duration of measurements, background corrections, time of day, and countless others. Usually, wind speeds in these specific standards are limited to low values (about 2 m/s or 5 mph) to minimize wind-induced noise effects. Measured data in the annexes show clearly that wind, even at these low wind speeds, significantly affects the measurements at very low frequencies. This standard is limited to measurement techniques, principally microphone wind-mitigation measures that can be used to quantify such wind effects. Hence, the wind-mitigation techniques for microphone protection described herein are supplemental to existing measurement standards.

Advanced signal processing techniques in the time domain that can detect ILFN signals in the presence of wind are discussed briefly and referenced.

2 Normative references

The following referenced documents are indispensable for the application of this standard. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ANSI/ASA S1.1-2013 *American National Standard Acoustical Terminology*

ANSI/ASA S1.4-2014/Part 1 / IEC 61672-1:2013 *American National Standard Electroacoustics – Sound Level Meters – Part 1: Specifications*

ANSI/ASA S1.11-2014/Part 1 / IEC 61260-1:2014 *American National Standard Electroacoustics - Octave-band and Fractional-octave-band Filters – Part 1: Specifications*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ANSI/ASA S1.1 and the following apply.

3.1

pseudo-noise

false indication of sound pressure level when in fact it is microphone response to pressure pulsations from airborne turbulence and stagnation pressure occurring in windy environments

NOTE Pseudo-noise is microphone-sensed pressure fluctuations that result from other than acoustic propagation, most commonly convective turbulent pressure fluctuations and vortex shedding by measurement microphones and accessories.

3.2

wind-induced noise

WIN

noise measured by a microphone and associated windscreen that results from the combination of pseudo-noise and the acoustic noise from objects put into motion by the wind (e.g., leaf rustle noise)

NOTE WIN (alone without any significant acoustic signals) can be measured in very quiet and remote environments essentially free of anthropogenic sources. For the purposes of this standard, WIN encompasses the frequency range of near 0.5 to 250 Hz. The overall weighted sound pressure levels, whether A-, C- or G-weighted, are calculated from this measured spectra to minimize contributions of higher frequency sources such as grass and tree-leaf rustle.

3.3

low-frequency noise

LFN

sound pressures in the one-third-octave bands having band center frequencies ranging from 20 to 200 Hz that generally may be audible and detectable

3.4

infrasound

sound at frequencies less than 20 Hz

NOTE For the purposes of this standard, the term “infrasound” may be considered synonymous with infrasonic-plus-low-frequency sound.

3.5

infrasonic-plus-low-frequency noise

ILFN

combination of infrasound and low-frequency noise covering the frequency range from 0.5 to 200 Hz

NOTE Noise is normally defined as unwanted sound at sensitive locations. It is recognized that ILFN measurement techniques addressed in this standard can be made for purposes other than investigating potential or perceived noise issues and the term noise may be inappropriate but it is used herein for convenience.

4 Instrumentation

4.1 Instrumentation sets and measurement grades

Sets of instrumentation are specified in this standard. Each set corresponds to one of the four combinations of source (LFN or ILFN) and grade (survey or precision).

- **Survey-grade measurements** are for general or routine-purpose situations.
- **Precision-grade measurements** are for situations requiring the best available precision.

It is the intent of this standard that these measurements can be made using readily available (from at least three suppliers) off-the-shelf instrumentation, but not to the exclusion of custom-built systems. The microphone/preamplifier used shall be selected based on the measurement grade and maximum low-frequency limit as described below. Windscreen requirements are given in 6.2 and 7.4 for indoors and outdoors, respectively.

4.2 Survey-grade LFN

4.2.1 All instrumentation shall meet the class 1 requirements given in ANSI/ASA S1.4-2014/Part 1 / IEC 61672-1:2013 and filters thereto shall meet the class 1 requirements given in ANSI/ASA S1.11-2014/Part 1 / IEC 61260-1:2014.

4.2.2 The microphone, preamplifier, and associated instruments shall be specially tested to verify that the frequency response is ± 1 dB in the frequency range included in the one-third-octave bands from 20 Hz through 200 Hz. Instrumentation with the readily available frequency range of 12.5 Hz through 200 Hz shall be used for the survey grade.

4.2.3 The microphone shall include a windscreen recommended by the manufacturer or better.

4.3 Survey-grade ILFN

4.3.1 All instrumentation shall meet the class 1 requirements given in ANSI/ASA S1.4-2014/Part 1 / IEC 61672-1:2013 and filters thereto shall meet the class 1 requirements given in ANSI/ASA S1.11-2014/Part 1 / IEC 61260-1:2014.

4.3.2 The microphone, preamplifier, and associated instruments shall be specially tested to verify that the frequency response is ± 1 dB in the frequency range included in the one-third-octave bands from 3.15 Hz through 200 Hz, and is ± 3 dB in the frequency range included in the one-third-octave bands from 0.5 Hz through 2.5 Hz. Instrumentation with the readily available frequency range of 0.5 Hz through 200 Hz shall be used for the survey grade.

4.3.3 The microphone shall include a windscreen recommended by the manufacturer or better.

4.4 Precision-grade LFN

4.4.1 All instrumentation shall meet the class 1 requirements given in ANSI/ASA S1.4-2014/Part 1 / IEC 61672-1:2013 and filters thereto shall meet the class 1 requirements given in ANSI/ASA S1.11-2014/Part 1 / IEC 61260-1:2014.

4.4.2 The microphone, preamplifier, and associated instruments shall be specially tested to verify that the frequency response is ± 0.5 dB in the frequency range included in the one-third-octave bands from 0.4 Hz through 200 Hz. Instrumentation with the readily available frequency range of 0.4 Hz through 200 Hz shall be used for the precision grade.