

TECHNICAL REPORT
ANSI/ISA–TR12.21.01–2004 (R2013)
Use of Fiber Optic Systems in
Class I Hazardous (Classified) Locations
ANSI Technical Report prepared by ISA
Approved 1 September 2013

ANSI/ISA-TR12.21.01-2004 (R2013)
Use of Fiber Optic Systems in Class I Hazardous (Classified) Locations

ISBN: 978-0-876640-30-2

Copyright © 2013 by the International Society of Automation (ISA). All rights reserved. Not for resale. Printed in the United States of America. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means (electronic mechanical, photocopying, recording, or otherwise), without the prior written permission of the Publisher.

ISA
67 Alexander Drive
P.O. Box 12277
Research Triangle Park, North Carolina 27709

Preface

This preface, as well as all footnotes and annexes, is included for information purposes and is not part of ANSI/ISA-TR12.21.01-2004 (R2013).

This document has been prepared as part of the service of ISA toward a goal of uniformity in the field of instrumentation. To be of real value, this document should not be static but should be subject to periodic review. Toward this end, the Society welcomes all comments and criticisms and asks that they be addressed to the Secretary, Standards and Practices Board; ISA; 67 Alexander Drive; P. O. Box 12277; Research Triangle Park, NC 27709; Telephone (919) 549-8411; Fax (919) 549-8288; E-mail: standards@isa.org.

The ISA Standards and Practices Department is aware of the growing need for attention to the metric system of units in general, and the International System of Units (SI) in particular, in the preparation of instrumentation standards. The Department is further aware of the benefits to USA users of ISA standards of incorporating suitable references to the SI (and the metric system) in their business and professional dealings with other countries. Toward this end, this Department will endeavor to introduce SI-acceptable metric units in all new and revised standards, recommended practices, and technical reports to the greatest extent possible. IEEE/ASTM SI 10, *American National Standard for Metric Practice*, and future revisions, will be the reference guide for definitions, symbols, abbreviations, and conversion factors.

It is the policy of ISA to encourage and welcome the participation of all concerned individuals and interests in the development of ISA standards, recommended practices, and technical reports. Participation in the ISA standards-making process by an individual in no way constitutes endorsement by the employer of that individual, of ISA, or of any of the standards, recommended practices, and technical reports that ISA develops.

CAUTION — ISA DOES NOT TAKE ANY POSITION WITH RESPECT TO THE EXISTENCE OR VALIDITY OF ANY PATENT RIGHTS ASSERTED IN CONNECTION WITH THIS DOCUMENT, AND ISA DISCLAIMS LIABILITY FOR THE INFRINGEMENT OF ANY PATENT RESULTING FROM THE USE OF THIS DOCUMENT. USERS ARE ADVISED THAT DETERMINATION OF THE VALIDITY OF ANY PATENT RIGHTS, AND THE RISK OF INFRINGEMENT OF SUCH RIGHTS, IS ENTIRELY THEIR OWN RESPONSIBILITY.

PURSUANT TO ISA'S PATENT POLICY, ONE OR MORE PATENT HOLDERS OR PATENT APPLICANTS MAY HAVE DISCLOSED PATENTS THAT COULD BE INFRINGED BY USE OF THIS DOCUMENT AND EXECUTED A LETTER OF ASSURANCE COMMITTING TO THE GRANTING OF A LICENSE ON A WORLDWIDE, NON-DISCRIMINATORY BASIS, WITH A FAIR AND REASONABLE ROYALTY RATE AND FAIR AND REASONABLE TERMS AND CONDITIONS. FOR MORE INFORMATION ON SUCH DISCLOSURES AND LETTERS OF ASSURANCE, CONTACT ISA OR VISIT WWW.ISA.ORG/STANDARDSPATENTS.

OTHER PATENTS OR PATENT CLAIMS MAY EXIST FOR WHICH A DISCLOSURE OR LETTER OF ASSURANCE HAS NOT BEEN RECEIVED. ISA IS NOT RESPONSIBLE FOR IDENTIFYING PATENTS OR PATENT APPLICATIONS FOR WHICH A LICENSE MAY BE REQUIRED, FOR CONDUCTING INQUIRIES INTO THE LEGAL VALIDITY OR SCOPE OF PATENTS, OR DETERMINING WHETHER ANY LICENSING TERMS OR CONDITIONS PROVIDED IN CONNECTION WITH SUBMISSION OF A LETTER OF ASSURANCE, IF ANY, OR IN ANY LICENSING AGREEMENTS ARE REASONABLE OR NON-DISCRIMINATORY.

ISA REQUESTS THAT ANYONE REVIEWING THIS DOCUMENT WHO IS AWARE OF ANY PATENTS THAT MAY IMPACT IMPLEMENTATION OF THE DOCUMENT NOTIFY THE ISA STANDARDS AND PRACTICES DEPARTMENT OF THE PATENT AND ITS OWNER.

ADDITIONALLY, THE USE OF THIS DOCUMENT MAY INVOLVE HAZARDOUS MATERIALS, OPERATIONS OR EQUIPMENT. THE DOCUMENT CANNOT ANTICIPATE ALL POSSIBLE APPLICATIONS OR ADDRESS ALL POSSIBLE SAFETY ISSUES ASSOCIATED WITH USE IN HAZARDOUS CONDITIONS. THE USER OF THIS DOCUMENT MUST EXERCISE SOUND PROFESSIONAL JUDGMENT CONCERNING ITS USE AND APPLICABILITY UNDER THE USER'S PARTICULAR CIRCUMSTANCES. THE USER MUST ALSO CONSIDER THE APPLICABILITY OF ANY GOVERNMENTAL REGULATORY LIMITATIONS AND ESTABLISHED SAFETY AND HEALTH PRACTICES BEFORE IMPLEMENTING THIS DOCUMENT.

THE USER OF THIS DOCUMENT SHOULD BE AWARE THAT THIS DOCUMENT MAY BE IMPACTED BY ELECTRONIC SECURITY ISSUES. THE COMMITTEE HAS NOT YET ADDRESSED THE POTENTIAL ISSUES IN THIS VERSION.

The following people served as members of ISA Subcommittee ISA12.21 which prepared this technical report:

NAME	COMPANY
P. Kelly, ISA12.21 Chair	UL LLC
M. Coppler, Managing Director	Det Norske Veritas Certification Inc.
D. Baker	P & D Electric Inc.
P. Byrne	FM Approvals
T. Dubaniewicz	NIOSH
R. Harner	The Dow Chemical Co.
C. Kurtzman	Rosemount Inc.
N. Ludlam	FM Approvals Ltd.
V. Maggioli	Feltronics Corp.
J. Miller	Detector Electronics Corp.
J. Thomas	Schlumberger

The following people served as members of ISA Committee ISA12:

NAME	COMPANY
T. Schnaare, ISA12 Chair	Rosemount Inc.
W. Lawrence, ISA12 Vice Chairman	FM Approvals LLC
M. Coppler, Managing Director	Det Norske Veritas Certification Inc.
R. Allen	Honeywell Inc.
D. Ankele	UL LLC
K. Boegli	Phoenix Contact
D. Burns	Shell P&T – Innovation / R&D
C. Casso	Nabors Industries
M. Dona	Santos Ltd.
T. Dubaniewicz	NIOSH
D. El Tawy	Solar Turbines, Inc.
W. Fiske	Intertek
G. Garcha	GE Energy
R. Holub	The DuPont Company Inc.
J. Jonscher	Adalet PLM
P. Kovscek	Industrial Scientific Corp.
J. Kuczka	Killark
E. Leubner	Cooper Crouse-Hinds
N. Ludlam	FM Approvals Ltd.
E. Massey	Baldor Electric Co.

J. Miller	Detector Electronics Corp.
A. Page	Consultant
R. Seitz	Artech Engineering
R. Sierra	USCG
M. Spencer	Columbia Gas Transmission
R. Wigg	E-x Solutions International Pty. Ltd.

This technical report was approved for publication by the ISA Standards and Practices Board on 22 July 2012.

NAME	COMPANY
E. Cosman, Vice President	The Dow Chemical Co.
D. Bartusiak	ExxonMobil Chemical Co.
P. Brett	Honeywell Inc.
J. Campbell	Consultant
M. Coppler	Det Norske Veritas Certification Inc.
B. Dumortier	Schneider Electric
D. Dunn	Aramco Services Co.
J. Federlein	Federlein & Assoc. Inc.
J. Gilsinn	Kenexis Consulting
E. Icaan	Atkins
J. Jamison	Spectra Energy Ltd.
K.P. Lindner	Endress+Hauser Process Solutions AG
V. Maggioli	Feltronics Corp.
T. McAviney	Instrumentation and Control Engineering, LLC
V. Mezzano	Fluor Corp.
C. Monchinski	Automated Control Concepts Inc.
R. Reimer	Rockwell Automation
S. Russell	Valero Energy Corp.
N. Sands	DuPont
H. Sasajima	Azbil Corp.
T. Schnaare	Rosemount Inc.
J. Tatera	Tatera & Associates Inc.
I. Verhappen	Industrial Automation Networks Inc.
W. Weidman	WCW Consulting
J. Weiss	Applied Control Solutions LLC
M. Wilkins	Yokogawa IA Global Marketing USMK
D. Zetterberg	Chevron Energy Technology Company

This page intentionally left blank.

Contents

Foreword	9
Abstract.....	9
Key Words.....	9
1 Scope	11
2 Purpose	11
3 Definitions and figures	11
4 Introduction	17
5 Optical ignition characteristics.....	17
6 Protection concepts.....	19
7 Installation and maintenance	24
8 References	25

This page intentionally left blank.

Foreword

At this time there is minimal awareness of the potential risk associated with optical ignitions even though fiber optic systems have been used for at least 20 years in hazardous (classified) locations. Hazardous (classified) locations are described in the *National Electrical Code*® (*NEC*®). (*National Electrical Code* and *NEC* are registered trademarks of the National Fire Protection Association, Quincy, MA.) One purpose of this technical report is to inform industry of potential ignition hazards associated with the use of fiber optic systems in explosive gas atmospheres. The technical report is also intended to suggest engineering and installation practices to reduce the ignition hazard from fiber optic systems in Class I locations. This technical report is provided for general guidelines pending the final results of ongoing testing and the development of official standards.

Safety standards to reduce human exposure hazards from laser equipment and fiber optic communication systems are found in IEC 60825, Parts 1 and 2.

Publication of this ANSI Technical Report has been approved by ISA. This document is registered as a Technical Report series of publication according to the procedures for the Registration of ANSI Technical Reports. This document is not an American National Standard and the material contained herein is not normative in nature. Comments on the content of this document should be sent to ISA.

Abstract

For optical wavelengths in the visible, near infrared, and certain regions of the mid infrared, ignition of an explosive gas atmosphere occurs with the lowest beam strength when a target intercepting the beam is heated to a high temperature. Minimum ignition criteria for explosive gas atmospheres are described in terms of the beam's spatial and temporal characteristics. Three protection concepts are described for preventing ignitions by fiber optic terminal devices and cables in Class I hazardous (classified) locations. Hazardous (classified) locations are described in the *National Electrical Code*. Inherent safety is an energy limitation approach to safety that also takes into consideration over-power fault conditions. Protected optical fiber is the second protection concept, where the level of safety is defined by the mechanical protection provided by robust cabling, raceway, cable tray, or conduit. Optical radiation interlock with optical fiber breakage is the third protection concept, where the transmit fiber optic terminal device shuts off or reduces the beam strength to a safe level upon detection of a loss in signal, such as occurs when there is a break in the optical fiber. Applications of the protection concepts as a function of Class I Divisions or Zones are suggested. Safe installation practices are recommended.

Key Words

Fiber optics, optical fiber, fiber optic cable, fiber optic terminal device, hazardous (classified) locations, Class I locations, *National Electrical Code*, explosive gas atmosphere, laser, nonbeam hazards.