

## STANDARDS AUSTRALIA

**Amendment No. 1**  
to  
**AS 1100.301—2008**  
**Technical drawing**  
**Part 301: Architectural drawing**

**REVISED TEXT**

The 2008 edition of AS 1100.301 is amended as follows; the amendment(s) should be inserted in the appropriate place(s).

SUMMARY: This Amendment applies to the Preface, Clauses 1.5.2.2, 4.2.1.1, 4.2.1.2, 4.2.1.3, 4.2.1.4, 4.2.1.5, 4.3.1.1, 4.3.1.2, 6.3.3, and Figures 4.1, 4.3, 4.10 and 4.11, and Appendix C.

Published on 18 May 2011.

AMDT  
No. 1  
MAY  
2011

**Preface**

*Delete* the seventh paragraph and *replace* with the following:

The 2008 edition of AS 1100.301 outlined differences in practice between Australia and New Zealand in the conventions for representing hinged doors and windows. That revised convention for Australia was chosen because it is commonly used in some overseas countries. However, this change in convention has not been accepted by the Australian community. Consequently, the convention in Australia for representing hinged doors and windows will now revert to that which existed prior to the 2008 edition of AS 1100.301 and as was shown in AS 1100.301—1985 and its supplement AS 1100.301 Supp 1—1986. There is no change to the New Zealand convention. A single convention now applies to both Australia and New Zealand.

Due to these changes, where necessary and especially with plans and/or documents that did or do relate to AS 1100.301—2008, systems should be put in place, in a timely manner, so as to avoid any misunderstanding when interpreting those or subsequent plans and/or documents.

At present, there is no convention for hinged windows and doors in International Standards. Many regions of the world have historically developed their own nomenclature, conventions and symbols that relate to architectural drawings and building works. It is thought that due to such a situation, a worldwide International Standard covering such items will not be possible and that regional or national areas will continue to use their own nomenclature, conventions and symbols.

**Clause 1.5.2.2 (a)**

*Delete* first sentence and *replace* with the following:

- (a) *Drawings at design stage* These drawings may also be referred to as concept drawings. Design (or concept) drawings are as follows:

**Clause 1.5.2.2 (b)(i)**

*Add* the following new paragraph at the end:

The location drawings may also be commonly referred to as architectural drawings, especially in the residential construction industry.

AMDT  
No. 1  
MAY  
2011

---

#### Clause 4.2.1.1

*Delete* the text and *replace* with the following:

Where a window is hinged along a side, that side shall be indicated by the base of an indication triangle, as shown in Figure 4.1.

---

AMDT  
No. 1  
MAY  
2011

#### Figure 4.1 caption

*Replace* the existing figure's caption with the following:

FIGURE 4.1 LEFT-SIDE HINGED WINDOW

---

AMDT  
No. 1  
MAY  
2011

#### Clause 4.2.1.2

*Delete* the text and *replace* with the following:

Where a window is pivoted, the pivot points shall be indicated by short lines through the points of the indication diamond, as shown in Figure 4.2.

---


AMDT  
No. 1  
MAY  
2011

#### Clause 4.2.1.3


*Delete* the entire Clause and *replace* with the following:

##### Clause 4.2.1.3 *Top or bottom hinged*

Where a window is hinged at the top or bottom, that part of the perimeter of the window containing the hinge(s) shall be indicated by the base of an indication triangle, as shown in Figure 4.3.



(a) Bottom hinged



(b) Top hinged

FIGURE 4.3 BOTTOM AND TOP HINGED WINDOWS

---

AMDT  
No. 1  
MAY  
2011

#### Clause 4.2.1.4

*Delete* the text and *replace* with the following:

Where a window is stayed on four points so that all sides can project out, a short line, separated from but parallel to an edge, shall be indicated at the apex of an indication triangle using dashed thin lines, as shown in Figure 4.4.

---

AMDT  
No. 1  
MAY  
2011

#### Clause 4.2.1.5

*Delete* the Clause's title and text and *replace* with the following:

##### 4.2.1.5 *Fixed and sliding sashes*

A sliding sash shall be indicated by an arrow drawn on it and pointing in the direction of opening, as shown in Figure 4.5.

A fixed sash shall be indicated by the letter 'F' drawn on it, as shown in Figure 4.5.

---