

STANDARDS AUSTRALIA

Amendment No. 1
to
AS 1756—1999
Household sinks

REVISED TEXT

The 1999 edition of AS 1756 is amended as follows; the amendment should be inserted in the appropriate places.

SUMMARY: This Amendment applies to Clauses 1.4.19, 1.4.19(A), 1.4.20(A), 1.5.2, 1.5.5, 1.5.8, 1.7(A), 2.5, 3.5, 4.4, 5.3 and 6.4.

Published on 4 December 2001.

AMDT
No. 1
DEC
2001

Page 6 Clause 1.4.19 Title

Delete ‘Sink’ and replace with ‘Drainer or bowl’.

AMDT
No. 1
DEC
2001

Page 6 New Clause 1.4.19(A)

Add New Clause as follows:

(a) ‘Soap recess

A profiled area designed to retain soap. A soap recess may be fluted, dimpled to aid drying of the soap’.

AMDT
No. 1
DEC
2001

Page 6 New Clause 1.4.20(A)

Add New Clause as follows:

(a) ‘Tap landing

An area near a bowl designed to support a tap, tap-set or other fitting’.

AMDT
No. 1
DEC
2001

Page 6 Clause 1.5.2

Delete existing text and replace with the following:

‘The main bowl of the sink shall be not less than 125 mm deep. Auxiliary bowls and drainers may be provided integral with or for mounting alongside sinks complying with all the specified design features of Section 1. Auxiliary bowls shall have a depth not less than 30 mm. Drainers may be of any depths and may be fluted, dimpled or plain. Overflow outlets shall not be provided. The finished product shall be free of sharp edges.’

Page 7 Clause 1.5.5

Delete existing text and replace with the following:

‘The drainer and the bottom of the sink shall have a continuous fall to a waste outlet.

Soap recesses, tap landings and rims of sinks shall be self-draining. Drainers shall be designed so as to have a positive fall towards the bowl or an unpluggable waste outlet. Drainers may be fluted, dimpled or plain.’

Page 7 Clause 1.5.8 First line

1 *Add after ‘holes’, ‘and tap landings’.*

2 *Add a new sentence as follows:*

‘The location shall be such as to allow the tap to discharge into a bowl of not less than 125 mm.’

Page 8, New Clause 1.7 (A)

Add new clause as follows:

1.7 (A) INFORMATIVE LABELLING

Sinks of all materials shall be supplied with a label giving detailed information on the prevention of damage and maintenance of the surface of the sink. The label shall be firmly attached to the sink in a position so that it is easily readable after installation and shall include the following wording, in English, and in capital letters not less than 2 mm high. The label shall be written

NOTICE	
PLEASE LEAVE THIS LABEL IN A POSITION FOR THE HOUSEHOLDER TO READ.	

CLEANING AND MAINTENANCE INSTRUCTIONS	

1	TO PRESERVE ITS POLISHED SURFACE, THIS SINK SHOULD BE CLEANED WITH A SOFT CLOTH USING WARM SOAPY WATER OR HOUSEHOLD DETERGENT.

2	IF ACCIDENTAL SCRATCHES, ABRASIONS OR BURNS OCCUR, THE SURFACE FINISH CAN BE RESTORED BY GENTLE POLISHING WITH A POLISH RECOMMENDED BY THE MANUFACTURER.

The label shall be capable of being removed after installation of the sink.
