

AS 19426.3:2024



Structures for mine shafts

Part 3: Sinking stages (ISO 19426-3:2018, MOD)



AS 19426.3:2024

This Australian Standard® was prepared by ME-018, Mining Equipment. It was approved on behalf of Standards Australia's Standards Development and Accreditation Committee on 03 October 2024.

This Standard was published on 18 October 2024.

The following are represented on Committee ME-018:

- Australian Industry Group
- Australasian Institute of Mining & Metallurgy
- Chamber of Minerals and Energy of Western Australia
- Construction and Mining Equipment Industry Group
- Department of Energy, Mines, Industry Regulation and Safety WA
- Department of Regional NSW
- Engineers Australia
- Engineers Australia/Mining Electrical and Mining Mechanical Engineering Society
- Minerals Council of Australia
- Resources Safety & Health Queensland
- South Australian Chamber of Mines and Energy

This Standard was issued in draft form for comment as DR AS 19426.3:2024.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

ISBN 978 1 76139 873 5

Structures for mine shafts

Part 3: Sinking stages (ISO 19426-3:2018, MOD)

First published as AS 19426.3:2024.

COPYRIGHT

© ISO 2024 — All rights reserved
© Standards Australia Limited 2024

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

Preface

This Standard was prepared by the Australian members of the Joint Standards Australia/Standards New Zealand Committee ME-018 Mining Equipment.

After consultation with stakeholders in both countries, Standards Australia and Standards New Zealand decided to develop this document as an Australian Standard rather than an Australian/New Zealand Standard.

The objective of this document is to specify the design loads and the design procedures for the structural design of stages and components of stages.

A list of all parts in the series can be found in the [Standards Australia online catalogue](#).

This document is an adoption with national modifications, and has been reproduced from, ISO 19426-3:2018, *Structures for mine shafts — Part 3: Sinking stages*.

Appendix ZZ lists the modifications to ISO 19426-3:2018, for the application of this document in Australia.

As this document has been reproduced from an International document, a full point substitutes for a comma when referring to a decimal marker.

The terms “normative” and “informative” are used in Standards to define the application of the appendices or annexes to which they apply. A “normative” appendix or annex is an integral part of a Standard, whereas an “informative” appendix or annex is only for information and guidance.

Contents

Preface	ii
Foreword	iv
Introduction	v
Section 1 Scope	1
Section 2 Normative references	1
Section 3 Terms and definitions	1
Section 4 Symbols	1
Section 5 Materials	4
5.1 Steel	4
5.1.1 Structural steel grades	4
5.1.2 High strength steel grades	4
5.2 Aluminium alloys	4
Section 6 Nominal loads	4
6.1 Permanent load	4
6.2 Imposed loads	4
6.2.1 Stage deck load	4
6.2.2 Shaft formwork winch load	5
6.2.3 Kibble cross-head support load	5
6.2.4 Jumbo unit load	5
6.2.5 Lashing unit load	6
6.2.6 Stage jack load	6
6.2.7 Stage skid load	6
6.2.8 Canopy load	6
6.2.9 Kibble guide load	7
6.2.10 Temporary stage support load	7
6.2.11 Blast load	7
6.2.12 Guard railing load	7
6.2.13 Special load	7
6.3 Emergency load	8
6.3.1 Emergency rope load	8
6.3.2 Emergency impact load	8
Section 7 Design procedures	8
7.1 Design loads	8
7.2 Design codes	8
7.3 Load reversal	8
7.4 Design of replaceable members	8
7.5 Impact energy design of top deck	9
7.6 Deflection limitations	9
Annex A (informative) Load factors and load combinations	10
Annex B (informative) Examples of jumbo unit loads	12
Annex C (informative) Examples of lashing unit loads	15
Annex D (informative) Examples of stage jack loads with lashing	20
Bibliography	24
Appendix ZZ (normative) Modifications to ISO 19426-3:2018 for Australia	26

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 82, *Mining*.

A list of all parts in the ISO 19426 series can be found on the ISO website.

Introduction

Many mining companies, and many of the engineering companies which provide designs for mines, operate globally so ISO 19426 was developed in response to a desire for a unified global approach to the safe and robust design of structures for mine shafts. The characteristics of ore bodies, such as their depth and shape, vary in different areas so different design approaches have been developed and proven with use over time in different countries. Bringing these approaches together in ISO 19426 will facilitate improved safety and operational reliability.

The majority of the material in ISO 19426 deals with the loads to be applied in the design of structures for mine shafts. Some principles for structural design are given, but for the most part it is assumed that local standards will be used for the structural design. It is also recognized that typical equipment varies from country to country, so the clauses in ISO 19426 do not specify application of the principles to specific equipment. However, in some cases examples demonstrating the application of the principles to specific equipment are provided in informative Annexes.

NOTES

Australian Standard®

Structures for mine shafts

Part 3: Sinking stages (ISO 19426-3:2018, MOD)

Section 1 Scope

This document specifies the design loads and the design procedures for the structural design of stages and components of stages.

The loads specified in this document are not applicable for the design of stage ropes or sheaves. Rope sizes are determined in accordance with other standards.

This document does not cover matters of operational safety, or layout of the sinking stage.

This document adopts a limit states design philosophy.

Section 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 10721-1, *Steel structures — Part 1: Materials and design*

ISO 10721-2, *Steel structures — Part 2: Fabrication and erection*

ISO 19426-1, *Structures for mine shafts — Part 1: Vocabulary*

ISO 22111, *Bases for design of structures — General requirements*

ISO 2394, *General principles on reliability for structures*

EN 1999-1-1, *Eurocode 9 — Part 1: Design of aluminium structures — Part 1: General structural rules*

EN 1999-1-3, *Eurocode 9 — Part 1: Design of aluminium structures — Part 3: Structures susceptible to fatigue*

EN 1999-1-4, *Eurocode 9 — Part 1: Design of aluminium structures — Part 4: Cold-formed structural sheeting*

CEN/TS 13001-3-1, *Cranes — General design — Part 3-1: Limit states and proof competence of steel structures*

Section 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 19426-1 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <http://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org>

Section 4 Symbols

<i>C</i>	lashing unit grab capacity (m ³)
<i>E</i>	emergency load, or load effect (N, Nm)

e_G	stage load eccentricity factor
E_a	emergency impact load (N)
E_p	emergency impact load on a protective platform (N)
E_R	emergency rope load (N)
F	design load, or load effect (N, Nm)
G	permanent load, or load effect (N, Nm)
G_D	jumbo unit self-weight (N)
G_L	lashing unit self-weight (N)
K	weight of the kibble and full load (N)
L	span of an element or floor beam (m)
L_1	lashing unit lever arm or the VSM lashing unit grab lever arm (m)
L_2	stage jack lever arm horizontal (m)
L_3	stage jack lever arm vertical (m)
L_4	jumbo unit centre of gravity lever arm or the VSM lashing unit centre of gravity lever arm (m)
L_{5i}	hydraulic cylinder horizontal lever arm to the boom pivot point (m)
L_{6i}	hydraulic cylinder vertical lever arm to the boom pivot point (m)
M_D	jumbo unit moment about the boom pivot point (Nm)
M_L	lashing unit moment about the boom pivot point (Nm)
N_L	total number of lashing unit cycles
P	payload used during doubling-down (N)
p_D	uniformly distributed load on stage decks (N/m ²)
P_A	canopy load (N)
P_B	blast load (N)
P_C	concentrated load on stage decks (N)
P_D	total uniformly distributed imposed load on stage decks (N)
P_G	stage skid load (N)
P_H	kibble cross-head support load (N)
P_J	stage jack load (N)
P_{JA}	stage jack axial load (N)
P_{JT}	stage jack transverse load (N)
P_K	kibble guide load (N)

P_{DH}	jumbo unit horizontal load (N)
P_{DV}	jumbo unit vertical load (N)
P_{LH}	horizontal lashing unit load (N)
P_{LV}	vertical lashing unit load (N)
P_P	special load (N)
P_R	hand railing load (N/m)
P_T	temporary stage support load (N)
P_W	winch load (N)
Q_1	predominant imposed load, or load effect (N, Nm)
Q_3 to Q_n	additional independent imposed loads, or load effects (N, Nm)
V_E	predominant imposed load, or load effect (N, Nm)
W_C	weight of the kibble cross-head (N)
W_{CHi}	horizontal hydraulic cylinder loads at maximum capacity (N)
W_{CVi}	vertical hydraulic cylinder load (N)
W_G	weight of the cactus grab including the grab crosshead (N)
W_{PL}	weight of rock in the lashing unit grab (N)
W_{DL}	jumbo drilling load (N)
W_K	weight of kibble and full load (N)
W_R	rated shutter winch load (N)
W_S	weight of the shutter (N)
W_W	grab winch safe working load (N)
α_B	bellmouth impact factor
α_C	impact factor for kibble cross-head support
α_D	jumbo unit impact factor
α_E	impact factor for emergency rope load
α_H	hydraulic cylinder impact factor
α_K	kibble guide impact factor
α_L	lashing unit impact factor
α_J	impact factor for stage jack load
α_R	winch rated load impact factor
α_S	formwork weight impact factor