

AS 2088:2022 Prams and strollers — Safety requirements

Amendment No. 1

Revised text amendment

Publishing and Approval Dates

Council of Standards Australia Approval: 18 June 2024

Published: 28 June 2024

Summary

This Amendment applies to the following elements:

- Clauses 3, 4.2.2, 8.6.2, 8.8.1, 8.13, J.4 and U.3
- Table 10.1

Amendment Details

AS 2088:2022 is amended as follows. The amendments should be inserted in the locations as instructed.

Element	Instruction/new text
CI 3	After Clause 3.25 <i>add</i> the following: 3.26 handle device or devices grasped by the user's hand or hands to control the motion of the vehicle to enable it to be pushed or pulled. The handle may be positioned at either end or both ends of the vehicle, may be reversible to position the handle at either end of the vehicle, and may be rigidly or flexibly attached to the frame or body of the vehicle
CI 4.2.2	<i>Delete</i> first paragraph and replace with the following: For vehicles designed for a single occupant, all parts directly behind the backrest and all parts directly under the seat and leg rest shall not be considered as child accessible parts.
CI 8.6.2	1 <i>Delete</i> item (d) and <i>replace</i> with the following: (d) be located within immediate reach of the user regardless of the position of the handle. 2 <i>Delete</i> "EXAMPLE Foot-operated parking brake actuators at the front and rear sets of wheels on a vehicle that has a reversible handle, and hand-operated actuators on the handle."
CI 8.8.1	<i>Delete</i> item (g) and replace with the following: (g) If the main buckle is designed to prevent loops being formed by the harness straps, the ends of the shoulder and the waist straps shall become disconnected from each other and from the buckle after actuation of the buckle. Where the waist and shoulder straps remain connected to each other following their release from the buckle, then they shall separate when a force of not more than 20 N is applied in all possible practical directions.
CI 8.13	<i>Delete</i> item (b) and <i>replace</i> with the following:

Element	Instruction/new text
	(b) The tether strap shall be permanently fixed to a handle of the vehicle so as to be always available to the vehicle operator.
Table 10.1	1 Column 3, Test Sequence 16, <i>delete</i> "9.6.1" and <i>replace</i> with "9.6.2"
	2 Column 3, Test Sequence 17, <i>delete</i> "9.6.2" and <i>replace</i> with "9.6.3"
	3 Column 3, Test Sequence 18, <i>delete</i> "9.6.3" and <i>replace</i> with "9.6.4"
	4 Column 3, Test Sequence 19, <i>delete</i> "9.6.4" and <i>replace</i> with "9.6.5"
CI J.4	<i>Delete</i> item (m) and <i>replace</i> with the following: (m) Where a vehicle has the option for a bassinet, toddler seat or other accessory that the child will sit or lie in or stand on, perform the test in accordance with this procedure but with the use of the applicable test masses specified in Appendix A.
CI U.3	<i>Delete</i> items (c) and (d) and <i>replace</i> with the following: (c) A means of applying and measuring a force of up to $10\text{ N} \pm 0.5\text{ N}$. (d) A means of applying and measuring a force of up to $200\text{ N} \pm 10\text{ N}$.