

STANDARDS AUSTRALIA

Amendment No. 1
to
AS 5041—2003
Methods of test—Security screen doors and window grilles

CORRECTION

The 2003 edition of AS 5041 is amended as follows; the amendment(s) should be inserted in the appropriate place(s).

SUMMARY: This Amendment applies to Clauses 2.4.1.1, 2.4.2.1, 3.6, 4.3, 4.4.1.4, 5.5, 5.5.4, and 8.4 and Figures 3.2 and 3.3.

Published on 20 December 2007.

AMDT
No. 1
DEC
2007

Clause 2.4.1.1

Insert the following new paragraph after Item (b):

The test specimen for Type I and Type II product shall consist of a piece of infill material with an incomplete pattern on one side and that side shall be subjected to the dynamic impact test as specified in Section 3. If the door or window fabricator manufactures a product with complete infill pattern then that configuration shall be tested.

AMDT
No. 1
DEC
2007

Clause 2.4.2.1

Insert the following new paragraph after Item (b):

The test specimen for Type I and Type II product shall consist of a piece of infill material with an incomplete pattern on one side and that side shall be subjected to the dynamic impact test as specified in Section 3. If the door or window fabricator manufactures a product with complete infill pattern then that configuration shall be tested.

AMDT
No. 1
DEC
2007

Clause 3.6(d)

Insert the following text after the first sentence:

Impact point (A) or (B,) as specified in Figure 3.3, shall be such that it is closest to the incomplete pattern at the edge of the infill material. If both edges of the infill material have complete patterns, then either impact point may be used (see Clause 2.4.1.1 and Clause 2.4.2.1).

Figure 3.2

Delete existing Figure and *replace* with the following:

