

AS ISO/IEC 39794.1:2023
ISO/IEC 39794-1:2019



STANDARDS
Australia



Information technology — Extensible biometric data interchange formats

Part 1: Framework



AS ISO/IEC 39794.1:2023

This Australian Standard ® was prepared by IT-032, Biometrics and Identification. It was approved on behalf of the Council of Standards Australia on 27 September 2023.

This Standard was published on 13 October 2023.

The following are represented on Committee IT-032:

- Australian Information Industry Association
- Australian Retailers Association
- Department of Defence (Australian Government)
- Department of Foreign Affairs and Trade (DFAT)
- Department of Home Affairs — Digital and Technology Policy Division
- Photo Marketing Association
- SITA

This Standard was issued in draft form for comment as DR AS ISO/IEC 39794.1:2023.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

ISBN 978 1 76139 359 4

Information technology — Extensible biometric data interchange formats

Part 1: Framework

First published as AS ISO/IEC 39794.1:2023.

COPYRIGHT

© ISO/IEC 2023 — All rights reserved
© Standards Australia Limited 2023

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

Preface

This Standard was prepared by the Standards Australia Committee IT-032, Biometrics and Identification, to supersede AS ISO/IEC 19794.1:2007, *Information technology — Biometric data interchange formats, Part 1: Framework*.

The objective of this document is to specify:

- (a) rules and guidelines for defining extensible biometric data interchange formats that are extensible without invalidating previous data structures;
- (b) the meaning of common data elements for use in extensible biometric data interchange formats;
- (c) common data structures for tagged binary data formats based on an extensible specification in ASN.1;
- (d) common data structures for textual data formats based on an XML schema definition; and
- (e) conformance testing concepts and methodologies for testing the syntactic conformance of biometric data blocks.

This document is identical with, and has been reproduced from, ISO/IEC 39794-1:2019, *Information technology — Extensible biometric data interchange formats — Part 1: Framework*.

As this document has been reproduced from an International document, a full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms “normative” and “informative” are used in Standards to define the application of the appendices or annexes to which they apply. A “normative” appendix or annex is an integral part of a Standard, whereas an “informative” appendix or annex is only for information and guidance.

Contents

Preface	ii
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Abbreviated terms	2
5 Conformance	3
6 General biometric system	3
6.1 Conceptual representation of general biometric system	3
6.2 Conceptual components of a general biometric system	4
6.2.1 Data capture subsystem	4
6.2.2 Transmission subsystem	4
6.2.3 Signal processing subsystem	5
6.2.4 Data storage subsystem	5
6.2.5 Comparison subsystem	5
6.2.6 Decision subsystem	5
6.2.7 Administration subsystem	6
6.2.8 Interface	6
6.3 Functions of general biometric system	6
6.3.1 Enrolment	6
6.3.2 Verification	7
6.3.3 Identification	7
7 Rules and guidelines	8
7.1 Capture date and time	8
7.2 Degree of processing	8
7.2.1 Overview	8
7.2.2 Captured biometric sample	9
7.2.3 Intermediate biometric sample	9
7.2.4 Biometric feature set	9
7.3 Relationship to CBEFF	9
7.3.1 Overview	9
7.3.2 BDB format owner and format identifiers	10
7.4 Types of extensible biometric data interchange formats	10
7.5 Criteria for standardizing biometric data interchange formats	10
7.6 Extensibility	11
7.7 Naming conventions for biometric data interchange formats	11
7.8 Treatment of multi-biometric data	11
7.9 Capture conditions	11
7.10 Capture device requirements	12
7.11 Quality requirements for biometric data	12
7.12 Biometric feature extraction algorithms	12
7.13 Biometric feature comparison algorithms	12
7.14 Identifiers for resources related to the ISO/IEC 39794 series	12
8 Abstract data elements	13
8.1 General	13
8.2 Version block	14
8.3 Representation block	14
8.3.1 Capture device block	14
8.3.2 Capture date/time block	15
8.3.3 Quality blocks	15

8.3.4	PAD data block	17
8.3.5	Extended data blocks	23
9	Tagged binary encoding scheme	23
9.1	General	23
9.2	Naming conventions for ASN.1 modules in the ISO/IEC 39794 series	24
9.2.1	ASN.1 module names	24
9.2.2	Object identifier for ASN.1 modules	24
9.2.3	Type and component names	24
9.3	Prototypes	25
9.4	Abstract syntax of common data types for the ISO/IEC 39794 series, in ASN.1	25
9.5	Abstract syntax of general BDB, in ASN.1	25
9.6	Definition extension in ASN.1	26
9.6.1	General	26
9.6.2	Addition of components to sequence types	26
9.6.3	Addition of components to choice types	27
9.6.4	Extension of an enumerated type with a new value	27
10	XML encoding scheme	29
10.1	General	29
10.2	Structure of XML schema definitions	29
10.3	Naming conventions for XML schema definitions in the ISO/IEC 39794 series	29
10.3.1	XML namespace names	29
10.3.2	Type and element names	29
10.4	Prototypes	30
10.5	XML schema definition of common data types for the ISO/IEC 39794 series	31
10.6	Definition extension in XML	31
10.6.1	General	31
10.6.2	Extending XML simple types	31
10.6.3	Extending XML sequence types	31
10.6.4	Extending XML choice types	32
10.6.5	Extending XML enumerations	33
Annex A	(normative) Formal specifications of common data types for the ISO/IEC 39794 series	35
Annex B	(normative) Abstract syntax of general tagged binary BDB in ASN.1	47
Annex C	(normative) Conformance testing methodology	49
Annex D	(informative) Examples of comparison scenarios	56
Bibliography		58

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see <http://patents.iec.ch>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 37, *Biometrics*.

A list of all parts in the ISO/IEC 39794 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

The purchase of this ISO/IEC document carries a copyright licence for the purchaser to use ISO/IEC copyright in the schemas in the annexes to this document for the purpose of developing, implementing, installing and using software based on those schemas, subject to ISO/IEC licensing conditions set out in the schemas.

Introduction

Biometric data interchange formats enable the interoperability of different biometric systems. The first generation of biometric data interchange formats was published between 2005 and 2007 in the first edition of the ISO/IEC 19794 series. From 2011 onwards, the second generation of biometric data interchange formats was published in the second edition of the established parts and the first edition of some new parts of the ISO/IEC 19794 series. In the second generation of biometric data interchange formats, new useful data elements such as those related to biometric sample quality were added, the header data structures were harmonized across all parts of the ISO/IEC 19794 series, and XML encoding was added in addition to the binary encoding.

The second generation of the biometric data interchange formats turned out to be syntactically incompatible with their first generation. The second generation, however, did not cancel and replace the first generation because the first generation has been adopted widely, e.g. for biometric data stored in machine-readable travel documents, which will be in the field for a long time. Therefore, the first editions of the ISO/IEC 19794 series are expected to be retained in the standards catalogue as long as needed alongside their second editions.

In anticipation of the need for additional data elements, and in order to avoid future compatibility issues, the ISO/IEC 39794 series provides standard biometric data interchange formats capable of being extended in a defined way. Extensible specifications in ASN.1 (Abstract Syntax Notation One) and the Distinguished Encoding Rules of ASN.1 form the basis for encoding biometric data in binary tag-length-value formats. XSDs (XML schema definitions) form the basis for encoding biometric data in XML (eXtensible Markup Language).

This document defines what is common for the extensible biometric data interchange formats considered in the specific parts of the ISO/IEC 39794 series, i.e. the common content, meaning and representation of biometric data interchange formats.

The ISO/IEC 39794 series is one of a family of international standards being developed by ISO/IEC JTC 1/SC 37 that supports interoperability and data interchange among biometric applications and systems. This family of standards specifies requirements on a wide variety of biometric recognition applications, whether such applications operate in an open systems environment or consist of a single, closed system. Open systems are built on standards-based, publicly defined data formats, interfaces and protocols to facilitate data interchange and interoperability with other systems, which may include components of different design or manufacture. A closed system can also be built on publicly defined standards, and may include components of different design or manufacture, but inherently has no requirement for data interchange and interoperability with any other system.

The ISO/IEC JTC 1/SC 37 biometric standards family includes a layered set of standards consisting of biometric data interchange formats and biometric interfaces, as well as biometric profiles that describe the use of these standards in specific application areas. [Figure 1](#) shows the interrelation of biometrics-related areas of standardization. Biometric data complying with one of the biometric data interchange formats defined in the ISO/IEC 19794 series^[7] and the ISO/IEC 39794 series represent the core component of biometric interoperability. The formats defined in the ISO/IEC 19785 series^[4] may be used as a wrapper around biometric data. Since biometric data are sensitive data and subject to attack, cryptographic protection is required in interchange environments. Biometrics-related profiles, security evaluation and performance evaluation also play an important role. Biometric interfaces are essential to facilitate easy integration and usage of biometric components. The harmonized biometric vocabulary is recommended for use in describing biometric technology. The deployment of applications using biometric verification or identification takes place within the context of societal and cross-jurisdictional requirements.

The ISO/IEC 19794 series and the ISO/IEC 39794 series specify biometric data interchange formats for different types of biometric characteristics. Parties that agree on a biometric data interchange format specified in the ISO/IEC 19794 series or the ISO/IEC 39794 series should be able to decode each other's biometric data.

The biometric interface standards include the Common Biometric Exchange Formats Framework (CBEFF) series (ISO/IEC 19785[4]) and the Biometric Application Programming Interface (BioAPI) series (ISO/IEC 19784[3]). These standards support exchange of biometric data within a system or among systems. The CBEFF series specifies the basic structure of a standardized biometric information record (BIR) which includes one or more biometric data blocks (BDB) with added metadata, such as date and time when it was captured, its expiry date, whether it is encrypted, etc. The BioAPI series specifies an open system API that supports communications between software applications and underlying biometric technology services.

The biometric profile series (ISO/IEC 24713[8]) facilitates implementations of the base standards (e.g. biometric data interchange format standards and biometric interface standards and possibly non-biometric standards) for defined applications. These profiles define the functions of an application (e.g. physical access control for employees at airports) and then specify use of options in the base standards to ensure biometric interoperability.

The ISO/IEC 24779[10] series specifies a family of icons and symbols used in association with devices for biometric enrolment, verification and/or identification. The symbols and icons are intended to show the type of biometric characteristics and to advise on the appropriate preparation and behaviour required when using a biometric system. They are also intended to assist capture subjects by guiding them as they use the biometric system.




Figure 1 — General interrelation model of biometric issues

NOTES

Australian Standard®

Information technology — Extensible biometric data interchange formats Part 1: Framework

1 Scope

This document specifies:

- rules and guidelines for defining extensible biometric data interchange formats that are extensible without invalidating previous data structures;
- the meaning of common data elements for use in extensible biometric data interchange formats;
- common data structures for tagged binary data formats based on an extensible specification in ASN.1;
- common data structures for textual data formats based on an XML schema definition; and
- conformance testing concepts and methodologies for testing the syntactic conformance of biometric data blocks.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 2382-37, *Information technology — Vocabulary — Part 37: Biometrics*

ISO 8601 (all parts), *Date and time — Representations for information interchange*

ISO/IEC 8824-1, *Information technology — Abstract Syntax Notation One (ASN.1): Specification of basic notation — Part 1*

ISO/IEC 8825-1, *Information technology — ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER) — Part 1*

ISO/IEC 19785-2,¹⁾ *Information technology — Common Biometric Exchange Formats Framework — Part 2: Procedures for the operation of the biometric registration authority*

ISO/IEC 29794-1, *Information technology — Biometric sample quality — Part 1: Framework*

ISO/IEC 30107-2, *Information technology — Biometric presentation attack detection — Part 2: Data formats*

IETF RFC 5141, *A Uniform Resource Name (URN) Namespace for the International Organization for Standardization (ISO)*

IETF RFC 5234, *Augmented BNF for Syntax Specifications: ABNF*

W3C Recommendation, *XML Schema Part 1: Structures* (Second Edition), 28 October 2004, <http://www.w3.org/TR/xmlschema-1/>

W3C Recommendation, *XML Schema Part 2: Datatypes* (Second Edition), 28 October 2004, <http://www.w3.org/TR/xmlschema-2/>

1) Second edition under preparation. Stage at time of publication: ISO/IEC DIS 19785-2:2013

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 2382-37 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia available at <http://www.electropedia.org/>;
- ISO Online Browsing Platform available at <http://www.iso.org/obp>.

3.1

biometric behavioural data

biometric data representing behavioural biometric characteristics of an individual

EXAMPLE Data resulting from writing, speaking or typing.

3.2

biometric data block

BDB

block of data conforming to a defined format

Note 1 to entry: The BDB is normally opaque to the processing of a standard biometric header (SBH) and is not required to be self-delimiting.

Note 2 to entry: This definition is aligned with ISO/IEC 19875-1.

3.3

biometric feature data unit

smallest individual unit of extracted biometric feature data

EXAMPLE Minutiae of a fingerprint.

3.4

biometric image data

biometric data that results from the presentation of biological biometric characteristics of an individual and is represented by pixels in a spatial coordinate system

EXAMPLE Fingerprint image data.

3.5

bit depth

number of bits used to represent a data element

3.6

octet

byte

contiguous sequence of 8 bits processed as a single unit of information

3.7

pixel

picture element

point in an image that is represented by an n -by- m matrix of points, where n is the number of horizontal rows and m is the number of vertical columns

4 Abbreviated terms

ABNF Augmented Backus-Naur Form

API application programming interface

ASN.1	Abstract Syntax Notation One
BDB	biometric data block
BIR	biometric information record
CBEFF	Common Biometric Exchange Formats Framework
DER	Distinguished Encoding Rules
HTTP	Hypertext Transfer Protocol
ICS	implementation conformance statement
IUT	implementation under test
NSS	namespace-specific string
PAD	presentation attack detection
SBH	standard biometric header
TLV	tag-length-value
URI	uniform resource identifier
URN	uniform resource name
UTC	Coordinated Universal Time
XML	eXtensible Markup Language
XSD	XML schema definition

5 Conformance

A binary biometric data interchange format conforms to this document if it satisfies the requirements specified within [Clauses 7, 8, 9](#), and [A.1](#).

A textual biometric data interchange format conforms to this document if it satisfies the requirements specified within [Clauses 7, 8, 10](#), and [A.2](#).

A general BDB embedding BDBs in formats defined elsewhere conforms to this document if it satisfies the requirements specified in [Annex B](#).

A biometric data interchange format conformance test conforms to this document if it satisfies the requirements specified in [Annex C](#).

6 General biometric system

6.1 Conceptual representation of general biometric system

Given the variety of applications and technologies, it can seem difficult to draw any generalizations about biometric systems. All such systems, however, have many elements in common. Captured biometric samples are acquired from a subject by a biometric capture device. The biometric capture device output is sent to a processor that extracts the distinctive but repeatable measures of the sample (the biometric features), discarding all other components. The resulting features can be stored in the biometric enrolment database as a biometric reference. In other cases, the sample itself (without biometric feature extraction) may be stored as the reference. A subsequent query or probe biometric

sample can be compared to a specific reference, to many references, or all references already in the database to determine if there is a match. A decision regarding the biometric claim is made based upon the similarities or dissimilarities between the features of the probe and those of the reference or references compared.

Figure 2 illustrates the information flow within a general biometric system, showing a general biometric system consisting of data capture, signal processing, data storage, comparison and decision subsystems. Figure 2 illustrates both enrolment and the operation of verification and identification systems. The subclauses in Clause 6 describe each of these subsystems in more detail.




Figure 2 — Components of a general biometric system

NOTE In any implemented system, some of these conceptual components can be absent or could not have a direct correspondence with a physical or software entity.

6.2 Conceptual components of a general biometric system

6.2.1 Data capture subsystem

The data capture subsystem collects an image or signal of a subject's biometric characteristics presented to the biometric capture device (sensor) and outputs this image/signal as a captured biometric sample.

6.2.2 Transmission subsystem

The transmission subsystem (not portrayed in Figure 2; not always present or visibly present in a biometric system) will transmit samples, features, probes and references between different subsystems. The captured biometric sample may be compressed and/or encrypted before transmission and expanded and/or decrypted before use. A captured biometric sample may be altered in transmission due to noise in the transmission channel as well as losses in the compression/expansion process. Data may be transmitted using standardized biometric data interchange formats and cryptographic techniques may be used to protect the authenticity, integrity and confidentiality of stored and transmitted biometric data.

6.2.3 Signal processing subsystem

Signal processing may include processes such as:

- enhancement, i.e. improving the quality and clarity of the captured biometric sample;
- segmentation, i.e. locating the signal of the subject's biometric characteristics within the captured biometric sample;
- biometric feature extraction, i.e. deriving the subject's repeatable and distinctive measures from the captured biometric sample; and
- quality control, i.e. assessing the suitability of samples, features, references, etc., possibly affecting other processes, such as:
 - returning control to the data capture subsystem to collect further samples or
 - modifying parameters for segmentation, biometric feature extraction, comparison.

In the case of enrolment, the signal processing subsystem creates a biometric reference. Sometimes the enrolment process requires features from several presentations of the individual's biometric characteristics. Sometimes the reference comprises just the features, in which case the reference may be called a biometric template. Sometimes the reference comprises just the sample, in which case biometric feature extraction from the reference occurs immediately before comparison.

In the case of verification and identification, the signal processing subsystem creates a biometric probe. Sequencing and iteration of the above-mentioned processes are determined by the specifics of each system.

6.2.4 Data storage subsystem

References are stored within an enrolment database held in the data storage subsystem. Each reference may be associated with some details of the enrolled subject or the enrolment process. Prior to being stored in the enrolment database, references may be reformatted into a biometric data interchange format. References may be stored within a biometric capture device, on a portable medium such as an integrated-circuit card, on a personal computer or local server, or in a central database.

6.2.5 Comparison subsystem

In the comparison subsystem, the features extracted from probes are compared against one or more references and comparison scores are passed to the decision subsystem. The comparison scores indicate the similarities or dissimilarities between the probes and references compared. For verification, a single specific claim of subject enrolment would lead to a single comparison score. For identification, many or all references may be compared with the probe, and a comparison score may be produced for each comparison.

6.2.6 Decision subsystem

The decision subsystem uses the comparison scores generated from one or more comparison attempts to provide the decision outcome for a verification or identification transaction.

In the case of verification, the probe is considered to match a compared reference when (assuming that higher scores correspond to greater similarity) the comparison score exceeds a specified threshold. A biometric claim can then be verified on the basis of the decision policy, which may allow or require multiple attempts.

In the case of identification, an enrollee is a potential candidate when (assuming that higher scores correspond to greater similarity) the comparison score exceeds a specified threshold, and/or when the comparison score is among the highest ranked values generated during comparisons across the entire

database. The decision policy may allow or require multiple attempts before making an identification decision.

NOTE Conceptually, it is possible to treat multi-biometric systems in the same manner as unibiometric systems, by treating the combined captured biometric samples/references/scores as if they were a single sample/reference/score and allowing the decision subsystem to operate score fusion or decision fusion as and if appropriate. See also ISO/IEC TR 24722[9].

6.2.7 Administration subsystem

The administration subsystem (not shown in [Figure 2](#)) governs the overall policy, implementation, configuration and usage of the biometric system, in accordance with the relevant legal, jurisdictional and societal constraints and requirements. Illustrative examples include:

- interacting with the biometric capture subject including providing guidance feedback to the subject during and/or after data capture and requesting additional information from the subject;
- storing and formatting of interchanged biometric data;
- providing final arbitration on output from decision and/or scores;
- setting threshold values for decision;
- setting biometric capture parameters;
- controlling the operational environment and non-biometric data storage;
- providing appropriate safeguards for subject privacy and data security; and
- interacting with the application that utilizes the biometric system.

6.2.8 Interface

The biometric system may or may not interface to an external application or system via a web services interface, an application programming interface, a hardware interface or a protocol interface (not shown in [Figure 2](#)).

6.3 Functions of general biometric system

6.3.1 Enrolment

In enrolment, a transaction by a biometric capture subject is processed by the system in order to generate and store a biometric reference for that individual.

Enrolment typically involves:

- capturing one or more biometric samples;
- sample restoration or enhancement;
- segmentation;
- biometric feature extraction;
- quality checks (which may reject the sample/features as being unsuitable for creating a reference, and require capture of further samples);
- (where system policy requires it) comparison against the stored biometric references to ensure that the subject is not already enrolled;

- biometric reference creation (which may require features from multiple samples) and possibly conversion into a biometric data interchange format;
- storage of the biometric reference;
- test verification or identification attempts to ensure that the resulting enrolment is usable; and
- allowing for repeat enrolment attempts, should the initial enrolment be deemed unsatisfactory (dependent on the enrolment policy).

6.3.2 Verification

In access control applications, a transaction by a subject may be processed by the system in order to verify a specific positive claim about the subject's enrolment (e.g. "I am enrolled as subject X").

NOTE Some biometric systems allow a single subject to enrol more than one instance of a biometric characteristic (for example, an iris system can allow subjects to enrol both iris images, while a fingerprint system can require enrolment of additional fingers for fall-back in case a primary finger is damaged).

Verification of a specific positive biometric claim typically involves:

- capturing one or more biometric samples;
- sample restoration or enhancement;
- segmentation;
- biometric feature extraction and possibly conversion into a standardized biometric data interchange format;
- quality checks (which may reject the samples/features as being unsuitable for comparison and require capture of further samples);
- comparison of the probe features against the reference for the claimed identity producing a comparison score; and
- a verification decision based on whether the comparison score exceeds a threshold (assuming that higher scores correspond to greater similarity) in one or more attempts as dictated by the decision policy.

The decision subsystem will either accept or reject the specific positive claim. The verification decision outcome is considered to be erroneous if either a false claim is accepted (false accept) or a true claim is rejected (false reject).

EXAMPLE In a verification system allowing up to three attempts, a false reject occurs if the reference for the biometric claim actually stems from the present biometric capture subject, but on all three attempts the probe does not match this reference. A false accept occurs if the reference for the biometric claim does not stem from the present biometric capture subject, but the probe falsely matches this reference on any of the three attempts.

6.3.3 Identification

In identification, a transaction by a subject is processed by the system and the enrolment database is searched to return identifiers of similar references. Identification provides a candidate list of identifiers that will contain zero, one, or more identifiers. Identification is considered correct when the subject is enrolled, and an identifier for their enrolment is in the candidate list. The identification is considered to be erroneous if either an enrolled subject's identifier is not in the resulting candidate list (false-negative identification error) or if a transaction by a non-enrolled subject produces a non-empty candidate list (false-positive identification error).

Identification typically involves:

- capturing one or more biometric samples;
- sample restoration or enhancement;
- segmentation;
- biometric feature extraction and possibly conversion into a standardized biometric data interchange format;
- quality checks (which may reject the sample/features as being unsuitable for comparison, and require capture of further samples);
- comparison of the probe features against some or all references in the enrolment database, producing a comparison score for each comparison; and
- determination of a candidate list based on whether the comparison score exceeds a threshold and/or is among the highest ranked scores returned (assuming that higher scores correspond to greater similarity) in one or more attempts, as dictated by the decision policy.

7 Rules and guidelines

7.1 Capture date and time

Some biometric characteristics (e.g. facial image or signature dynamics) may undergo changes as a capture subject ages. Therefore, the capture date and time of biometric data should be recorded.

7.2 Degree of processing

7.2.1 Overview

The degree of processing of biometric data may be one of the following:

- captured biometric sample: the data are in raw form as delivered by the capture device;
- intermediate biometric sample: the data has been processed from the form delivered by the sensor, but is not in a form usable for comparison – such data is referred to as biometric image data or biometric behavioural data;
- processed data: the data is in a form that can be used for comparison – such data is referred to as biometric feature set.

[Figure 3](#) illustrates the degrees of processing of biometric data. For data interchange, intermediate biometric samples (e.g. image data or behavioural data) and biometric feature sets are of special relevance. Examples of scenarios using biometric data at different degrees of processing are shown in [Annex D](#).




Figure 3 — Captured biometric sample, intermediate biometric sample and biometric feature set

7.2.2 Captured biometric sample

The captured biometric sample is influenced by some or all of the following:

- underlying biometric characteristic;
- presentation of the biometric characteristic to the capture device;
- intermediate biometric sample processing (as part of data acquisition) within the capture device;
- technical characteristics of the capture device;
- environmental conditions (e.g. lighting, background noise).

Captured biometric samples are usually not used for data interchange.

7.2.3 Intermediate biometric sample

7.2.3.1 Biometric image data

In many cases, the captured biometric sample of a static biometric characteristic delivered by a biometric capture device is subsampled, scaled, interpolated, compressed or otherwise processed to produce an image of the characteristic. The first important convention to be made concerns the general image file format (e.g. BMP, TIFF, GIF, JPEG, JPEG-LS, JPEG2000) and the compression level to make images readable for all systems. Further conventions are needed for certain parameters concerning the image capturing process and the hardware to be used, which have a strong impact on the resulting image, e.g. bit depth (8 bit, 16 bit, etc.), spatial sampling rate, position of the biometric characteristic to be represented, and lighting conditions during image capture process.

7.2.3.2 Biometric behavioural data

In contrast to image data, which is based on a static biological characteristic like a fingerprint, behavioural data is based on a dynamic action with contributions from conditioned behaviour patterns as well as biological characteristics. For behavioural biometric characteristics, common analysis approaches are time-based and frequency-based analysis. Therefore, standardization concentrates on data interchange formats for such approaches.

7.2.3.3 Other intermediate biometric samples

Not all data used for the extraction of biometric features is image data or behavioural data.

EXAMPLE DNA profiles are neither extracted from image data nor from behavioural data.

7.2.4 Biometric feature set

A biometric feature set may consist of several feature data units. A biometric feature data unit may consist of several data elements, e.g. coordinates and angles. The structure and content of a feature data unit depends on the type of biometric characteristics.

7.3 Relationship to CBEFF

7.3.1 Overview

A BDB in a format defined in the ISO/IEC 39794 series may, but need not be, embedded in a record in an appropriate CBEFF patron format (see ISO/IEC 19785-3[6]).

7.3.2 BDB format owner and format identifiers

Within records in a CBEFF patron format, the format of the BDB is identified by:

- the CBEFF biometric organization identifier of the BDB format owner, and
- a BDB format identifier that is unambiguous within the scope of the BDB format owner.

For all extensible biometric data interchange formats defined in the ISO/IEC 39794 series, the format owner is ISO/IEC JTC 1/SC 37. The CBEFF biometric organization identifier for ISO/IEC JTC 1/SC 37 is 257 (0101_{Hex}).

For each extensible biometric data interchange format defined in the ISO/IEC 39794 series, ISO/IEC JTC 1/SC 37 assigns a BDB format identifier. Each part of the ISO/IEC 39794 series defines and lists the BDB format identifier, short name and full object identifier for each extensible biometric data interchange format it contains.

7.4 Types of extensible biometric data interchange formats

The structure, content, and encoding of BDBs depend on where the biometric data is intended to be used. There may be:

- self-contained data structures providing all necessary information;
- data structures designed for embedment in a CBEFF biometric information record (BIR) not duplicating information that is present in the CBEFF standard biometric header (SBH); and
- data structures designed for on-card biometric comparison as defined in ISO/IEC 24787[11].

Depending on the available storage space and data transmission rate, biometric data may be encoded in different encoding styles including:

- tagged binary formats; and
- more verbose, human readable textual formats following XML schema definitions.

7.5 Criteria for standardizing biometric data interchange formats

The standardization of biometric data interchange formats is intended to provide interoperability. Therefore, the number of standardized formats should be kept small and manageable. The conditions listed below should be considered before a new data interchange format may enter the standardization process. The new data interchange format:

- uses an encoding style that is very different from the one of an already standardized data interchange format, such as XML encoding vs. binary encoding;
- represents the essential data required for an alternative mathematical approach of biometric feature extraction and/or comparison;
- is a prevalent alternative representation of data that is defined in the ISO/IEC 19794 series or the ISO/IEC 39794 series;
- represents data of a widely used type of biometric characteristics not yet considered in the ISO/IEC 19794 series or the ISO/IEC 39794 series;
- represents data of a different degree of processing and has become widely used for data interchange or has the potential for it;
- enables interoperability among algorithms that use individual non-standardized data interchange formats of an advanced degree of processing;

- significantly reduces the size of data of an already standardized data interchange format and is suitable for use within integrated circuit cards and other tokens;
- has the potential to be used for different types of biometric characteristics, e.g. an image format;
- combines existing data interchange formats without increasing size;
- allows an improved biometric performance.

7.6 Extensibility

Requirements for new data elements may arise in the future. The extensible biometric data interchange formats shall be capable of being extended without invalidating the already standardized formats.

If a future amendment or revision will augment an extensible biometric data interchange format defined in the ISO/IEC 39794 series, systems capable of reading data conformant to the base format shall be able to also parse data conformant to the revised format, ignoring new data elements that were not in the base format. The revised format shall at least include the mandatory data items of the base standard. Systems capable of reading data conformant to the revised format shall also be able to read and understand data in the base format.

7.7 Naming conventions for biometric data interchange formats

The name of the data interchange format should indicate the type of biometric characteristics and, where different biometric sample or feature data formats are available, the respective biometric sample or feature.

EXAMPLE Finger minutiae data, finger image data, signature/sign time series data, hand geometry silhouette data, voice data, DNA data.

7.8 Treatment of multi-biometric data

Multi-biometrics may be used to improve the performance of biometric systems in terms of error rates. Multi-biometrics can be divided into five subcategories, which are defined in ISO/IEC TR 24722[9]:

- multi-type – use of multiple types of biometric characteristics such as face and fingerprint;
- multi-algorithmic – use of two or more distinct algorithms for processing the same biometric sample;
- multi-instance – use of at least two instances of the same type of biometric characteristics, e.g. left and right iris or left and right index finger;
- multi-sensorial – use of multiple capture devices for capturing samples of one biometric instance;
- multi-presentation – use of either multiple presentation samples of one instance of a biometric characteristic or of a single presentation that results in the capture of multiple samples.

If multi-type systems are used, data structures of several parts of the ISO/IEC 39794 series may be involved in a verification or identification process. Multi-instance or multi-presentation data may be stored in several biometric representations that are contained in one BDB.

7.9 Capture conditions

Biometric samples and reference data from the same capture subject do not generally result in a perfect match when performing a comparison. The data capture subsystem may never capture exactly identical biometric samples since these depend on a lot of factors where small changes result in different data (e.g. translation, rotation and distortion of fingers). Therefore, the other parts of the ISO/IEC 39794