

AS/NZS 15506:1999
ISO/IEC 15506:1997

Australian/New Zealand Standard™

**Information technology—
Telecommunications and
information exchange between
systems—Private integrated
services network—Inter-exchange
signalling protocol—Message
waiting indication supplementary
service**

STANDARDS AUSTRALIA
✓

STANDARDS NEW ZEALAND
AVA

Documents

Document Sharing Hub

AS/NZS 15506:1999

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee IT/16, Private Telecommunications Networking. It was approved on behalf of the Council of Standards Australia on 7 December 1998 and on behalf of the Council of Standards New Zealand on 7 December 1998. It was published on 5 March 1999.

The following interests are represented on Committee IT/16:

Australia Post
Australian Communications Authority
Australian Electrical and Electronic Manufacturers Association
Australian Telecommunications User Group
New Zealand Standards Committee SC605 WG1
N.S.W. Public Works and Services
Optus Communications, Australia
Telstra Corporation, Australia

Review of Standards. To keep abreast of progress in industry, Joint Australian/New Zealand Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Joint Standards and related publications will be found in the Standards Australia and Standards New Zealand Catalogue of Publications; this information is supplemented each month by the magazines 'The Australian Standard' and 'Standards New Zealand', which subscribing members receive, and which give details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Joint Standards, addressed to the head office of either Standards Australia or Standards New Zealand, are welcomed. Notification of any inaccuracy or ambiguity found in a Joint Australian/New Zealand Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

AS/NZS 15506:1999

Australian/New Zealand Standard™

**Information technology—
Telecommunications and
information exchange between
systems—Private integrated
services network—Inter-exchange
signalling protocol—Message
waiting indication supplementary
service**

First published as AS/NZS 15506:1999.

Published jointly by:

Standards Australia
1 The Crescent,
Homebush NSW 2140 Australia

Standards New Zealand
Level 10, Radio New Zealand House,
155 The Terrace,
Wellington 6001 New Zealand

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee IT/16, Private Telecommunications Networking.

This Standard is identical with, and has been reproduced from, ISO/IEC 15506:1997, *Information technology—Telecommunications and information exchange between systems—Private Integrated Services Network—Inter-exchange signalling protocol—Message waiting indication supplementary service*.

The objective of this Standard is to provide private integrated services network (PISN) designers and users with the specification for the signalling protocol for use at the Q reference point between PISN exchanges, in order to allow a message waiting indication to be sent to a served user and for this indication to be cancelled worldwide.

The Standard is one of a series of emerging ISO/IEC Standards applicable to private integrated services networking. The series uses the ISDN concepts as developed by ITU-T and is also within the framework of Standards for Open Systems Interconnection (OSI) as defined by ISO/IEC JTC 1.

The number of this Standard is not reproduced on each page; its identity is shown only on the cover and title page.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the annex to which they apply. A 'normative' annex is an integral part of a Standard, whereas an 'informative' annex is only for information and guidance.

For the purpose of this Standard, the ISO/IEC text should be modified as follows:

- (a) The words 'this Australian/New Zealand Standard' should replace the words 'this International Standard' wherever they appear.
- (b) References to International Standards should be replaced by references, where appropriate, to the following Australian/New Zealand Standards:

<i>Reference to International Standard or other publication</i>		<i>Australian/New Zealand Standard</i>	
ISO/IEC		AS/NZS	
8601	Data elements and interchange formats—Information interchange—Representation of dates and times	3802	Data elements and interchange formats—Information interchange—Representation of dates and times
11579	Information technology—Telecommunications and information exchange between systems—Private Integrated Services Network	4136	Information technology—Telecommunications and information exchange between systems—Private integrated services network
11579-1	Part 1: Reference configuration for PISN Exchanges (PINX)	4136.1	Part 1: Reference configuration for PISN exchanges (PINX)
11582	Information technology—Telecommunications and information exchange between systems—Private Integrated Services Network—Generic functional protocol for the support of supplementary services—Inter-exchange signalling procedures and protocol	4239	Information technology—Telecommunications and information exchange between systems—Private integrated services network—Generic functional protocol for the support of supplementary services—Inter-exchange signalling procedures and protocol

iii

ISO/IEC		AS/NZS	
13873	Information technology— Telecommunications and information exchange between systems— Private Integrated Services Network— Inter-exchange signalling protocol— Call diversion supplementary services	4342	Information technology— Telecommunications and information exchange between systems— Private integrated services network— Inter-exchange signalling protocol— Call diversion supplementary services
15505	Information technology— Telecommunications and information exchange between systems— Private Integrated Services Network— Specification, functional model and information flows—Message waiting indication supplementary service	15505	Information technology— Telecommunications and information exchange between systems— Private integrated services network— Specification, functional model and information flows—Message waiting indication supplementary service
ITU-T			
Rec. I.112	Vocabulary of terms for ISDNs	—	
Rec. I.210	Principles of telecommunication services supported by an ISDN and the means to describe them	—	
Rec. Q.950	Digital subscriber signalling system No.1 (DSSI)— Supplementary services protocols, structure and general principles	—	
Rec. Z.100	Specification and description language	—	
CCITT			
Rec. I.130	Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN	—	

© Copyright – STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Users of Standards are reminded that copyright subsists in all Standards Australia and Standards New Zealand publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia or Standards New Zealand may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia or Standards New Zealand. Permission may be conditional on an appropriate royalty payment. Australian requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia. New Zealand requests should be directed to Standards New Zealand.

Up to 10 percent of the technical content pages of a Standard may be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia or Standards New Zealand.

Inclusion of copyright material in computer software programs is also permitted without royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia or Standards New Zealand at any time.

CONTENTS

	<i>Page</i>
1 Scope	1
2 Conformance	1
3 Normative references	1
4 Definitions	2
4.1 External definitions	2
4.2 Other definitions	2
5 List of acronyms	2
6 Signalling protocol for the support of SS-MWI	3
6.1 SS-MWI description	3
6.2 SS-MWI operational requirements	3
6.2.1 Requirements on a Message Centre PINX	3
6.2.2 Requirements on a Served User PINX	3
6.2.3 Requirements on a Transit PINX	3
6.3 SS-MWI coding requirements	4
6.3.1 Operations	4
6.3.2 Information elements	6
6.3.3 Messages	7
6.4 SS-MWI state definitions	7
6.4.1 States at the Message Centre PINX	7
6.4.2 States at the Served User PINX	7
6.5 SS-MWI signalling procedures	7
6.5.1 Actions at the Message Centre PINX	7
6.5.2 Actions at the Served User PINX	8
6.5.3 Actions at a Transit PINX	9
6.6 SS-MWI impact of interworking with public ISDNs	9
6.6.1 Incoming Gateway PINX procedures	9
6.6.2 Outgoing Gateway PINX procedures	9
6.7 SS-MWI impact of interworking with non-ISDNs	9
6.8 Protocol interactions between SS-MWI and other supplementary services and ANFs	9
6.8.1 Interaction with Advice Of Charge (SS-AOC)	9
6.8.2 Interaction with Call Deflection (SS-CD)	9
6.8.3 Interaction with Call Forwarding Unconditional (SS-CFU)	9

	<i>Page</i>
6.8.4 Interaction with Call Forwarding Busy (SS-CFB)	9
6.8.5 Interaction with Call Forwarding No Reply (SS-CFNR)	10
6.8.6 Interaction with Call Interception (ANF-CINT)	10
6.8.7 Interaction with Call Intrusion (SS-CI)	10
6.8.8 Interaction with Call Offer (SS-CO)	10
6.8.9 Interaction with Call Transfer (SS-CT)	10
6.8.10 Interaction with Calling Name Identification Presentation (SS-CNIP)	10
6.8.11 Interaction with Connected Name Identification Presentation (SS-CONP)	10
6.8.12 Interaction with Completion of Call to Busy Subscriber (SS-CCBS)	10
6.8.13 Interaction with Completion of Call on No Reply (SS-CCNR)	10
6.8.14 Interaction with Do Not Disturb (SS-DND)	10
6.8.15 Interaction with Do Not Disturb Override (SS-DNDO)	10
6.8.16 Interaction with Path Replacement (ANF-PR)	10
6.8.17 Interaction with Recall (SS-RE)	10
6.8.18 Interaction with Route Restriction Class (ANF-RRC)	10
6.9 SS-MWI parameter values (timers)	10
6.9.1 Timer T1	10
6.9.2 Timer T2	10
Annex A - Protocol Implementation Conformance Statement (PICS) Proforma	11
Annex B - Examples of Message Sequences	16
Annex C - Specification and Description Language (SDL) Representation of Procedures	20
Annex D - Imported ASN.1 definitions	26

AUSTRALIAN/NEW ZEALAND STANDARD

Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Inter-exchange signalling protocol — Message waiting indication supplementary service

1 Scope

This International Standard specifies the signalling protocol for the support of the Message Waiting Indication supplementary service (SS-MWI) at the Q reference point between Private Integrated Services Network Exchanges (PINXs) connected together within a Private Integrated Services Network (PISN).

The supplementary service MWI enables a Served User to be sent a Message Waiting Indication and also enables this Message Waiting Indication to be cancelled. The Served User may also be permitted to interrogate the Message Centre for any Message Waiting Indication.

The Q reference point is defined in ISO/IEC 11579-1.

Service specifications are produced in three stages and according to the method specified in CCITT Rec. I.130. This International Standard contains the stage 3 specification for the Q reference point and satisfies the requirements identified by the stage 1 and stage 2 specifications in International Standard ISO/IEC 15505.

The signalling protocol for SS-MWI uses certain aspects of the generic procedures for the control of supplementary services specified in ISO/IEC 11582.

This International Standard also specifies additional signalling protocol requirements for the support of interactions at the Q reference point between SS-MWI and other supplementary services and ANFs.

NOTE - Additional interactions that have no impact on the signalling protocol at the Q reference point can be found in the relevant stage 1 specifications.

This International Standard is applicable to PINXs which can interconnect to form a PISN.

2 Conformance

In order to conform to this International Standard, a PINX shall satisfy the requirements identified in the Protocol Implementation Conformance Statement (PICS) proforma in annex A.

Conformance to this International Standard includes conforming to those clauses that specify protocol interactions between SS-MWI and other supplementary services and ANFs for which signalling protocols at the Q reference point are supported in accordance with the stage 3 standards concerned.

3 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO/IEC 8601:1988,	<i>Data elements and interchange formats — Information interchange — Representation of dates and times.</i>
ISO/IEC 11579-1:1994,	<i>Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Part 1: Reference configuration for PISN Exchanges (PINX).</i>
ISO/IEC 11582:1995,	<i>Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Generic functional protocol for the support of supplementary services — Inter-exchange signalling procedures and protocol.</i>
ISO/IEC 13873:1995,	<i>Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Inter-exchange signalling protocol — Call diversion supplementary services.</i>

- ISO/IEC 15505:1997, *Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Specification, functional model and information flows — Message waiting indication supplementary service.*
- ITU-T Rec. I.112:1993, *Vocabulary of terms for ISDNs.*
- CCITT Rec. I.130:1988, *Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN.*
- ITU-T Rec. I.210:1993, *Principles of telecommunication services supported by an ISDN and the means to describe them.*
- ITU-T Rec. Q.950:1993, *Digital subscriber signalling system no.1 (DSS1) — Supplementary services protocols, structure and general principles.*
- ITU-T Rec. Z.100:1993, *Specification and description language.*

4 Definitions

For the purposes of this International Standard, the following definitions apply:

4.1 External definitions

This International Standard uses the following terms defined in other documents:

- | | |
|---|--------------------|
| - Application Protocol Data Unit (APDU) | (ISO/IEC 11582) |
| - Basic Service | (ITU-T Rec. I.210) |
| - Call-Independent | (ISO/IEC 11582) |
| - Gateway PINX | (ISO/IEC 11582) |
| - Originating PINX | (ISO/IEC 11582) |
| - Private Integrated Services Network (PISN) | (ISO/IEC 11579-1) |
| - Private Integrated Services Network Exchange (PINX) | (ISO/IEC 11579-1) |
| - Signalling | (ITU-T Rec. I.112) |
| - Supplementary Service | (ITU-T Rec. I.210) |
| - Supplementary Service Control Entity | (ISO/IEC 11582) |
| - Terminating PINX | (ISO/IEC 11582) |
| - Transit PINX | (ISO/IEC 11582) |

4.2 Other definitions

4.2.1 Message Centre PINX : The PINX serving the Message Centre entity for activation, deactivation.

4.2.2 Served User : The user to whom the Message Waiting Indication is sent on initiative of the Message Centre.

4.2.3 Message Centre : The entity which activates or deactivates the Message Waiting Indication as a result of storage or retrieval of messages.

4.2.4 Message Waiting Indication : An indication to the Served User when messages are waiting for the Served User.

5 List of acronyms

ANF	Additional Network Feature
APDU	Application Protocol Data Unit
ASN.1	Abstract Syntax Notation no. 1
ISDN	Integrated Services Digital Network
MWI	Message Waiting Indication
NFE	Network Facility Extension

PINX	Private Integrated Services Network Exchange
PISN	Private Integrated Services Network
SDL	Specification and Description Language
SS	Supplementary Service

6 Signalling protocol for the support of SS-MWI

6.1 SS-MWI description

SS-MWI enables a Served User to be sent a Message Waiting Indication and also enables this Message Waiting Indication to be cancelled.

This service also includes an option to interrogate the Message Waiting Indication stored against the Served User.

6.2 SS-MWI operational requirements

6.2.1 Requirements on a Message Centre PINX

Generic procedures for the call-independent control (connection-oriented) of supplementary services, as specified in ISO/IEC 11582 for an Originating PINX and for a Terminating PINX, shall apply.

6.2.2 Requirements on a Served User PINX

Generic procedures for the call-independent control (connection-oriented) of supplementary services, as specified in ISO/IEC 11582 for a Terminating PINX and for an Originating PINX, shall apply.

6.2.3 Requirements on a Transit PINX

Generic procedures for the call-independent control (connection-oriented) of supplementary services, as specified in ISO/IEC 11582 for a Transit PINX, shall apply.

6.3 SS-MWI coding requirements

6.3.1 Operations

The operations defined in Abstract Syntax Notation number 1 (ASN.1) in table 1 shall apply.

Table 1 - Operations in support of SS-MWI

SS-MWI-Operations			
{ iso (1) standard (0) pss1-message-waiting-indication (15506) message-waiting-operations (0)}			
DEFINITIONS EXPLICIT TAGS ::=			
BEGIN			
IMPORTS	OPERATION, ERROR FROM Remote-Operation-Notation {joint-iso-ccitt (2) remote-operations (4) notation (0)}		
	Extension FROM Manufacturer-specific-service-extension-definition {iso (1) standard (0) pss1-generic-procedures (11582) msi-definition (0)}		
	basicServiceNotProvided, notActivated, notSubscribed, invalidServedUserNr FROM General-Error-List {ccitt (2) recommendation (0) q (17) 950 general-error-list (1) }		
	PartyNumber FROM Addressing-Data-Elements {iso (1) standard (0) pss1-generic-procedures (11582) addressing-data-elements (9) }		
	BasicService FROM Call-Diversion-Operations {iso (1) standard (0) pss1- call-diversion (13873) call-diversion-operations (0) }		
	;		
MWIActivate	::=	OPERATION ARGUMENT RESULT ERRORS {	MWIActivateArg DummyRes notSubscribed, invalidServedUserNr, basicServiceNotProvided, unspecified }
MWIDeactivate	::=	OPERATION ARGUMENT RESULT ERRORS {	MWIDeactivateArg DummyRes notSubscribed, invalidServedUserNr, basicServiceNotProvided, unspecified }