

STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Amendment No. 1
to
AS/NZS 1748.1:2011
Timber—Solid—Stress-graded for structural purposes
Part 1: General requirements

REVISED TEXT

The 2011 edition of AS/NZS 1748.1 is amended as follows; the amendment should be inserted in the appropriate place.

SUMMARY: This Amendment applies to Appendix C.

Published on 31 October 2012.

Approved for publication in New Zealand on behalf of the Standards Council of New Zealand on 27 September 2012.

AMDT
No. 1
OCT
2012

Paragraph C1, Appendix C

Delete Paragraph C1 and *replace* with the following:

C1 GENERAL

Where timber is purported to comply with this Standard, each piece shall be clearly marked to identify the following:

- (a) The stress-grade of the timber.
- (b) The manufacturer of the timber (entity responsible for grading).
- (c) Reference to this Standard, i.e., AS/NZS 1748.1, or the generic number of this series of Standards, i.e., AS/NZS 1748.
- (d) Where the stress grade has seasoned and unseasoned options and, if graded as seasoned, the inclusion of one of the following:
 - (i) The word 'SEASONED' or 'DRY', or an abbreviation of seasoned (e.g., 'SEAS', 'S').
 - (ii) If kiln dried, 'KD'.

The timber marking shall be one of the following:

- (A) Marked with a brand, or stamp, that will remain legible in service.
- (B) Marked with a label that cannot be removed without obvious damage to the mark.
- (C) Tagged with an end tag (only where an appearance requirement has been specified).

NOTES:

- 1 In many applications, pieces are used in lengths shorter than the production lengths and stress grade marking at 1200 mm centres, or less, will give the appropriate stress grade information on shorter pieces that are cut from the originally graded lengths.
 - 2 Additional information may also be incorporated in the marking.
-

This page has been left intentionally blank.