

AS/NZS 2794:1994

ISO/IEC 2593:1993

## Australian/New Zealand Standard

---

**Information technology—  
Telecommunications and  
information exchange between  
systems—34-pole DTE/DCE  
interface connector mateability  
dimensions and contact number  
assignments**

---

STANDARDS AUSTRALIA

STANDARDS NEW ZEALAND



Documents

Document Sharing Hub

**AS/NZS 2794:1994**

---

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee IT/1, Information Systems—Interconnection. It was approved on behalf of the Council of Standards Australia on 13 April 1994 and on behalf of the Council of Standards New Zealand on 9 May 1994. It was published on 20 June 1994.

The following interests are represented on Committee IT/1:

Australian Bankers Association  
 Australian Bureau of Statistics  
 Australian Chamber of Commerce and Industry  
 Australian Committee of Directors and Principals  
 Australian Computer Society  
 Australian Computer Users Association  
 Australian Information Industry Association  
 Australian Vice Chancellors Committee  
 Department of Defence, Australia  
 Department of Industry, Technology and Regional Development, Australia  
 Government Computing Service, New Zealand  
 Information Exchange Steering Committee, Australia  
 Institute of Information and Communication Technologies, CSIRO, Australia  
 OPTUS Communications, Australia  
 Telecom Australia  
 Telecom New Zealand

**Review of Standards.** To keep abreast of progress in industry, Joint Australian/New Zealand Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Joint Standards and related publications will be found in the Standards Australia and Standards New Zealand Catalogue of Publications; this information is supplemented each month by the magazines 'The Australian Standard' and 'Standards New Zealand', which subscribing members receive, and which give details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Joint Standards, addressed to the head office of either Standards Australia or Standards New Zealand, are welcomed. Notification of any inaccuracy or ambiguity found in a Joint Australian/New Zealand Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

AS/NZS 2794:1994

## Australian/New Zealand Standard

---

# **Information technology— Telecommunications and information exchange between systems—34-pole DTE/DCE interface connector mateability dimensions and contact number assignments**

---

First published in Australia as part of AS 1484.4—1973.  
Revised and redesignated in part as AS 2794—1985.

Jointly revised and designated as Joint Standard  
AS/NZS 2794:1994.

PUBLISHED JOINTLY BY:

STANDARDS AUSTRALIA  
1 The Crescent,  
Homebush NSW 2140 Australia

STANDARDS NEW ZEALAND  
Level 10, Standards House,  
155 The Terrace,  
Wellington 6001 New Zealand

ISBN 0 7262 8939 6



**Documents**

Document Sharing Hub

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee IT/1 on Information Systems—Interconnection to supersede AS 2794—1985, *Data communication 34-pin DTE/DCE interface connector and pin assignments*. It is identical with and has been reproduced from ISO/IEC 2593:1993, *Information technology—Telecommunications and information exchange between systems—34-pole DTE/DCE interface connector mateability dimensions and contact number assignments*.

This Standard is issued as a Joint Standard under the terms of the Active Cooperation Agreement between Standards Australia and Standards New Zealand.

The objective of this Standard is to provide communications engineers with specifications for the 34-pole connector, including assignments, which is to be used between data terminal equipment and data circuit-terminating equipment where the ITU-T Recommendation V.35 or Recommendation X.21bis is applicable.

This Standard is one of a series of Open Systems Interconnection (OSI) Standards which are currently under development. Since OSI Standards are developmental, there may be some minor difficulties encountered in their implementation. For this reason, Standards Australia will be providing, through the OSI Help Desk, a service to coordinate and disseminate information concerning difficulties which are identified in using this Standard.

The term ‘normative’ has been used in this Standard to define the application of the annex to which it applies. A ‘normative’ annex is an integral part of a Standard.

Users of this Standard are advised by Standards Australia and Standards New Zealand, under arrangements made with ISO and IEC, as well as certain other Standards organizations, that the number of this Standard is not reproduced on each page; its identity is shown only on the cover and title pages.

For the purpose of this Standard, the source text should be modified as follows:

- (a) *Terminology* The words ‘this Australian/New Zealand Standard’ should replace the words ‘this International Standard’ wherever they appear.
- (b) *Decimal marker* Substitute a full point for a comma where it appears as a decimal marker.
- (c) *References* The references to international Standards should be replaced by references, where appropriate, to the following Australian or Joint Australian/New Zealand Standards:

| Reference to International Standard<br>or other publication |                                                                                                              | Australian or Joint<br>Australian/New Zealand Standard |                                                                                                               |
|-------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|--------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|
| ISO                                                         |                                                                                                              | AS                                                     |                                                                                                               |
| 261                                                         | ISO general purpose metric screw threads—General plan                                                        | 1721                                                   | General purpose metric screw threads                                                                          |
|                                                             |                                                                                                              | AS/NZS                                                 |                                                                                                               |
| 4902                                                        | Information technology—Data communication—37-pole DTE/DCE interface connector and contact number assignments | 3612                                                   | Information technology—Data communication—37-pole DTE/DCE interface connector and contact number assignments  |
|                                                             |                                                                                                              | AS                                                     |                                                                                                               |
| 4903                                                        | Information technology—Data communication—15-pole DTE/DCE interface connector and contact number assignments | 3613                                                   | Information technology—Data communications—15-pole DTE/DCE interface connector and contact number assignments |

## ITU-T Recommendation

- |         |                                                                                                                                                                     |   |
|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|
| V.10    | Electrical characteristics for unbalanced double-current interchange circuits for general use with integrated circuit equipment in the field of data communications | — |
| V.11    | Electrical characteristics for balanced double-current interchange circuits for general use with integrated circuit equipment in the field of data communications   | — |
| X.21    | Interface between data terminal equipment (DTE) and data circuit-terminating equipment (DCE) for synchronous operation on public data networks                      | — |
| X.21bis | Use of public data networks on data terminal equipment (DTE) which is designed for interfacing to synchronous V-series modems                                       | — |
| V.28    | Electrical characteristics for unbalanced double-current interchange circuits                                                                                       | — |

## © Copyright – STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Users of Standards are reminded that copyright subsists in all Standards Australia and Standards New Zealand publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia or Standards New Zealand may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia or Standards New Zealand. Permission may be conditional on an appropriate royalty payment. Australian requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia. New Zealand requests should be directed to Standards New Zealand.

Up to 10 percent of the technical content pages of a Standard may be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia or Standards New Zealand.

Inclusion of copyright material in computer software programs is also permitted without royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia or Standards New Zealand at any time.

# Information technology—Telecommunications and information exchange between systems—34-pole DTE/DCE interface connector mateability dimensions and contact number assignments

## 1 Scope

This International Standard specifies the 34-pole connector and the assignment of contact numbers at the interface between data terminal equipment (DTE) and data circuit-terminating equipment (DCE) where CCITT<sup>1)</sup> Recommendation V.35 or Recommendation X.21bis together with Recommendation V.10 and V.11 are applicable.

**NOTE 1** An interoperation between interfaces designed according to electrical characteristics specified in CCITT Recommendation V.35 and those specified in CCITT Recommendation V.11 is, at least to a limited degree, possible. This can be achieved, for example, by using a passive adaptor which joins the interface connectors in accordance with ISO 2593 and ISO 4902 or ISO 4903, respectively

This International Standard specifies the dimensions of the connector housing and gives recommendations for the type of locking device (jack-screw system) and connector shielding.

## 2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 261:1973, *ISO general purpose metric screw threads — General plan.*

ISO 4902:1990, *Information technology — Data communication — 37-pole DTE/DCE interface connector and contact number assignments.*

ISO 4903:1989, *Information technology — Data communication — 15-pole DTE/DCE interface connector and contact number assignments.*

CCITT Recommendation V.10 (or X.26):1988, *Electrical characteristics for unbalanced double-current interchange circuits for general use with integrated circuit equipment in the field of data communications.*

CCITT Recommendation V.11 (or X.27):1988, *Electrical characteristics for balanced double-current interchange circuits for general use with integrated circuit equipment in the field of data communications.*

CCITT Recommendation X.21:1988, *Interface between data terminal equipment (DTE) and data circuit-terminating equipment (DCE) for synchronous operation on public data networks.*

CCITT Recommendation X.21bis:1988, *Use of public data networks on data terminal equipment (DTE) which is designed for interfacing to synchronous V-series modems.*

CCITT Recommendation V.28:1988, *Electrical characteristics for unbalanced double-current interchange circuits.*

1) International Telegraph and Telephone Consultative Committee.

CCITT Recommendation V.35:1984, *Data transmission at 48 kilobits per second using 60-108 kHz group band circuits*.<sup>2)3)</sup>

IEC 50(581):1978, *International Electrotechnical Vocabulary — Chapter 581: Electromechanical components for electronic equipment*.

IEC 807-6:1988, *Rectangular connectors for frequencies below 3 MHz — Part 6: Detail specification for a range of connectors with size 20 (7.5 A) round contacts having polarized guides — Fixed solder contact types*.

### 3 Definitions

For the purposes of this International Standard, the definitions given in IEC 50(581) apply. For the convenience of the users of this International Standard, the following definitions are repeated.

**3.1 cable adaptor:** A part of a connector or an accessory consisting of a rigid housing for attachment to the connector body. It may incorporate provision for a cable clamp or seal for terminating screens and provide shielding to electrical interference. It may be straight or angled.

**3.2 connector housing:** The part of a connector into which the insert and contacts are assembled.

**3.3 contact arrangement:** The number, spacing and configuration of contacts in a component.

**3.4 female contact:** A contact intended to make electrical engagement on its inner surface and which will accept entry of a male contact.

**3.5 intermateable connectors:** Two connectors are intermateable when they are capable of being connected electrically and mechanically but without regard to their performance and intermountability.

**3.6 jack-screw system:** A device comprising a set of captive screws and nuts used to couple and uncouple mating components. It may also provide a polarization facility.

**3.7 locking device:** A feature incorporated in certain components to provide mechanical retention of their mating part.

**3.8 male contact:** A contact intended to make electrical engagement on its outer surface and which will enter a female contact.

**3.9 mounting flange:** A projection from a component for the purpose of attaching the component to a rigid surface.

**3.10 (n-pole-)connector:** A component which terminates conductors for the purpose of providing connection and disconnection to a suitable mating component.

**3.11 polarization:** Features on mating components to prevent incorrect mating.

## 4 Connector specifications

A 34-pole connector shall be provided for the DTE/DCE interface.

Figures 1 to 5 illustrate the 34-pole connector. Only those dimensions that are essential for mating are shown.

Figure 1 illustrates the DTE connector which has 34 male contacts in a connector housing. Figure 2 illustrates the DCE connector which has 34 female contacts in a connector housing. The connector housing on the DTE connector is dimensioned to fit inside the connector housing on the DCE connector (see figures 1 and 2). Contact identification lettering is also specified in figures 1 and 2. The use of shields and mounting flanges is illustrated in figures 1 and 2 respectively. Since their shape and size is not essential for mating, the use of different shape and size from those illustrated does not affect conformance with this International Standard.

Figure 3 illustrates the dimensions for the contact spacing.

Figures 4 and 5 illustrate the dimensions for the male and female contacts respectively.

Figures 8 and 9 illustrate the connector mountings.

The connectors shall be equipped with a jack-screw system (see figures 6 and 7 and tables 2 and 3). On the DTE connector, the female jack-screw (nut) shall be positioned adjacent to the male contact lettered A and the male jack-screw shall be positioned adjacent to the male contact lettered MM. Both jack-screws of the DTE connector shall be rotateable. On the DCE connector, the female jack-screw (nut) shall be positioned adjacent to the female contact lettered MM and the male jack-screw shall be positioned adjacent to the female contact lettered A. Both jack-screws of the DCE connector shall be fixed to prevent rotation.

Connectors shall use either the 6-32 UNC thread in accordance with the present specification of

2) Other CCITT Recommendations for group band modems, viz. V.36 and V.37, are available.

3) In the Melbourne, 1988, version of the V-series Recommendations, the text of Recommendation V.35 has been replaced by a note stating CCITT's intention to withdraw this Recommendation and discourage its use in new equipment.

IEC 807-6 or, if required by national regulations or mutual user agreement, M 3 as specified in ISO 261.

When procuring equipment internationally which will use this 34-pole connector, the user shall specify the thread type in accordance with national requirements.

NOTES

2 The nominal contact diameter of 1,6 mm is referred to as size 16 in IEC 807-7.

3 The first edition of this International Standard did not specify all the connector dimensions required to ensure mechanical compatibility. As a result, contacts with nominal diameter of both 1 mm and 1,6 mm and two different arrangements of male shell and female shell and different dimensions of jack-screws are now in use in different countries. This International Standard specifies 1,6 mm contacts and the particular arrangement of male shell and of female shell described above; where arrangements occur which do not conform with this edition, adaptors can be necessary.

4 The male shell specified in this International Standard does not contain the optional polarizing pin specified in IEC 807-6.

5 Assignment of contact letters

The assignment of contact letters is given in table 1.

6 Connector shielding

Connector shielding is optional. If it is used, e.g. due to national regulations, etc., it shall be accomplished by the use of

- a metallic male shell together with a connector housing and a cable adaptor with a DTE connector; or
- a metallic female shell with a DCE connector.

A polarization pin shall not be used on the male shell.

Table 1 — Assignment of contact numbers

| Contact | Function <sup>1)</sup>                                             | CCITT circuit number | Direction |
|---------|--------------------------------------------------------------------|----------------------|-----------|
| A       | See note 1                                                         | —                    | —         |
| B       | Signal ground or common return                                     | 102                  | common    |
| C       | Request to send                                                    | 105                  | from DTE  |
| D       | Ready for sending                                                  | 106                  | to DTE    |
| E       | Data set ready                                                     | 107                  | to DTE    |
| F       | Data channel received line signal detector                         | 109                  | to DTE    |
| H       | Connect data set to line (see note 2)                              | 108/1                | from DTE  |
|         | Data terminal ready (see note 2)                                   | 108/2                | from DTE  |
| J       | Calling indicator (see note 2)                                     | 125                  | to DTE    |
| K       | F <sub>1</sub>                                                     | —                    | —         |
| L       | Local loopback (see note 2)                                        | 141                  | from DTE  |
| M       | F <sub>1</sub>                                                     | —                    | —         |
| N       | Loopback/Maintenance test                                          | 140                  | from DTE  |
| R       | Received data A-wire                                               | 104                  | to DTE    |
| T       | Received data B-wire                                               | 104                  | to DTE    |
| V       | Receiver signal element timing (DCE source) A-wire                 | 115                  | to DTE    |
| X       | Receiver signal element timing (DCE source) B-wire                 | 115                  | to DTE    |
| Y       | Transmitter signal element timing (DCE source) A-wire              | 114                  | to DTE    |
| AA      | Transmitter signal element timing (DCE source) B-wire              | 114                  | to DTE    |
| P       | Transmitted data A-wire                                            | 103                  | from DTE  |
| S       | Transmitted data B-wire                                            | 103                  | from DTE  |
| U       | Transmitter signal element timing (DTE source) A-wire (see note 2) | 113                  | from DTE  |
| Z       | F <sub>2</sub>                                                     | —                    | —         |
| W       | Transmitter signal element timing (DTE source) B-wire (see note 2) | 113                  | from DTE  |
| BB      | F <sub>2</sub>                                                     | —                    | —         |
| CC      | F <sub>3</sub>                                                     | —                    | —         |