

STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Amendment No. 1
to
AS/NZS 2890.1:2004
Parking facilities
Part 1: Off-street car parking

REVISED TEXT

The 2004 edition of AS/NZS 2890.1 is amended as follows; the amendment(s) should be inserted in the appropriate place(s).

SUMMARY: This Amendment applies to Clauses 1.3, 2.3.4, 3.2.4, 3.3 and 5.4(b), and Appendix B.

Published on .

Approved for publication in New Zealand on behalf of the Standards Council of New Zealand on

AMDT
No. 1

Page 7 Clause 1.3

Add new Clause 1.3.19 as follows:

1.3.19 Private car park

A car park (e.g. at a residential development or place of employment) which is not open to or intended to be used by the public or casual users.

Renumber existing Clauses 1.3.19 to 1.3.26 accordingly.

AMDT
No. 1

Page 12 Clause 2.3.4

Add new Clause 2.3.4 as follows:

2.3.4 Assignment of user class to parking modules

The user class shall be assigned to parking modules according to the appropriate classification specified in Clause 1.4.

Any one parking module in other than a private car park shall comprise spaces for one user class only, with the exception that spaces for people with disabilities and spaces for small cars, see Clause 2.4.1, may be added to any module.

NOTE: The provision of a higher class module for a relatively small number of users in that class can be avoided by creating a separate module for that class (e.g. a visitors' car park separate from an employees' car park). The separate purposes may need to be clearly signposted.

In a private car park a single module catering for a mixture of classes (e.g. employees plus visitors) may be used provided that the spaces for each separate class are grouped together.

AMDT
No. 1

Page 31 Clause 3.2.4

In Item (b), after 'car park', *insert* 'or domestic driveway'.

AMDT
No. 1

Page 33 Clause 3.3

In Item (a), second paragraph preamble, *delete* 'under the following conditions:' and *replace* with 'provided all three of the following conditions are met:'

.

AMDT
No. 1

Page 50 Clause 5.4(b)

- 1 In Item (i), first sentence, *delete* the following:

‘the spaces shall be contiguous with a further car door clearance of 300 mm minimum on the outside of each outer space,’

and *replace* with:

the spaces shall be contiguous with the end spaces having a minimum width between the centre-line of the space and the end wall or obstruction of 1.5 m to allow clearance for door opening,

- 2 In Item (ii) *delete* the second sentence and *insert* the following:

The end spaces shall have a minimum width between the centre-line of the space and the end wall or obstruction of 1.5 m to allow clearance for car door opening.

NOTE: The clearance of 1.5 m in Items (i) and (ii) comprises half the width of a 2.4 m wide space plus a further 300 mm clearance for door opening.

AMDT
No. 1

Page 57 Paragraph B3.1

Insert after Item (b), the following note:

NOTE: The unbroken lines on Figures B3, B4, B5 and B6 represent the swept path of the body of the design vehicle. The radius of the outer unbroken line will therefore be slightly larger than the nominated turn radius which is measured from the outer front wheel.

AMDT
No. 1

Page 67 Paragraph B4.8

In the first line *delete* ‘6.3 m to 5.5 m’ and *insert* ‘6.2 m to 5.8 m’.
