

STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Amendment No. 2
to
AS/NZS 3350.2.14 :1995
Safety of household and similar electrical appliances
Part 2.14: Particular requirements—Kitchen machines

REVISED TEXT

The 1995 edition of AS/NZS 3350.2.14 is amended as follows; the amendments should be inserted in the appropriate places.

SUMMARY: This Amendment applies to the Preface and Clauses 4.2, 7, 11.7.1, 15.2, 20.116, 25.14 and Annex ZZ.

Published on 5 April 2001.

Approved for publication in New Zealand on behalf of the Standards Council of New Zealand on 4 July 2000.

Page ii Preface

Delete the fourth paragraph and *replace* with the following:

This Standard is technically equivalent to and has been reproduced from the third edition of IEC 60335-2-14:1994, *Safety of household and similar electrical appliances*, Part 2.14: *Particular requirements for kitchen machines* including Amendment 1. It is to be used in conjunction with the latest edition of AS/NZS 3350.1, *Safety of household and similar electrical appliances*, Part 1: *General requirements* and its Amendments. It was established on the basis of AS/NZS 3350.1:1994.

This Amendment forms part of the Standard on publication.

Page 6 Clause 4.2

Delete Clause 4.2 and *replace* with the following:

4.2 Addition:

NOTE 1 The additional test of 25.14 is carried out on a separate appliance.

NOTE 2 Three additional coffee mills and grain grinders are required for the test of 19.101.

This Amendment forms part of the Standard on publication.

Page 6 Clause 7

After the first paragraph *insert* the following:

7.1 Modification

Appliances shall be marked with **rated power input**.

This Amendment forms part of the Standard 2 years from publication.

AMDT
No. 2
APR.
2001

AMDT
No. 2
APR.
2001

AMDT
No. 2
APR.
2001

AMDT
No. 2
APR.
2001

Page 7 Clause 11.7.1

Delete the first sentence and *replace* with the following:

Food mixers with beaters for cake-batter mixing are operated for 15 min unless they incorporate a **biased-off switch** in which case they are operated for 5 min.

This Amendment forms part of the Standard on publication.

AMDT
No. 2
APR.
2001

Page 10 Clause 15.2

Delete Clause 15.2 and *replace* with the following:

15.2 *Addition:*

Water outlets for potato peelers are blocked.

Modification:

Instead of overfilling the liquid container, the test is carried out as follows:

*The liquid container of the appliance is completely filled with water containing approximately 1% NaCl. The appliance is then supplied at **rated voltage** and operated for 15 s. Lids are in position or removed, whichever is more unfavourable. During the test, the leakage current shall not exceed the values specified in clause 13.*

Saline solution is then added to the liquid container until it is completely full again. A further quantity equal to 15% of the capacity of the container or 0.25 l, whichever is greater, is poured in steadily over a period of 1 min.

This Amendment forms part of the Standard on publication.

AMDT
No. 2
APR.
2001

Page 17 Clause 20.116

After Clause 20.115 *add* the following:

20.116 Centrifugal juicers for fruit and vegetables shall be constructed so that parts cannot become disengaged when the appliance is operated at high speed.

Compliance is checked by the following test which is carried out without load.

*The appliance with the lid removed is supplied at **rated voltage** with the control set to give the highest speed. The appliance is operated 10 times.*

No part of the appliance shall become disengaged.

The appliance is operated again but with the lid in position. When the speed reaches its maximum value, an attempt is made to remove the lid. The test is carried out 10 times.

No part of the appliance shall become disengaged.

This Amendment forms part of the Standard on publication.
