

AS/NZS 3612:1994
ISO 4902:1989

Australian/New Zealand Standard

Information technology—Data communication—37-pole DTE/DCE interface connector and contact number assignments

STANDARDS AUSTRALIA 

STANDARDS NEW ZEALAND  **Documents**
Document Sharing Hub

AS/NZS 3612:1994

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee IT/1, Information Systems—Interconnection. It was approved on behalf of the Council of Standards Australia on 12 October 1993 and on behalf of the Council of Standards New Zealand on 22 April 1993. It was published on 17 January 1994.

The following interests are represented on Committee IT/1:

Australian Association of Permanent Building Societies
 Australian Bankers Association
 Australian Bureau of Statistics
 Australian Chamber of Commerce and Industry
 Australian Committee of Directors and Principals
 Australian Computer Society
 Australian Computer Users Association
 Australian Information Industry Association
 Australian Telecommunications Users Group
 Australian Vice Chancellors Committee
 Department of Defence, Australia
 Department of Industry, Technology and Commerce, Australia
 Information Exchange Steering Committee, Australia
 Institute of Information and Communication Technologies, CSIRO, Australia
 Life Insurance Federation of Australia
 OPTUS Communications, Australia
 Telecom Australia

Review of Standards. To keep abreast of progress in industry, Joint Australian/New Zealand Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Joint Standards and related publications will be found in the Standards Australia and Standards New Zealand Catalogue of Publications; this information is supplemented each month by the magazines 'The Australian Standard' and 'Standards New Zealand', which subscribing members receive, and which give details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Joint Standards, addressed to the head office of either Standards Australia or Standards New Zealand, are welcomed. Notification of any inaccuracy or ambiguity found in a Joint Australian/New Zealand Standard should be made without delay in order that the matter may be investigated and appropriate action taken.



Documents

Document Sharing Hub

AS/NZS 3612:1994

Australian/New Zealand Standard

Information technology—Data communication—37-pole DTE/DCE interface connector and contact number assignments

First published in Australia as AS 3612—1989.

First published in New Zealand as NZS/ISO 4902:1980.

AS 3612—1989 and NZS/ISO 4902:1980 jointly revised,
amalgamated and designated as Joint Standard
AS/NZS 3612:1994.

PUBLISHED JOINTLY BY:

STANDARDS AUSTRALIA
1 The Crescent,
Homebush NSW 2140 Australia

STANDARDS NEW ZEALAND
6th Floor, Wellington Trade Centre,
181-187 Victoria Street,
Wellington 1 New Zealand

 **Documents**
Document Sharing Hub
ISBN 0 7262 8666 4

PREFACE

This Standard was prepared by the Joint Australia/New Zealand Standards Committee IT/1, on Information Systems—Interconnection. It is identical with, and has been reproduced from, ISO 4902:1989, *Information technology—Data communication—37-pole DTE/DCE interface connector and contact number assignments*.

This Joint Standard is one of a series of Open Systems Interconnection (OSI) Standards which are currently under development. Since OSI Standards are developmental, there may be some minor difficulties encountered in their implementation. For this reason, Standards Australia will be providing, through the OSI Help Desk, a service to coordinate and disseminate information concerning difficulties which are identified in using this Joint Standard.

Under arrangements made between Standards Australia/Standards New Zealand and the international Standards bodies, ISO and IEC, as well as certain other Standards organizations, users of this Joint Standard are advised of the following:

- (a) In Australia, copyright is vested in Standards Australia. In New Zealand, copyright is vested in Standards New Zealand.
- (b) The number of this Joint Standard is not reproduced on each page; its identity is shown only on the cover and title pages.

For the purpose of this Joint Standard, the ISO/IEC text should be modified as follows:

- (i) *Terminology* The words ‘Australian Standard’, ‘New Zealand Standard’ or ‘Joint Australian/New Zealand Standard’ should replace the words ‘International Standard’ wherever they appear.
- (ii) *References* The references to International Standards should be replaced by references to the following Australian/New Zealand Standards:

<i>Reference to International Standard or other Publication</i>		<i>Australian/New Zealand Standard</i>	
ISO		AS	
261	ISO general purpose metric screw threads—General plan	1721	General purpose metric screw threads
2110	Data communication—25-pin DTE/DCE interface connector and pin assignments	2748	Information technology—Data communication—25-pole DTE/DCE interface connector and contact number assignments
4903	Data communication—15-pin DTE/DCE interface connector and pin assignments	3613	Information technology—Data communications—15-pole DTE/DCE interface connector and contact number assignments
CCITT			
V.10	Electrical characteristics for unbalanced double-current interchange circuits for general use with integrated circuit equipment in the field of data communications	—	

iii

CCITT		AS	
V.11	Electrical characteristics for balanced double-current interchange circuits for general use with integrated circuit equipment in the field of data communications	—	
V.24	List of definitions for interchange circuits between data terminal equipment (DTE) and data circuit-terminating equipment (DCE)	—	
V.28	Electrical characteristics for unbalanced double-current interchange circuits	—	
V.36	Modems for synchronous data transmission using 60-108 kHz group band circuits	—	
V.37	Synchronous data transmission at a data signalling rate higher than 72 kbit/s using 60-108 kHz group band circuits	—	
IEC			
50	International Electrotechnical Vocabulary	1852	International Electrotechnical Vocabulary
50(581)	Chapter 581: Electromechanical components for electronic equipment	1852.581	Part 581: Electromechanical components for electronic equipment
807	Rectangular connectors for frequencies below 3 MHz		
807-2	Part 2: Detail specification for a range of connectors with round contacts—Fixed solder contact types	—	

© Copyright — STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Users of Standards are reminded that copyright subsists in all Standards Australia and Standards New Zealand publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia or Standards New Zealand may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia or Standards New Zealand. Permission may be conditional on an appropriate royalty payment. Australian requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia. New Zealand requests should be directed to Standards New Zealand.

Up to 10 percent of the technical content pages of a Standard may be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia or Standards New Zealand.

Inclusion of copyright material in computer software programs is also permitted without royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia or Standards New Zealand at any time.

Information technology—Data communication— 37-pole DTE/DCE interface connector and contact number assignments

1 Scope

This International Standard specifies the 37-pole connector and the assignment of contact numbers at the interface between data terminal equipment (DTE) and data circuit-terminating equipment (DCE) where CCITT¹⁾ Recommendation V.24 together with Recommendations V.10 and V.11 are applicable.

International Standard ISO 4902 additionally provides the dimensions of the connector housing, as well as the recommended means of providing a locking device (latching block) and connector shielding.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 261 : 1973, *ISO general purpose metric screw threads — General plan*.

ISO 2110 : 1980, *Data communication — 25-pin DTE/DCE interface connector and pin assignments*.

ISO 4903 : 1980, *Data communication — 15-pin DTE/DCE interface connector and pin assignments*.

CCITT Recommendation V.10 (or X.26) : 1989, *Electrical characteristics for unbalanced double-current interchange circuits for general use with integrated circuit equipment in the field of data communications*.

CCITT Recommendation V.11 (or X.27) : 1989, *Electrical characteristics for balanced double-current interchange circuits for general use with integrated circuit equipment in the field of data communications*.

CCITT Recommendation V.24 : 1989, *List of definitions for interchange circuits between data terminal equipment (DTE) and data circuit-terminating equipment (DCE)*.

CCITT Recommendation V.28 : 1989, *Electrical characteristics for unbalanced double-current interchange circuits*.

CCITT Recommendation V.36 : 1989, *Modems for synchronous data transmission using 60-108 kHz group band circuits*.

CCITT Recommendation V.37 : 1989, *Synchronous data transmission at a data signalling rate higher than 72 kbit/s using 60-108 kHz group band circuits*.

IEC Publication 50(581) : 1978, *International Electrotechnical Vocabulary — Chapter 581 : Electromechanical components for electronic equipment*.

IEC Publication 807-2 : 1985, *Rectangular connectors for frequencies below 3 MHz — Part 2: Detail specification for a range of connectors with round contacts — Fixed solder contact types*.

3 Definitions

The following definitions have been taken from IEC Publication 50(581) : 1978.

3.1 cable adaptor: A part of a connector or an accessory consisting of a rigid housing for attachment to the connector body. It may incorporate provision for a cable clamp or seal for terminating screens and provide shielding from electrical interference. It may be straight or angled.

3.2 connector housing: A part of a connector into which the insert and contacts are assembled.

3.3 contact arrangement: The number, spacing and configuration of contacts in a component.

3.4 female contact: A contact intended to make electrical engagement on its inner surface and which will accept entry of a male contact.

3.5 intermateable connectors: Two connectors are intermateable when they are capable of being connected electrically and mechanically but without regard to their performance and intermountability.

1) International Telegraph and Telephone Consultative Committee.

2

3.6 locking device: A feature incorporated in certain components to provide mechanical retention of their mating part.

3.7 male contact: A contact intended to make electrical engagement on its outer surface and which will enter a female contact.

3.8 (n-pole-)connector: A component which terminates conductors for the purpose of providing connection and disconnection to a suitable mating component.

4 Connector

Figures 1 to 5 illustrate the 37-pole connector. Only those dimensions that are essential to mating are shown.

Figure 1 illustrates the DTE connector which has 37 male contacts in a connector housing. Figure 2 illustrates the DCE connector which has 37 female contacts in a connector housing. The connector housing on the DCE connector is dimensioned to fit inside the connector housing on the DTE connector (see figures 1 and 2). Contact numbering is specified in figures 1 and 2. Figure 3 illustrates the dimensions for the contact spacing. Figures 4 and 5 illustrate the dimensions for the male and female contacts respectively.

The DCE connector shall be equipped with a locking device consisting of two latching blocks as specified in figure 2. Due to the fact that the latching blocks have threaded holes which can act as nuts, the DTE connector may be equipped either with lever devices for latching to the latching blocks on the DCE connector or with screws that fit into the threaded holes in the latching blocks.

The thread of the latching blocks shall be M3 as specified in figure 2.

Sufficient connector dimensions are provided in this International Standard to ensure intermateable connectors. They are consistent with the detailed connector specification in IEC Publication 807-2.

In annex A, diagrams for finger clearance areas are given to provide guidance for equipment designers. Figure A.1 shows the maximum DTE connector outline including all means for latching to the latching blocks. Figure A.2 shows the minimum DCE connector spacing when multiple interface arrangements are used.

5 Assignment of contact numbers

The assignment of contact numbers for the selected interchange circuits specified in CCITT Recommendation V.24 that may be implemented in modems complying with CCITT Recommendations V.36 and V.37 is given in table 1. Although table 1 provides the total list of interchange circuits designated in all the above listed modem CCITT Recommendations, only those interchange circuits required for the particular equipment need to be implemented. Table 2 shows the preferred assignments of circuits which may be applied for national use. Table 3 gives a list of the applicable interchange circuits used in tables 1 and 2 and their description. Additionally, notes 5 and 6 to table 1 provide preferred assignment of contact numbers for some optional circuits which may be applied for national use.

6 Connector shielding

Connector shielding is optional. If it is used, for example due to national regulations, etc., it shall be accomplished by the use of metallic connector housings on both the DTE connector and the DCE connector.

7 Interconnecting configurations for mixed use of V.10, V.11 and V.28 electrical characteristics

Considerations for the interworking of equipment implementing V.10 on one side of the interface with equipment implementing V.11 on the other side of the interface are given in annex A, clause A.2 of CCITT Recommendations V.10 and V.11. In addition, the definition of the category 1 and 2 receiver configurations is provided in V.10.

Guidance concerning possible interconnecting configurations applicable to V.28 interfaces is provided in annex B.

Guidance concerning the necessary adaptation when there is a need for a DTE or DCE implementing V.10 characteristics to interwork with a DCE or DTE implementing V.28 characteristics is given in annex C. Any adapters required to accomplish the interworking with V.28 and ISO 2110 shall be provided with equipment meeting the requirements of this International Standard. No revisions or modifications shall be required in the existing equipment using V.28 electrical characteristics.

The annex C interworking between V.10 and V.28 characteristics is not required in CCITT Recommendations V.36 and V.37.

Table 1 — Assignment of contact numbers

First segment assignment ²⁾			Second segment assignment ²⁾			Receiver category ⁴⁾	Direction to	
Contact number	Circuit number	Interchange points ³⁾	Contact number	Circuit number	Interchange points		DTE	DCE
1	1)					—	—	—
2	N	A-A'	20	102b	C-B'	2	X	
3	N	A-A'	21	N	B/C-B'	1	X	
4	103	A-A'	22	103	B/C-B'	1		X
5	114	A-A'	23	114	B/C-B'	1	X	
6	104	A-A'	24	104	B/C-B'	1	X	
7	105	A-A'	25	105	B/C-B'	1		X
8	115	A-A'	26	115	B/C-B'	1	X	
9	106	A-A'	27	106	B/C-B'	1	X	
10	141	A-A'	28	N	A-A'	2		X
11	107	A-A'	29	107	B/C-B'	1	X	
12	108*	A-A'	30	108*	B/C-B'	1	X	
13	109	A-A'	31	109	B/C-B'	1	X	
14	140	A-A'	32	N	A-A'	2		X
15	N	A-A'	33	N	A-A'	2	X	
16	111	A-A'	34	N	A-A'	2		X
17	113	A-A'	35	113	B/C-B'	1		X
18	142	A-A'	36	N	A-A'	2	X	
19	102	C-C'	37	102a	C-B'			X

Key: N — Contact permanently reserved for national use.

- — Circuit 108/1 or circuit 108/2 (if one of them is provided).

NOTES

1 Contact 1 is assigned for connecting the shields between tandem sections of the shielded interface cable. The shield may be connected either to protective ground or to signal ground at either the DTE or DCE or both in accordance with national regulations.

Signal ground may be further connected to protective ground in accordance with national safety regulations. Caution should be exercised to avoid establishment of ground loops carrying high currents.

2 The assignment of contact numbers for each segment has been aligned to specify pairing and connection to multipaired interconnecting cable. Each row of the table presents the respectively paired contacts, i.e. 2 and 20, 3 and 21, etc.

3 A, A', B, B', C and C' indicate the associated interchange points as designated in figure 2 of CCITT Recommendations V.10 and V.11. Where B/C is indicated in table 1, the B designation applies only when a V.11 generator is used and the C designation applies only when a V.10 generator is used (see annex B).

4 The receiver categories are as designated in V.10. Where category 1 receivers apply, either V.10 or V.11 generators may be used. Only V.11 generators may be used for circuits 103, 104, 113, 114, 115. Where category 2 receivers apply, V.10 generators are used.

Table 2 — Preferred assignment of contact numbers of circuits for national use

Contact number	Circuit number	Description
2	112	Data signalling rate selector (DCE source)
15	125	Calling indicator
33	110	Data signal quality detector
34	136	New signal
3/21	128	Receiver signal element timing (DCE source)