

STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Amendment No. 1
to
AS/NZS 4158:2003
Thermal-bonded polymeric coatings on valves and fittings for water industry purposes

CORRECTION

The 2003 edition of AS/NZS 4158 is amended as follows; the amendment(s) should be inserted in the appropriate place(s).

SUMMARY: This Amendment applies to Clauses 2.3.8, 2.3.10, 2.3.11, Tables 2.1, and Appendices B and C.

Published on 30 September 2005.

Approved for publication in New Zealand on behalf of the Standards Council of New Zealand on 23 September 2005.

AMDT
No. 1
SEP
2005

Page 7 Clause 2.3.8

Delete the first sentence and *replace* with the following:

The test shall be carried out either in accordance with AS/NZS 4352, using Test Cell A or B, at 23 ±2°C for 28 days, or in accordance with BS 3900, Part F11 at 23 ±2°C for 28 days.

AMDT
No. 1
SEP
2005

Page 7 Clause 2.3.10

Delete second sentence and *replace* with the following:

The coating preparation and test requirements shall be in accordance Clauses 2.3.9.1 and 2.3.9.2.

AMDT
No. 1
SEP
2005

Page 7 Clause 2.3.11 (b)

Delete first sentence and *replace* with the following:

The repair coating material shall be tested in accordance with Clause 2.3.3 for water absorption.

AMDT
No. 1
SEP
2005

Page 8 Table 2.1

Under 'Test' column for Cathodic disbondment, *amend* to read:

AS/NZS 4352 or BS 3900 Part F11.

AMDT
No. 1
SEP
2005

Page 16 Table B1

Under 'Test method' heading for Clause 2.3.8, *amend* to read:

AS/NZS 4352 or BS 3900 Part F11.

AMDT
No. 1
SEP
2005

Page 17 Appendix C

Add as follows:

BS 3900 Part F11: Methods of test for paint. Durability tests on paint films. Determination of resistance to cathodic disbonding of coatings for use on land-based buried structures

This page has been left intentionally blank.