

AS/NZS 4335:1997
ISO/IEC 13863:1995

AS/NZS 4335

Australian/New Zealand Standard[®]

**Information technology—
Telecommunications and
information exchange between
systems—Private integrated
services network—Specification,
functional model and information
flows—Path replacement additional
network feature**

STANDARDS AUSTRALIA

STANDARDS NEW ZEALAND



Documents

Document Sharing Hub

AS/NZS 4335:1997

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee IT/16, Private Telecommunications Networking. It was approved on behalf of the Council of Standards Australia on 28 January 1997 and on behalf of the Council of Standards New Zealand on 7 March 1997. It was published on 5 May 1997.

The following interests are represented on Committee IT/16:

Airline interests, New Zealand
AUSTEL
Australia Post
Australian Electrical and Electronic Manufacturers Association
Australian Telecommunications User Group
New Zealand Standards Committee SC605 WG1
N.S.W. Public Works and Services
Optus Communications, Australia
Telecom New Zealand
Telstra Corporation, Australia

Review of Standards. To keep abreast of progress in industry, Joint Australian/New Zealand Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Joint Standards and related publications will be found in the Standards Australia and Standards New Zealand Catalogue of Publications; this information is supplemented each month by the magazines 'The Australian Standard' and 'Standards New Zealand', which subscribing members receive, and which give details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Joint Standards, addressed to the head office of either Standards Australia or Standards New Zealand, are welcomed. Notification of any inaccuracy or ambiguity found in a Joint Australian/New Zealand Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 96484.

**Documents**

Document Sharing Hub

AS/NZS 4335:1997

Australian/New Zealand Standard[®]

**Information technology—
Telecommunications and
information exchange between
systems—Private integrated
services network—Specification,
functional model and information
flows—Path replacement additional
network feature**

Originated as AS/NZS 4335(Int):1995.
Second edition AS/NZS 4335:1997

PUBLISHED JOINTLY BY:

STANDARDS AUSTRALIA
1 The Crescent,
Homebush NSW 2140 Australia

STANDARDS NEW ZEALAND
Level 10, Standards House,
155 The Terrace,
Wellington 6001 New Zealand

ISBN 0 7337 1053 0



Documents

Document Sharing Hub

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee IT/16, Private Telecommunication Networking, to supersede AS/NZS 4335(Int):1995.

This Standard is identical with, and has been reproduced from, ISO/IEC 13863:1995, *Information technology—Telecommunications and information exchange between systems—Private Integrated Services Network—Specification, functional model and information flows—Path replacement additional network feature*.

The objective of this Standard is to provide private integrated services network (PISN) designers and users with the specification of the path replacement additional network feature in order to allow the connection of an established call between PISN exchanges to be replaced by a new connection worldwide.

The Standard is one of a series of emerging ISO/IEC Standards applicable to private integrated services networking. The series uses the ISDN concepts as developed by ITU-T and is also within the framework of Standards for Open Systems Interconnection (OSI) as defined by ISO/IEC JTC 1.

Users of this Standard are advised by Standards Australia and Standards New Zealand, under arrangements made with ISO and IEC, as well as certain other Standards organizations, that the number of this Standard is not reproduced on each page; its identity is shown only on the front cover, inside front cover and title pages.

The term 'informative' has been used in this Standard to define the application of the annex to which it applies. An 'informative' annex is only for information and guidance.

For the purpose of this Joint Standard, the ISO/IEC text should be modified as follows:

- (a) *Terminology* The words 'this Australian/New Zealand Standard' should replace the words 'this International Standard' wherever they appear.
- (b) *References* The references to international Standards should be replaced by references, where appropriate, to the following Australian/New Zealand Standards:

<i>Reference to International Standard or other Publication</i>		<i>Australian/New Zealand Standard</i>	
ISO/IEC		AS/NZS	
11571	Information technology— Telecommunications and information exchange between systems— Numbering and subaddressing in private integrated services networks	4134	Information technology— Telecommunications and information exchange between systems— Numbering and sub-addressing in private integrated services networks
11574	Information technology— Telecommunications and information exchange between systems— Private Integrated Services Network—Circuit mode 64 kbit/s bearer services—Service description, functional capabilities and information flows	4135	Information technology— Telecommunications and information exchange between systems— Private integrated services network— Circuit-mode 64 kbit/s bearer services—Service description, functional capabilities and information flows
11579	Information technology— Telecommunications and information exchange between systems— Private Integrated Services Network	4136	Information technology— Telecommunications and information exchange between systems— Private integrated services network
11579-1	Part 1: Reference configuration for PISN exchanges (PINX)	4136.1	Part 1: Reference configuration for PISN exchanges (PINX)

CCITT

Rec.I.112	Vocabulary of terms for ISDNs (Blue Book)	—
Rec.I.130	Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN (Blue Book)	—
Rec.I.210	Principles of telecommunication services supported by an ISDN and the means to describe them (Blue Book)	—
Rec.Z.100	Specification and Description Language (Blue Book)	—

© Copyright – STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Users of Standards are reminded that copyright subsists in all Standards Australia and Standards New Zealand publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia or Standards New Zealand may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia or Standards New Zealand. Permission may be conditional on an appropriate royalty payment. Australian requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia. New Zealand requests should be directed to Standards New Zealand.

Up to 10 percent of the technical content pages of a Standard may be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia or Standards New Zealand.

Inclusion of copyright material in computer software programs is also permitted without royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia or Standards New Zealand at any time.

CONTENTS

Page

1 Scope 1

2 Conformance 1

3 Normative references 1

4 Definitions 2

 4.1 External definitions 2

 4.2 Other definitions 2

5 List of acronyms 3

6 ANF-PR stage 1 specification 3

 6.1 Description 3

 6.2 Procedure 3

 6.3 Interaction with other supplementary services and ANFs 4

 6.4 Interworking considerations 5

 6.5 Overall SDL 6

7 ANF-PR stage 2 specification - basic operation 6

 7.1 Functional model 6

 7.2 Information flows 7

 7.3 Functional entity actions 11

 7.4 Functional entity behaviour 12

 7.5 Allocation of functional entities to physical equipment 14

 7.6 Interworking considerations 15

8 ANF-PR stage 2 specification - re-use of connection elements 15

 8.1 Functional model 15

 8.2 Information flows 16

 8.3 Functional entity actions 20

 8.4 Functional entity behaviour 21

 8.5 Allocation of functional entities to physical equipment 23

 8.6 Interworking considerations 24

Annex A - Circumstances in which ANF-PR might be invoked 25

Annex B - Avoidance of unacceptable disruption to user information 27

AUSTRALIAN/NEW ZEALAND STANDARD

Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Specification, functional model and information flows - Path replacement additional network feature

1 Scope

This International Standard specifies the Path Replacement additional network feature (ANF-PR), which is applicable to various basic services supported by Private Integrated Services Networks (PISN). Basic services are specified in ISO/IEC 11574.

ANF-PR is a feature which applies to an established call, allowing that call's connection between Private Integrated Services Network Exchanges (PINXs) to be replaced by a new connection. If the new connection is required to satisfy certain criteria, ANF-PR should be used in conjunction with other supplementary services and/or ANFs. Annex A gives examples of the circumstances under which ANF-PR can be used and criteria which can govern the selection of the new connection.

Additional network feature specifications are produced in three stages, according to the method described in CCITT Recommendation I.130 for supplementary services. This International Standard contains the stage 1 and stage 2 specifications of ANF-PR. The stage 1 specification (clause 6) specifies the feature as seen by an entity which initiates path replacement, the ANF-PR user. The stage 2 specification (clauses 7 and 8) identifies the functional entities involved in the feature and the information flows between them. Clause 7 contains the stage 2 specification for basic operation of the feature. Clause 8 contains the stage 2 specification for an enhanced mode of working which can be employed when supported by all the equipment involved. It allows some of the elements of the old connection to be re-used.

2 Conformance

In order to conform to this International Standard, a stage 3 International Standard shall specify signalling protocols and equipment behaviour that are capable of being used in a PISN which supports the feature specified in this International Standard. This means that, to claim conformance, a Stage 3 International Standard is required to be adequate for the support of those aspects of clause 6 (stage 1) and clauses 7 and 8 (stage 2) which are relevant to the interface or equipment to which the Stage 3 International Standard applies.

3 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO/IEC 11571:1994, *Information technology - Telecommunications and information exchange between systems - Numbering and sub-addressing in private integrated services networks*.

ISO/IEC 11574:1994, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Circuit-mode 64 kbit/s bearer services - Service description, functional capabilities and information flows*.

ISO/IEC 11579-1:1994, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Part 1: Reference configuration for PISN exchanges (PINX)*.

CCITT Rec. I.112(1988), *Vocabulary of terms for ISDNs (Blue Book)*.

CCITT Rec. I.130(1988), *Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN (Blue Book)*.

CCITT Rec. I.210(1988), *Principles of telecommunication services supported by an ISDN and the means to describe them (Blue Book)*.

CCITT Rec. Z.100(1988), *Specification and Description Language (Blue Book)*.

4 Definitions

For the purposes of this International Standard, the following definitions apply.

4.1 External definitions

This International Standard uses the following terms defined in other documents:

- Basic service (CCITT Rec. I.210)
- Private Integrated Services Network (PISN) (ISO/IEC 11579-1)
- Private Integrated Services Network Exchange (PINX) (ISO/IEC 11579-1)
- Service (CCITT Rec. I.112)
- Signalling (CCITT Rec. I.112)
- Supplementary Service (CCITT Rec. I.210)
- User (except in the context of ANF-PR user) (ISO/IEC 11574)

This International Standard refers to the following basic call functional entities (FEs) defined in ISO/IEC 11574:

- Call Control (CC)
- Call Control Agent (CCA)

This International Standard refers to the following basic call inter-FE relationships defined in ISO/IEC 11574:

- r1
- r2
- r3

This International Standard refers to the following basic call information flows defined in ISO/IEC 11574:

- Channel_Acknowledge request/indication
- Release request/indication
- Release response/confirmation
- Setup request/indication
- Setup response/confirmation.

This International Standard refers to the following basic call information flow service element defined in ISO/IEC 11574:

- Destination Number.

4.2 Other definitions

4.2.1 additional network feature (ANF): A capability, over and above that of a basic service, provided by a PISN, but not directly to a PISN user

4.2.2 ANF-PR user: An entity, within a PISN, that requests ANF-PR.

4.2.3 call, basic call: An instance of the use of a basic service.

4.2.4 connection: As defined in CCITT Rec. I.112, but limited to the case of providing for the transfer of signals between two PINXs.

NOTE 1 — A connection between two PINXs can pass through zero or more Transit PINXs.

4.2.5 new connection: The connection established by ANF-PR and used to replace all or part of the old connection.

4.2.6 old connection: The connection existing before ANF-PR is invoked.

4.2.7 trombone connection: A connection which has both its ends in the same PINX but which involves at least one Transit PINX.

5 List of acronyms

ANF	additional network feature
ANF-PR	ANF Path Replacement
CC	Call Control (functional entity)
CCA	Call Control Agent (functional entity)
CID	Call Identity (information flow service element)
FE	Functional Entity
ISDN	Integrated Services Digital Network
PINX	Private Integrated Services Network Exchange
PISN	Private Integrated Services Network
PRE	Path Replacement Error (information flow)
PRP	Path Replacement Propose (information flow)
PRR	Path Replacement Re-use (information flow)
PRRR	PRR Result (information flow service element)
PRS	Path Replacement Setup (information flow)
PRSR	PRS Result (information flow service element)
RN	Rerouting Number (information flow service element)
SDL	Specification and Description Language

6 ANF-PR stage 1 specification

6.1 Description

6.1.1 General description

ANF-PR is invoked by an ANF-PR user for an established call, allowing that call's connection through the PISN to be replaced by a new connection. If the new connection is required to satisfy certain criteria, ANF-PR should be used in conjunction with other supplementary services and/or ANFs. Annex A gives examples of the circumstances under which ANF-PR can be used and criteria which can govern the selection of the new connection.

6.1.2 Qualifications On Applicability To Telecommunication Services

This additional network feature is applicable to all basic services defined in ISO/IEC 11574.

NOTE 2 — For certain teleservices or certain applications of certain basic bearer services the changeover from the old connection to the new connection can cause unacceptable disruption. See annex B.

6.2 Procedure

6.2.1 Provision/withdrawal

This ANF shall be PISN instigated.

NOTE 3 — Means can be provided for preventing the use of ANF-PR for applications where the changeover from the old connection to the new connection is likely to cause unacceptable disruption. See annex B.

6.2.2 Normal procedures

6.2.2.1 Activation/deactivation/registration/interrogation

The feature shall be permanently activated.

6.2.2.2 Invocation and operation

Invocation shall be on request from an ANF-PR user and shall be permitted only after a call has reached the active state.

On invocation an attempt shall be made to establish a new connection between the Originating PINX and the Terminating PINX. In the absence of specific criteria, the new connection shall be established using the routing rules which apply to basic call establishment. If the new connection is successfully established it shall be used to replace the old connection, which shall be released.

Changeover from the old connection to the new connection should be done in a manner which minimises disruption to user information.

NOTE 4 — The means of specifying criteria and ensuring that the new connection satisfies those criteria can involve the use of another ANF or supplementary service, which can be either standardised or manufacturer specific.

In some circumstances it may be possible to re-use some elements of the old connection, so that only part of the old connection has to be replaced by a new connection, subject to the given criteria being achievable in that way.

6.2.3 Exceptional procedures

6.2.3.1 Activation/deactivation/registration/interrogation

Not applicable.

6.2.3.2 Invocation and operation

If it is not possible to establish a new connection, the call shall continue to use the old connection and any resources reserved for the new connection shall be released. There shall be no disruption to user information.

In the event of two ANF-users (at opposite ends of the connection) requesting the feature simultaneously, both requests shall be rejected.

NOTE 5 — An ANF-PR user can request the feature again later in the event of failure. In the case of failure due to simultaneous requests, care should be taken to avoid a repeat occurrence, e.g., by use of a random delay.

6.3 Interaction with other supplementary services and ANFs

Interactions with other supplementary services and ANFs for which PISN International Standards were available at the time of publication of this International Standard are specified below.

6.3.1 Calling Line Identification Presentation (SS-CLIP)

No interaction.

6.3.2 Connected Line Identification Presentation (SS-COLP)

No interaction.

6.3.3 Calling/connected Line Identification Restriction (SS-CLIR)

No interaction.

6.3.4 Calling Name Identification Presentation (SS-CNIP)

No interaction.

6.3.5 Connected Name Identification Presentation (SS-CONP)

No interaction.

6.3.6 Calling/connected Name Identification Restriction (SS-CNIR)

6.3.7 Completion of Calls to Busy Subscriber (SS-CCBS)

No interaction

6.3.8 Completion of Calls on No Reply (SS-CCNR)

No interaction

6.3.9 Call Transfer (SS-CT)

If call transfer occurs while ANF-PR is in progress, ANF-PR shall be aborted.

ANF-PR can apply to a call which has been transferred. The fact that transfer has occurred can be a reason for invoking ANF-PR (see annex A).

6.3.10 Call Forwarding Unconditional (SS-CFU)

ANF-PR can apply to a call which has been forwarded.

6.3.11 Call Forwarding Busy (SS-CFB)

ANF-PR can apply to a call which has been forwarded.

6.3.12 Call Forwarding No Reply (SS-CFNR)

ANF-PR can apply to a call which has been forwarded.

6.3.13 Call Deflection (SS-CD)

ANF-PR can apply to a call which has been deflected.

6.4 Interworking considerations

The requirements below apply to both incoming calls and outgoing calls.

It shall be possible to use ANF-PR on the PISN part of the connection. The new connection through the PISN shall replace the old connection through the PISN.

When interworking with another network which supports an equivalent feature, it may be possible to cooperate with the other network in order to replace the entire connection.