

AS/NZS 4449:1997

ISO 12083:1994

Australian/New Zealand Standard[®]

**Information and documentation—
Electronic manuscript preparation
and markup**

STANDARDS AUSTRALIA



STANDARDS NEW ZEALAND



Documents

Document Sharing Hub

AS/NZS 4449:1997

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee IT/19, Computer Applications in Information and Documentation. It was approved on behalf of the Council of Standards Australia on 19 November 1996 and on behalf of the Council of Standards New Zealand on 9 November 1996. It was published on 5 March 1997.

The following interests are represented on Committee IT/19:

Australian Publishers Association
 Australian Council of Libraries and Information Services
 Australian Information Industry Association
 Australia Library and Information Association
 Australian Z39 Implementors
 Council of Australian State Libraries
 Council of Australian University Librarians
 CSIRO, Information Service, Australia
 National Library of Australia
 National Library of New Zealand
 National University Librarians Association, New Zealand
 New Zealand Library and Information Association
 Tertiary Library Networks, Australia
 Vendor interests, New Zealand
 Victorian Association for Library Automation, Australia
 Victoria University, New Zealand

Review of Standards. To keep abreast of progress in industry, Joint Australian/New Zealand Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Joint Standards and related publications will be found in the Standards Australia and Standards New Zealand Catalogue of Publications; this information is supplemented each month by the magazines 'The Australian Standard' and 'Standards New Zealand', which subscribing members receive, and which give details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Joint Standards, addressed to the head office of either Standards Australia or Standards New Zealand, are welcomed. Notification of any inaccuracy or ambiguity found in a Joint Australian/New Zealand Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

AS/NZS 4449:1997

Australian/New Zealand Standard[®]

**Information and documentation—
Electronic manuscript preparation
and markup**

First published as AS/NZS 4449:1997.

PUBLISHED JOINTLY BY:

STANDARDS AUSTRALIA
1 The Crescent,
Homebush NSW 2140 Australia

STANDARDS NEW ZEALAND
Level 10, Standards House,
155 The Terrace,
Wellington 6001 New Zealand

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee IT/19, Computer Applications in Information and Documentation.

This Standard is identical with, and has been reproduced from, ISO 12083:1994, *Information and documentation—Electronic manuscript preparation and markup*.

The objective of this Standard is to provide authors, publishers and the library community with a set of four document architectures in order to create and interchange books, articles and serial publications.

Users of this Standard are advised by Standards Australia and Standards New Zealand, under arrangements made with ISO and IEC, as well as certain other Standards organizations, that the number of this Standard is not reproduced on each page; its identity is shown only on the cover, inside front cover and title pages.

The term 'informative' has been used in this Standard to define the application of the annexes to which it applies. An 'informative' annex is only for information and guidance.

For the purpose of this Joint Standard, the ISO/IEC text should be modified as follows:

- (i) *Terminology* The words 'this Australian/New Zealand Standard' should replace the words 'this International Standard' wherever they appear.
- (ii) *References* The references to international Standards should be replaced by references, where appropriate, to the following Australian/New Zealand Standards:

*Reference to International Standard
or other Publication*

Australian/New Zealand Standard

ISO

3166 Codes for the representation of names of countries —

5127 Documentation and information—
Vocabulary

5127-2 Part 2: Traditional documents —

AS/NZS

8601 Data elements and interchange formats—Information interchange—
Representation of dates and times

AS

8879 Information processing—
Text and office systems—
Standard Generalized Markup
Language (SGML)

3514

Information processing—
Text and office systems—
Standard generalized markup
language (SGML)

ISO/IEC

9070 Information technology—
SGML support facilities—
Registration procedures for public
text owner identifiers

AS/NZS

4097 Information processing—
SGML support facilities—
Registration procedures for public
text owner identifiers

TR 9573 Techniques for applying SGML

AS

3967 Information processing—
SGML support facilities—
Techniques for using SGML

3967.1 Part 1: SGML Tutorial



Documents

Document Sharing Hub

iii

ISO/IEC

10744 Information Technology—
Hypermedia/Time based Structuring
Language (HyTime)

AS/NZS

4148 Information technology—
Hypermedia/Time-based structuring
language(HyTime)

© Copyright – STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Users of Standards are reminded that copyright subsists in all Standards Australia and Standards New Zealand publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia or Standards New Zealand may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia or Standards New Zealand. Permission may be conditional on an appropriate royalty payment. Australian requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia. New Zealand requests should be directed to Standards New Zealand.

Up to 10 percent of the technical content pages of a Standard may be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia or Standards New Zealand.

Inclusion of copyright material in computer software programs is also permitted without royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia or Standards New Zealand at any time.

CONTENTS

	<i>Page</i>
1 Scope	1
2 Normative references	1
3 Definitions	2
4 Conformance	2
5 SGML declaration	3
6 The Book DTD	3
7 The Article DTD	19
8 The Serial DTD	34
9 The Mathematics DTD	38
 ANNEXES	
A Comments on the DTDs	45
B Description of the Elements	99
C Examples	173

AUSTRALIAN/NEW ZEALAND STANDARD

Information and documentation — Electronic manuscript preparation and markup

1 Scope

This International Standard presents four document type definitions and additional facilities conforming to ISO 8879. This International Standard is intended to provide document architectures for the creation and interchange of books, articles and serial publications.

It specifies:

- a) the SGML declaration defining the syntax used by the document type definitions and document instances;
- b) the document type definitions for the following document classes:
 - i) Books;
 - ii) Articles;
 - iii) Serials, which are collections of articles;
- c) a document type definition for Mathematics which may be embedded in other SGML applications.

This International Standard provides a toolkit for developers of these types of publications to use as a basis for developing custom applications. The applications developed may be for authors, publishers, libraries, their users, and/or their database vendors. The document type definitions included in this International Standard have been designed to be flexible enough to expand or limit markup depending on the use of the application. For example, if the application is intended for authors, the copyright information could be removed. The markup is sufficiently general to enable its use for similarly structured documents, e.g. the Book DTD can also be used for technical reports.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent

editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 8879:1986, *Information processing - Text and office systems - Standard Generalized Markup Language (SGML)*.

ISO/IEC TR 9573:1988, *Techniques for applying SGML*.

ISO/IEC 10744:1992, *Information Technology - Hypermedia/Time based Structuring Language (HyTime)*.

ISO 8601:1988, *Data elements and interchange formats - Information interchange - Representation of dates and times*.

ISO 5127-2:1983, *Documentation and information - Vocabulary - Part 2: Traditional documents*.

ISO/IEC 9070:1991, *Information technology - SGML support facilities - Registration procedures for public text owner identifiers*.

ISO 3166:1994, *Codes for the representation of names of countries*.

3 Definitions

For the purposes of this International Standard, the definitions given in ISO 8879, ISO/IEC TR 9573 and ISO 5127/2 apply.

4 Conformance

The intent of this International Standard is to provide a base set of elements to support the production and delivery cycle of a publication. Elements (e.g. table), or references to (e.g. mathematics) entity sets may be removed or modified as necessary for a specific application. The application should satisfy the following conditions to comply with this International Standard. It should:

- a) use the reference concrete syntax;
- b) declare user-defined elements in external parameter entities;
- c) identify use of this International Standard as a base by using the appropriate public identifier;
- d) override parameter entities defined in this International Standard to specify different order and occurrence or to specify user-defined elements or attributes;

- e) not allow user-defined elements to specify an alias of an element already defined in this International Standard;
- f) follow consistent naming conventions found in the document type definitions of this International Standard when creating new elements or attributes;
- g) conform to ISO 8879.

If the application is developed for interchange purposes, it is recommended that the DTD be registered following ISO/IEC 9070.

5 SGML declaration

The document type definitions in this International Standard use the reference concrete syntax.

The document type definitions in this International Standard are intended for use with basic SGML documents. These documents should use the SGML declaration in ISO 8879:1986, figure 8, subclause 15.1.1. Note that OMITTAG and SHORTTAG are allowable minimization features.

Use of the SGML Document Access or HyTime facilities may necessitate a change of the APPINFO parameter in the SGML declaration, replacing the keyword NONE by SDA or HYTIME or both (see Annex A Clauses 8.5 and 9.1):

APPINFO "SDA HYTIME"

6 The Book DTD

```
<!-- This is the ISO12083:1994 document type definition for Books.      -->
<!-- Copyright: (C) International Organization for Standardization 1994.
Permission to copy in any form is granted for use with conforming SGML
systems and applications as defined in ISO 8879:1986, provided this notice
is included in all copies.                                             -->

<!-- ===== -->
<!-- PUBLIC DOCUMENT TYPE DEFINITION SUBSET -->
<!-- ===== -->

<!-- Typical invocation:
<?HyTime VERSION "ISO/IEC 10744:1992" HQCNT=32                      >
<?HyTime MODULE base                                                >
<?HyTime MODULE locs multloc anydtd mixspace                        >
<?HyTime MODULE links                                              >
```

```

<!DOCTYPE book PUBLIC "ISO 12083:1994//DTD Book//EN"
[<!ENTITY % ISOnum PUBLIC "ISO 8879:1986//ENTITIES Numeric and
    Special Graphic//EN"
    <!ENTITY % ISOpub PUBLIC "ISO 8879:1986//ENTITIES
    Publishing//EN"
    <!ENTITY % ISOtech PUBLIC "ISO 8879:1986//ENTITIES
    General Technical//EN"
    <!ENTITY % ISodia PUBLIC "ISO 8879:1986//ENTITIES
    Diacritical Marks//EN"
    <!ENTITY % ISolat1 PUBLIC "ISO 8879:1986//ENTITIES
    Added Latin 1//EN"
    <!ENTITY % ISolat2 PUBLIC "ISO 8879:1986//ENTITIES
    Added Latin 2//EN"
    <!ENTITY % ISOamso PUBLIC "ISO 8879:1986//ENTITIES
    Added Math Symbols: Ordinary//EN"
    <!ENTITY % ISOgrk1 PUBLIC "ISO 8879:1986//ENTITIES
    Greek Letters//EN"
    <!ENTITY % ISOgrk3 PUBLIC "ISO 8879:1986//ENTITIES
    Greek Symbols//EN"
    %ISOnum;
    %ISOpub;
    %ISOtech;
    %ISodia;
    %ISolat1;
    %ISolat2;
    %ISOamso;
    %ISOgrk1;
    %ISOgrk3;
    <!ENTITY % ereview PUBLIC "-//USA-DOD//DTD
    SUP MIL-M-28001 EREVIEW REV B//EN"
    %ereview;
]>
-->

<!-- NOTES: 1. ISO/IEC TR 9573 Parts 12-16 are currently under review and will
    contain complete special character entity sets.
    2. MIL-M-28001 EREVIEW are the CALS facilities for electronic
    review.
-->

<!-- ===== -->
<!-- Entity Naming Conventions -->
<!-- ===== -->

<!-- Prefix = where used:
    p. = in paragraphs (also in phrases if .ph suffix)
    s. = in sections (i.e., among paragraphs)
    i. = where allowed by inclusion exceptions
    m. = content model or declared content
    a. = attribute definition
    NONE= specific use defined in models

```

```

Suffix = allowed content:
.ph = elements whose content is %m.ph;
.d = elements whose content has same model as defaults
.zz = for subelements
NONE= individually defined elements
-->

<!ENTITY % doctype "book" -- default document type generic identifier -->

<!-- ++++++ Specialized Elements ++++++ -->
<!-- Specialized Elements -->
<!-- ++++++ -->

<!ENTITY % ade.ph "street|city|state|country|postcode|san|email|postbox|
phone|fax" -- address elements -->
<!ENTITY % bib "author|corpauth|msn|sertitle|location|date|pages|subject|
othinfo" -- bibliographic, date is the publication date-->

<!-- The following 5 declarations are specific to Books -->
<!ENTITY % bmsec.d "afterwrdr|notes|vita" -- back matter sections -->
<!ENTITY % bmsec.i "glossary|index" -- indexes and glossary -->
<!ENTITY % fmsec.d "foreword|intro|preface|ack|ded|abstract|supmatl"
-- front matter sections -->
<!ENTITY % pub "sponsor|contract|reprint|cpyrt|date|pubname|location|
confgrp|avail" -- pubfront, date is publication date -->
<!ENTITY % pub.ph "coden|acqno|isbn|lccardno|reportid|edition|volid|catalog|
acidfree|price|extent|package|pubid"
-- publication related front matter material -->

<!-- ===== Basic Document Elements ===== -->
<!-- Basic Document Elements -->
<!-- ===== -->

<!ENTITY % i.float "figgrp|footnote|note" -- floating elements -->
<!ENTITY % p.el "deflist|orgaddr|indaddr|artwork|bq|lit|date|biblist|
author|corpauth|keyword|keyphras|poem|nameloc|indxflag"
-- general -->
<!ENTITY % p.em.ph "emph" -- emphasis -->
<!ENTITY % p.lst.d "list" -- list -->

<!-- The following declaration is specific to Books -->
<!ENTITY % p.rf.ph "noteref|fnoteref|figref|tableref|artref|appref|citeref|
secref|formref|glosref|indexref" -- references -->

<!ENTITY % p.tbl "table" -- table matter -->
<!ENTITY % p.form "formula|dformula|dformgrp" -- mathematical formulas -->
<!ENTITY % p.zz "({p.el;})|({p.tbl;})|({p.lst.d;})|({p.form;})" -- paragraph
subelements -->
<!ENTITY % p.zz.ph "q|pages|({p.em.ph;})|({p.rf.ph;})" -- phrases -->
<!ENTITY % s.zz "p|({p.zz;})" -- section subelements -->

```

```

<!-- ++++++ -->
<!--      Models      -->
<!-- ++++++ -->

<!ENTITY % m.addr    "(%ade.ph;)*" -- address (no name)      -->
<!ENTITY % m.bib     "(no?, title, (%bib;))*" -- bibliographic entry -->
<!ENTITY % m.copy     "(date|cpyrtm|cpyrtclr)+*" -- copyright notice data -->
<!ENTITY % m.date     "(#PCDATA)" -- date -->
<!ENTITY % m.fig      "EMPTY" -- default FIG content -->
<!ENTITY % m.sec      "(title?, (%s.zz;)*, section*)" -- section -->
<!ENTITY % m.name     "((fname? & surname), (degree|school)*, role*, (%ade.ph;)*, aff?)" -- name components -->
<!ENTITY % m.org      "(orgname, orgdiv*, %m.addr;)" -- organization name -->
<!ENTITY % m.ph       "(#PCDATA|(%p.zz.ph;)|(%p.form;))*" -- phrase model -->
<!ENTITY % m.pseq     "(p, (p|(%p.zz;))*" -- P with sequence -->
<!ENTITY % m.poem     "(stanza+|poemline+)" -- poetry sub-elements -->

<!-- ++++++ -->
<!--      Attribute Definitions      -->
<!-- ++++++ -->

<!ENTITY % a.id       "id ID #IMPLIED" -- ID attribute definition -->
<!ENTITY % a.rid       "rid IDREF #REQUIRED" -- IDREF attribute definition -->
<!ENTITY % au.rid      "rids IDREFS #IMPLIED" -- to refer to a unique id of an affiliation -->

<!ENTITY % a.sizes     "sizex NUTOKEN #IMPLIED
                        sizey NUTOKEN #IMPLIED
                        unit CDATA #IMPLIED"
-- unit must be specified if sizex or sizey are. -->
<!ENTITY % a.types     "(latin|greek|cyrillic|hebrew|kanji) latin"
-- Indicates which alphabet is used in the element
-- (title, p, q). This may be changed to a notation
-- attribute, where the notation could describe a keyboard
-- mapping. Modify the set as necessary. -->
<!ENTITY % d.types     "(1|2|3|4|5) #IMPLIED"
-- Suggestions for date types:
-- 1=ISO 8601:1988, 2=mm-dd-yy, 3=mm/dd/yy, 4=dd-mm-yy,
-- 5=month day year; if more needed (e.g. day month year)
-- modify or extend this list as necessary. -->
<!ENTITY % e.types     "(1|2|3|4|5|6) #IMPLIED"
-- Suggestions for emphasis types:
-- 1=bold, 2=italic, 3=bold italic, 4=underline,
-- 5=non proportional, 6=smallcaps; if more needed
-- modify or extend this list as necessary. -->
<!ENTITY % l.types     "(1|2|3|4|5|6) #IMPLIED"
-- Suggestions for list types:
-- 1=arabic, 2=uppercase alpha, 3=roman, 4=bullet, 5=dash,
-- 6=unlabelled; if more needed (e.g. lower alpha)
-- modify or extend this list as necessary. -->

<!-- The following 2 declarations are specific to Books -->

<!ENTITY % m.idx       "({%m.sec;|((indxname|indxsubj)*,pages*)})"
-- model for indexes and glossary -->

```

```

<!ENTITY % m.toc      "EMPTY" -- table of contents; automatic generation
                           assumed, add a specific content model if required      -->

<!-- ++++++ Accessible Document Parameter Entities ++++++ -->
<!-- ++++++ Accessible Document Parameter Entities ++++++ -->

<!ENTITY % SDAFORM    "SDAFORM    CDATA    #FIXED"      >
<!ENTITY % SDARULE    "SDARULE    CDATA    #FIXED"      >
<!ENTITY % SDAPREF    "SDAPREF    CDATA    #FIXED"      >
<!ENTITY % SDASUFF    "SDASUFF    CDATA    #FIXED"      >
<!ENTITY % SDASUSP    "SDASUSP    NAME     #FIXED"      >

<!-- ===== -->
<!-- DATA CONTENT NOTATIONS -->
<!-- ===== -->

<!-- These are examples. Add other public notations as required. -->

<!NOTATION eps        PUBLIC
"*/ISBN 0-201-18127-4::Adobe//NOTATION Postscript Language Reference
Manual//EN"
<!NOTATION tex        PUBLIC
"*/ISBN 0-201-13448-9::Knuth//NOTATION The TeXbook//EN"
<!NOTATION cgmchar    PUBLIC      "ISO 8632/2//NOTATION Character encoding//EN" >
<!NOTATION cgmclear   PUBLIC      "ISO 8632/4//NOTATION Clear text encoding//EN" >
<!NOTATION tiff       PUBLIC      "ISO 12083:1993//NOTATION TIFF-1//EN" >

<!-- ===== -->
<!-- THE DOCUMENT STRUCTURE -->
<!-- ===== -->

<!-- ELEMENT          MIN CONTENT          (EXCEPTIONS) -->
<!ELEMENT (%doctype;) - - (front, body, appmat?, back?)
                           +(%i.float;) >

<!-- ===== -->
<!-- FRONT MATTER ELEMENTS -->
<!-- ===== -->

<!-- The following 2 declarations are specific to Books -->
<!ELEMENT front        O O (titlegrp, authgrp, date?, pubfront?,
                           (%fmsec.d;)*, toc?) >
<!ELEMENT (%fmsec.d;) - O %m.sec; >

<!-- ++++++ Title Group ++++++ -->
<!-- ++++++ Title Group ++++++ -->
<!-- ++++++ Title Group ++++++ -->

<!ELEMENT titlegrp     O O (msn?, sertitle?, no?, title, subtitle?) >

```

```

<!ELEMENT (title|subtitle)      - O  %m.ph;                                >

<!-- ++++++----->
<!--   Author Group                -->
<!-- ++++++----->

<!ELEMENT authgrp              O O  (author|corpauth|aff)*                >
<!ELEMENT author                - O  %m.name;                            >
<!ELEMENT (fname|surname|role|degree|orgname|orgdiv)
                                     - O  (#PCDATA)                        >
<!ELEMENT (aff|corpauth|school)
                                     - O  %m.org;                          >
<!ELEMENT (%ade.ph;)            - O  (#PCDATA)                            >

<!-- ++++++----->
<!--   Publisher's Front Matter    -->
<!-- ++++++----->

<!ELEMENT pubfront              - O  ((%pub;)|(%pub.ph;))*                >
<!ELEMENT (%pub.ph;|contract)   - O  (#PCDATA)                            >
<!ELEMENT (pubname|avail|sponsor)
                                     - O  %m.org;                          >
<!ELEMENT reprint               - O  (%m.org;|%m.name;)                    >

<!-- ++++++----->
<!--   Copyright                    -->
<!-- ++++++----->

<!ELEMENT cpyrt                 - -  %m.copy;                            >
<!ELEMENT cpyrtclr              - -  %m.org;                             >
<!ELEMENT cpyrtname             - -  (%m.org;|%m.name;)                    >

<!-- ++++++----->
<!--   Conference Group            -->
<!-- ++++++----->

<!ELEMENT confgrp               - -  (no?, confname, date?, location?,
                                     sponsor?)                              >
<!ELEMENT confname              - O  (#PCDATA)                            >

<!-- ++++++----->
<!--   Date                        -->
<!-- ++++++----->

<!ELEMENT date                  - O  %m.date;                            >

```

```

<!-- ***** -->
<!-- Table of Contents -->
<!-- ***** -->

<!ELEMENT toc - O %m.toc; >

<!-- ===== -->
<!-- BODY ELEMENTS -->
<!-- ===== -->

<!-- ***** -->
<!-- Body Structure -->
<!-- ***** -->

<!ELEMENT body O O (part+|chapter+) >
<!ELEMENT part - O (no?, title?, (%s.zz;)*, chapter+) >
<!ELEMENT chapter - O (no?, %m.sec;) >
<!ELEMENT section - O (no?, title?, (%s.zz;)*, subsect1*) >
<!ELEMENT subsect1 - O (no?, title?, (%s.zz;)*, subsect2*) >
<!ELEMENT subsect2 - O (no?, title?, (%s.zz;)*, subsect3*) >
<!ELEMENT subsect3 - O (no?, title?, (%s.zz;)*, subsect4*) >
<!ELEMENT subsect4 - O (no?, title?, (%s.zz;)*, subsect5*) >
<!ELEMENT subsect5 - O (no?, title?, (%s.zz;)*, subsect6*) >
<!ELEMENT subsect6 - O (no?, title?, (%s.zz;)* >
<!ELEMENT no - O (#PCDATA) >

<!-- ***** -->
<!-- Section Subelements -->
<!-- ***** -->

<!ELEMENT p - O (#PCDATA|(%p.zz.ph;)|(%p.zz;))* >

<!-- ***** -->
<!-- Paragraph Subelements -->
<!-- ***** -->

<!ELEMENT bq - - %m.pseq; >
<!ELEMENT indaddr - O %m.name; -- individual address -->
<!ELEMENT orgaddr - O %m.org; -- organization address -->
<!ELEMENT artwork - O EMPTY >

<!ELEMENT lit - - RCDATA >

<!ELEMENT (%p.lst.d;) - - (head?, item)* >
<!ELEMENT item - O %m.pseq; >

<!ELEMENT deflist - - ((head, ddhd)?, term, dd)* >
<!ELEMENT (term|head|ddhd) - O %m.ph; >
<!ELEMENT dd - O %m.pseq; >

<!ELEMENT biblist - O (head?, citation)* >
<!ELEMENT citation - O %m.bib; >

```

```

<!ELEMENT (othinfo|subject|sertitle)
      - O %m.ph; >

<!ELEMENT location - O %m.addr; >
<!ELEMENT (msn|pages) - O (#PCDATA) >
<!ELEMENT keyword - O (#PCDATA) >
<!ELEMENT keyphras - O (#PCDATA) >
<!ELEMENT indxflag - O EMPTY >

<!-- ++++++ -->
<!-- Poetry -->
<!-- ++++++ -->

<!ELEMENT poem - O %m.poem; >
<!ELEMENT stanza - O (poemline)+ >
<!ELEMENT poemline - O (#PCDATA|cline|&p.em.ph;)* >
<!ELEMENT cline - O (#PCDATA|&p.em.ph;)* >

<!-- ++++++ -->
<!-- Phrases -->
<!-- ++++++ -->

<!ELEMENT q - - %m.ph; >
<!ELEMENT (&p.em.ph;) - - %m.ph; >
<!ELEMENT (&p.rf.ph;) - - (#PCDATA) >

<!-- ++++++ -->
<!-- For HyTime Links -->
<!-- ++++++ -->

<!ELEMENT nameloc - O (nmlist*) -- assigns a local ID to
      named objects -->
<!ELEMENT nmlist - O (#PCDATA) -- list of local ID or entity
      names -->

<!-- ++++++ -->
<!-- Floating Elements -->
<!-- ++++++ -->

<!ELEMENT figgrp - - (title? & fig*) >
<!ELEMENT fig - O %m.fig; >
<!ELEMENT footnote - - (no?, %m.pseq;) -(%i.float;) >
<!ELEMENT note - - (no?, %m.pseq;) >

<!-- ++++++ -->
<!-- Tables -->
<!-- ++++++ -->

<!ELEMENT table - - (no?, title?, tbody) -(%i.float;) >
<!ELEMENT tbody - O (head*, tsubhead*, row*) >

```

```

<!ELEMENT row                - O (tstub?, cell*)
<!ELEMENT tsubhead           - O %m.ph;
<!ELEMENT (tstub|cell)       - O %m.pseq;

<!-- *****
<!--   Mathematics
<!-- *****

<!ENTITY % maths PUBLIC "ISO 12083:1994//DTD Mathematics//EN"
%maths;

<!-- Remove these comments if the formula's follow a NOTATION rather than
      SGML.
<!ELEMENT dformgrp           - O (dformula)+
<!ELEMENT (formula|dformula) - - CDATA
-->

<!-- =====
<!--   APPENDIX ELEMENTS
<!-- =====

<!ELEMENT appmat             - O (appendix+)
<!ELEMENT appendix           - O (no?, %m.sec;

<!-- =====
<!--   BACK MATTER ELEMENTS
<!-- =====

<!-- The following 3 declarations are specific to Books
<!ELEMENT back                - O ((%bmsec.d;)|(%bmsec.i;)|biblist)*
<!ELEMENT (%bmsec.d;)         - O %m.sec;
<!ELEMENT (%bmsec.i;)         - O %m.idx;

<!ELEMENT (indxname|indxsubj) - O (#PCDATA)

<!-- =====
<!--   ATTRIBUTE DEFINITION LISTS
<!-- =====

<!-- HyTime attributes were added to all references,
      the citation and doclink elements

<!-- The SGML Document Access attributes for Braille, large print
and voice synthesis markup have been added to the attributes already
declared in this DTD in the first section following, and then for
all elements which have no attributes except for the SDA set.

<!--   ELEMENT   NAME      VALUE      DEFAULT
<!ATTLIST abstract %a.id;
      %SDAPREF;
      "<h1>Abstract</h1>"

```

```

<!ATTLIST ack      %a.id;
      %SDAPREF;
      "<h1>Acknowledgements</h1>" >

<!ATTLIST aff      %a.id;
      %SDAPREF;
      "<h1>Afterword</h1>" >

<!ATTLIST afterwrđ %a.id;
      %SDAPREF;
      "<h1>Appendix</h1>" >

<!ATTLIST appendix %a.id;
      %SDAPREF;
      "<h1>Appendix</h1>" >

<!ATTLIST artwork  %a.id;
      %a.sizes;
      name          ENTITY      #IMPLIED
      %SDAFORM;
      "fig #attrib ID" >

<!ATTLIST author   %au.rid;
      %SDAFORM;
      "au" >

<!ATTLIST biblist  file      ENTITY      #IMPLIED
      %SDAFORM;
      "list"
      %SDAPREF;
      "Bibliography" >

<!ATTLIST chapter  %a.id;
      SDABDY        NAMES      #FIXED      "title h1"
      SDAPART       NAMES      #FIXED      "title h2" >

<!ATTLIST citation id        ID          #REQUIRED
      HyTime          NAME          #FIXED bibloc
      %SDARULE;
      "title it
      author para
      corpauth para
      sertitle it" >

<!ATTLIST corpauth %a.id;
      %SDAFORM;
      "au" >

<!ATTLIST country  cnycode    NAME          #IMPLIED
      --name should follow ISO 3166-->

<!ATTLIST date     type       %d.types;
      %SDAPREF;
      "Date:" >

<!ATTLIST dd       %a.id;
      %SDAFORM;
      "para" >

<!ATTLIST ded      %a.id;
      %SDAPREF;
      "<h1>Dedication</h1>" >

<!ATTLIST deflist  %a.id;
      %SDAFORM;
      "list"
      %SDAPREF;
      "<?SDATRANS>Definitions " >

```

```

<!--ATTLIST %doctype; %a.id;
                                HyTime      NAME      #FIXED HyDoc
                                %SDAFORM;      "book"
                                >

<!--ATTLIST fig      %a.id;
                                %a.sizes;
                                name      ENTITY      #IMPLIED
                                scale      NUMBER      100
                                %SDAPREF;      "<?SDATTRANS>Figure: "
                                >

<!--ATTLIST figgrp      %a.id;
                                %SDARULE;      "title para"
                                >

<!--ATTLIST footnote      %a.id;
                                %SDAFORM;      "fn"
                                >

<!--ATTLIST foreword      %a.id;
                                %SDAPREF;      "<h1>Foreword</h1>"
                                >

<!--ATTLIST glossary      %a.id;
                                %SDAPREF;      "<h1>Glossary</h1>"
                                >

<!--ATTLIST index      %a.id;
                                %SDAPREF;      "<h1>Index</h1>"
                                >

<!--ATTLIST indxflag      ref1      CDATA      #IMPLIED
                                ref2      CDATA      #IMPLIED
                                ref3      CDATA      #IMPLIED
                                ref4      CDATA      #IMPLIED
                                >

<!--ATTLIST intro      %a.id;
                                %SDAPREF;      "<h1>Introduction</h1>"
                                >

<!--ATTLIST item      %a.id;
                                %SDAFORM;      "litem"
                                >

<!--ATTLIST note      %a.id;
                                %SDAFORM;      "note"
                                >

<!--ATTLIST nameloc      HyTime      NAME      nameloc
                                id      ID      #REQUIRED
                                -- multloc attributes --
                                ordering      (ordered|noorder)
                                                noorder
                                -- is ordering of locations significant? --
                                set      (set|notset)      notset
                                -- make multiple a set by ignoring duplicates --
                                aggloc      (aggloc|agglink|nagg)
                                                nagg
                                -- are multiple locations an aggregate? --
                                %SDAPREF;      "<?SDATTRANS>Nameloc:"
                                >

```

```

<!ATTLIST nmlist      HyTime      NAME      nmlist
                        nametype (entity|element) entity
                        -- entity names or IDs of elements --
                        obnames (obnames|nobnames) nobnames
                        -- objects treated as names? --
                        docorsub  ENTITY      #IMPLIED
                        dtdorlpd  NAMES       #IMPLIED
                        %SDAPREF;                "<?SDATRANS>Namelist:"      >

<!ATTLIST p           %a.id;
                        alphabet  %a.types;
                        %SDAFORM;                "para"                      >

<!ATTLIST part
                        %SDARULE;                "chapter #use SDAPART"      >

<!ATTLIST preface    %a.id;
                        %SDAPREF;                "<h1>Preface</h1>"      >

<!ATTLIST %p.em.ph;  type      %e.types;
                        %SDARULE;                "[emph type=1] b
                                                [emph type=2] it
                                                [emph type=(3|4|5|6)] other" >

<!ATTLIST %p.lst.d;  %a.id;
                        type      %l.types;
                        %SDAFORM;                "list"
                        %SDAPREF;                "[list type=1]#set (item,#count(item,1))
                                                [list type=2]#set (item,#count(item,A))
                                                [list type=3]#set (item,#count(item,I))
                                                [list type=4]#set (item,#count(item,'* '))
                                                [list type=5]#set (item,#count(item,'- '))" >

<!ATTLIST (%p.rf.ph;)
                        %a.id;
                        %a.rid;
                        HyTime      NAME      #FIXED clink
                        HyNames     CDATA     #FIXED "rid linkend"
                        %SDAFORM;                "xref #attrib IDREF"      >

<!ATTLIST %p.tbl;    %a.id;
                        %SDAFORM;                "table"
                        %SDARULE;                "title h3
                                                head hcell"
                        %SDAPREF;                "<?SDATRANS>"      >

<!ATTLIST q           %a.id;
                        alphabet  %a.types;
                        %SDAPREF;                ""
                        %SDASUFF;                ""                      >

<!ATTLIST section    %a.id;
                        SDABDY      NAMES     #FIXED      "title h2"
                        SDAPART      NAMES     #FIXED      "title h3"      >

```

```

<!ATTLIST subsect1  %a.id;
                SDABDY  NAMES      #FIXED      "title h3"
                SDAPART NAMES      #FIXED      "title h4"
                                                    >

<!ATTLIST subsect2  %a.id;
                SDABDY  NAMES      #FIXED      "title h4"
                SDAPART NAMES      #FIXED      "title h5"
                                                    >

<!ATTLIST subsect3  %a.id;
                SDABDY  NAMES      #FIXED      "title h5"
                SDAPART NAMES      #FIXED      "title h6"
                                                    >

<!ATTLIST subsect4  %a.id;
                SDABDY  NAMES      #FIXED      "title h6"
                SDAPART NAMES      #FIXED      "title b"
                                                    >

<!ATTLIST (subsect5|subsect6)
                %a.id;
                SDABDY  NAMES      #FIXED      "title b"
                SDAPART NAMES      #FIXED      "title b"
                                                    >

<!ATTLIST term      %a.id;
                %SDAFORM;
                                                    "term"
                                                    >

<!ATTLIST title      alphabet  %a.types;
                purpose  (normal|run)  normal
                %SDAFORM;
                "ti"
                                                    >

<!-- ===== -->
<!-- SDA ATTRIBUTES -->
<!-- ===== -->

<!-- The following declarations support elements whose only
       attributes are SDA attributes: -->

<!ATTLIST acqno
                %SDAFORM;
                %SDAPREF;
                "para"
                "Acquisition/order number: " >

<!ATTLIST avail
                %SDAFORM;
                %SDAPREF;
                "para"
                "Available from: " >

<!ATTLIST body
                %SDARULE;
                "chapter #use SDABDY " >

<!ATTLIST bq
                %SDAFORM;
                "bq" >

<!ATTLIST cpyrtclr
                %SDAFORM;
                %SDAPREF;
                "para"
                "Copyright clearance center: ">

```

<!ATTLIST coden	%SDAFORM;	%SDAPREF;	"para"	"CODEN: "	>
<!ATTLIST contract	%SDAFORM;	%SDAPREF;	"para"	"Contract or grant number: "	>
<!ATTLIST sponsor	%SDAFORM;	%SDAPREF;	"para"	"(Contract or grant) sponsor:">	
<!ATTLIST catalog	%SDAFORM;	%SDAPREF;	"para"	"<?SDATRANS>Cataloguing in publication information: "	>
<!ATTLIST cell	%SDAFORM;		"cell"		>
<!ATTLIST confgrp	%SDAFORM;	%SDAPREF;	"para"	"Conference group: "	>
<!ATTLIST confname	%SDAFORM;	%SDAPREF;	"para"	"Conference name: "	>
<!ATTLIST cpyrt	%SDAFORM;	%SDAPREF;	"para"	"<?SDATRANS>Copyright notice:">	
<!ATTLIST ddhd	%SDAFORM;		"lhead"		>
<!ATTLIST email	%SDAFORM;	%SDAPREF;	"para"	"Electronic address: "	>
<!ATTLIST edition	%SDAFORM;	%SDAPREF;	"para"	"<?SDATRANS>Edition: "	>
<!ATTLIST extent	%SDAFORM;	%SDAPREF;	"para"	"Number of pages: "	>
<!ATTLIST fax	%SDAFORM;	%SDAPREF;	"para"	"Fax number: "	>
<!ATTLIST head	%SDAFORM;		"lhead"		>

```

<!ATTLIST (indaddr|orgaddr)
    %SDAFORM;
    %SDAPREF;
    "para"
    "Address: "
    >

<!ATTLIST (indxname|indxsubj)
    %SDAFORM;
    "term"
    >

<!ATTLIST isbn
    %SDAFORM;
    %SDAPREF;
    "para"
    "ISBN: "
    >

<!ATTLIST (keyphras|keyword)
    %SDAFORM;
    "term"
    >

<!ATTLIST lccardno
    %SDAFORM;
    %SDAPREF;
    "para"
    "LC card number: "
    >

<!ATTLIST lit
    %SDAFORM;
    "lit"
    >

<!ATTLIST location
    %SDAFORM;
    %SDAPREF;
    "para"
    "Location: "
    >

<!ATTLIST notes
    %SDAPREF;
    "<h1>Notes</h1>"
    >

<!ATTLIST othinfo
    %SDAFORM;
    "para"
    >

<!ATTLIST acidfree
    %SDAFORM;
    %SDAPREF;
    "para"
    "Acid free paper indicator: "
    >

<!ATTLIST phone
    %SDAFORM;
    %SDAPREF;
    "para"
    "Phone: "
    >

<!ATTLIST pubid
    %SDAFORM;
    %SDAPREF;
    "para"
    "Publisher's ID number: "
    >

<!ATTLIST package
    %SDAFORM;
    %SDAPREF;
    "para"
    "Packaging method: "
    >

<!ATTLIST pubname
    %SDAFORM;
    %SDAPREF;
    "para"
    "Publisher: "
    >

<!ATTLIST pages
    %SDAFORM;
    "pp"
    >

```

```
<!-- ATTLIST price
      %SDAFORM;
      %SDAPREF;
      "para"
      "Price: "
      >

<!-- ATTLIST reportid
      %SDAFORM;
      %SDAPREF;
      "para"
      "Report identifier: "
      >

<!-- ATTLIST reprint
      %SDAFORM;
      %SDAPREF;
      "para"
      "Reprint source: "
      >

<!-- ATTLIST row
      %SDAFORM;
      "row"
      >

<!-- ATTLIST san
      %SDAFORM;
      %SDAPREF;
      "para"
      "Standard address number: "
      >

<!-- ATTLIST subtitle
      %SDAFORM;
      "h1"
      >

<!-- ATTLIST subject
      %SDAFORM;
      "it"
      >

<!-- ATTLIST supmat1
      %SDAFORM;
      %SDAPREF;
      "para"
      "Supporting material: "
      >

<!-- ATTLIST sertitle
      %SDAFORM;
      "ti"
      >

<!-- ATTLIST tbody
      %SDAFORM;
      "tbody"
      >

<!-- ATTLIST tstub
      %SDAFORM;
      "stubcell"
      >

<!-- ATTLIST tsubhead
      %SDAFORM;
      "hdcell"
      >

<!-- ATTLIST toc
      %SDAFORM;
      %SDAPREF;
      "list"
      "<?SDATRANS>Contents"
      >

<!-- ATTLIST volid
      %SDAFORM;
      %SDAPREF;
      "para"
      "Volume identifier: "
      >

<!-- Remove the comment declaration around the next three declarations
      if formulas follow a notation rather than SGML
```

```

<!ATTLIST formula
    %a.id;
    notation NOTATION (tex)          #IMPLIED
    alphabet %a.types;
    %SDAPREF;                        "<?SDATTRANS>Inline formula: "
    %SDASUSP;                        "SUSPEND"
                                     >

<!ATTLIST dformula
    %a.id;
    alphabet %a.types;
    notation NOTATION (tex)          #IMPLIED
    num      CDATA                   #IMPLIED
    align    (left|center|right)     center
    %SDAPREF;                        "<?SDATTRANS>Display formula: "
    %SDASUSP;                        "SUSPEND"
                                     >

<!ATTLIST dformgrp
    %a.id;
    num      CDATA                   #IMPLIED
    align    (left|center|right)     center
    %SDAPREF;                        "<?SDATTRANS>Display formula group: ">
-->

```

7 The Article DTD

```

<!-- This is the ISO12083:1994 document type definition for an Article.
      It can be embedded in a Serial.
-->
<!-- Copyright: (C) International Organization for Standardization 1994.
Permission to copy in any form is granted for use with conforming SGML
systems and applications as defined in ISO 8879:1986, provided this
notice is included in all copies.
-->

<!-- ===== -->
<!-- PUBLIC DOCUMENT TYPE DEFINITION SUBSET -->
<!-- ===== -->

<!-- Typical invocation:
<?HyTime VERSION "ISO/IEC 10744:1992" HQCNT=32
-->
<?HyTime MODULE base
-->
<?HyTime MODULE locs multloc anydtd mixspace
-->
<?HyTime MODULE links
-->
<!DOCTYPE article PUBLIC "ISO 12083:1994//DTD Article//EN"
[<!ENTITY % ISOnum PUBLIC "ISO 8879:1986//ENTITIES Numeric and
    Special Graphic//EN"
-->
    <!ENTITY % ISOpub PUBLIC "ISO 8879:1986//ENTITIES
    Publishing//EN"
-->
    <!ENTITY % ISOpub PUBLIC "ISO 8879:1986//ENTITIES
    Publishing//EN"
-->
    <!ENTITY % ISotech PUBLIC "ISO 8879:1986//ENTITIES
    General Technical//EN"
-->

```

```

<!ENTITY % ISodia PUBLIC "ISO 8879:1986//ENTITIES
    Diacritical Marks//EN"
<!ENTITY % ISolat1 PUBLIC "ISO 8879:1986//ENTITIES
    Added Latin 1//EN"
<!ENTITY % ISolat2 PUBLIC "ISO 8879:1986//ENTITIES
    Added Latin 2//EN"
<!ENTITY % ISOamso PUBLIC "ISO 8879:1986//ENTITIES
    Added Math Symbols: Ordinary//EN"
<!ENTITY % ISOgrk1 PUBLIC "ISO 8879:1986//ENTITIES
    Greek Letters//EN"
<!ENTITY % ISOgrk3 PUBLIC "ISO 8879:1986//ENTITIES
    Greek Symbols//EN"

%ISONum;
%ISOpub;
%ISOTech;
%ISodia;
%ISolat1;
%ISolat2;
%ISOamso;
%ISOgrk1;
%ISOgrk3;
<!ENTITY % ereview PUBLIC "-//USA-DOD//DTD
    SUP MIL-M-28001 EREVIEW REV B//EN"
%ereview;
]>

<!-- NOTES: 1. ISO/IEC TR 9573 Parts 12-16 are currently under review and will
    contain complete special character entity sets.
    2. MIL-M-28001 EREVIEW are the CALS facilities for electronic
    review.

<!-- =====
<!--      Entity Naming Conventions
<!-- =====

<!-- Prefix = where used:
    p. = in paragraphs (also in phrases if .ph suffix)
    s. = in sections (i.e., among paragraphs)
    i. = where allowed by inclusion exceptions
    m. = content model or declared content
    a. = attribute definition
    NONE= specific use defined in models

    Suffix = allowed content:
    .ph = elements whose content is %m.ph;
    .d  = elements whose content has same model as defaults
    .zz = for subelements
    NONE= individually defined elements

<!ENTITY % doctype "article" -- default document type generic identifier -->

```

```

<!-- ++++++ Specialized Elements ++++++ -->
<!-- Specialized Elements -->
<!-- ++++++ -->

<!ENTITY % ade.ph "street|city|state|country|postcode|san|email|postbox|
phone|fax" -- address elements -->
<!ENTITY % bib "author|corpauth|msn|sertitle|location|date|pages|subject|
othinfo" -- bibliographic, date is the publication date -->

<!-- The following 4 declarations are specific to Articles -->
<!ENTITY % bmsec.d "ack|vita" -- back matter cps elements -->
<!ENTITY % fmsec.d "ded|abstract|supmat1" -- front matter sections -->
<!ENTITY % pub "sponsor|contract|reprint|cpyrt|date|pubname|location|
confgrp|avail|history"
-- pubfront, date is the publication date -->
<!ENTITY % pub.ph "fpage|lpage|coden|acqno|issn|acidfree|price|extent|artid|
category|pubid"
-- publication related front matter material -->

<!-- ===== Basic Document Elements ===== -->
<!-- Basic Document Elements -->
<!-- ===== -->

<!ENTITY % i.float "figgrp|footnote|note" -- floating elements -->
<!ENTITY % p.el "deflist|orgaddr|indaddr|artwork|bq|lit|date|biblist|author
|corpauth|keyword|keyphras|poem|nameloc|indxflag"
-- general -->
<!ENTITY % p.em.ph "emph" -- emphasis -->
<!ENTITY % p.lst.d "list" -- list -->

<!-- The following declaration is specific to Articles -->
<!ENTITY % p.rf.ph "noteref|fnoteref|figref|tableref|artref|appref|citeref|
secref|formref" -- references -->

<!ENTITY % p.tbl "table" -- table matter -->
<!ENTITY % p.form "formula|dformula|dformgrp" -- mathematical formulas -->
<!ENTITY % p.zz "(%p.el;)|(%p.tbl;)|(%p.lst.d;)|(%p.form;)"
-- paragraph subelements -->

<!ENTITY % p.zz.ph "q|pages|(%p.em.ph;)|(%p.rf.ph;)" -- phrases -->
<!ENTITY % s.zz "p|(%p.zz;)" -- section subelements -->

<!-- ++++++ Models ++++++ -->
<!-- Models -->
<!-- ++++++ -->

<!ENTITY % m.addr "(%ade.ph;)*" -- address (no name) -->
<!ENTITY % m.bib "(no?, title, (%bib;))*" -- bibliographic entry -->
<!ENTITY % m.copy "(date|cpyrtname|cpyrtclr)*" -- copyright notice data -->
<!ENTITY % m.date "(#PCDATA)*" -- date -->
<!ENTITY % m.fig "EMPTY" -- default FIG content -->
<!ENTITY % m.sec "(title?, (%s.zz;)*, section*)" -- section -->

```

```

<!ENTITY % m.name "((fname? & surname), (degree|school)*, role*, (%ade.ph;)*,
                    aff?)" -- name components -->
<!ENTITY % m.org "(orgname, orgdiv*, %m.addr;)" -- organization name -->
<!ENTITY % m.ph "(#PCDATA|(%p.zz.ph;)|(%p.form;))*" -- phrase model -->
<!ENTITY % m.pseq "(p, (p|(%p.zz;))*)" -- P with sequence -->
<!ENTITY % m.poem "(stanza+|poemline+)" -- poetry sub-elements -->

<!-- ++++++ -->
<!-- Attribute Definitions -->
<!-- ++++++ -->

<!ENTITY % a.id "id ID #IMPLIED" -- ID attribute definition -->
<!ENTITY % a.rid "rid IDREF #REQUIRED" -- IDREF attribute definition -->
<!ENTITY % au.rid "rids IDREFS #IMPLIED" -- to refer to a unique id of
                                         an affiliation -->

<!ENTITY % a.sizes "sizex NUTOKEN #IMPLIED
                    sizey NUTOKEN #IMPLIED
                    unit CDATA #IMPLIED"
-- unit must be specified if sizex or sizey are. -->

<!ENTITY % a.types "(latin|greek|cyrillic|hebrew|kanji) latin"
-- Indicates which alphabet is used in the
element (title, p, q). This may be changed to a notation
attribute, where the notation could describe a keyboard
mapping. Modify the set as necessary. -->

<!ENTITY % d.types "(1 | 2 | 3 | 4 | 5) #IMPLIED"
-- Suggestions for date types:
1=ISO 8601:1988, 2=mm-dd-yy, 3=mm/dd/yy, 4=dd-mm-yy,
5=month day year; if more needed (e.g. "day month year")
modify or extend this list as necessary. -->

<!ENTITY % e.types "(1|2|3|4|5|6) #IMPLIED"
-- Suggestions for emphasis types:
1=bold, 2=italic, 3=bold italic, 4=underline,
5=non proportional, 6=smallcaps; if more needed
modify or extend this list as necessary. -->

<!ENTITY % l.types "(1 | 2 | 3 | 4 | 5| 6) #IMPLIED"
-- Suggestions for list types:
1=arabic, 2=upper alpha, 3=roman, 4=bullet, 5=dash,
6=unlabelled; if more needed (e.g. lower alpha)
modify or extend this list as necessary. -->

<!-- ++++++ -->
<!-- Accessible Document Parameter Entities -->
<!-- ++++++ -->

<!ENTITY % SDAFORM "SDAFORM CDATA #FIXED" >
<!ENTITY % SDARULE "SDARULE CDATA #FIXED" >
<!ENTITY % SDAPREF "SDAPREF CDATA #FIXED" >
<!ENTITY % SDASUFF "SDASUFF CDATA #FIXED" >
<!ENTITY % SDASUSP "SDASUSP NAME #FIXED" >

```

```

<!-- ===== -->
<!-- DATA CONTENT NOTATIONS -->
<!-- ===== -->

<!-- These are only some examples. Add other public notations as required. -->

<!-- NOTATION eps PUBLIC
*///ISBN 0-201-18127-4::Adobe//NOTATION PostScript Language Reference
Manual//EN"
<!-- NOTATION tex PUBLIC
*///ISBN 0-201-13448-9::Knuth//NOTATION The TeXbook//EN"
<!-- NOTATION cgmchar PUBLIC *ISO 8632/2//NOTATION Character encoding//EN"
<!-- NOTATION cgmclear PUBLIC *ISO 8632/4//NOTATION Clear text encoding//EN"
<!-- NOTATION tiff PUBLIC *ISO 12083:1993//NOTATION TIFF-1//EN"

<!-- ===== -->
<!-- THE DOCUMENT STRUCTURE -->
<!-- ===== -->

<!-- ELEMENT MIN CONTENT (EXCEPTIONS) -->
<!-- ELEMENT (%doctype;) - - (front, body, appmat?, back?)
+{%i.float;} >

<!-- ===== -->
<!-- FRONT MATTER ELEMENTS -->
<!-- ===== -->

<!-- The following declaration is specific to Articles -->
<!-- ELEMENT front 0 0 (titlegrp, authgrp, date?, pubfront?,
((%fmsec.d;)|keyword|keyphras)*) >

<!-- ELEMENT (%fmsec.d;) - 0 %m.sec; >

<!-- ===== -->
<!-- Title Group -->
<!-- ===== -->

<!-- ELEMENT titlegrp 0 0 (title, subtitle*) >
<!-- ELEMENT (title|subtitle) - 0 %m.ph; >

<!-- ===== -->
<!-- Author Group -->
<!-- ===== -->

<!-- ELEMENT authgrp 0 0 (author|corpauth|aff)* >
<!-- ELEMENT author - 0 %m.name; >
<!-- ELEMENT (fname|surname|role|degree|orgname|orgdiv)
- 0 (#PCDATA) >

<!-- ELEMENT (aff|corpauth|school)
- 0 %m.org; >

```

```

<!ELEMENT (%ade.ph;) - O (#PCDATA) >

<!-- ++++++ -->
<!-- Publisher's Front Matter -->
<!-- ++++++ -->

<!ELEMENT pubfront - O ((%pub;) | (%pub.ph;))* >
<!ELEMENT (%pub.ph;|contract) - O (#PCDATA) >
<!ELEMENT (pubname|avail|sponsor) - O %m.org; >
<!ELEMENT reprint - O (%m.org;|%m.name;) >

<!-- ++++++ -->
<!-- Article's History -->
<!-- ++++++ -->

<!-- The following 2 declarations are specific to Articles -->
<!ELEMENT history - O (received|accepted|revised|misc)* >
<!ELEMENT (received|accepted|revised) - O (date) >
<!ELEMENT misc - O (p*, date) >

<!-- ++++++ -->
<!-- Copyright -->
<!-- ++++++ -->

<!ELEMENT cpyrt - - %m.copy; >
<!ELEMENT cpyrtclr - - %m.org; >
<!ELEMENT cpyrtname - - (%m.org;|%m.name;) >

<!-- ++++++ -->
<!-- Conference Group -->
<!-- ++++++ -->

<!ELEMENT confgrp - - (no?, confname, date?, location?, sponsor?) >
<!ELEMENT confname - O (#PCDATA) >

<!-- ++++++ -->
<!-- Date -->
<!-- ++++++ -->

<!ELEMENT date - O %m.date; >

```

```

<!-- ===== -->
<!-- BODY ELEMENTS -->
<!-- ===== -->

<!-- ++++++ -->
<!-- Body Structure -->
<!-- ++++++ -->

<!ELEMENT body 0 0 (part+|chapter+) >
<!ELEMENT part - 0 (no?, title?, (%s.zz;)*, chapter+) >
<!ELEMENT chapter - 0 (no?, %m.sec;) >
<!ELEMENT section - 0 (no?, title?, (%s.zz;)*, subsect1*) >
<!ELEMENT subsect1 - 0 (no?, title?, (%s.zz;)*, subsect2*) >
<!ELEMENT subsect2 - 0 (no?, title?, (%s.zz;)*, subsect3*) >
<!ELEMENT subsect3 - 0 (no?, title?, (%s.zz;)*, subsect4*) >
<!ELEMENT subsect4 - 0 (no?, title?, (%s.zz;)*, subsect5*) >
<!ELEMENT subsect5 - 0 (no?, title?, (%s.zz;)*, subsect6*) >
<!ELEMENT subsect6 - 0 (no?, title?, (%s.zz;)*, subsect6*) >
<!ELEMENT no - 0 (#PCDATA) >

<!-- ++++++ -->
<!-- Section Subelements -->
<!-- ++++++ -->

<!ELEMENT p - 0 (#PCDATA|(%p.zz.ph;)|(%p.zz;))* >

<!-- ++++++ -->
<!-- Paragraph Subelements -->
<!-- ++++++ -->

<!ELEMENT bq - - %m.pseq; >
<!ELEMENT indaddr - 0 %m.name; -- individual address -->
<!ELEMENT orgaddr - 0 %m.org; -- organization address -->
<!ELEMENT artwork - 0 EMPTY >

<!ELEMENT lit - - RCDATA >

<!ELEMENT (%p.lst.d;) - - (head?, item)* >
<!ELEMENT item - 0 %m.pseq; >

<!ELEMENT deflist - - ((head, ddhd)?, term, dd)* >
<!ELEMENT (term|head|ddhd) - 0 %m.ph; >
<!ELEMENT dd - 0 %m.pseq; >

<!ELEMENT biblist - 0 (head?, citation)* >
<!ELEMENT citation - 0 %m.bib; >
<!ELEMENT (othinfo|subject|sertitle) - 0 %m.ph; >

<!ELEMENT location - 0 %m.addr; >
<!ELEMENT (msn|pages) - 0 (#PCDATA) >
<!ELEMENT keyword - 0 (#PCDATA) >
<!ELEMENT keyphras - 0 (#PCDATA) >

```

```

<!ELEMENT indxflag          - O EMPTY                                >

<!-- ++++++ -->
<!-- Poetry -->
<!-- ++++++ -->

<!ELEMENT poem              - O %m.poem;                            >
<!ELEMENT stanza            - O (poemline)+                          >
<!ELEMENT poemline          - O (#PCDATA|cline|&p.em.ph;)*          >
<!ELEMENT cline              - O (#PCDATA|&p.em.ph;)*                >

<!-- ++++++ -->
<!-- Phrases -->
<!-- ++++++ -->

<!ELEMENT q                  - - %m.ph;                               >
<!ELEMENT (&p.em.ph;)        - - %m.ph;                               >
<!ELEMENT (&p.rf.ph;)        - - (#PCDATA)                            >

<!-- ++++++ -->
<!-- For HyTime Links -->
<!-- ++++++ -->

<!ELEMENT nameloc            - O (nmlist*) -- assigns a local ID to   -->
                                   named objects                      -->
<!ELEMENT nmlist             - O (#PCDATA) -- list of local ID or entity -->
                                   names                             -->

<!-- ++++++ -->
<!-- Floating Elements -->
<!-- ++++++ -->

<!ELEMENT figgrp             - - (title? & fig*)                      >
<!ELEMENT fig                - O %m.fig;                              >
<!ELEMENT footnote           - - (no?, %m.pseq;)                      -(%i.float;) >
<!ELEMENT note               - - (no?, %m.pseq;)                      >

<!-- ++++++ -->
<!-- Tables -->
<!-- ++++++ -->

<!ELEMENT table              - - (no?, title?, tbody)              -(%i.float;) >
<!ELEMENT tbody             - O (head*, tsubhead*, row*)           >
<!ELEMENT row                - O (tstub?, cell*)                    >
<!ELEMENT tsubhead           - O %m.ph;                              >
<!ELEMENT (tstub|cell)       - O %m.pseq;                            >

```

```

<!-- ***** -->
<!--      Mathematics      -->
<!-- ***** -->

<!ENTITY % maths PUBLIC "ISO 12083:1994//DTD Mathematics//EN"
%maths; >

<!-- Remove these comments if the formulas follow a NOTATION rather than SGML.
<!ELEMENT dformgrp          - O (dformula)+ >
<!ELEMENT (formula|dformula) - - CDATA >
-->

<!-- ===== -->
<!--      APPENDIX ELEMENTS      -->
<!-- ===== -->

<!ELEMENT appmat          - O (appendix+) >
<!ELEMENT appendix        - O (no?, %m.sec;) >

<!-- ===== -->
<!--      BACK MATTER ELEMENTS      -->
<!-- ===== -->

<!-- The following declaration is specific to Articles
<!ELEMENT back          - O (%bmsec.d;|biblist)+ >
<!ELEMENT (%bmsec.d;)    - O %m.sec; >

<!-- ===== -->
<!--      ATTRIBUTE DEFINITION LISTS      -->
<!-- ===== -->

<!-- HyTime attributes were added to all references,
the citation and doclink elements -->

<!-- The SGML Document Access attributes for Braille, large print
and voice synthesis markup have been added to the attributes already
declared in this DTD in the first section following, and then for
all elements which have no attributes except for the SDA set. -->

<!--      ELEMENT      NAME      VALUE      DEFAULT      -->
<!ATTLIST abstract %a.id; >
%SDAPREF; " <h1>Abstract</h1>" >

<!ATTLIST ack %a.id; >
%SDAPREF; " <h1>Acknowledgements</h1>" >

<!ATTLIST acqno >
%SDAFORM; "para"
%SDAPREF; "Acquisition/order number: " >

<!ATTLIST aff %a.id; >

```

```

<!ATTLIST appendix  %a.id;
                    %SDAPREF;
                                "<h1>Appendix</h1>"
                                >

<!ATTLIST artwork  %a.id;
                    %a.sizes;
                    name      ENTITY      #IMPLIED
                    %SDAFORM;
                                "fig #attrib ID"
                                >

<!ATTLIST author    %au.rid;
                    %SDAFORM;
                                "au"
                                >

<!ATTLIST biblist    file      ENTITY      #IMPLIED
                    %SDAFORM;
                                "list"
                    %SDAPREF;
                                "Bibliography"
                                >

<!ATTLIST chapter    %a.id;
                    SDABDY      NAMES      #FIXED
                    SDAPART      NAMES      #FIXED
                                "title h1"
                                "title h2"
                                >

<!ATTLIST citation   id         ID          #REQUIRED
                    HyTime      NAME        #FIXED bibloc
                    %SDARULE;
                                "title it
                                author para
                                corpauth para
                                sertitle it"
                                >

<!ATTLIST corpauth   %a.id;
                    %SDAFORM;
                                "au"
                                >

<!ATTLIST country    cnycode    NAME        #IMPLIED
                                -- name should follow ISO 3166 -->

<!ATTLIST date        type      %d.types;
                    %SDAPREF;
                                "Date:"
                                >

<!ATTLIST dd          %a.id;
                    %SDAFORM;
                                "para"
                                >

<!ATTLIST deflist     %a.id;
                    %SDAFORM;
                                "list"
                    %SDAPREF;
                                "<?SDATrans>Definitions "
                                >

<!ATTLIST %doctype;  %a.id;
                    HyTime      NAME        #FIXED HyDoc
                    %SDAFORM;
                                "article"
                                >

<!ATTLIST fig         %a.id;
                    %a.sizes;
                    name      ENTITY      #IMPLIED
                    scale     NUMBER      100
                    %SDAPREF;
                                "<?SDATrans>Figure: "
                                >

<!ATTLIST figgrp      %a.id;
                    %SDARULE;
                                "title para"
                                >

```

```

<!ATTLIST footnote %a.id;
    %SDAFORM;
    "fn"
>

<!ATTLIST indxflag ref1 CDATA #IMPLIED
    ref2 CDATA #IMPLIED
    ref3 CDATA #IMPLIED
    ref4 CDATA #IMPLIED
>

<!ATTLIST item %a.id;
    %SDAFORM;
    "litem"
>

<!ATTLIST nameloc HyTime NAME nameloc
    id ID #REQUIRED
    -- multloc attributes --
    ordering (ordered|noorder)
    noorder
    -- is ordering of locations significant? --
    set (set|notset) notset
    -- make multiple a set by ignoring duplicates --
    aggloc (aggloc|agglink|nagg)
    nagg
    -- are multiple locations an aggregate? --
    %SDAPREF;
    "<?SDATRANS>Nameloc:"
>

<!ATTLIST nmlist HyTime NAME nmlist
    nametype (entity|element)
    entity
    -- entity names or IDs of elements --
    obnames (obnames|nobnames)
    nobnames
    -- objects treated as names? --
    docorsub ENTITY #IMPLIED
    dtdorlpd NAMES #IMPLIED
    %SDAPREF;
    "<?SDATRANS>Namelist:"
>

<!ATTLIST note %a.id;
    %SDAFORM;
    "note"
>

<!ATTLIST p %a.id;
    alphabet %a.types;
    %SDAFORM;
    "para"
>

<!ATTLIST part %a.id;
    %SDARULE;
    "chapter #use SDAPART"
>

<!ATTLIST %p.em.ph; type %e.types;
    %SDARULE;
    "[emph type=1] b
    [emph type=2] it
    [emph type={3|4|5|6}] other"
>

```

```

<!--ATTLIST %p.lst.d; %a.id;
      type                                %l.types;
      %SDAFORM;                          "list"
      %SDAPREF;                          "[list type=1]#set (item,#count(item,1))
                                         [list type=2]#set (item,#count(item,A))
                                         [list type=3]#set (item,#count(item,I))
                                         [list type=4]#set (item,#count(item,'* '))
                                         [list type=5]#set (item,#count(item,'- '))" >

<!--ATTLIST (%p.rf.ph;) %a.rid;
      %a.id;
      HyTime NAME #FIXED clink
      HyNames CDATA #FIXED "rid linkend"
      %SDAFORM;    "xref #attrib IDREF" >

<!--ATTLIST %p.tbl; %a.id;
      %SDAFORM;    "table"
      %SDARULE;    "title h3
                   head hdcell"
      %SDAPREF;    "<?SDATrans>" >

<!--ATTLIST q      %a.id;
      alphabet      %a.types;
      %SDAPREF;    ""
      %SDASUFF;    "" >

<!--ATTLIST section %a.id;
      SDABDY NAMES #FIXED "title h2"
      SDAPART NAMES #FIXED "title h3" >

<!--ATTLIST subsect1 %a.id;
      SDABDY NAMES #FIXED "title h3"
      SDAPART NAMES #FIXED "title h4" >

<!--ATTLIST subsect2 %a.id;
      SDABDY NAMES #FIXED "title h4"
      SDAPART NAMES #FIXED "title h5" >

<!--ATTLIST subsect3 %a.id;
      SDABDY NAMES #FIXED "title h5"
      SDAPART NAMES #FIXED "title h6" >

<!--ATTLIST subsect4 %a.id;
      SDABDY NAMES #FIXED "title h6"
      SDAPART NAMES #FIXED "title b" >

<!--ATTLIST (subsect5|subsect6)
      %a.id;
      SDABDY NAMES #FIXED "title b"
      SDAPART NAMES #FIXED "title b" >

<!--ATTLIST term      %a.id;
      %SDAFORM;    "term" >

```

```

<!-- ATTLIST title      alphabet  %a.types;
                        purpose    (normal|run)  normal
                        %SDAFORM;                "ti"
                                                >

<!-- ===== -->
<!-- SDA ATTRIBUTES -->
<!-- ===== -->

<!-- The following declarations support elements whose only attributes are
SDA attributes:
-->

<!-- ATTLIST avail
      %SDAFORM;
      %SDAPREF;
                        "para"
                        "Available from: "
                                                >

<!-- ATTLIST body
      %SDARULE;
                        "chapter #use SDABDY "
                                                >

<!-- ATTLIST bq
      %SDAFORM;
                        "bq"
                                                >

<!-- ATTLIST cell
      %SDAFORM;
                        "cell"
                                                >

<!-- ATTLIST cpyrtclr
      %SDAFORM;
      %SDAPREF;
                        "para"
                        "Copyright clearance center: ">

<!-- ATTLIST coden
      %SDAFORM;
      %SDAPREF;
                        "para"
                        "CODEN: "
                                                >

<!-- ATTLIST contract
      %SDAFORM;
      %SDAPREF;
                        "para"
                        "Contract or grant number: "
                                                >

<!-- ATTLIST sponsor
      %SDAFORM;
      %SDAPREF;
                        "para"
                        "(Contract or grant) sponsor:">

<!-- ATTLIST confgrp
      %SDAFORM;
      %SDAPREF;
                        "para"
                        "Conference group: "
                                                >

<!-- ATTLIST confname
      %SDAFORM;
      %SDAPREF;
                        "para"
                        "Conference name: "
                                                >

<!-- ATTLIST cpyrt
      %SDAFORM;
      %SDAPREF;
                        "para"
                        "<?SDATRANS>Copyright notice:">

<!-- ATTLIST ddhd
      %SDAFORM;
                        "lhead"
                                                >

```

<!ATTLIST ded	%SDAPREF;	" Dedication "	>
<!ATTLIST email	%SDAFORM;	"para"	
%SDAPREF;	"Electronic address: "		>
<!ATTLIST extent	%SDAFORM;	"para"	
%SDAPREF;	"Number of pages: "		>
<!ATTLIST fax	%SDAFORM;	"para"	
%SDAPREF;	"FAX number: "		>
<!ATTLIST head	%SDAFORM;	"lhead"	>
<!ATTLIST (indaddr orgaddr)	%SDAFORM;	"para"	
%SDAPREF;	"Address: "		>
<!ATTLIST issn	%SDAFORM;	"para"	
%SDAPREF;	"ISSN: "		>
ATTLIST (keyphras keyword)	%SDAFORM;	"term"	>
ATTLIST lit	%SDAFORM;	"lit"	>
<!ATTLIST location	%SDAFORM;	"para"	
%SDAPREF;	"Location: "		>
<!ATTLIST othinfo	%SDAFORM;	"para"	>
<!ATTLIST acidfree	%SDAFORM;	"para"	
%SDAPREF;	"Acid free paper indicator: "		>
<!ATTLIST phone	%SDAFORM;	"para"	
%SDAPREF;	"Phone: "		>
<!ATTLIST pubid	%SDAFORM;	"para"	
%SDAPREF;	"Publisher's ID number: "		>
<!ATTLIST pubname	%SDAFORM;	"para"	
%SDAPREF;	"Publisher: "		>

```
<!-- ATTLIST pages
      %SDAFORM;
      "pp"
      >

<!-- ATTLIST price
      %SDAFORM;
      %SDAPREF;
      "para"
      "Price: "
      >

<!-- ATTLIST row
      %SDAFORM;
      "row"
      >

<!-- ATTLIST reprint
      %SDAFORM;
      %SDAPREF;
      "para"
      "Reprint source: "
      >

<!-- ATTLIST san
      %SDAFORM;
      %SDAPREF;
      "para"
      "Standard address number: "
      >

<!-- ATTLIST subtitle
      %SDAFORM;
      "h1"
      >

<!-- ATTLIST subject
      %SDAFORM;
      "it"
      >

<!-- ATTLIST supmatl
      %SDAFORM;
      %SDAPREF;
      "para"
      "Supporting material: "
      >

<!-- ATTLIST sertitle
      %SDAFORM;
      "ti"
      >

<!-- ATTLIST tbody
      %SDAFORM;
      "tbody"
      >

<!-- ATTLIST tstub
      %SDAFORM;
      "stubcell"
      >

<!-- ATTLIST tsubhead
      %SDAFORM;
      "hdcell"
      >

<!-- Remove this comment around the next three declarations if formulas
      follow a notation rather than SGML.
<!-- ATTLIST formula
      %a.id;
      notation NOTATION (tex)
      alphabet %a.types;
      %SDAPREF;
      %SDASUSP;
      #IMPLIED
      "<?SDATRANS>Inline formula: "
      "SUSPEND"
      >
```

```

<!ATTLIST dformula
    %a.id;
    alphabet %a.types;
    notation NOTATION (tex)          #IMPLIED
    num      CDATA                    #IMPLIED
    align    (left|center|right)     center
    %SDAPREF;                          "<?SDATRANS>Display formula: "
    %SDASUSP;                          "SUSPEND"
-->

<!ATTLIST dformgrp
    %a.id;
    num      CDATA                    #IMPLIED
    align    (left|center|right)     center
    %SDAPREF;                          "<?SDATRANS>Display formula group: ">
-->

```

8 The Serial DTD

```

<!-- This is the ISO12083:1994 document type definition for Serials. -->
<!-- Copyright: (C) International Organization for Standardization 1994.
Permission to copy in any form is granted for use with conforming SGML
systems and applications as defined in ISO 8879:1986, provided this
notice is included in all copies. -->
<!-- ===== -->
<!-- PUBLIC DOCUMENT TYPE DEFINITION SUBSET -->
<!-- ===== -->

<!-- Typical invocation:
<!DOCTYPE serial PUBLIC "ISO 12083:1994//DTD Serial//EN"
[<!ENTITY % ISOnum PUBLIC "ISO 8879:1986//ENTITIES Numeric and
    Special Graphic//EN"
    <!ENTITY % ISOpub PUBLIC "ISO 8879:1986//ENTITIES
    Publishing//EN"
    <!ENTITY % ISOtech PUBLIC "ISO 8879:1986//ENTITIES
    General Technical//EN"
    <!ENTITY % ISodia PUBLIC "ISO 8879:1986//ENTITIES
    Diacritical Marks//EN"
    <!ENTITY % ISolat1 PUBLIC "ISO 8879:1986//ENTITIES
    Added Latin 1//EN"
    <!ENTITY % ISolat2 PUBLIC "ISO 8879:1986//ENTITIES
    Added Latin 2//EN"
    <!ENTITY % ISOamso PUBLIC "ISO 8879:1986//ENTITIES
    Added Math Symbols: Ordinary//EN"
    <!ENTITY % ISOgrk1 PUBLIC "ISO 8879:1986//ENTITIES
    Greek Letters//EN"
    <!ENTITY % ISOgrk3 PUBLIC "ISO 8879:1986//ENTITIES
    Greek Symbols//EN"
    %ISOnum;
    %ISOpub;
    %ISOtech;
    %ISodia;
    %ISolat1;

```

```

%ISolat2;
%ISOamso;
%ISOgrk1;
%ISOgrk3;
<!ENTITY % ereview PUBLIC "-//USA-DOD//DTD
      SUP MIL-M-28001 EREVIEW REV B//EN"
%ereview;
]>
-->

<!-- NOTES: 1. ISO/IEC TR 9573 Parts 12-16 are currently under review and will
      contain complete special character entity sets.
      2. MIL-M-28001 EREVIEW are the CALS facilities for electronic
      review.
-->

<!-- This is the document type declaration subset for a Serial. Articles will
be embedded within this document type.
-->

<!-- Entity naming conventions are the same as for Books and Article
-->

<!ENTITY % serial "serial" -- default document type generic identifier
-->

<!-- ++++++
<!-- Specialized Elements
<!-- ++++++
-->

<!ENTITY % bmsec.i "glossary|index" -- indexes and glossary
-->
<!ENTITY % spub "reprint|cpyrt|date|pubname|location|confgrp|avail|
      issueid|coden|acqno|acidfree|price|extent"
-- serial pubfront
-->
<!ENTITY % spub.ph "lccardno|reportid|edition|volid|catalog|package|pubid"
-- serial publication related front matter material
-->
<!ENTITY % i.sflt "aseqntl|advert" -- serial floats
-->

<!-- ++++++
<!-- Models
<!-- ++++++
-->

<!ENTITY % m.adv "EMPTY" -- default advertisement content
-->
<!ENTITY % m.toc "EMPTY" -- table of contents model
-->

<!-- Article declaration subset is included here.
-->
<!ENTITY % serart PUBLIC "ISO 12083:1994//DTD Article//EN"
%serart;
>

<!-- end article declaration subset
-->

<!ENTITY % m.idx "(%m.sec;|((indxname|indxsubj)*,pages*))" -- model for
indexes and glossary
-->

```

```

<!-- ===== -->
<!-- THE DOCUMENT STRUCTURE -->
<!-- ===== -->

<!-- ELEMENT MIN CONTENT (EXCEPTIONS) -->
<!-- ELEMENT (%serial;) - - (serfront, serbody, serback?) -->
                                +(%i.sflt;|%i.float;)>

<!-- ===== -->
<!-- FRONT MATTER ELEMENTS -->
<!-- ===== -->

<!-- ELEMENT serfront O O (title, stitle?, alttitle?, serpubfr?,
                                toc?)>

<!-- ===== -->
<!-- Title Group -->
<!-- ===== -->

<!-- ELEMENT (stitle|alttitle) O O %m.ph; >

<!-- ===== -->
<!-- Serial Publisher's Front Matter -->
<!-- ===== -->

<!-- ELEMENT serpubfr - O ((%spub;)|(%spub.ph;))* >
<!-- ELEMENT (%spub.ph;) - O (#PCDATA) >
<!-- ELEMENT issueid - O (issueno, issuept?, supplid?) >
<!-- ELEMENT (issueno|issuept|supplid) - O (#PCDATA) >

<!-- ===== -->
<!-- Table of Contents -->
<!-- ===== -->

<!-- ELEMENT toc - O %m.toc; >

<!-- ===== -->
<!-- BODY ELEMENTS -->
<!-- ===== -->

<!-- ===== -->
<!-- Body Structure -->
<!-- ===== -->

<!-- ELEMENT serbody O O (serpart+|sersec+) >
<!-- ELEMENT serpart - O (title?, (%s.zz;|sersec|article)*) -->
                                -- Department or Special Features -->
<!-- ELEMENT sersec - O (title?, (%s.zz;|article)*) -->
                                -- Book Reviews, Engineering Notes, etc. -->

```

```

<!-- ++++++ -->
<!--      Floating elements      -->
<!-- ++++++ -->

<!ELEMENT advert      - O %m.adv;      >
<!ELEMENT aseqntl     - - %m.sec;      >
      -- Asequential elements are intended to be used as filler items -->

<!-- ===== -->
<!--      BACK MATTER ELEMENTS      -->
<!-- ===== -->

<!ELEMENT serback      - O ((%bmsec.d;)|(%bmsec.i;))*      >
<!ELEMENT (%bmsec.i;)  - O %m.idx;      >
<!ELEMENT (indxname|indxsubj)      >
      - O (#PCDATA)      >

<!-- ===== -->
<!--      ATTRIBUTE DEFINITION LISTS      -->
<!-- ===== -->
<!-- The SGML Document Access attributes for Braille, large print
and voice synthesis markup have been added. -->

<!--      ELEMENT      NAME      VALUE      DEFAULT      -->

<!ATTLIST advert      %a.id;
      %a.sizes;
      name      ENTITY      #IMPLIED
      %SDAFORM;      "fig"      >

<!ATTLIST catalog      %SDAFORM;      "para"
      %SDAPREF;      "<?SDATRANS>Cataloguing
in publication information:" >

<!ATTLIST %serial;      %a.id;
      %SDAFORM;      "serial"      >

<!ATTLIST edition      %SDAFORM;      "para"
      %SDAPREF;      "<?SDATRANS>Edition:" >

<!ATTLIST glossary      %a.id;
      %SDAPREF;      "<h1>Glossary</h1>" >

<!ATTLIST index      %a.id;
      %SDAPREF;      "<h1>Index</h1>" >

<!ATTLIST (indxname|indxsubj)
      %SDAFORM;      "term"      >

<!ATTLIST lccardno      %SDAFORM;      "para"
      %SDAPREF;      "LC card number:" >

```

```

<!-- ATTLIST package %SDAFORM; "para"
                        %SDAPREF; "Packaging method:" >

<!-- ATTLIST reportid %SDAFORM; "para"
                        %SDAPREF; "Report identifier:" >

<!-- ATTLIST (stitle|alttitle)
                        alphabet %a.types;
                        %SDAFORM; "ti" >

<!-- ATTLIST toc %SDAFORM; "list"
                  %SDAPREF; "<?SDATRANS>Contents" >

<!-- ATTLIST volid %SDAFORM; "para"
                  %SDAPREF; "Volume identifier:" >

```

9 The Mathematics DTD

```
<!-- This is the ISO12083:1994 document type definition for Mathematics -->
```

```

<!-- Copyright: (C) International Organization for Standardization 1994.
Permission to copy in any form is granted for use with conforming SGML
systems and applications as defined in ISO 8879:1986, provided this notice
is included in all copies. -->

```

```

<!-- ===== -->
<!-- PUBLIC DOCUMENT TYPE DEFINITION SUBSET -->
<!-- ===== -->

```

```
<!--
```

This DTD is included by the Book and Article DTDs of ISO12083:1994.
As it is a separate entity it may also be included by other DTDs.

Since there is no consensus on how to describe the semantics of formulas, it only describes their presentational or visual structure. Since, however, there is a strong need for such description (especially within the print-disabled community), it is recommended that the following declaration be added where there is a requirement for a consistent, standardized mechanism to carry semantic meanings for the SGML elements declared throughout this part of this International Standard:

```
<!-- ENTITY % SDAMAP "SDAMAP NAME #IMPLIED" >
```

and that the attribute represented by %SDAMAP; be made available for all elements which may require a semantic association, or, in the simpler case, be added to all elements in this DTD. -->

```

<!-- ===== -->
<!-- Parameter entities describing the possible contents of formulas. -->
<!-- ===== -->

<!ENTITY % p.trans "bold|italic|sansser|typewrit|smallcap|roman"
      -- character transformations -->
<!ENTITY % m.math "fraction|subform|sup|inf|top|bottom|middle|fence|mark|
      post|box|overline|undrline|radical|array|hspace|vspace|break|markref|
      #PCDATA" -- mathematical formula elements -->

<!-- ===== -->
<!-- Accessible Document and other Parameter Entities
      If this DTD is not imbedded by a ISO12083:1994 Book or Article,
      the comment delimiters should be removed. -->
<!-- ===== -->

<!--ENTITY % SDAFORM      "SDAFORM      CDATA      #FIXED" -->
<!--ENTITY % SDARULE      "SDARULE      CDATA      #FIXED" -->
<!--ENTITY % SDAPREF      "SDAPREF      CDATA      #FIXED" -->
<!--ENTITY % SDASUFF      "SDASUFF      CDATA      #FIXED" -->
<!--ENTITY % SDASUSP      "SDASUSP      NAME      #FIXED" -->

<!-- ===== -->
<!-- This entity is for an attribute to indicate which alphabet is
      used in the element (formula, dformula). This may be changed to
      a notation attribute, where the notation could describe a
      keyboard mapping. Modify the set as necessary.
      If this DTD is not imbedded by a ISO12083:1994 Book or Article,
      the comment delimiters should be removed. -->
<!-- ===== -->

<!--ENTITY % a.types "(latin|greek|cyrillic|hebrew|kanji) latin" -->

<!-- ===== -->
<!-- Character transformations -->
<!-- ===== -->

<!-- ELEMENT MIN CONTENT EXPLANATIONS -->
<!ELEMENT bold - - (%p.trans;|#PCDATA)* -- bold -->
<!ELEMENT italic - - (%p.trans;|#PCDATA)* -- italic -->
<!ELEMENT sansser - - (%p.trans;|#PCDATA)* -- sans serif -->
<!ELEMENT typewrit - - (%p.trans;|#PCDATA)* -- typewriter -->
<!ELEMENT smallcap - - (%p.trans;|#PCDATA)* -- small caps -->
<!ELEMENT roman - - (%p.trans;|#PCDATA)* -- roman -->

```

```

<!-- ===== -->
<!-- Fractions -->
<!-- ===== -->

<!-- ELEMENT MIN CONTENT EXPLANATIONS -->
<!-- ELEMENT fraction - - (num, den) -- fraction -->
<!-- ELEMENT num - - (%p.trans;|%m.math;)* -- numerator -->
<!-- ELEMENT den - - (%p.trans;|%m.math;)* -- denominator -->
<!-- ELEMENT NAME VALUE DEFAULT -->
<!-- ATTTLIST fraction shape (built|case) #IMPLIED
align (left|center|right)
center
style (single|double|triple|dash|dot|bold|blank|none)
single >

<!-- ===== -->
<!-- Superiors, inferiors, accents, over and under -->
<!-- ===== -->

<!-- ELEMENT MIN CONTENT EXPLANATIONS -->
<!-- ELEMENT sup - - (%p.trans;|%m.math;)* -- superior -->
<!-- ELEMENT inf - - (%p.trans;|%m.math;)* -- inferior -->
<!-- ELEMENT NAME VALUE DEFAULT -->
<!-- ATTTLIST sup location (pre|post) post
arrange (compact|stagger)
compact >
<!-- ATTTLIST inf location (pre|post) post
arrange (compact|stagger) compact >

<!-- ===== -->
<!-- Embellishments -->
<!-- ===== -->

<!-- ELEMENT MIN CONTENT EXPLANATIONS -->
<!-- ELEMENT top - - (%p.trans;|%m.math;)*
-- top embellishment -->
<!-- ELEMENT middle - - (%p.trans;|%m.math;)*
-- middle, or "through" -->
<!-- ELEMENT bottom - - (%p.trans;|%m.math;)*
-- bottom embellishment -->
<!-- ELEMENT NAME VALUE DEFAULT -->
<!-- ATTTLIST top align (left|center|right)
center
sizeid ID #IMPLIED
-- to pass on the height -->
<!-- ATTTLIST middle align (left|center|right)
center
sizeid ID #IMPLIED
-- to pass on the height -->
<!-- ATTTLIST bottom align (left|center|right)
center
sizeid ID #IMPLIED
-- to pass on the height -->

```

```

<!-- The subform element is defined later -->

<!-- ===== -->
<!-- Fences, boxes, overlines and underlines -->
<!-- ===== -->

<!-- ELEMENT MIN CONTENT EXPLANATIONS -->
<!-- ELEMENT mark - 0 EMPTY >
<!-- ELEMENT fence - - (%p.trans;|%m.math;)* -- fence -->
<!-- ELEMENT post - 0 EMPTY -- post -->
<!-- ELEMENT box - - (%p.trans;|%m.math;)* -- box -->
<!-- ELEMENT overline - - (%p.trans;|%m.math;)* -- overline -->
<!-- ELEMENT undrline - - (%p.trans;|%m.math;)* -- underline -->

<!-- ELEMENT NAME VALUE DEFAULT -->
<!-- ATTLIST mark id ID #REQUIRED >
<!-- ATTLIST fence lpost CDATA "|" -- left post --
rpost CDATA "|" -- right post --
style (single|double|triple|dash|dot|bold|blank|none)
single
sizeid ID #IMPLIED
sizeref IDREF #IMPLIED
-- to pass on the height --
-- to pick up a height -->
<!-- ATTLIST post post CDATA "|"
style (single|double|triple|dash|dot|bold|blank|none)
single
sizeid ID #IMPLIED
sizeref IDREF #IMPLIED
-- to pass on the height --
-- to pick up a height -->
<!-- ATTLIST box style (single|double|triple|dash|dot|bold|blank|none)
single >
<!-- ATTLIST overline type CDATA "-" -- embellishment type --
style (single|double|triple|dash|dot|bold|blank|none)
single
start IDREF #IMPLIED
end IDREF #IMPLIED >
<!-- ATTLIST undrline type CDATA "_" -- embellishment type --
style (single|double|triple|dash|dot|bold|blank|none)
single
start IDREF #IMPLIED
end IDREF #IMPLIED >

<!-- ===== -->
<!-- Labelled arrows -->
<!-- ===== -->

<!-- ELEMENT MIN CONTENT EXPLANATIONS -->
<!-- ELEMENT subform - - (%p.trans;|%m.math;)* -- base element -->

```

```

<!--      ELEMENT      NAME      VALUE      DEFAULT      -->
<!--      <!--      subform      sizeid      ID      #IMPLIED      -->
-- to pass on a width, or
a height      --
--      sizeref      IDREF      #IMPLIED      -->
-- to pick up a width      -->

<!-- ===== -->
<!--      Roots      -->
<!-- ===== -->

<!--      ELEMENT      MIN      CONTENT      EXPLANATIONS      -->
<!--      <!--      radical      - -      (radix?, radicand) -- root or radical -->
<!--      <!--      radix      - -      (%p.trans;|%m.math;)* -- radix -->
<!--      <!--      radicand      0 0      (%p.trans;|%m.math;)* -- radicand -->

<!-- ===== -->
<!--      Arrays      -->
<!-- ===== -->

<!--      ELEMENT      MIN      CONTENT      EXPLANATIONS      -->
<!--      <!--      array      - -      (arrayrow+(arraycol+) -- array -->
<!--      <!--      arrayrow      - 0      (arraycel+) -- array row -->
<!--      <!--      arraycol      - 0      (arraycel+) -- array column -->
<!--      <!--      arraycel      - 0      (%p.trans;|%m.math;)* -- array cell -->

<!--      ELEMENT      NAME      VALUE      DEFAULT      -->
<!--      <!--      array      rowalign      NMTOKENS      #IMPLIED -- row alignment --
--      colalign      NMTOKENS      #IMPLIED -- column
-- alignment --
--      rowsep      NMTOKENS      #IMPLIED -- row separators --
--      colsep      NMTOKENS      #IMPLIED -- column
-- separators -->

<!-- ===== -->
<!--      Spacing      -->
<!-- ===== -->

<!--      ELEMENT      MIN      CONTENT      EXPLANATIONS      -->
<!--      <!--      hspace      - 0      EMPTY      -- horizontal spacing -->
<!--      <!--      vspace      - 0      EMPTY      -- vertical spacing -->
<!--      <!--      break      - 0      EMPTY      -- turn line, break -->
<!--      <!--      markref      - 0      EMPTY      -- hmark reference -->

<!--      ELEMENT      NAME      VALUE      DEFAULT      -->
<!--      <!--      hspace      space      CDATA      "1 mm"
-- units as required -->
<!--      <!--      vspace      space      CDATA      "1 mm"
-- units as required -->
<!--      <!--      markref      refid      IDREF      #REQUIRED
--      direct      (hor|ver)      hor
-- horizontal or vertical -->

```

```

<!-- ===== -->
<!-- Formula elements -->
<!-- ===== -->

<!-- ELEMENT          MIN  CONTENT          EXPLANATIONS -->
<!-- ELEMENT formula  - -  (%p.trans;%m.math;)*
                                     -- in-line formula -->
<!-- ELEMENT dformula - -  (%p.trans;%m.math;)*
                                     -- display formula -->
<!-- ELEMENT dformgrp - -  (formula|dformula)+
                                     -- display formula group -->

<!-- ELEMENT  NAME      VALUE      DEFAULT      -->
<!-- ATTLIST formula  id      ID      #IMPLIED
                        alphabet %a.types;
                        %SDAPREF;  "<?SDATRANS>Inline formula"
                        %SDASUSP;  "SUSPEND"
<!-- ATTLIST dformula id      ID      #IMPLIED
                        num      CDATA  #IMPLIED
                        align    (left|center|right)
                                     center
                        alphabet %a.types;
                        %SDAPREF;  "<?SDATRANS>Display formula"
                        %SDASUSP;  "SUSPEND"
<!-- ATTLIST dformgrp id      ID      #IMPLIED
                        num      CDATA  #IMPLIED
                        align    (left|center|right)
                                     center
                        %SDAPREF;  "<?SDATRANS>Display formula group"

```

Annex A

(informative)

Comments on the DTDs

A.1 Design philosophy

The Document Type Definitions comprising this International Standard are based on ANSI Z39.59-1988, Electronic Manuscript Preparation and Markup originally created by the Association of American Publishers (AAP). The structure of the original DTDs permit easy modification and extension. The present DTDs continue this philosophy.

ANSI Z39.59-1988 was designed before the SGML standard (ISO 8879:1986) was available. This International Standard draws on the experience gained with SGML since the completion of ANSI Z39.59-1988. All ambiguities, redundancies and formatting specific aspects were removed from ANSI Z39.59-1988. The short reference syntax is deprecated by this International Standard, but short references can be added by current users. The names of the generic identifiers were made longer and more meaningful. Five major groups influenced the modifications of ANSI Z39.59-1988:

- a. The European Workgroup on SGML. The work of this group of European publishers was published in 1991, in the form of the Majour DTD for article headers. Elements and attributes which were required to make ANSI Z39.59-1988 compatible with Majour were added.
- b. The European Physical Society. This professional organization submitted a set of comments which were all applied. The Society endorses the use of this International Standard by its members.
- c. International Committee for Accessible Document Design (ICADD). These comments enable easy translation of SGML coded documents using ISO 12083 into Braille, large type and computer voice. ICADD endorses the use of this International Standard. (See Annex A.8)
- d. ISO 10744:1992, HyTime. Several comments on the draft of this International Standard mentioned the lack of facilities for hypertext. Documents conforming to this International Standard are minimal hyperlinking HyTime documents.
- e. The AAP Math Update Committee. The objective of this committee was to make a harmonized DTD for mathematics that would replace the mathematics DTD in ISO/IEC TR 9573:1988, the AAP mathematics DTD and the DTD in use by the Euromath project. Several comments on the draft of this International Standard proposed that this International Standard adopt the work of this committee.