

STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Amendment No. 1
to
AS/NZS 4601:1999
Vehicle immobilizers

REVISED TEXT

The 1999 edition of AS/NZS 4601 is amended as follows; the amendment(s) should be inserted in the appropriate place(s).

SUMMARY: This Amendment applies to the Clauses 1.3.8, 2.2.11, 2.2.12, 2.3.3, 3.3.7(a)(i) and 3.3.9.

Published on 18 March 2003.

Approved for publication in New Zealand on behalf of the Standards Council of New Zealand on 5 March 2003.

AMDT
No. 1
MAR
2003

Page 5 Clause 1.3.7(A)

Add the following definition:

1.3.7(A) Primary wires

Wires consisting of immobilizer wires, supply line wires, ignition wires and door/boot/bonnet wires.

AMDT
No. 1
MAR
2003

Page 9 Clause 2.2.11

Delete the last paragraph and *replace* with the following:

The current consumption of the VSIS in the set state, including all of its sensors, shall not exceed 30 mA (mean value) at nominal voltage.

AMDT
No. 1
MAR
2003

Page 9 Clause 2.2.12

Delete existing text and *replace* with the following:

All primary wires emanating from and connecting to the VSIS control unit shall be black in colour and of the same diameter. There shall be a minimum of nine black coloured wires emanating from/connecting to the control unit. All installation labels shall be removed after installation. Plugs and sockets concerned with the primary wires shall be fully contained by the VSIS control unit housing.

AMDT
No. 1
MAR
2003

Page 9 Clause 2.3.3

Add the following after the first paragraph:

There shall not be a master override PIN.

AMDT
No. 1
MAR
2003

Page 15 Clause 3.3.7(a)(i)

Replace the text comprising the third and fourth sentences with the following:

The VSIS shall comply with functional status Class C for test pulses 1 and 2 and functional status Class A for all other pulses.

Page 16 Clause 3.3.9

Delete existing text and *replace* with the following:

The sound pressure level and frequency band of any optional acoustic signalling device, if fitted, shall meet the requirements of AS/NZS 3749.1.
