

ANSI/ASABE AD11001-1:2016 NOV2016

Agricultural wheeled tractors — Three-point hitch couplers — Part 1: U-frame coupler



STANDARD

American Society of Agricultural and Biological Engineers

ASABE is a professional and technical organization, of members worldwide, who are dedicated to advancement of engineering applicable to agricultural, food, and biological systems. ASABE Standards are consensus documents developed and adopted by the American Society of Agricultural and Biological Engineers to meet standardization needs within the scope of the Society; principally agricultural field equipment, farmstead equipment, structures, soil and water resource management, turf and landscape equipment, forest engineering, food and process engineering, electric power applications, plant and animal environment, and waste management.

NOTE: ASABE Standards, Engineering Practices, and Data are informational and advisory only. Their use by anyone engaged in industry or trade is entirely voluntary. The ASABE assumes no responsibility for results attributable to the application of ASABE Standards, Engineering Practices, and Data. Conformity does not ensure compliance with applicable ordinances, laws and regulations. Prospective users are responsible for protecting themselves against liability for infringement of patents.

ASABE Standards, Engineering Practices, and Data initially approved prior to the society name change in July of 2005 are designated as "ASAE", regardless of the revision approval date. Newly developed Standards, Engineering Practices and Data approved after July of 2005 are designated as "ASABE".

Standards designated as "ANSI" are American National Standards as are all ISO adoptions published by ASABE. Adoption as an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by ASABE.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

CAUTION NOTICE: ASABE and ANSI standards may be revised or withdrawn at any time. Additionally, procedures of ASABE require that action be taken periodically to reaffirm, revise, or withdraw each standard.

Copyright American Society of Agricultural and Biological Engineers. All rights reserved.

ASABE, 2950 Niles Road, St. Joseph, MI 49085-9659, USA, phone 269-429-0300, fax 269-429-3852, hq@asabe.org

Agricultural wheeled tractors — Three-point hitch couplers — Part 1: U-frame coupler

These materials are subject to copyright claims of ISO and ASABE. No part of this publication may be reproduced in any form, including an electronic retrieval system, without the prior written permission of ASABE. All request pertaining to the ANSI/ASABE AD11001-1:2016 NOV2016 Standard should be submitted to ASABE.

ANSI/ASAE S278 history: Proposed by Advisory Engineering Committee of Farm and Industrial Equipment Institute; approved by ASAE Power and Machinery Division Technical Committee; adopted by ASAE December 1964; revised December 1965, June 1967; reconfirmed December 1971; revised April 1974, February 1975; corrected editorially April 1977; revised December 1978, March 1980; reconfirmed December 1984; revised editorially and reconfirmed December 1989; reaffirmed December 1994; revised editorially February 1995; reaffirmed December 1999, January 2001, December 2001, February 2003. Adoption with modification of ISO 11001-1:1993 and addition of ASAE Foreword with deviations July 2003. Approved by ANSI September 2003; reaffirmed by ASABE February 2009; reaffirmed by ANSI May 2009; ASABE periodic review extended one year October 2013; ANSI periodic review extended to October 21, 2015 on April 21, 2014. Replaced by adoption with deviations of ISO 11001-1:2016 and approved by ANSI November 2016.

Keywords: Coupler, Hitch, Implements, Three-point, Tractors

0 Foreword

0.1 ANSI/ASABE AD11001-1:2016, Agricultural wheeled tractors — Three-point hitch couplers — Part 1: U-frame coupler, is an adoption with deviations of the identically titled ISO 11001-1:2016, Agricultural wheeled tractors — Three-point hitch couplers — Part 1: U-frame coupler. Deviations noted in the following Foreword sections pertain to those provisions where harmonization could not be achieved between ASABE and the International Standard.

Deviations from the subsequently printed international standard are noted with underscore (addition) or strikethrough (deletions) text. Deviations from the international standard figures and equations are clearly marked.

0.2 This part of ISO 11001 specifies the essential dimensions for the attachment of three-point hitch implements to agricultural wheeled and track-laying tractors equipped with a three-point free link hitch according to ANSI/ASABE AD730:2009 W/Amd. 1:2014 or ANSI/ASABE AD8759-1:1998 and a U-frame hitch coupler.

NOTE In general the dimensions associated with the tractor and implement for use with hitch couplers are the same as those for the three-point linkage specified in ANSI/ASABE AD730:2009 W/Amd. 1:2014 or ANSI/ASABE AD8759-1:1998, and those for the clearance zone specified in ISO 2332.

The three-point hitch coupler systems constitute a special method of implement mounting. The hitch couplers are an additional component located between the three-point linkage and the implement, making it possible to hitch and unhitch from the operator's seat. Due to the special construction and function of hitch couplers, it can be necessary to vary the length of the upper and lower links indicated in the referenced standards.

This part of ISO 11001 applies to categories 1, 2N, 2, 3N, 3, 4N, and 4 of agricultural wheeled and tracklaying tractors as defined in ANSI/ASABE AD730:2009 W/Amd. 1:2014 or ANSI/ASABE AD8759-1:1998.

0.3 Three normative references are listed in ISO 11001-1:2016. The responsible ASABE committee has reviewed these references and approved the following deviations.

0.3.1 Replace ISO 730, Agricultural wheeled tractors — Rear-mounted three-point linkage — Categories 1N, 1, 2N, 2, 3N, 3, 4N and 4, with ANSI/ASABE AD730:2009 W/Amd. 1:2014, Agricultural wheeled tractors — Rear-mounted three-point linkage — Categories 1N, 1, 2N, 2, 3N, 3, 4N and 4. Any reference to ISO 730 in the printed portion of ISO 11001-1:2016 shall be replaced by ANSI/ASABE AD730:2009 W/Amd. 1:2014.

0.3.2 Replace ISO 8759-1, Agricultural wheeled tractors — Front-mounted equipment — Part 1: Power take-off and three-point linkage, with ANSI/ASABE AD8759-1:1998, Agricultural wheeled tractors — Front-mounted equipment — Part 1: Power take-off and three-point linkage. Any reference to ISO 8759-1 in the printed portion of ISO 11001-1:2016 shall be replaced by ANSI/ASABE AD8759-1:1998.

0.4 This standard has been approved as an American National standard by ANSI (American National Standard Institute). The original content of ISO 11001-1 was based on ASABE standard S278.

0.5 This standard deviates from ISO 11001-1:2016 as follows:

0.5.1 See Section 0.3 for Normative reference deviations.

0.5.2 Replace 4.8 with the following:

For tractors designed with U-frame couplers as standard equipment, the lower links should be shortened so that the distance to the lower U-frame coupler jaw falls within the range for dimension L specified in ANSI/ASABE AD730:2009 W/Amd. 1:2014. For tractors that offer U-frame couplers as an option, the lower links should be designed to the minimum L dimension given in ANSI/ASABE AD730:2009 W/Amd. 1:2014 as far as possible to minimize the distance that the combined lower link and U-frame coupler length is over the upper limit of the L dimension given in ANSI/ASABE AD730:2009 W/Amd. 1:2014.

NOTE For hitch Category 1, dimension B_1 in this part of ISO 11001 means the lower socket offset may be larger than the range allowed in ANSI/ASABE AD730:2009 W/Amd. 1:2014.

Text of ISO 11001-1:2016, Agricultural wheeled tractors — Three-point hitch couplers — Part 1: U-frame coupler, with deviations noted, follows.

1 Scope

This part of ISO 11001 specifies the essential dimensions for the attachment of three-point hitch implements to agricultural wheeled and track-laying tractors equipped with a three-point free link hitch according to ~~ISO 730~~ [ANSI/ASABE AD730:2009 W/Amd. 1:2014](#) or ~~ISO 8759-1~~ [ANSI/ASABE AD8759-1:1998](#) and a U-frame hitch coupler.

NOTE In general the dimensions associated with the tractor and implement for use with hitch couplers are the same as those for the three-point linkage specified in ~~ISO 730~~ [ANSI/ASABE AD730:2009 W/Amd. 1:2014](#) or ~~ISO 8759-1~~ [ANSI/ASABE AD8759-1:1998](#), and those for the clearance zone specified in ISO 2332.

The three-point hitch coupler systems constitute a special method of implement mounting. The hitch couplers are an additional component located between the three-point linkage and the implement, making it possible to hitch and unhitch from the operator's seat. Due to the special construction and function of hitch couplers, it can be necessary to vary the length of the upper and lower links indicated in the referenced standards.

This part of ISO 11001 applies to categories 1, 2N, 2, 3N, 3, 4N, and 4 of agricultural wheeled and tracklaying tractors as defined in ~~ISO 730~~ [ANSI/ASABE AD730:2009 W/Amd. 1:2014](#) or ~~ISO 8759-1~~ [ANSI/ASABE AD8759-1:1998](#).