

**ASAE EP408.3 OCT2014 (R2018)**  
**Surface Irrigation Runoff Reuse Systems**



**American Society of  
Agricultural and Biological Engineers**

**S  
T  
A  
N  
D  
A  
R  
D**

ASABE is a professional and technical organization, of members worldwide, who are dedicated to advancement of engineering applicable to agricultural, food, and biological systems. ASABE Standards are consensus documents developed and adopted by the American Society of Agricultural and Biological Engineers to meet standardization needs within the scope of the Society; principally agricultural field equipment, farmstead equipment, structures, soil and water resource management, turf and landscape equipment, forest engineering, food and process engineering, electric power applications, plant and animal environment, and waste management.

**NOTE:** ASABE Standards, Engineering Practices, and Data are informational and advisory only. Their use by anyone engaged in industry or trade is entirely voluntary. The ASABE assumes no responsibility for results attributable to the application of ASABE Standards, Engineering Practices, and Data. Conformity does not ensure compliance with applicable ordinances, laws and regulations. Prospective users are responsible for protecting themselves against liability for infringement of patents.

ASABE Standards, Engineering Practices, and Data initially approved prior to the society name change in July of 2005 are designated as "ASAE", regardless of the revision approval date. Newly developed Standards, Engineering Practices and Data approved after July of 2005 are designated as "ASABE".

Standards designated as "ANSI" are American National Standards as are all ISO adoptions published by ASABE. Adoption as an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by ASABE.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

**CAUTION NOTICE:** ASABE and ANSI standards may be revised or withdrawn at any time. Additionally, procedures of ASABE require that action be taken periodically to reaffirm, revise, or withdraw each standard.

Copyright American Society of Agricultural and Biological Engineers. All rights reserved.

ASABE, 2950 Niles Road, St. Joseph, MI 49085-9659, USA, phone 269-429-0300, fax 269-429-3852, [hq@asabe.org](mailto:hq@asabe.org)



**Documents**

Document Sharing Hub

# Surface Irrigation Runoff Reuse Systems

*Developed by the ASAE Surface Irrigation Committee; approved by the Soil and Water Division Standards Committee; adopted by ASAE November 1981; revised February 1987; revised editorially July 1989; reconfirmed December 1991; reaffirmed December 1992, December 1993, revised March 1995; reaffirmed December 1999, February 2005, January 2010; revised October 2014, reaffirmed October 2018.*

**Keywords:** Irrigation, Runoff

## 1 Purpose and Scope

**1.1** This Engineering Practice is a guide to engineers, technicians and farmers designing and operating systems to collect runoff from surface irrigated fields for subsequent use on the same or other fields. Tailwater runoff reuse is most commonly applied to furrow irrigation, but the concepts apply to any irrigation system that produces runoff and to the reuse of subsurface drain water. This Engineering Practice is not intended to serve as a complete set of design criteria and specifications for construction. All systems should be designed in conformance with local regulations (i.e., construction, safety, and water quality standards).

## 2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies unless noted. For undated references, the latest approved edition of the referenced document (including any amendments) applies.

ANSI/ASAE EP302.4, *Design and Construction of Surface Drainage Systems on Agricultural Lands in Humid Areas*

ANSI/ASAE S376.2, *Design, Installation and Performance of Underground, Thermoplastic Irrigation Pipelines*

ANSI/ASAE S397.4, *Electrical Service and Equipment for Irrigation*

ASAE EP267.7, *Prevention of Mosquito Problems Associated with Irrigation and Drainage Systems*

ASAE S318.17, *Safety for Agricultural Field Equipment*

ASAE EP369.1, *Design of Agricultural Drainage Pumping Plants*

ASAE S442.1, *Water and Sediment Control Basins*

ASAE S526.3, *Soil and Water Terminology*

## 3 Benefits

**3.1** Irrigation runoff reuse systems can improve irrigation efficiency, improve downstream water quality, reduce irrigation labor, and conserve soil and nutrient resources. Reuse systems enable irrigators (farm irrigation water managers) to meet surface water discharge restrictions.

**3.2 Water savings.** Irrigation practices to uniformly distribute water on sloping, open-ended, furrow-irrigated fields usually result in 20 to 50% of the applied water running off. Water may also run off from border-irrigated fields. Runoff reuse reduces water loss from the farm.

**3.2.1** Basin-wide water savings from on-farm reuse may be much less than on-farm savings. Runoff from a farm often reenters a downstream irrigation delivery system and is reused. If on-farm reuse decreases downstream water supplies, water deliveries may have to be adjusted to satisfy downstream water rights, including reduced deliveries to farmers who reuse their runoff.

**3.2.2** For maximum water and labor savings, runoff reuse systems should be integrated with the total farm irrigation system. Pumping capacities, delivery points, storage locations, and storage capacities should be designed to give the farmer flexibility in the use of water and allow efficient conjunctive use with other irrigation water supplies.

**3.3 Water quality.** Collection and reuse of runoff keeps eroded soil, and water- and soil-borne pollutants on the originating farm. Potential pollutants include sediment, plant residues, nutrients, agricultural chemicals, plant pathogens, nematodes, and weed seeds. The irrigated farm benefits from conservation of soil and nutrients. Downstream irrigators and other water users benefit from cleaner, safer water supplies. Downstream water quality improvement is a primary reason for runoff reuse in some areas.

**3.4 Chemical application.** When agricultural chemicals or nutrients that have potential to cause economic or environmental damages downstream are applied in surface irrigation water, a runoff reuse system should be used to prevent transport of those chemicals to downstream users and water bodies.

## 4 System Components

**4.1** Irrigation runoff reuse systems have four basic components:

- runoff collection and conveyance channels (tailwater ditches, drains);
- storage reservoir (tailwater pit, pond, sump);
- pumping plant (reuse, return, pumpback pump);
- delivery pipe (return, pumpback pipe).

**4.2 Collection.** Runoff from irrigated fields is intercepted by a system of open channels or pipelines and conveyed by gravity to a storage reservoir or pumping plant.

**4.2.1** Capacity of the channels and pipelines should be sufficient to convey the maximum expected runoff rate from irrigation. Also, the collection system should be able to safely convey or bypass runoff from precipitation.

**4.2.2** Runoff collection channels should be designed to minimize channel erosion. In erodible soils, flow velocities greater than 0.5 m/s may result in erosion. Erosion potential can be reduced by reducing flow velocity with check/drop structures, shallow cross sections, or rough surfaces; or by protecting the soil surface with vegetation or other erosion resistant materials. ANSI/ASAE S302 describes some aspects of channel design for erosion control.

**4.2.3 Sedimentation.** Runoff water carrying sediments increase maintenance requirements for conveyance channels and pipelines, the storage reservoir, and the pump. On-field practices that reduce erosion and sediment runoff (improved water management, reduced tillage, residue management, and vegetated filter strips at the outflow ends of fields) should be applied.

**4.2.3.1** If erosion is not adequately controlled at the field, a sediment collection basin should be constructed in the runoff collection system. The sediment basin should provide a one-to-two hour flow detention time to allow the sand and most silt-sized sediments to settle out. Basins should be dimensioned to allow sediment removal