

ASAE EP538.2 OCT2008 (R2018)
Design Loads for Bunker (Horizontal) Silos



**American Society of
Agricultural and Biological Engineers**

**S
T
A
N
D
A
R
D**

ASABE is a professional and technical organization, of members worldwide, who are dedicated to advancement of engineering applicable to agricultural, food, and biological systems. ASABE Standards are consensus documents developed and adopted by the American Society of Agricultural and Biological Engineers to meet standardization needs within the scope of the Society; principally agricultural field equipment, farmstead equipment, structures, soil and water resource management, turf and landscape equipment, forest engineering, food and process engineering, electric power applications, plant and animal environment, and waste management.

NOTE: ASABE Standards, Engineering Practices, and Data are informational and advisory only. Their use by anyone engaged in industry or trade is entirely voluntary. The ASABE assumes no responsibility for results attributable to the application of ASABE Standards, Engineering Practices, and Data. Conformity does not ensure compliance with applicable ordinances, laws and regulations. Prospective users are responsible for protecting themselves against liability for infringement of patents.

ASABE Standards, Engineering Practices, and Data initially approved prior to the society name change in July of 2005 are designated as "ASAE", regardless of the revision approval date. Newly developed Standards, Engineering Practices and Data approved after July of 2005 are designated as "ASABE".

Standards designated as "ANSI" are American National Standards as are all ISO adoptions published by ASABE. Adoption as an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by ASABE.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

CAUTION NOTICE: ASABE and ANSI standards may be revised or withdrawn at any time. Additionally, procedures of ASABE require that action be taken periodically to reaffirm, revise, or withdraw each standard.

Copyright American Society of Agricultural and Biological Engineers. All rights reserved.

ASABE, 2950 Niles Road, St. Joseph, MI 49085-9659, USA, phone 269-429-0300, fax 269-429-3852, hq@asabe.org

Design Loads for Bunker (Horizontal) Silos

Developed by the ASAE Horizontal Silo Loads Subcommittee of the Structures Group; approved by the Structures and Environment Division Standards Committee; adopted by ASAE December 1996; reaffirmed December 2001, January 2007; revised editorially January 2007; revised December 2007, October 2008; reaffirmed November 2013, November 2018.

Keywords: Bunker, Design, Loads, Silos

1 Purpose and Scope

1.1 This Standard is intended to provide design loads for the walls of bunker (horizontal) silos for storing whole plant silages.

1.2 The design loads in this Standard do not include hydrostatic pressures that may occur when the silage becomes saturated.

2 Terminology

2.1 bunker (horizontal) silo: A storage bunker for silage with a floor at ground level and walls on two or three sides to retain the silage material, which is compacted with a tractor or other heavy vehicle.

2.2 silage load: The load that the silage exerts on the silo wall after compaction of the silage is completed.

2.3 compaction load: The load transferred through the silage onto the silo wall from the compaction equipment operating on the surface of the silage.

3 Nomenclature

DM is dry matter fraction of silage

g is gravitational acceleration (9.81 m/s^2)

K is pressure factor

K_f is force factor

L is design line load normal to wall, N/m

L_t is load per unit length on one track, N/m

p is silage pressure normal to wall, Pa

P is design load normal to the wall, N

P_w is maximum wheel load, N

