

ASABE/ISO 12140-1:2020 JUN2024

Agricultural trailers and trailed equipment — Drawbar jacks — Part 1: Design safety, test methods and acceptance criteria



ASABE

American Society of Agricultural
and Biological Engineers



STANDARD

ASABE is a professional and technical organization, of members worldwide, who are dedicated to advancement of engineering applicable to agricultural, food, and biological systems. ASABE Standards are consensus documents developed and adopted by the American Society of Agricultural and Biological Engineers to meet standardization needs within the scope of the Society; principally agricultural field equipment, farmstead equipment, structures, soil and water resource management, turf and landscape equipment, forest engineering, food and process engineering, electric power applications, plant and animal environment, and waste management.

NOTE: ASABE Standards, Engineering Practices, and Data are informational and advisory only. Their use by anyone engaged in industry or trade is entirely voluntary. The ASABE assumes no responsibility for results attributable to the application of ASABE Standards, Engineering Practices, and Data. Conformity does not ensure compliance with applicable ordinances, laws and regulations. Prospective users are responsible for protecting themselves against liability for infringement of patents.

ASABE Standards, Engineering Practices, and Data initially approved prior to the society name change in July of 2005 are designated as “ASAE”, regardless of the revision approval date. Newly developed Standards, Engineering Practices and Data approved after July of 2005 are designated as “ASABE”.

Standards designated as “ANSI” are American National Standards as are all ISO adoptions published by ASABE. Adoption as an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by ASABE.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

CAUTION NOTICE: ASABE and ANSI standards may be revised or withdrawn at any time. Additionally, procedures of ASABE require that action be taken periodically to reaffirm, revise, or withdraw each standard.

ASABE, 2950 Niles Road, St. Joseph, MI 49085-9659, USA, phone 269-429-0300, hq@asabe.org

Agricultural trailers and trailed equipment — Drawbar jacks — Part 1: Design safety, test methods and acceptance criteria

These materials are subject to copyright claims of ISO and ASABE. No part of this publication may be reproduced in any form, including an electronic retrieval system, without the prior written permission of ASABE. All requests pertaining to ASABE/ISO 12140-1:2020 standard should be submitted to ASABE.

History of ASAE S485: Developed by the ASAE Implement Jacks Committee; approved by the Power and Machinery Standards Division Committee; adopted by ASAE October 2001; reaffirmed February 2006; revised April 2007, revised November 2010; revised April 2011.

ASAE S485 was used as the basis document for ISO 12140:2013. Agricultural machinery — Agricultural trailers and trailed equipment — Drawbar jacks. ASAE S485 replaced by an identical adoption of ISO 12140:2013 and approved as an American National Standard June 2014; reaffirmed December 2018; replaced by an identical adoption of ISO 12140-1:2020 June 2024.

Keywords: Implement, Jack, Safety, Trailer

0 Foreword

0.1 ASABE/ISO 12140-1:2020 JUN2024, Agricultural trailers and trailed equipment — Drawbar jacks — Part 1: Design safety, test methods and acceptance criteria, is an adoption without modification of the identically titled ISO 12140-1:2020, Agricultural trailers and trailed equipment — Drawbar jacks — Part 1: Design safety, test methods and acceptance criteria.

0.2 ASABE/ISO 12140-1:2020 JUN2024 specifies criteria for construction, establishes performance test methods and defines acceptance criteria for telescopic mechanical screw- and nut-type drawbar jacks and hydraulic drawbar jacks intended to be fitted on the implement tongue of interchangeable towed machinery [here after referred to as "implement(s)"] as original equipment or as replacement jacks. In addition, it specifies minimum markings and information for use to be provided by the jack manufacturer.

These jacks are used specifically for

- supporting the hitch points of implements during storage;
- lifting and lowering of implement tongues to facilitate attaching to or disconnecting from an agricultural tractor; and
- levelling an implement for stationary use.

0.3 One normative reference is listed in ISO 12140-1:2020. This reference has been reviewed and accepted as part of the adoption of the ISO 12140-1:2020 in ASABE/ISO 12140-1:2020.

0.4 This standard has been approved as an American National standard by ANSI (American National Standard Institute). The original content of ISO 12140 was based on ASAE S485.3, Implement Mounted, Screw-Type Jacks.

Text of ISO 12140-1:2020, Agricultural trailers and trailed equipment — Drawbar jacks — Part 1: Design safety, test methods and acceptance criteria, follows.

Agricultural trailers and trailed equipment — Drawbar jacks — Part 1: Design safety, test methods and acceptance criteria

1 Scope

This document specifies criteria for construction, establishes performance test methods and defines acceptance criteria for telescopic mechanical screw- and nut-type drawbar jacks and hydraulic drawbar jacks intended to be fitted on the implement tongue of interchangeable towed machinery [here after referred to as "implement(s)"] as original equipment or as replacement jacks. In addition, it specifies minimum markings and information for use to be provided by the jack manufacturer.

These jacks are used specifically for

- supporting the hitch points of implements during storage;
- lifting and lowering of implement tongues to facilitate attaching to or disconnecting from an agricultural tractor; and
- levelling an implement for stationary use.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 9227, Corrosion tests in artificial atmospheres — Salt spray tests

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at [https:// www .iso .org/ obp](https://www.iso.org/obp)
- IEC Electropedia: available at [http:// www .electropedia .org/](http://www.electropedia.org/)

3.1 jack

hand or power-operated telescopic mechanism with a ground contact pad (base) or wheel and fixing point [jack mount (3.11) or mounting point] designed for controlled vertical movement

NOTE 1 to entry: A hand-operated jack typically uses mechanical means to control vertical movement. A powered operated jack typically uses hydraulic fluid displacement to control vertical movement.

3.2 static compressive load

vertical force used to support the intended application under static conditions

3.3 dynamic compressive load

vertical force used to lift the intended application measured during actuation of the jack

3.4 static tensile load

force opposite of static compressive load (3.2) resulting in a tension load applied to the jack (3.1)

3.5 dynamic tensile load

force opposite of dynamic compressive load (3.3) resulting in a tension load applied to the jack (3.1)

3.6 side load

< fore-aft > force applied in a plane perpendicular to the longitudinal axis of the jack (3.1) in a direction generally aligning with the towing direction of the implement

3.7 side load

< lateral > force applied in a plane perpendicular to the longitudinal axis of the jack (3.1) at right angles to the general towing direction of the implement

3.8 screw and nut

threaded shaft and nut that transforms rotational motion of the crank assembly (3.13) into linear motion of the jack (3.1)

3.9 outer tube

tube with the largest cross-sectional dimension

3.10 inner tube

free-moving and generally smaller tube moving within the outer tube (3.9)

3.11 jack mount

portion of the outer tube (3.9) that mates with the implement mount

3.12 swivel mount

mounting method that allows the jack (3.1) to be rotated to a storage position without removing the jack from the implement

3.13 crank assembly

device used to actuate the screw (3.8) to extend or retract the jack (3.1)

3.14 base

contact pad

bottom load bearing portion of the inner tube (3.10) or drop leg, if provided, that transmits force to the ground or floor

3.15 jack cycle

extension of the jack through 65% of the jack travel and retraction back to its original length

NOTE 1 to entry: If a particular jack has added travel for the purpose of greater unloaded range, the jack cycle can be based on 65% of the normal travel.

3.16 extended length

maximum attainable dimension from the centre of the jack mount (3.11) to the bottom of the base (3.14) of the jack (3.1)

3.17 basic rated life

L_{10}

90% of the reliable life of samples tested that pass a given requirement

3.18 rated static compressive load capacity

static compressive load (3.2) that the jack (3.1) is rated to support or sustain while meeting the requirements of this document

3.19 rated dynamic compressive load capacity

dynamic compressive load (3.3) that the jack (3.1) is rated to repeatedly lift while meeting the requirements of this document

3.20 rated static tensile load capacity

static tensile load (3.4) that the jack (3.1) is rated to sustain while meeting the requirements of this document