

ASAE S374 MAR1975 (R2015)

Terminology and Specification Definitions for Agricultural Auger Conveying Equipment



**American Society of
Agricultural and Biological Engineers**

**S
T
A
N
D
A
R
D**

ASABE is a professional and technical organization, of members worldwide, who are dedicated to advancement of engineering applicable to agricultural, food, and biological systems. ASABE Standards are consensus documents developed and adopted by the American Society of Agricultural and Biological Engineers to meet standardization needs within the scope of the Society; principally agricultural field equipment, farmstead equipment, structures, soil and water resource management, turf and landscape equipment, forest engineering, food and process engineering, electric power applications, plant and animal environment, and waste management.

NOTE: ASABE Standards, Engineering Practices, and Data are informational and advisory only. Their use by anyone engaged in industry or trade is entirely voluntary. The ASABE assumes no responsibility for results attributable to the application of ASABE Standards, Engineering Practices, and Data. Conformity does not ensure compliance with applicable ordinances, laws and regulations. Prospective users are responsible for protecting themselves against liability for infringement of patents.

ASABE Standards, Engineering Practices, and Data initially approved prior to the society name change in July of 2005 are designated as "ASAE", regardless of the revision approval date. Newly developed Standards, Engineering Practices and Data approved after July of 2005 are designated as "ASABE".

Standards designated as "ANSI" are American National Standards as are all ISO adoptions published by ASABE. Adoption as an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by ASABE.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

CAUTION NOTICE: ASABE and ANSI standards may be revised or withdrawn at any time. Additionally, procedures of ASABE require that action be taken periodically to reaffirm, revise, or withdraw each standard.

Copyright American Society of Agricultural and Biological Engineers. All rights reserved.

ASABE, 2950 Niles Road, St. Joseph, MI 49085-9659, USA, phone 269-429-0300, fax 269-429-3852, hq@asabe.org

Terminology and Specification Definitions for Agricultural Auger Conveying Equipment

Proposed for the Auger and Elevator Manufacturers Council of the Farm and Industrial Equipment Institute; approved by the ASAE Power and Machinery Division Standards Committee; adopted by ASAE March 1975; reaffirmed December 1979, December 1984, December 1989; revised editorially September 1990; reaffirmed December 1990; December 1995, January 2001, February 2006; January 2011, December 2015.

Keywords: Auger, Conveying, Definitions

1 Purpose and Scope

1.1 The purpose of this Standard is to provide uniform terminology, performance specifications and dimensional specifications for portable farm augers and their related accessories designed primarily for conveying agricultural materials on farms.

2 Performance Specifications

2.1 Capacity. The capacity of units shall be expressed in bushels per hour (one bushel = 1.244 cubic feet) or liters per hour.

2.2 Power. The power requirements shall be expressed in horsepower or watts.

3 Dimensional Specifications (See Figure 1)

3.1 auger length: The length of the tube assembly including any intake but not including any intake hopper or head drive components (dimension A)

3.2 intake length: The length of the visible flighting with the control gate (if unit is so equipped) in the full open position (dimension B)

3.3 transport angle: The angle included between the auger tube and the ground when the unit is in the lowest recommended transport position and with hitch on the ground (dimension C)

3.4 maximum operating angle: The angle included between the auger tube and the ground when the unit is in the highest recommended operating position, and with the hitch on the ground (dimension D)

3.5 auger size: The outside diameter of the auger tube (dimension E)

3.6 reach at maximum height: The horizontal distance from the foremost part of the undercarriage to the center of the discharge end when the unit is at the maximum recommended operating angle with hitch on ground (dimension F)

3.7 maximum lift height: The vertical distance from the ground to the lowest point of the discharge (excluding down spout attachments) when the unit is raised to the maximum recommended operating angle and with the hitch on the ground (dimension G)

3.8 Transport height: The vertical distance from the ground to the uppermost portion with the unit in the lowest transport position and with the hitch on the ground (dimension H)