

ANSI/ASAE S396.3 JUN2016
Combine Capacity and Performance Test Procedure



STANDARD

American Society of Agricultural and Biological Engineers

ASABE is a professional and technical organization, of members worldwide, who are dedicated to advancement of engineering applicable to agricultural, food, and biological systems. ASABE Standards are consensus documents developed and adopted by the American Society of Agricultural and Biological Engineers to meet standardization needs within the scope of the Society; principally agricultural field equipment, farmstead equipment, structures, soil and water resource management, turf and landscape equipment, forest engineering, food and process engineering, electric power applications, plant and animal environment, and waste management.

NOTE: ASABE Standards, Engineering Practices, and Data are informational and advisory only. Their use by anyone engaged in industry or trade is entirely voluntary. The ASABE assumes no responsibility for results attributable to the application of ASABE Standards, Engineering Practices, and Data. Conformity does not ensure compliance with applicable ordinances, laws and regulations. Prospective users are responsible for protecting themselves against liability for infringement of patents.

ASABE Standards, Engineering Practices, and Data initially approved prior to the society name change in July of 2005 are designated as "ASAE", regardless of the revision approval date. Newly developed Standards, Engineering Practices and Data approved after July of 2005 are designated as "ASABE".

Standards designated as "ANSI" are American National Standards as are all ISO adoptions published by ASABE. Adoption as an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by ASABE.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

CAUTION NOTICE: ASABE and ANSI standards may be revised or withdrawn at any time. Additionally, procedures of ASABE require that action be taken periodically to reaffirm, revise, or withdraw each standard.

Copyright American Society of Agricultural and Biological Engineers. All rights reserved.

ASABE, 2950 Niles Road, St. Joseph, MI 49085-9659, USA, phone 269-429-0300, fax 269-429-3852, hq@asabe.org

ANSI/ASAE S396.3 JUN2016

Revision approved June 2016 YEAR as an American National Standard

Combine Capacity and Performance Test Procedure

Developed by the ASAE Grain Harvesting Committee; approved by the Power and Machinery Division Standards Committee; adopted by ASAE as a Tentative Standard March 1979; reaffirmed December 1979; reclassified as a full Standard February 1981; reaffirmed December 1985; revised March 1988; approved as an American National Standard August 1988; revised January 1991; reaffirmed December 1994, December 1995, December 1996; March 1998, December 2001, March 2004; February 2009; reaffirmed January 2014; revised June 2016.

Keywords: Capacity, Combine, Harvesting, Residue, Test procedure

1 Purpose and Scope

1.1 This Standard is intended to provide the basic requirements for a uniform procedure for measuring and reporting combine capacity, as defined in American National Standard ANSI/ASAE S343, Terminology for Combines and Grain Harvesting. Because crop conditions are variable and uncontrollable, the procedure provides only for the comparative testing of one combine, or one combine configuration, relative to another, in a particular crop condition.

1.2 In addition to measuring and reporting combine capacity, this Standard is also intended to provide the basic requirements for evaluating the uniformity of material spread from harvest residue spreading or chopping device(s). Harvest residue spreaders may be evaluated for spreading either straw or chaff separately or as a system for spreading both together.

2 Normative References

ANSI/ASAE S343, Terminology for Combines and Grain Harvesting

ANSI/ASAE S358, Moisture Measurement — Forages.

ANSI/ASAE S424, Method of Determining and Expressing Particle Size of Chopped Forage Materials by Screening

ASAE S352, Moisture Measurement — Unground Grain and Seeds

USDA 810, Official United States Standards for Grains

3 Terminology

3.1 test combine: The combine or combine configuration to be tested

3.2 comparison combine: The combine or combine configuration with which the test combine is being compared

3.3 test run: The events necessary to record a single set of measurements

3.4 test series: All the events and data of the test combine and the comparison combine that define their performance during the test runs on each combine

3.5 catch: Any material collected during a test run

3.5.1 grain catch: Any material collected through the primary clean grain discharge point for the purpose of sample analysis

3.5.2 separator system catch: Any material collected from the machine's normal point of discharge from the separator

3.5.3 cleaning system catch: Any material collected from the machine's normal point of discharge from the cleaning system

4 Selection of Crop

4.1 Capacity tests should preferably be conducted in crops and conditions listed in ANSI/ASAE Standard S343, Terminology for Combines and Grain Harvesting. Where test data indicate that such requirements have not been adhered to, the reasons for departures shall be stated in the test report.

4.2 Crops used for tests shall be reasonably uniform, free of disease, weeds and other crops. They should in general be standing well. If local climatic conditions or local practices lead to different conditions typical of the locality (for instance widespread lodging or the windrowing of crops), the circumstances should be stated in the test report.

5 Machines

5.1 The test combine shall be fully identified as to make, model, year and other pertinent information. The terminology and methods of measurement defined by ANSI/ASAE Standard S343, Terminology for Combines and Grain Harvesting, shall be used where relevant.

5.2 The comparison combine shall be similarly identified, functionally sound and one which has been available on the open market for a continuous period of at least one year prior to the date of the test.

5.3 At the time of the test, both test and comparison combines shall be in good working order with all working surfaces free of thick or sticky paint, rust, grease, or other impediments to smooth operation. A run-in period of 25 h is required to ensure this condition on a new combine, or one that has not been used recently.

5.4 Immediately prior to testing, both test and comparison combines should be adjusted for optimum performance in the same piece of crop that will be used for the tests. Pretest adjustments should aim for optimum performance with harvesting conditions typical of normal practice in the relevant locality. Care should be taken to ensure that the dockage level in the clean grain sample of the test combine is similar to that of the comparison combine. Persons responsible for adjusting the machines shall be given adequate time and opportunity to do so, with regard to the time requirements of Section 7 Test Procedures, for conduct of the test proper. They shall also be responsible for deciding when the optimum adjustments have been attained.

5.5 No operator adjustment of the threshing, separating, or cleaning devices and header height shall be permitted during a test on either combine.

6 Collection of Samples

6.1 Apparatus for catching crop material discharged from the combine shall be built and operated so that: