ASAE EP479.1 DEC2013 (R2018)
Operation of Controlled Drainage Systems in Humid Regions

American Society of Agricultural and Biological Engineers

STANDARD

ASABE is a professional and technical organization, of members worldwide, who are dedicated to advancement of engineering applicable to agricultural, food, and biological systems. ASABE Standards are consensus documents developed and adopted by the American Society of Agricultural and Biological Engineers to meet standardization needs within the scope of the Society; principally agricultural field equipment, farmstead equipment, structures, soil and water resource management, turf and landscape equipment, forest engineering, food and process engineering, electric power applications, plant and animal environment, and waste management.

NOTE: ASABE Standards, Engineering Practices, and Data are informational and advisory only. Their use by anyone engaged in industry or trade is entirely voluntary. The ASABE assumes no responsibility for results attributable to the application of ASABE Standards, Engineering Practices, and Data. Conformity does not ensure compliance with applicable ordinances, laws and regulations. Prospective users are responsible for protecting themselves against liability for infringement of patents.

ASABE Standards, Engineering Practices, and Data initially approved prior to the society name change in July of 2005 are designated as “ASAE”, regardless of the revision approval date. Newly developed Standards, Engineering Practices and Data approved after July of 2005 are designated as “ASABE”.

Standards designated as “ANSI” are American National Standards as are all ISO adoptions published by ASABE. Adoption as an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by ASABE.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

CAUTION NOTICE: ASABE and ANSI standards may be revised or withdrawn at any time. Additionally, procedures of ASABE require that action be taken periodically to reaffirm, revise, or withdraw each standard.

Copyright American Society of Agricultural and Biological Engineers. All rights reserved.

ASABE, 2950 Niles Road, St. Joseph, MI 49085-9659, USA, phone 269-429-0300, fax 269-429-3852, hq@asabe.org

Documents
Document Sharing Hub

Copyright American Society of Agricultural and Biological Engineers
Provided by IHS Markit under license with ASABE
No reproduction or networking permitted without license from IHS
Full document details: ASAE EP479.1 182

Licensee=/, User=,
Not for Resale,

Operation of Controlled Drainage Systems in Humid Regions

Developed by the ASAE Design and Installation of Subsurface Drainage Committee; approved by the Soil and Water Division Standards Committee; adopted by ASAE March 1990; reaffirmed December 1994, December 1995, December 1996; reaffirmed for five years December, 1999; revised editorially March 2000; reaffirmed July 2005; periodic review extended two years January 2010; revised December 2013, reaffirmed November 2018.

Keywords: Controlled drainage, Drainage Water Management

1 Scope and Purpose

1.1 This Engineering Practice is intended as a guide for the design, installation and operation of a drainage system and head control structures whose purpose is the efficient management of the free water surface in the soil for drainage. This Engineering Practice is limited to systems utilizing pipe drains or open ditches to effect artificial subsurface drainage.

1.2 Water management systems, when operated in a drainage mode, have the potential of improving surface water quality by increasing soil water storage available for infiltration thereby reducing runoff that may carry sediment and undesirable chemicals. When operated in the controlled drainage mode, reduction in drainage depth or volume may occur, thereby reducing nutrient export, specifically nitrate-nitrogen. In open ditch systems, reduction in phosphorus loss can occur due to sedimentation in the channel upstream of the control structure.

2 References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies unless noted. For undated references, the latest approved edition of the referenced document (including any amendments) applies.

ANSI/NFPA No. 70, National Electrical Code

ASAE EP480, Design of Subsurface Drains in Humid Areas*

ASAE EP481, Construction of Subsurface Drains in Humid Areas*

ASAE EP302, Design and Construction of Surface Drainage Systems on Agricultural Lands in Humid Areas

ASAE EP407.1, Agricultural Drainage Outlets — Open Channels.

*ASAE EP480 and ASAE EP481 under revision. To be replaced with ASAE EP260.

3 Definitions

3.1 Terminology common to controlled drainage is defined below.

Documents Document Sharing Hub
Copyright American Society of Agricultural and Biological Engineers
Provided by IHS Markit under license with ASABE
No reproduction or networking permitted without license from IHS
Licensee=/, User=,
Not for Resale,
Full document details: ASAE EP479.1 182