



Designation: E2955 – 13 (Reapproved 2019)

Standard Practice for Simulating Profilograph Response to Longitudinal Profiles of Traveled Surfaces¹

This standard is issued under the fixed designation E2955; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 These practices cover the calculation of profilograph response to longitudinal profiles of traveled surface roughness.

1.2 These practices utilize computer simulations to obtain profilograph responses, including surface sensing wheel (recording wheel) vertical displacement and reference platform wheels (supporting wheels) motions as a function of distance.

1.3 These practices present standard profilograph simulations for use in the calculations.

1.4 The values stated in SI units are to be regarded as standard. The values given in parentheses are for information only and are not considered standard.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.6 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*²

[E950/E950M Test Method for Measuring the Longitudinal Profile of Traveled Surfaces with an Accelerometer-Established Inertial Profiling Reference](#)

[E1274 Test Method for Measuring Pavement Roughness Using a Profilograph](#)

¹ This practice is under the jurisdiction of ASTM Committee E17 on Vehicle - Pavement Systems and is the direct responsibility of Subcommittee E17.33 on Methodology for Analyzing Pavement Roughness.

Current edition approved Dec. 1, 2019. Published December 2019. Originally approved in 2013. Last previous edition approved in 2013 as E2955 – 13. DOI: 10.1520/E2955-13R19.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

3. Terminology

3.1 See Test Method [E1274](#).

4. Summary of Practices

4.1 These practices use a measured profile (see Test Method [E950/E950M](#)) or a synthesized profile as part of a computer simulation to obtain the response of the surface sensing wheel of a profilograph. The first practice uses a kinematic profilograph simulation model to obtain typical profilograph profiles as a function of distance. The second practice obtains the vertical displacement of the surface sensing wheel using the surface sensing wheel size, supporting wheel locations, and the spacing between the supporting wheels. The output is the continuous vertical motion of the surface sensing wheel of the simulated profilograph for a predetermined distance. The units are relative vertical movement (millimetres (inches)) at longitudinal surface profile location (metres (feet)). Pertinent information affecting the results must be noted.

5. Significance and Use

5.1 These practices provide a means for evaluating traveled surface roughness characteristics directly from a measured profile. The calculated output values represent profilograph response to traveled surface roughness.

5.2 These practices provide pavement surface profiles to evaluate pavement condition using the profilograph index.

6. Apparatus

6.1 *Computer*—The computer is used to calculate the surface sensing wheel vertical displacement of a profilograph with twelve reference platform wheels in response to a traveled surface profile using a synthesized profile or a profile obtained in accordance with Test Method [E950/E950M](#) as the input. Filtering shall be provided to permit calculation (for example, butterworth low pass or moving average low pass filters).

6.2 *Data Storage Device*—A data storage device shall be provided for the reading of profiles and the recording and long-term storage of computed data. Profile data shall be scaled to maintain a resolution of 0.025 mm (0.001 in.) and to accommodate the full range of amplitudes encountered during normal profile-measuring operations. The device shall not

contribute to the recorded data any noise amplitude larger than 0.025 mm (0.001 in.).

6.3 Simulation Input—Digital profile recordings of pavement surface profiles shall be obtained in accordance with Test Method E950/E950M or synthesized. The profile must be recorded at intervals no greater than 30.48 mm (1.2 in.). When more than one path of a traveled surface is measured, the recorded profile data for the paths shall be at the same longitudinal location along the measured profiles to avoid phase shift between the paths. The recorded profile shall include all of the noted field data described in the Procedure (Data Acquisition) and Report sections of Test Method E950/E950M. The length of the pavement surface profile must be reported with the results; however, caution must be exercised to ensure that transients in the simulation do not influence the results. It is recommended that the profile input to the simulation include a lead-in section at least 150 m (500 ft) long to eliminate the effects of start-up transients.

7. Profilograph Simulation Program

7.1 These practices use a typical California profilograph model with twelve supporting wheels as shown in Fig. 1. The mathematical model is described in FHWA report.³ The mathematical model was developed with the following assumptions:

7.1.1 All structural connections are perfectly rigid,

7.1.2 All hinge joints and wheel bearings are frictionless, and

7.1.3 All wheels are at a point-contact with the pavement surface at all times.

7.2 The calculation procedure to produce the profilograph vertical movement at position x , $R(x)$, from the recorded pavement surface profile is defined as:⁴

$$R(x) = \left(\sum_{i=1}^N C_i P_i (x - d_i) \right) - P_r (x - d_r) \quad (1)$$

where:

N = the number of wheels in the left and right side of the support system,

P_i = the recorded profile, on which the i^{th} wheel is traveling (subscript r refer to those of the surface sensing wheel),

d_i = the offset distance from the location x for each wheel (subscript r refer to those of the surface sensing wheel), and

C_i = the influence coefficient corresponding to the i^{th} wheel ($C_i = 1/16$ for the eight right-side wheels and $C_i = 1/8$ for the four left-side wheels).

7.2.1 As the California Profilograph shown in Fig. 1 travels on a pavement, three profile paths will be passed: four left wheels travel on one path, eight right wheels travel on another, and the third is under the recording wheel. Comparing the traces from the mathematical model using the same measured profile for all wheels with the real recorded traces using the profilograph on the same pavement in the study,⁵ showed that both traces are similar to each other. Therefore, it can be assumed that all wheels travel on the same profile when computing the “Profilograph Index” in 8.2.

7.2.2 As defined in Test Method E1274, the blanking band is a band of uniform height with its longitudinal center

⁴ See <http://www.airporttech.tc.faa.gov/NAPTF/Download/Roughness/CA%20Profilograph%20Index%20Calculation%20Model.doc>.

⁵ Walker, P. S. and Lin, H. T., “Profilograph Correlation Study with Present Serviceability Index (PSI)”, FHWA-88-072-002, Federal Highway Administration, 1988.

³ Kulakowski, B. T. and Wambold, J. C., “Development of Procedures for the Calibration of Profilographs,” Report No. FHWA-DP- 89-110, Federal Highway Administration, August 1989.




FIG. 1 A Typical California Profilograph Configuration

positioned optimally between the highs and lows of the profilograph trace depicting at least 100 ft of pavement. In general, a band height between 0.0 mm (0.0 in.), 2.54 mm (0.1 in.), or 5.08 mm (0.2 in.) is used in computing the “Profilograph Index” in 8.2.

7.2.3 Scallop s are the excursions of the trace above and below the blanking band as defined in Test Method E1274. The vertical maximum of a scallop must not be less than 0.762 mm (0.03 in.) and the longitudinal length must be longer than 0.6 m (2 ft) as defined in Test Method E1274 and previous studies.^{6,7}

8. Applications

8.1 *Excessive Height Template*—A clear plastic piece marked with a 25.0 ± 0.5 mm (1.00 ± 0.02 in.) line that is the stipulated cutoff height distance from a straightedge on the template. The cutoff height is defined as 7.614 mm (0.3 in.), 10.152 mm (0.4 in.), or 12.69 mm (0.5 in.).

8.1.1 The procedure for manually determining bump height from a template and a profilograph paper trace has been implemented using a simulated profilograph profile. A Bump Height Template Index (BHTI) is defined as:

$$BHTI = \frac{\text{Computed Bump Height}}{\text{Bump Height Limit}} = \frac{h_B}{h_L} \quad (2)$$

8.1.2 Therefore, when BHTI exceeds a value of one, the limit has been exceeded. Bump Height Limit, h_L , in the equation is equal to the cutoff height.

8.2 *Profilograph Index (PI)*—Profilograph Index is defined by the blanking band, scallop height, and total number of scallops in the segment, m . The equations are defined as:

$$PI_{\text{segment}} = \frac{\sum_{j=1}^m S_{\text{max}, j}}{L} \text{ (in./mile)} \quad (3)$$

where:

⁶ American Concrete Pavement Association, “Constructing Smooth Concrete Pavements,” ACPA TB-006.0-C, 1990.

⁷ “Operation of California Profilograph and Evaluation of Profiles,” California Test 526, 1978.

$$PI = \frac{\sum_{k=1}^s PI_k \times L_k}{\sum_{k=1}^s L_k} \text{ (in./mile)} \quad (4)$$

where:

PI_{segment} = profilograph index for a segment,

$S_{\text{max}, j}$ = the maximum of absolute height in the j^{th} scallop, and

L = the segment length.

8.2.1 Subscript k indicates the k^{th} segment in the pavement divided into s segments. L is the segment length.

9. Calibration

9.1 There is no calibration involved in the use of these practices. The profile collection equipment should be calibrated in accordance with the manufacturer’s requirements.

10. Report

10.1 Report at least the following information for this practice:

10.1.1 Data from profiles obtained in accordance with Test Method E950/E950M including date, the time of day of the measurement, or the date of the synthesized profile,

10.1.2 Profilograph simulation program used,⁸

10.1.3 Parameter values used to calculate Profilograph Index,

10.1.4 Parameter values used to calculate Bump Height Template Index, and

10.1.5 Results of the analysis.

11. Keywords

11.1 bump height; ProFAA; profilograph index; profilograph simulation; ProVAL

⁸ Currently two computer programs, ProFAA and ProVAL, provide profilograph simulations and analysis. “ProFAA” is the Federal Aviation Administration’s computer program for computing pavement elevation profile roughness indexes (<http://www.airporttech.tc.faa.gov>). “ProVAL” is an engineering software application used to view and analyze pavement profiles (<http://www.roadprofile.com>).

APPENDIXES

(Nonmandatory Information)

X1. PROFILOGRAPH INDEX COMPUTER PROGRAM

X1.1 Included in this appendix is the coding in Visual Basic.NET language for a computer subroutine (ProFAA), SUBROUTINE PROFILOGRAPH INDEX (PI) (see Fig. X1.1), which calculates the Profilograph Index as prescribed by this practice. A sample subroutine is also included which, when executed, prompts the user for the name of a data file containing the profile data to be processed and the parameters needed by the subroutine to compute the PI. The subroutine is

called and returns the computed PI values to the main program which then displays them.

X1.2 The sample program can process data files containing two profile tracks in either SI or inch-pound units. For example, “UnitsOut.ft” in Fig. X1.1 is utilized to convert inch-pound units (feet) to SI units (metres).

```
Partial Public Class MainWindow ' CAProfilograph

' Subroutines from ProFAA 2.0 for computing:
' 1. CA Profilograph measuring wheel displacement in response to an
'   elevation profile sampled at 75 mm spacing.
' 2. CA Profilograph Profile Index (PI) from the measuring wheel
'   displacement found in step 1.
' 3. CA Profilograph must grind bump template.

' The subroutines are implemented in Microsoft Visual Studio 2012,
' Visual Basic.NET.

Public Shared CAProfilographDone As Boolean
Public Shared BandPassDone As Boolean
Public CADeltaX As Double
Private CAProfilographProfile() As Single, CAProfilographIndex() As Single
Private CAProfilographSamples As Integer, CAProfilographDeltaX As Double
Private PIIndex() As Single, PIlenght() As Single
Private HalfBand As Double = 0.1 ' inch
Private ScallopMin As Double = 0.03 ' inch,
Private ScallopLmin As Double = 2.0 ' ft
Private ScallopAbove, ScallopBelow As Integer
Public Shared Lprofilograph As Double = 500.0 ' ft
Private PIN, PINmin As Integer
Private PICum As Double

Private BTEdgeMaxX As Double, BTHeightLimit As Double
Private BTProfile() As Single, BTSamples As Integer
Private BTBumpHeight() As Single, BTBumpLength() As Single
Private BTIndex() As Single, BTEdgeLength() As Single
Private BTDone As Boolean, BTDeltaX As Double
```

FIG. X1.1 Sample Subroutines in Microsoft Visual Basic.NET to Compute Profilograph Index

```

Private Sub StartRunCAProfilograph(Index As Integer)
    ' Preliminaries to computing measuring wheel and PI.

    If PlotCanvas(0) Is Nothing Then
        Ret = MsgBox("A profile has not been loaded. Please read a file" _
            & vbCrLf & "to load the profile before running CA _
            Profilograph.", , "Invalid Selection")

        Exit Sub
    End If

    sbrStatus.Items(0) = "Computing CA Profilograph" : DoEvents()
    Dim DecimateN As Integer = 3      ' Decimation rate, 75 mm spacing.

    ' Returns CAProfilographProfile as decimated Profile
    ' with length CAProfilographSamples.
    Call DecimateProfile(PlotCanvas(0).ArrayLength, CAProfilographProfile,
        CAProfilographSamples, DecimateN)
    CAProfilographDeltaX = DeltaD * DecimateN
    Call WriteIndexLabel(Indexes.CAProfiler + 1, "")
    Call RunCAProfilograph(CAProfilographProfile, CAProfilographSamples,
        CAProfilographDeltaX)

Sub RunCAProfilograph(ByRef Profile() As Single, ByVal NSamples As Integer,
    ByVal DX As Double)

    Dim I, II, PartN, IStart, IEnd As Integer
    Dim TempZ1, TempZN, ZAVE, PIndexSect As Double
    Dim CenterX, TandemSpacing As Double
    Dim LW1, LW2, LW3, LW4 As Integer
    Dim WheelRad, ZW(), TotalLength As Double
    Dim J, NRad, NSegs As Integer
    Dim PIOffset, PITotal, PartLength() As Double
    Dim SA, SB, NSASB, Nloop, NSend(), AddNlast As Integer
    Dim FFreq As Double
    Dim BandA(), BandB() As Double
    Dim SingleBCL(), BCLL As Single
    Dim IBCL, IIBCL, NBCL As Integer
    ' The following are Public variables.
    ' Dim CAProfilographIndex() As Single
    ' Dim PIN, PINmin As Integer
    ' Dim ScallopMi, PICum, HalfBand As Double
    ' Dim ScallopAbove%, ScallopBelow%

    ' DX = sample spacing in feet.
    ' Profile() = an array containing the measuring wheel values in inches.

```

FIG. X1.1 Sample Subroutines in Microsoft Visual Basic.NET to Compute Profilograph Index *(continued)*