



Designation: E3028 – 23

Standard Practice for Computing Wheelchair Pathway Roughness Index as Related to Comfort, Passability, and Whole-Body Vibrations from Longitudinal Profile Measurements¹

This standard is issued under the fixed designation E3028; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This practice covers the mathematical processing of longitudinal profile measurements to produce a wheelchair pathway roughness statistic called the Wheelchair Pathway Roughness Index (WPRI).

1.2 This provides a standard practice for computing and reporting an estimate of pathway roughness for sidewalks and other pedestrian surfaces.

1.3 The values stated in SI units are to be regarded as the standard. The inch-pound units given in parentheses are for information only.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.5 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*²

E1364 Test Method for Measuring Road Roughness by Static Level Method

E2133 Test Method for Using a Rolling Inclinator to Measure Longitudinal and Transverse Profiles of a Traveled Surface

¹ This practice is under the jurisdiction of ASTM Committee E17 on Vehicle - Pavement Systems and is the direct responsibility of Subcommittee E17.33 on Methodology for Analyzing Pavement Roughness.

Current edition approved May 1, 2023. Published May 2023. Originally approved in 2016. Last previous edition approved in 2016 as E3028 – 16^{ε1}. DOI: 10.1520/E3028-23.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

3. Terminology

3.1 *Definitions:*

3.1.1 *longitudinal profile measurement, n*—a series of elevation values taken at a constant interval along a wheel track.

3.1.1.1 *Discussion*—Elevation measurements may be taken statically, as with rod and level per Test Method E1364, or dynamically using a rolling inclinometer per Test Method E2133.

3.1.2 *traveled surface roughness*—the deviations of a surface from a true planar surface with characteristics dimensions that affect vehicle dynamics, ride quality, dynamic loads, and drainage, for example, longitudinal profile, transverse profile, and cross slope.

3.1.3 *wave number, n*—the inverse of wavelength.

3.1.3.1 *Discussion*—Wave number, sometimes called spatial frequency, typically has units of cycle/m or cycle/ft.

3.2 *Definitions of Terms Specific to This Standard:*

3.2.1 *Wheelchair Pathway Roughness Index (WPRI), n*—an index computed from a longitudinal profile measurement using a standard 70 mm (2.5 in.) diameter wheel with no deformation and no affects from speed. The index represents the total vertical deflection of that wheel as it travels over a surface.

3.2.1.1 *Discussion*—WPRI is reported in either millimeters per meter (mm/m) or inches per foot (in./ft).

3.2.2 *Mean Wheelchair Pathway Roughness Index (MWPRI), n*—the average of the WPRI values for multiple trials expressed in millimeters per meter or inches per foot.

3.2.3 *True Wheelchair Pathway Roughness Index, n*—the value of WPRI computed for a longitudinal profile measurement with the constant interval approaching zero.

3.2.4 *wheel path, n*—a line or path followed by a non-deformable tire of a wheeled vehicle on a traveled surface as it approaches zero speed.


4. Summary of Practice

4.1 This practice was developed specifically for estimating wheelchair pathway roughness from longitudinal profile measurements.

4.2 Longitudinal profile measurements for one wheel track are transformed mathematically by a computer program and accumulated to obtain the WPRI. The profile shall be represented as a series of elevation values measured at equally spaced intervals along the traveled path.

4.3 The WPRI scale starts at zero for a surface with no roughness and covers positive numbers that increase in proportion to roughness. Fig. 1 provides WPRI value descriptors derived from simulated and community surfaces made of wood, segmental paving units, cast-in-place concrete, and asphalt.³

³ Duvall, J., et al., “Development of Surface Roughness Standards for Pathways Used by Wheelchairs,” *Transportation Research Record*, No. 2387, 2013, pp. 149–156.



NOTE 1—The MWPRI scale is identical to the WPRI scale.

FIG. 1 Wheelchair Pathway Roughness Index and Ratings

5. Significance and Use

5.1 This practice provides a means for obtaining a quantitative estimate of a surface property defined as roughness using longitudinal profile measuring equipment.

5.1.1 The WPRI can be obtained from instruments which can capture high-resolution (described in X1.1.2) longitudinal profiles.

5.1.2 The WPRI is stable with time because true WPRI is based on the concept of a true longitudinal profile, rather than the physical properties of a particular type of instrument.

5.2 When profiles are measured simultaneously for multiple traveled wheel tracks, the MWPRI is a better measure of wheelchair pathway surface roughness than the WPRI for either individual wheel track.

5.3 Wheelchair pathway roughness data can be useful in determining the vibration exposure experienced by a wheelchair user. (See Fig. 1.)

5.3.1 Vibration exposure has been linked to pain and injuries in wheelchair users and the WPRI of traveled surfaces provides the ability to quantify the vibration exposure a wheelchair user will experience when traveling that surface.^{4,5}

5.3.2 Knowledge of the vibration exposure a wheelchair user will experience on traveled surfaces will allow steps to be taken to minimize their exposure, reducing the likelihood of pain and injury.

6. Longitudinal Profile Measurement

6.1 The longitudinal profile measurements can be obtained from equipment that operates in a range of speeds, but the speed shall not affect the longitudinal profile data.

6.2 The elevation profile measuring equipment used to collect the longitudinal profile data used in this practice shall have accuracy to measure the longitudinal profile attributes for computation of the WPRI in accordance with Appendix X1.

7. Computation of Wheelchair Pathway Roughness Index

7.1 This practice computes a WPRI from an algorithm shown in Appendix X2.

7.2 This practice presents a sample computer program for the computation of the WPRI from the recorded longitudinal profile measurement.

7.2.1 The computer program accepts the elevation and horizontal profile datasets as input and then calculates the WPRI values for that profile dataset.

7.2.2 A listing of the computer program for the computation of WPRI is included in this practice as Appendix X2.

7.2.3 A provision has been made in the computer program listing (Appendix X2) for the computation of WPRI from recorded longitudinal profile measurements in either SI or inch-pound units.

⁴ Boninger, M. L., et al., “Investigating neck pain in wheelchair users,” *Am J Phys Med Rehabil*, Vol 82, No. 3, 2003, pp. 197–202.

⁵ DiGiovine, C. P., et al., “Whole-body vibration during manual wheelchair propulsion with selected seat cushions and back supports,” *IEEE Trans Neural Syst Rehabil Eng*, Vol 11, No. 3, 2003, pp. 311–322.

7.2.4 The input to the sample WPRI computer program is a numerical profile dataset stored in a 2×N .xls format. In this format, the profile data appear as a multi-row, two-column array with the longitudinal distance data points in Column 1 and the vertical distance data points in Column 2. The profile data point interval should be in the range of 0.5 to –2.0 mm.

7.2.4.1 The computer program shall round the input to three decimal places no matter the input.

7.2.4.2 If the input to the WPRI computer program is in inch-pound units, alternative code has been provided to convert the data to millimeters with the least significant digit being equal to the least significant digit provided by the input or 0.1 mm.

7.3 The distance interval over which the WPRI is computed is discretionary, but shall be reported along with the WPRI results. An interval of 16 ft (4.87 m) has been used successfully in the past and has been shown to be repeatable.⁶

7.4 Validation of the WPRI program shall be completed when it is installed. Provision for the WPRI program installation validation is in this practice.

7.4.1 The sample profile dataset SAMPLE DATA.XLS has been provided in SI units in [Appendix X2](#) for validation of the computer program installation.

7.4.2 Using the sample profile dataset SAMPLE DATA.XLS in [Appendix X2](#) as input to the WPRI computer program, a WPRI value of 72.64 mm should be computed.

⁶ Duvall, J. et al., “Proposed pedestrian pathway roughness thresholds to ensure safety and comfort for wheelchair users,” *Assistive Technology*, Vol 28, No. 4, 2016, pp. 209–215.

8. Report

8.1 Include the following information in the report for this practice:

8.1.1 *Profile Measuring Device*—The name, serial number, manufacturer, and class of the profile measuring device used to make the profile measurement per Test Method [E1364](#) and Test Method [E2133](#).

8.1.2 *Longitudinal Profile Measurements*—Data from the profile measuring process shall include the date and time of day of the measurement, the location of the measurement (latitude/longitude coordinates), length of measurement, and the descriptions of the surface being measured.

8.1.3 *WPRI Resolution*—If units reported are mm/m, then the WPRI shall be reported to the nearest one tenth of a mm/m. If the reported units are in./ft, then report the WPRI to the nearest hundredth of an in./ft.

8.1.4 *Profile Segment*—If a continuous profile contains sections that cannot be measured using the profile measuring device, the report shall note the location, length, and include a description of each discontinuity.

9. Precision and Bias

9.1 The precision and bias of the computed WPRI is limited by the procedures used in making the longitudinal profile measurement.

9.2 For the effects of the precision and bias of the measured profile on the computed WPRI, see precision and bias in [Appendix X1](#).

10. Keywords

10.1 longitudinal profile; pathway; pedestrian; roughness; sidewalk; wheelchair; Wheelchair Pathway Roughness Index

APPENDIXES

(Nonmandatory Information)

X1. PRECISION AND BIAS

X1.1 Precision

X1.1.1 The precision of the computed WPRI is limited by the procedures used in making the longitudinal profile measurement.

X1.1.2 WPRI precision depends on the interval between adjacent profile elevation measurements. Reducing the interval typically improves the precision. An interval in accordance with [X1.2.2](#) is recommended. For some surface types, a shorter interval will improve precision. More information about the sensitivity of WPRI to the profile data interval is being developed.

X1.1.3 WPRI precision is limited by the degree to which a traveled path on the pedestrian pathway can be profiled. Errors in locating the traveled path longitudinally and laterally can influence the WPRI values, because the WPRI will be com-

puted for the profile of the traveled path as measured, rather than the travel path as intended. These errors are reduced by using longer profiles.

X1.1.4 If measurements are taken so that the least significant digit is 0.1 mm or smaller, computational errors due to rounding can be safely ignored.

X1.2 Bias

X1.2.1 The bias of the computed WPRI is typically limited by the procedures used in making the longitudinal profile measurement.

X1.2.2 WPRI bias depends on the interval between adjacent profile elevation measurements. An interval of between 0.5 and 2.0 mm is necessary. Shorter intervals improve precision but have little effect on bias. More information about the sensitivity of WPRI to the profile data interval is being determined.