



Designation: F 1511 – 02

An American National Standard

Standard Specification for Mechanical Seals for Shipboard Pump Applications¹

This standard is issued under the fixed designation F 1511; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers mechanical end-face seals for centrifugal and positive displacement pumps for shipboard use.

1.2 The following types of seals are not included in this specification: lip seals, oil seals, circumferential seals, labyrinth seals, or gas seals.

1.3 The values stated in inch-pound units are to be regarded as the standard. The SI units given in parentheses are for information only. A companion hard metric standard is in the process of preparation.

1.4 Special requirements for U.S. Navy Shipboard Pump Applications are included in Supplement S1.

2. Referenced Documents

2.1 ASTM Standards:

- A 108 Specification for Steel Bars, Carbon, Cold-Finished, Standard Quality²
- A 182/A182M Specification for Forged or Rolled Alloy-Steel Pipe Flanges, Forged Fittings, and Valves and Parts for High-Temperature Service³
- A 240/A 240M Specification for Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Applications⁴
- A 276 Specification for Stainless Steel Bars and Shapes⁴
- A 313/A 313M Specification for Stainless Steel Spring Wire⁴
- A 351/A351M Specification for Castings, Austenitic, Austenitic-Ferritic (Duplex), for Pressure-Containing Parts⁵
- A 436 Specification for Austenitic Gray Iron Castings⁵
- A 494/A494M Specification for Castings, Nickel and Nickel Alloy⁵
- A 564/A564M Specification for Hot-Rolled and Cold-Finished Age-Hardening Stainless Steel Bars and Shapes⁴
- A 579 Specification for Superstrength Alloy Steel Forgings²

- A 693 Specification for Precipitation-Hardening Stainless and Heat-Resisting Steel Plate, Sheet, and Strip⁴
- A 705/A705M Specification for Age-Hardening Stainless and Steel Forgings⁴
- A 744/A744M Specification for Castings, Iron-Chromium-Nickel, Corrosion Resistant, for Severe Service⁵
- B 62 Specification for Composition Bronze or Ounce Metal Castings⁶
- B 127 Specification for Nickel-Copper Alloy (UNS N04400) Plate, Sheet, and Strip⁷
- B 164 Specification for Nickel-Copper Alloy Rod, Bar, and Wire⁷
- B 166 Specification for Nickel-Chromium-Iron Alloys (UNS N06600, N06601, N06603, N06690, N06693, N06025, and N06045) and Nickel-Chromium-Cobalt-Molybdenum Alloy (UNS N06617) Rod, Bar, and Wire⁷
- B 168 Specification for Nickel-Chromium-Iron Alloys (UNS N06600, N06601, N06603, N06690, N06693, N06025, and N06045) and Nickel-Chromium-Cobalt-Molybdenum Alloy (UNS N06617) Plate, Sheet, and Strip⁷
- B 271 Specification for Copper-Base Alloy Centrifugal Castings⁶
- B 333 Specification for Nickel-Molybdenum Alloy Plate, Sheet, and Strip⁷
- B 335 Specification for Nickel-Molybdenum Alloy Rod⁷
- B 338 Specification for Seamless and Welded Titanium and Titanium Alloy Tubes for Condensers and Heat Exchangers⁷
- B 348 Specification for Titanium and Titanium Alloy Bars and Billets⁷
- B 367 Specification for Titanium and Titanium Alloy Castings⁷
- B 443 Specification for Nickel-Chromium-Molybdenum-Columbium Alloy (UNS N06625) and Nickel-Chromium-Molybdenum-Silicon Alloy (UNS N06219) Plate, Sheet, and Strip⁷
- B 446 Specification for Nickel-Chromium-Molybdenum-Columbium Alloy (UNS N06625), Nickel-Chromium-Molybdenum-Silicon Alloy (UNS N06219) and Nickel-Chromium-Molybdenum-Tungsten Alloy (UNS N06650) Rod and Bar⁷

¹ This specification is under the jurisdiction of ASTM Committee F25 on Ships and Marine Technology and is the direct responsibility of Subcommittee F25.11 on Machinery.

Current edition approved July 10, 2002. Published September 2002. Originally published as F 1511 – 94. Last previous edition F 1511 – 98.

² *Annual Book of ASTM Standards*, Vol 01.05.

³ *Annual Book of ASTM Standards*, Vol 01.01.

⁴ *Annual Book of ASTM Standards*, Vol 01.03.

⁵ *Annual Book of ASTM Standards*, Vol 01.02.

⁶ *Annual Book of ASTM Standards*, Vol 02.01.

⁷ *Annual Book of ASTM Standards*, Vol 02.04.



- B 472 Specification for Nickel Alloy UNS N06030, UNS N06022, UNS N06200, UNS N08020, UNS N08026, UNS N08024, UNS N08926, UNS N08367, UNS N10276, UNS N10665, UNS N10675 and UNS R20033 Nickel Alloy Billets and Bars for Reforging⁷
- B 473 Specification for UNS N08020, UNS N08024, and UNS N08026 Nickel Alloy Bar and Wire⁷
- B 505 Specification for Copper-Base Alloy Continuous Castings⁶
- B 574 Specification for Low-Carbon Nickel-Molybdenum-Chromium, Low-Carbon Nickel-Chromium-Molybdenum, Low-Carbon Nickel-Molybdenum-Chromium-Tantalum, Low-Carbon Nickel-Chromium-Molybdenum Copper, and Low-Carbon Nickel-Chromium-Molybdenum Tungsten Alloy Rod⁷
- B 575 Specification for Low-Carbon Nickel-Molybdenum-Chromium, Low-Carbon Nickel-Chromium-Molybdenum-Copper, Low-Carbon Nickel-Chromium-Molybdenum-Tantalum, and Low-Carbon Nickel-Chromium-Molybdenum-Tungsten, and Low-Carbon Nickel-Chromium-Molybdenum Alloy Plate, Sheet, and Strip⁷
- B 584 Specification for Copper Alloy Sand Castings for General Applications⁶
- B 637 Specification for Precipitation-Hardening Nickel Alloy Bars, Forgings, and Forging Stock for High-Temperature Service⁷
- B 670 Specification for Precipitation-Hardening Nickel Alloy (UNS N07718) Plate, Sheet, and Strip for High-Temperature Service⁷
- D 1141 Specification for Preparation of Substitute Ocean Water⁸
- D 1418 Practice for Rubber and Rubber Latex Nomenclature⁹
- D 3294 Specification for Polytetrafluoroethylene (PTFE) Resin Molded Basic Shapes¹⁰
- D 3951 Practice for Commercial Packaging¹¹
- 2.2 *ASQC Standards*:¹²
- Z1.4 American Society of Quality Control, Quality Conformance Inspection
- 2.3 *ANSI Standards*:¹³
- Y14.1 Drawing Sheet Size and Format
- Y14.2 Line Convention and Lettering
- Y14.3 Multi and Sectional View Drawings
- Y14.5 Dimensioning and Tolerancing for Engineering Drawings

- Y14.6 Screw Thread Representation
- Y14.26.3 Computer-Aided Preparation of Production Definition Data, Terms and Definitions
- 2.4 *Military Standards*:¹⁴
- MIL-S-901 Shock Tests, H.I. (High Impact); Shipboard Machinery, Equipment & Systems, Requirements for
- MIL-P-16789 Packaging of Pumps, Including Prime Movers and Associated Repair Parts
- MIL-R-83248 Rubber Fluorocarbon Elastomer, High Temperature, Fluid, and Compression Set Resistant
- 2.5 *ISO Standard*:¹³
- ISO 9001 Quality Systems—Model for Quality Assurance in Design/Development, Production, Installation, and Service
- 2.6 *Other Document*:¹⁴
- Metals and Alloys —Unified Numbering System-DS-56f

3. Terminology

3.1 Refer to Annex A1 for terminology relating to mechanical seals.

4. Classification of Seal Arrangements

4.1 For this specification, mechanical seals shall be classified by type, grade, and class. The categories are divided by application arrangement in the equipment in which it is installed:

- 4.1.1 Type A—Inside Single Mounted Seals
 - 4.1.2 Type B—Outside Single Mounted Seals
 - 4.1.3 Type C—Double Seals
 - 4.1.4 Type D—Tandem Seals
 - 4.1.5 Type E—Special Arrangements/Applications Vacuum or Gas Seal
 - 4.1.6 Grade 1—Basic End Face Seal
 - 4.1.7 Grade 2—Cartridge Seal
 - 4.1.8 Grade 3—Split Seal
 - 4.1.9 Class 0—Nonsplit Seal Assembly
 - 4.1.10 Class 1—Partial Split Seal Assembly, Solid Gland
 - 4.1.11 Class 2—Partial Split Seal Assembly, Split Gland
 - 4.1.12 Class 3—Fully Split Seal Assembly, Solid Gland
 - 4.1.13 Class 4—Fully Split Seal Assembly, Split Gland
- 4.2 Figs. 1-6 give general orientation information for various types of seals. The specific design of seal shown is not limited to that particular application.

5. Ordering Information

5.1 The purchaser shall provide the manufacturer with all of the pertinent application data shown in Figs. 7-9. If special operating conditions exist that are not shown in the checklist, they shall also be described.

⁸ *Annual Book of ASTM Standards*, Vol 11.02.

⁹ *Annual Book of ASTM Standards*, Vol 09.01.

¹⁰ *Annual Book of ASTM Standards*, Vol 08.02.

¹¹ *Annual Book of ASTM Standards*, Vol 15.09.

¹² Available from American Society for Quality (ASQ), 600 N. Plankinton Ave., Milwaukee, WI 53203.

¹³ Available from American National Standards Institute, 25 W. 43rd St., 4th Floor, New York, NY 10036.

¹⁴ Available from Standardization Documents Order Desk, Bldg. 4, Section D, 700 Robbins Ave., Philadelphia, PA 19111-5098, Attn: NPODS.

ASTM F 1511 – 02




FIG. 1 Single Seal—Inside Mounted Classification Type A Grade 1




FIG. 2 Single Seal—Inside Mounted Classification Type A Grade 1

ASTM F 1511 – 02




FIG. 3 Single Seal—Outside Mounted Classification Type B Grade 1




FIG. 4 Double Seals—Back to Back Classification Type C Grade 1

ASTM F 1511 – 02




FIG. 5 Double Seals—Face to Face Classification Type C Grade 1




FIG. 6 Tandem Seals Classification Type D Grade 1



		Material	ASTM
1.1 Seal Description			
Type _____	Grade _____		
1.2 Pump Description			
Pump Mfg. _____	Model _____	Copper alloy	B 271, B 584, B 505
Pump S/N _____	Size _____	Bronze	B 62
Pump Type (Horizontal, Vertical, etc.) _____		Alloy 20	B 472 and B 473 (UNS N08020, N08026)
No. of Stages _____		316 stainless steel	A 240/A 240M, A 276, and A 313/A 313M (UNS S316XX)
Sleeve or Shaft Mat'l _____	Casting Mat'l _____	304 stainless steel	A 182/A 182M, A 313/A 313M (UNS S304XX), A 351/A 351M (CF3, 3A; CF8, 8A; CF8C; CF10)
Cooling Water Available? _____ °F _____ GPM			
Stuffing Box Water Jacketed? Yes _____ No _____		Alloyed stainless steel (cast)	A 744/A 744M (CN-7M, CN-7MS)
Is Face of Stuffing Box Machined? Yes _____ No _____		17-4 PH	A 564/A 564M and A 693 (UNS S17400)
FILL OUT STUFFING BOX DIMENSIONS SHOWN ON FIG. 8		AM 350	A 579 (Grade 61)
2.1 Liquid Pumped		NiCu ^A	B 164 (UNS N04400, N04405), B 127, A 494/A 494M (Grades M35-1, M35-2, M-30H, M-25S)
Fluid _____	Concentration _____		
	Specify for unique cargo pump fluid application		
Pumping Temperature (°F)	Normal _____	NiMo	A 494/A 494M (Grades CW-2M, N-12 MV)
	Max _____	NiMo ^B (Alloy B)	B 333 and B 335 (UNS N10001, N10665, N10675)
	Min _____		
Specific Gravity at Operating Condition _____		NiCrFe ^C NiCrMoCo	B 166, B 168
Viscosity Range at Operating Conditions/Temp. _____ SSU		NiCr	B 637, B 670
Vapor Pressure at Operating Conditions/Pressure _____ psig		NiCrMoCb ^D	B 443, B 446
Corrosion/Erosion Caused by: _____ % Solids		Steel	A 108
Abrasive Separator To be Supplied—Yes _____ No _____		Austenitic grey iron	A 436
2.2 Operating Conditions		Titanium	B 338, B 348, B 367
Rated Discharge Pressure Max (psig) _____		Nickel cast iron (ductile nodular or graphitic)	A 436 Type 1
Suction Box Pressure Range (psig) _____			
Stuffing Box Pressure Range (psig) _____			
Stuffing Box Temperature Max (°F) _____			
Hydrostatic Test Pressure (psig) _____			
Speed (rpm) _____			
Direction of Rotation From Drive End CW or CCW _____			
3.1 Preservation and Packaging			
Special Preservation & Packaging for Storage & Shipment _____			
Special Marking _____			
4.1 Other Special Requirements			
Seal Manufacturer's Certification of Compliance Required—Yes _____ No _____			
5.1 US Navy Application Requirements			
Supplement S1, ----- Yes _____ No _____			
Check applicable dimensional Table below:			
Table No. S1, Standard Long Mechanical Seal _____			
Table No. S2, Standard Short Mechanical Seal _____			
Table No. S3, Special Cartridge Seals Grade 2 _____			
Table No. S4, Special Seals Grade 1 _____			

FIG. 7 Ordering Data Checklist

6. Material

6.1 Mechanical seals shall be constructed of materials selected from Tables 1-3 after reviewing temperature, pressure/velocity (PV), and corrosion resistance requirements for all parts for each application.

6.2 Metal Components:

6.2.1 Mechanical seal metal parts in contact with the pumped liquid shall be compatible with their environment.

6.2.2 Table 1 identifies metal component compatibility.

6.2.3 Material specifications:

^AMonel[®] or equivalent has been found satisfactory for this purpose.

^BHastelloy B or equivalent has been found satisfactory for this purpose.

^CInconel X750[®] or equivalent has been found satisfactory for this purpose.

^DInconel 625[®] or equivalent has been found satisfactory for this purpose.

6.3 *Face Materials*—Mechanical seal-wearing faces shall be selected to provide the desired performance and corrosion resistance for the specified design life of the seal.

6.3.1 Performance ranges for face combinations are listed in Table 2.

6.3.2 Face materials shall be of solid construction only; no overlays, deposited coatings, or sprayed on coatings are permitted.

6.3.3 Carbon is preferred for one of the faces unless the service is abrasive, dirty, or chemically active.

6.3.4 For special service requirements, hard on hard seal face combinations may be required. Face material combinations, such as silicon carbide versus silicon carbide, silicon carbide versus tungsten carbide, and tungsten carbide versus tungsten carbide, may be used as similar or dissimilar contacting face materials when recommended by the supplier and approved by the user.

6.4 Face Material Specifications:

6.4.1 *Carbon*—Suitable for service as recommended by the manufacturer. A carbon seal grade is a material having carbonaceous filler system comprised of pitch and resins, compacted and baked to a final temperature. These grades are subsequently impregnated with resin until they become impervious. All available carbons may not be suitable for a particular




FIG. 8 Stuffing Box Arrangement



F 1511 – 02

Refers to Fig. 8a

Ref 8 _____

A.	_____	K.	_____
B.	_____	L.	_____
C.	_____	M.	_____
D.	_____	N.	_____
E.	_____	P.	_____
F.	_____	R.	_____
G.	_____	S.	_____
H.	_____	T.	_____
J.	_____	U.	_____
N.P.T. _____			
Bolt Holes or Stud Loc. _____			
Thread Size _____			
Auxiliary Pipe Tap Loc. _____			
Comments _____			

FIG. 9 Stuffing Box Dimensions

TABLE 1 Metal Component Compatibility

NOTE 1—For fluids or materials not covered here, seal selection to be mutually agreed upon by seal manufacturer, pump supplier, and end user.

NOTE 2— X = Suitable for use as seal components.

Fluid	Materials ^a						
	316 Stainless Steel	Ni-Cu	Alloy 20	Highly Alloyed Stainless Steel	Ni-Mo	Ni-Cr-Mo-Cb Ni-Cr-Fe	
<i>Fresh Water</i>							
Demineralized water		X		X	X	X	X
Boiler feed		X		X	X	X	X
Potable	X	X	X	X	X	X	X
<i>Salt Water</i>							
Seawater			X	X	X	X	X
Distiller brine			X		X	X	X
<i>Fuel Oil</i>							
Navy distillate		X	X	X	X	X	X
JP-5		X	X	X	X	X	X
Diesel		X	X	X	X	X	X
Kerosene		X	X	X	X	X	X
Crude oil		X	X	X	X	X	X
Lube oil		X	X	X	X	X	X
Sewage			X	X	X	X	X

^aSee Section 6 for material specifications.

application. Carbons considered for use in a particular application shall be checked for suitability in accordance with the requirements of this specification.

6.4.2 *Tungsten Carbide*—6 to 10 % nickel or cobalt-bound solid tungsten carbide.

6.4.3 *Ceramic*—99.5 % minimum alumina ceramic suitable for the service as recommended by the manufacturer.

6.4.4 *Silicon Carbide*—(a) *Reaction-Bonded*—Solid fine-grained reaction-bonded silicon carbide 8 to 12 % free silicon, essentially free of carbon, impervious structure requiring no impregnant. (b) *Reaction-Bonded With Graphite*—A composite material of fine-grain reaction-bonded silicon carbide; 5 to 10 % free silicon and 10 to 30 % graphite; impervious structure requiring no impregnant. (c) *Direct Sintered*—Solid homogeneous silicon carbide essentially free of silicon and carbon, impervious structure requiring no impregnant. (d) *Direct Sintered Silicon Carbide*—Contains 10 % free graphite. (e) *Sili-*

conized Carbon Graphite—Approximately 0.025-in. (0.64-mm) thick conversion of silicon carbide on carbon substructure and impregnated with thermosetting resin.

6.5 *Elastomeric Materials*:

6.5.1 Special care should be given to the selection and installation of elastomeric components, such as bellows and O-rings. One of the most important considerations for elastomers is fluid compatibility. Table 3 references most shipboard applications. Consult the seal manufacturer for fluids not listed.

6.5.2 *Material Classification/Specification*:

6.5.2.1 Nitrile—Practice D 1418, Class Designation NBR.

6.5.2.2 Chloroprene—Practice D 1418, Class Designation CR.

6.5.2.3 Fluorocarbon—Practice D 1418, Class Designation FKM.

6.5.2.4 Ethylene Propylene (EP)—Practice D 1418, Class Designation EPM/EPDM.



Documents

Document Sharing Hub