



Designation: F 2340 – 04

Standard Specification for Developing and Validating Prediction Equation(s) or Model(s) Used in Connection with Livestock, Meat, and Poultry Evaluation Device(s) or System(s) to Determine Value¹

This standard is issued under the fixed designation F 2340; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last approval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers methods to collect and analyze data, document the results, and make predictions by any objective method for any characteristic used to determine value in any species using livestock, meat, and poultry evaluation devices or systems.

1.2 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory requirements prior to use.*

2. Terminology

2.1 Definitions:

2.1.1 *calibration data set, n*—data set used to develop the initial prediction equations; same as developmental or prediction data set.

2.1.2 *coefficient of determination, n*—percentage of variability in the response (dependent) variable that can be explained by the prediction equation.

$$R^2 = 1 - \frac{\sum(y - \hat{y})^2}{\sum(y - \bar{y})^2}$$

2.1.3 *evaluation device, n*—equipment designed to measure composition, or quality constituents used to determine value of live animals, carcasses, and individual cuts of meat.

2.1.4 *evaluation system, n*—device or group of devices used to measure and record composition, or quality constituents used to determine value of live animals, carcasses, and individual cuts of meat.

2.1.5 *independent third party, n*—unbiased person or entity that is a knowledgeable expert for the specific activity.

2.1.6 *root mean square error for calibration, n*—square root of the sum of squared residuals divided by $n_c - (k + 1)$, where

n_c is the sample size for the calibration data set, and k is the number of explanatory variables in the prediction equation.

$$\sqrt{\frac{\sum(y - \hat{y})^2}{n_c - (k + 1)}}$$

2.1.7 *root mean square error for validation, n*—square root of the sum of squared residuals divided by n_v , where n_v is the sample size for the validation data set.

$$\sqrt{\frac{\sum(y - \hat{y})^2}{n_v}}$$

2.1.8 *validation data set, n*—the data set used to test the predictive accuracy of the equations developed from the calibration data set.

2.1.9 *value, commerce, n*—measure of economic worth in commerce.

3. Significance and Use

3.1 The procedures in this specification are to be used by all parties interested in predicting composition or quality, or both, for the purpose of establishing value based upon device or system measurements. Whenever new prediction equations are established, or when a change is experienced that could affect the performance of existing equations, these procedures shall be used.

4. Procedure

4.1 Experimental Design:

4.1.1 *Define the Population for Development of a Prediction Equation:*

4.1.1.1 To establish the predictive ability and validity of an equation(s) using measures (independent variables) from an evaluation device or system, it is necessary to define the population on which the prediction model is intended to be used.

(1) The species on which measurements will be made must be defined.

¹ This specification is under the jurisdiction of ASTM Committee F10 on Livestock, Meat, and Poultry Evaluation Systems and is the direct responsibility of Subcommittee F10.40 on Predictive Accuracy.

Current edition approved May 1, 2004. Published May 2004.

(2) The population for scope of use must be clearly defined. This may include, but is not limited to, factors such as geographical location, gender, age, breed type, or any other factor that may affect the equation accuracy.

(3) The characteristic to be predicted must be clearly defined.

4.1.2 Select a Sample Population for Development of a Prediction Equation:

4.1.2.1 The sample size for the calibration data set should be a minimum $10k$, where k is the number of variables in the prediction equation. The sample size for the validation data set should be at least 20 % of the size of the validation data set. For example, if the prediction equation has five explanatory variables, the calibration data set should have at least 50 observations and the validation set should have at least ten observations. These recommendations are minimal, larger sample sizes are encouraged, keeping in mind that the calibration data set should be larger than the validation data set.

NOTE 1—The committee may wish to set the minimum for the calibration data set at 50 or 100 and use the 20 % for the validation data set. Looking at past studies may give you a better idea of where to set the minimum for the calibration data set.

4.1.2.2 The sample size must be large enough to be representative of the population; otherwise the resultant equation will not be suitable for use in the population to which the equation will be applied. This may require a larger sample size than the minimal requirement in 4.1.2.1. When possible, it may be useful to refer to existing data sets that describe a particular population to ensure that the sample includes most of the variation in the population. For example, if one were developing an equation to predict yield grade in U.S. fed beef packing plants, one would want to make sure that the samples used to develop and validate the regression model encompassed most of the normal variation in yield grade, yield grade factors, and factors that might affect the accuracy of the model. In this example, the simple statistics of these characteristics in the calibration data sets should be compared to the simple statistics of these characteristics in references such as the National Beef Quality Audits. Users are encouraged to work with a statistician.

4.1.3 Develop an Experimental Process:

4.1.3.1 A clearly defined process must be established and documented. That process, which includes consistent, repeatable methods, should be used to obtain the measurements under the same conditions in which the device or system would be expected to operate. In particular, the validity of the approach and the repeatability of the procedure must be

documented and demonstrated. For many of the common characteristics to be predicted (such as percent lean), there are a number of reference methods commonly accepted within the discipline. Where accepted methods exist, they should be used and cited. Where accepted methods do not exist, a sound, science-based process of method development should be followed. Consideration should be given to sources of variation for the measurements and strategies to minimize any bias that may exist.

4.1.4 Independent Third-Party Consultation:

4.1.4.1 After the experimental process has been established (but before initiation of the sampling), it is recommended that the users obtain an independent third-party consultation to review the procedures for compliance with the guidelines established in the previous sections. The consultation should focus on areas such as the number of samples, the sample selection protocol, and the project procedures to ensure that the process will allow the users to determine effectively the predictive ability and validity of the equation or model.

4.1.5 Develop the Model or Equation:

4.1.5.1 Collect data for the calibration (developmental) data set and develop the model or equation. Report the value of the coefficient of determination, R^2 , for the calibration data set.

4.1.5.2 Describe the sample used to develop the model or equation. Calculate the simple statistics (standard deviation, mean, minimum, and maximum values) of the data set that was used to develop the prediction model (calibration data set—for example, see Table 1).

4.1.6 Validation of Prediction Models or Equation(s):

4.1.6.1 *Objective*—To demonstrate the validity of the initial prediction model or equation with a different sample.

4.1.6.2 Select a sample for validation of a prediction equation. A general recommendation is for the size of the validation data set to be 20 % of the size of the calibration data set. However, the sample must be large and variable enough to be representative of the population to which the equation or model will be applied (refer to the calibration data set statistics for guidance).

4.1.6.3 Collect data for the validation data set. In validation trials, data used to determine predicted values must be collected under conditions where the devices or systems will be used or as close to on-line as possible. Prediction equations must not be applied to populations whose range of relevant characteristics (independent and dependent variables or factors that affect the relationship between independent and dependent variables) is practically different from the range of those characteristics in the calibration data set.

TABLE 1 Simple Statistics of Beef Carcass Characteristics for Calibration Data Set ($n = 400$)

Data Set	Characteristic	Mean	SD	Minimum	Maximum
Calibration	Hot carcass weight, kg	351	41	227	460
Calibration	Marbling score ^A	505	106	250	1090
Calibration	Preliminary yield grade	3.07	0.58	2.1	5.5
Calibration	Adjusted preliminary yield grade	3.29	0.62	2.0	5.6
Calibration	Adjustment of preliminary yield grade	0.22	0.22	-0.3	1.1
Calibration	Kidney, pelvic, and heart fat, %	2.08	0.69	0.0	4.5
Calibration	Longissimus area, cm ²	90.2	11.3	53.5	135.5
Calibration	Yield grade	2.65	1.06	-0.5	6.3

^A 200 = Practically Devoid⁰; 300 = Traces⁰; 400 = Slight⁰; 500 = Small⁰; 600 = Modest⁰; 700 = Moderate⁰; 800 = Slightly Abundant⁰; 900 = Moderately Abundant⁰; 1000 = Abundant⁰.