

Standard Specification for Performance of Aeroplanes¹

This standard is issued under the fixed designation F3179/F3179M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification establishes the airworthiness design standards associated with general aeroplane performance.

1.2 This specification is applicable to small aeroplanes as defined in Terminology F3060.

1.3 The applicant for a design approval shall seek the individual guidance to their respective civil aviation authority (CAA) body concerning the use of this specification as part of a certification plan. For information on which CAA regulatory bodies have accepted this specification (in whole or in part) as a means of compliance to their small aircraft airworthiness regulations (hereinafter referred to as “the Rules”), refer to the ASTM Committee F44 webpage (www.astm.org/COMMITTEE/F44.htm) which includes CAA website links.

1.4 *Units*—The values stated in either SI units or inch-pound units are to be regarded separately as standard. The values stated in each system may not be exact equivalents; therefore, each system shall be used independently of the other. Combining values from the two systems may result in nonconformance with the standard.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards:*²

F3060 Terminology for Aircraft

F3173 Specification for Handling Characteristics of Aeroplanes

F3174/F3174M Specification for Establishing Operating Limitations and Information for Aeroplanes

¹ This specification is under the jurisdiction of ASTM Committee F44 on General Aviation Aircraft and is the direct responsibility of Subcommittee F44.20 on Flight. Current edition approved Feb. 1, 2016. Published March 2016. DOI: 10.1520/F3179_F3179M-16.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

3. Terminology

3.1 Refer to Terminology F3060.

4. Performance Requirements

4.1 General:

4.1.1 Unless otherwise prescribed, the performance requirements of this specification shall be met for:

4.1.1.1 Still air and standard atmosphere.

4.1.1.2 Ambient atmospheric conditions for high-speed Level 1 and 2 aeroplanes and all Level 3 and 4 aeroplanes.

4.1.2 Performance data shall be determined over not less than the following conditions for all aeroplanes except for aeroplanes with $V_{SO} \leq 45$ KCAS:

(1) Airport altitude from sea level to 3084 m [10 000 ft];

(2) The temperature from standard to 30°C [86°F] above standard or the maximum ambient atmospheric temperature at which compliance with the cooling provisions of is shown, if lower;

(3) With any means for controlling the engine cooling air supply in the position used in the engine cooling tests;

(4) The available propulsive thrust shall correspond to engine power, not exceeding the approved power, less:

(a) Installation losses.

(b) The power absorbed by the accessories and services appropriate to the particular ambient atmospheric conditions and the particular flight condition.

4.1.2.1 The performance, as affected by engine power or thrust, shall be based on a relative humidity:

(1) Of 80 % at and below standard temperature.

(2) From 80 % at the standard temperature, varying linearly down to 34 % at the standard temperature plus 28°C [plus 50°F].

4.1.3 Unless otherwise prescribed in determining the takeoff and landing distances, changes in the aeroplane's configuration, speed, and power shall be made in accordance with procedures established by the applicant for operation in service. These procedures shall be able to be executed consistently by pilots of average skill in atmospheric conditions reasonably expected to be encountered in service.

4.1.4 Takeoff and landing distances shall be determined on a smooth, dry, hard-surfaced runway.

NOTE 1—The effect on these distances of operation on other types of surfaces (for example, grass and gravel) when dry, may be determined or derived, and these surfaces listed in the aeroplane flight manual in

accordance with Specification **F3174/F3174M**.

4.1.5 For high-speed Level 3 aeroplanes and all Level 4 aeroplanes, the following also apply:

4.1.5.1 Unless otherwise prescribed, the applicant shall select the takeoff, en route, approach, and landing configurations for the aeroplane;

4.1.5.2 The aeroplane configuration may vary with weight, altitude, and temperature to the extent they are compatible with the operating procedures required by **4.1.5.3**;

4.1.5.3 Unless otherwise prescribed, in determining the critical engine-inoperative takeoff performance, takeoff flight path, the accelerate-stop distance, changes in the aeroplane's configuration, speed, and power shall be made in accordance with procedures established by the applicant for operation in service;

4.1.5.4 Procedures for the execution of discontinued approaches and balked landings associated with the conditions prescribed in **4.12.3.4** and **4.17.3** shall be established; and

4.1.5.5 The procedures established under **4.1.5.3** and **4.1.5.4** shall:

(1) Be able to be consistently executed by a crew of average skill in atmospheric conditions reasonably expected to be encountered in service,

(2) Use methods or devices that are safe and reliable, and

(3) Include allowance for any reasonably expected time delays in the execution of the procedures.

4.2 Stalling Speed:

4.2.1 V_{S0} and V_{S1} are the stalling speeds or the minimum steady flight speeds in knots (KCAS) at which the aeroplane is controllable with:

4.2.1.1 The propulsive thrust not greater than zero at the stalling speed, or, if the resultant thrust has no appreciable effect on the stalling speed, with engine(s) at minimum flight thrust and throttle(s) closed with:

(1) The propeller(s) in the takeoff position;

(2) The aeroplane in the configuration existing in the test, in which V_{S0} and V_{S1} are being used;

(3) The center of gravity in the position that results in the highest value of V_{S0} and V_{S1} ; and

(4) The weight used when V_{S0} or V_{S1} are being used as a factor to determine compliance with a required performance standard.

4.2.2 V_{S0} and V_{S1} shall be determined by flight tests using the procedure and meeting the flight characteristics specified in the appropriate stall handling characteristics testing.

4.3 Takeoff Speeds:

4.3.1 The rotation speed, V_R , is the speed at which the pilot makes a control input with the intention of lifting the aeroplane out of contact with the runway or water surface.

4.3.1.1 For low-speed Levels 1, 2, and 3 multiengine landplanes, V_R shall not be less than the greater of $1.05 V_{MC}$ or $1.10 V_{S1}$.

4.3.1.2 For single-engine landplanes, V_R shall not be less than V_{S1} .

4.3.1.3 For seaplanes and amphibians taking off from water, V_R may be any speed that is shown to be safe under all

reasonably expected conditions, including turbulence and complete failure of the critical engine.

4.3.2 The speed at 15 m [50 ft] above the takeoff surface level shall not be less than:

4.3.2.1 For low-speed Level 1 aeroplanes with $V_{S0} \leq 45$ knots, not less than $1.3 V_{S1}$;

4.3.2.2 For low-speed Levels 1, 2, and 3 multiengine aeroplanes, the highest of:

(1) A speed that is shown to be safe for continued flight (or emergency landing, if applicable) under all reasonable expected conditions, including turbulence and complete failure of the critical engine;

(2) $1.10 V_{MC}$; or

(3) $1.20 V_{S1}$.

4.3.2.3 For Level 1 with a $V_{S0} > 45$ knots and all Levels 2 and 3 single-engine aeroplanes, the higher of:

(1) A speed that is shown to be safe under all reasonably expected conditions, including turbulence and complete engine failure, or

(2) $1.20 V_{S1}$.

4.3.3 For high-speed multiengine aeroplanes and all Level 4 aeroplanes, the following apply:

4.3.3.1 The value, V_1 , shall be established in relation to V_{EF} as follows:

(1) The value, V_{EF} , is the calibrated airspeed at which the critical engine is assumed to fail. The value, V_{EF} , shall be selected by the applicant but shall not be less than $1.05 V_{MC}$ determined under Specification **F3173** or, at the option of the applicant, not less than V_{MCG} determined under Specification **F3173**.

(2) The takeoff decision speed, V_1 , is the calibrated airspeed on the ground at which, as a result of engine failure or other reasons, the pilot is assumed to have made a decision to continue or discontinue the takeoff. The takeoff decision speed, V_1 , shall be selected by the applicant but shall not be less than V_{EF} plus the speed gained with the critical engine inoperative during the time interval between the instant at which the critical engine is failed and the instant at which the pilot recognizes and reacts to the engine failure, as indicated by the pilot's application of the first retarding means during the accelerate-stop determination of **4.5**.

4.3.3.2 The rotation speed, V_R , in terms of calibrated airspeed, shall be selected by the applicant and shall not be less than the greatest of the following:

(1) V_1 ;

(2) $1.05 V_{MC}$ determined under Specification **F3173**;

(3) $1.10 V_{S1}$; or

(4) The speed that allows attaining the initial climb-out speed, V_2 , before reaching a height of 11 m [35 ft] above the takeoff surface in accordance with **4.6**.

4.3.3.3 For any given set of conditions, such as weight, altitude, temperature, and configuration, a single value of V_R shall be used to show compliance with both the one-engine-inoperative takeoff and all-engines-operating takeoff requirements.