



Designation: F92 – 93(Reapproved 2008)

## Standard Practice for Determination of Character Yield of Inked Fabric Typewriter and Printer Ribbons<sup>1</sup>

This standard is issued under the fixed designation F92; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

### 1. Scope

1.1 This practice covers the determination of the usable image producing life of an inked fabric typewriter ribbon or an inked fabric printer ribbon expressed as the number of impressions obtainable from a given unit.

1.2 This practice is not applicable to one-time typewriter ribbons such as carbon ribbons.

1.3 This practice is suitable for narrow printer ribbons with a width of 2 in. (50.8 mm) or less.

1.4 The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

### 2. Referenced Documents

2.1 *ASTM Standards:*<sup>2</sup>

**D685 Practice for Conditioning Paper and Paper Products for Testing** (Withdrawn 2010)<sup>3</sup>

**D725 Method for Identification of Wire Side of Paper; Reinstated 1990 as D 5039** (Withdrawn 1979)<sup>3</sup>

**D3460 Specification for White Watermarked and Unwatermarked Bond, Reprographic, and Laser Printer Cut-Sized Office Papers**

**F149 Terminology Relating to Optical Character Recognition**

<sup>1</sup> This practice is under the jurisdiction of ASTM Committee F05 on Business Imaging Products and is the direct responsibility of Subcommittee F05.02 on Inked Transfer Imaging Products.

Current edition approved July 1, 2008. Published July 2008. Originally approved in 1968. Last previous edition approved in 2003 as F92 – 93 (2003). DOI: 10.1520/F0092-93R08.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

<sup>3</sup> The last approved version of this historical standard is referenced on www.astm.org.

**F221 Terminology Relating to Carbon Paper and Inked Ribbon Products and Images Made Therefrom**

**F497 Practice for Use of the Electric and Electronic Typewriter as a Test Instrument**

**F1174 Practice for Using a Personal Computer Printer as a Test Instrument**

2.2 *ANSI Standards:*

**PH 2.17 Density Measurements—Geometric Conditions for Reflection Density**<sup>4</sup>

**PH 2.18 Density Measurements—Spectral Conditions**<sup>4</sup>

### 3. Terminology

3.1 *Definitions:*

3.1.1 For definition of terms related to this practice refer to Terminology **F149** and **F221**.

3.2 *Definitions of Terms Specific to This Standard:*

3.2.1 *hot spotting*—printed images produced with an inked fabric ribbon where occasional individual images are darker than those around them. This condition occurs when the amount of ink is not consistent throughout the fabric ribbon.

### 4. Summary of Practice

4.1 This practice consists of testing a ribbon under simulated use conditions by employing a programmed electric typewriter or computer printer to use the ribbon completely.

### 5. Significance and Use

5.1 This practice is used to determine the number of useful impressions obtainable under normal operating conditions of a given typewriter or printer ribbon. It is suitable for service evaluation or research and development. This practice is generally not considered practical for manufacturing control specification acceptance because of the length of time required to obtain results.

5.2 Interpretation of the test result is to be made on a comparative basis, not on the basis of absolute values.

### 6. Interferences

6.1 Different typewriters, printers, print speeds, platens, type or font styles, impact adjustments, and print modes will

<sup>4</sup> Available from American National Standards Institute (ANSI), 25 W. 43rd St., 4th Floor, New York, NY 10036, http://www.ansi.org.

cause variation in results. Calibration as described in Section 10 will give the same results.

6.2 Type, thickness, and weight of fabric will cause variations in image quality.

6.3 Each specimen should be tested using equal time schedules and equivalent environmental conditions.

6.4 Ribbons with reinking systems may exhibit fluctuations in image density that will effect the reliability of graphic analysis as described in 14.2.

6.5 Cartridge internal construction can cause variation in print density.

## 7. Apparatus

7.1 *Electronic Typewriter or Printer*, that has been conditioned and calibrated in accordance with Sections 10 and 11 of Practice F497, or in accordance with Sections 9 and 10 of Practice F1174.

7.2 *Reflection Densitometer*—A reflection densitometer meeting the geometric conditions of PH 2.17 and the spectral conditions of PH 2.18. The specimen shall be backed with an infinite pad of the paper.

7.3 *Typewriter or Printer Driver*—An electro-mechanical robot device or computer program to activate the print mechanism to produce a uniform, repeatable print pattern at a constant speed.

7.4 *Type Font*, which produces a printed image with a stroke width exceeding 0.008 in. (0.2 mm).

7.5 *Alarm Clock*, or other time-measurement device.

## 8. Materials

8.1 *Paper*, in accordance with Specification D3460, Type 1, bond, in roll or fanfold form, single part. Other paper, as normally used in typewriters or printers may also be selected. It is important that the same paper be used in all comparison tests as the paper type may effect the result.

## 9. Test Specimen

9.1 The test specimen should be a ribbon or known portion thereof that is unused and fresh (not subject to excessive handling or abnormal storage conditions).

## 10. Calibration and Standardization

10.1 Adjust the typewriter or printer used to conduct the character yield test in accordance with Practice F497 or Practice F1174.

10.2 *Typewriter or Printer Driver*—If an electro-mechanical robot device is used, adjust in accordance with the instructions supplied by the manufacturer. If a computer or self test program is used, prepare for appropriate start-stop cycles.

10.3 Calibrate the densitometer (see 7.2) in accordance with the manufacturer's instructions for visual measurement.

## 11. Conditioning

11.1 Condition the samples to be tested and test paper in accordance with Method D685.

11.2 If standard condition is not available, make certain that wide changes in temperature and humidity do not take place while test is conducted.

## 12. Procedure

12.1 Insert the sample ribbon in the typewriter or printer in the normal manner prescribed by the manufacturer. Be certain that the imaging ribbon feeds properly and is taut across the print head.

12.2 Insert the test paper in the normal manner using pin drives if available. Insert the paper in such a manner so that the test pattern is produced on the felt side of the paper if possible. Refer to Method D725 to determine wire or felt side of paper. If paper side cannot be determined, always use the same side as drawn from package or box.

12.3 Adjust the bail rails, margin guides, and platen settings to ensure free travel of paper and production of a uniform, unimpeded print pattern.

12.4 Determine the test pattern.

12.5 *Time Schedule*—The time schedule selected should approximate the actual use condition of the printer. Examples of time schedules: 1-h run, 15-min wait, repeat, and 4-h run, 30-min wait, repeat. A nonstop wear test may be conducted should the printing condition require continuous printing to exhaustion. Set alarm clock or other time-measurement device to ensure adherence to the time schedule.

12.6 Operate the typewriter or printer at the print speed recommended by the manufacturer. Where a printer can be set at varying speeds, choose a mid-range setting to duplicate average use. The characters must be even with proper spacing both vertically and horizontally between them. They must not overlap.

12.7 Following the selected time schedule, continue running the test print pattern until printed image is illegible or unsatisfactory. A predetermined measurement can be agreed upon as the point of illegibility between concerned parties. (See Appendix.)

NOTE 1—Different inks may have differing color tones that will affect the visual appearance as compared to reflectance readings. For best results, continue running the test pattern well past the agreed point of illegibility.

12.8 Number pages beginning at “1” and at convenient intervals (50, 100, etc). If roll paper is used, each 11 in. (279 mm) is equivalent to a standard letter size page.

12.9 Remove the paper upon which the test pattern has been produced from the typewriter or printer being careful to avoid any smudging of the pattern.

## 13. Interpretation of Results

13.1 *Image Density Requirements*:

13.1.1 Standardize the reflection densitometer as selected in 7.2.

13.1.2 Place the test specimen under the viewing head of the instrument and read the value of the reflection density as follows: