



Designation: F 942 – 02

## Standard Guide for Selection of Test Methods for Interlayer Materials for Aerospace Transparent Enclosures<sup>1</sup>

This standard is issued under the fixed designation F 942; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

### 1. Scope

1.1 This guide summarizes the standard test methods available for determining physical and mechanical characteristics of interlayer materials used in multi-ply aerospace transparent enclosures.

1.2 Interlayer materials are used to laminate glass-to-glass, glass-to-plastic, and plastic-to-plastic. Interlayer materials are basically transparent adhesives with high-quality optical properties. They can also serve as an energy absorbing medium, a fail-safe membrane to contain cockpit pressure and to prevent entry of impact debris; a strain insulator to accommodate different thermal expansion rates of members being laminated and as an adherent to prevent spalling of inner surface ply material fragments. The relative importance of an interlayer characteristic will be a function of the prime use it serves in its particular application.

1.3 This guide, as a summary of various methods in Section 2, is intended to facilitate the selection of tests that can be applied to interlayer materials.

1.4 The test methods listed are for use in determining basic design characteristics and in assuring lot-to-lot uniformity of the materials being tested except as noted in 3.3.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

### 2. Referenced Documents

#### 2.1 ASTM Standards:

C 177 Test Method for Steady-State Heat Flux Measurements and Thermal Transmission Properties by Means of the Guarded Hot-Plate Apparatus<sup>2</sup>

D 149 Test Method for Dielectric Breakdown Voltage and Dielectric Strength of Solid Electrical Insulating Materials at Commercial Power Frequencies<sup>3</sup>

D 412 Test Methods for Vulcanized Rubber and Thermoplastic Rubbers and Thermoplastic Elastomers-Tension<sup>4</sup>

D 542 Test Methods for Index of Refraction of Transparent Organic Plastics<sup>5</sup>

D 570 Test Method for Water Absorption of Plastics<sup>5</sup>

D 696 Test Method for Coefficient of Linear Thermal Expansion of Plastics Between –30°C and 30°C With a Vitreous Silica Dilatometer<sup>5</sup>

D 792 Test Methods for Specific Gravity (Relative Density) and Density of Plastics by Displacement<sup>5</sup>

D 1003 Test Method for Haze and Luminous Transmittance of Transparent Plastics<sup>5</sup>

D 1004 Test Method for Initial Tear Resistance of Plastic Film and Sheet<sup>5</sup>

D 1045 Methods of Sampling and Testing Plasticizers Used in Plastics<sup>5</sup>

D 1204 Test Method for Linear Dimensional Changes of Nonrigid Thermoplastic Sheet or Film at Elevated Temperature<sup>5</sup>

D 1824 Test Method for Apparent Viscosity of Plastics and Organosols at Low Shear Rates by Brookfield Viscometer<sup>5</sup>

D 2240 Test Method for Rubber Property—Durometer Hardness<sup>4</sup>

D 2766 Test Method for Specific Heat of Liquids and Solids<sup>6</sup>

D 2857 Test Method for Dilute Solution Viscosity of Polymers<sup>7</sup>

D 3167 Test Method for Floating Roller Peel Resistance of Adhesives<sup>8</sup>

D 3465 Test Method for Purity of Monomeric Plasticizers by Gas Chromatography<sup>7</sup>

D 3835 Test Method for Determination of Properties of Polymeric Materials by Means of a Capillary Rheometer<sup>7</sup>

E 1640 Test Method for Assignment of the Glass Transition Temperature by Dynamic Mechanical Analysis<sup>9</sup>

<sup>1</sup> This guide is under the jurisdiction of ASTM Committee F07 on Aerospace and Aircraft and is the direct responsibility of Subcommittee F07.08 on Transparent Enclosures and Materials.

Current edition approved May 10, 2002. Published June 2002. Originally published as F 942 – 85. Last previous edition F 942 – 93.

<sup>2</sup> Annual Book of ASTM Standards, Vol 04.06.

<sup>3</sup> Annual Book of ASTM Standards, Vol 10.01.

<sup>4</sup> Annual Book of ASTM Standards, Vol 09.01.

<sup>5</sup> Annual Book of ASTM Standards, Vol 08.01.

<sup>6</sup> Annual Book of ASTM Standards, Vol 05.02.

<sup>7</sup> Annual Book of ASTM Standards, Vol 08.02.

<sup>8</sup> Annual Book of ASTM Standards, Vol 15.06.

<sup>9</sup> Annual Book of ASTM Standards, Vol 14.02.



F 520 Test Method for Environmental Resistance of Aerospace Transparencies<sup>10</sup>

F 521 Test Methods for Bond Integrity of Transparent Laminates<sup>10</sup>

F 1164 Test Method for Evaluation of Transparent Plastics Exposed to Accelerated Weathering Combined with Biaxial Stress<sup>10</sup>

F 1316 Test Method for Measuring the Transmissivity of Transparent Parts<sup>10</sup>

F 1362 Test Method for Shear Strength and Shear Modulus of Aerospace Glazing Interlayer Materials<sup>10</sup>

### 3. Significance and Use

3.1 This guide is intended for use by material suppliers, aircraft transparent enclosure fabricators, airframe manufacturers, government agencies, and others that may become involved in the testing of transparent interlayer materials. These test methods provide data on both individual interlayer materials and material combinations commonly used in the fabrication of aerospace transparent enclosures and provide a means of evaluating the performance of one interlayer material against another.

3.2 Primary characteristics and their long-term stability are critical to the performance of an interlayer material. Basic tests

define the as-manufactured material characteristics of the interlayer material. Ageing procedures provide for representative exposure to environments that may induce changes in material characteristics. Tests performed before and after ageing exposure provide a means of estimating the potential useable life-span of an interlayer material or to compare the durability of one interlayer material with another.

3.3 When employing these test methods for the comparison of interlayer materials after exposure to selected environmental conditions, the user shall be aware that many factors influencing degradation due to weathering vary from one location and exposure period to another location and exposure period. For direct weathering comparisons, the interlayer materials to be compared shall be subjected to the exposure and have the tests performed at the same time. It is emphasized that the test values obtained under these simultaneously applied conditions are for comparative use and their use as design characteristics shall be made with caution.

3.4 The test methods listed include those considered critical to the performance of aircraft transparent enclosures. The user is advised to use the latest revision of any test method.

### 4. Keywords

4.1 aerospace; interlayer materials; laminates; transparent enclosures

<sup>10</sup> Annual Book of ASTM Standards, Vol 15.03.

*ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.*

*This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.*

*This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).*