

Methods of testing

Refractory materials —

Part 3: General and textural
properties —

Section 3.14 Determination of hydration
tendency

Confirmed
February 2011

Committees responsible for this British Standard

The preparation of this British Standard was entrusted to Technical Committee RPI/1, Physical testing of refractory materials, upon which the following bodies were represented:

- British Ceramic Research Ltd.
- British Industrial Ceramic Manufacturers Association
- British Metallurgical Plant Constructors Association
- British Steel Industry
- British Vermiculite Association
- Refractories Association of Great Britain
- Refractories Contractors Association
- Society of Glass Technology

This British Standard, having been prepared under the direction of the Sector Board for Materials and Chemicals, was published under the authority of the Standards Board and comes into effect on 15 January 1996

© BSI 08-1999

First published October 1987
Second edition January 1996

The following BSI references relate to the work on this standard:
Committee reference RPI/1
Draft for comment 93/309165 DC

ISBN 0 580 23736 2

Amendments issued since publication

Amd. No.	Date	Comments

Contents

	Page
Committees responsible	Inside front cover
Foreword	ii
1 Scope	1
2 References	1
3 Designation	1
4 Method for dead-burned magnesia grain, without pressure	1
5 Method for dead-burned magnesia grain, to determine disintegration tendency	2
6 Method for refractory bricks (storage test)	2
7 Method for refractory bricks (accelerated test for destructive service conditions)	3
8 Test report	4
Figure 1 — Arrangement of crucibles and baffles within the boiling flask (method 1902-314/1)	4
List of references	Inside back cover