

Basic environmental testing procedures —

Part 2.1: Tests —

Test Z/BM: Combined dry heat/low air pressure tests

(This Part should be read in conjunction with Part 1.1 General)

UDC [621.37/.39].001.4:620.169.1:[620.193.94 – 976 + 620.193.9 – 984]

This British Standard, having been prepared under the direction of the General Electrotechnical Engineering Standards Committee, was published under the authority of the Executive Board on 30 September 1977

© BSI 09-1999

The following BSI references relate to the work on this standard:
Committee reference GEL/15
Draft for approval 77/21388

ISBN 0 580 09654 6

Amendments issued since publication

Amd. No.	Date of issue	Comments
5031	February 1986	Indicated by a sideline in the margin

Contents

	Page
National foreword	ii
1 Introduction	1
1.1 General	1
1.2 Low air pressure	1
1.3 Temperature	1
1.4 Related documents	1
2 Object	1
3 General description	1
4 Description of test apparatus	1
4.1 Test chamber	1
4.2 Mounting	1
5 Severities	1
5.1 General	1
5.2 Preferred combinations of temperature, air pressure and duration	2
6 Preconditioning	2
7 Initial measurements	2
8 Conditioning	2
8.1 General	2
8.2 Procedure for heat-dissipating specimen without artificial cooling of the specimen and for non-heat-dissipating specimen	2
8.3 Precautions when testing specimens with artificial cooling	3
9 Intermediate measurements	3
10 Recovery	3
11 Final measurements	3
12 Information to be given in the relevant specification	3
Figure 1a — Test profile for non-heat-dissipating specimens	4
Figure 1b — Test profile for heat-dissipating specimens	5