

Methods of testing

Plastics —

Part 3: Mechanical properties —

Method 327A: Determination of tensile strength and elongation at break of polytetrafluoroethylene (PTFE) products

IMPORTANT NOTE. Before reading this method it is essential to read BS 2782-0, Introduction, issued separately.

Confirmed November 2008

Committees responsible for this British Standard

The preparation of this British Standard was entrusted by the Plastics and Rubber Standards Policy Committee (PRM/-) to Technical Committee PRM/31, upon which the following bodies were represented:

- British Fluoropolymers Processors' Group
- British Plastics Federation
- Engineering Equipment and Materials Users' Association
- Ministry of Defence

This British Standard, having been prepared under the direction of the Plastics and Rubber Standards Policy Committee, was published under the authority of the Standards Board and comes into effect on 15 March 1993

© BSI 06-1999

First published December 1982
Second edition March 1993

The following BSI references relate to the work on this standard:
Committee reference PRM/31
Draft for comment 91/48973 DC

ISBN 0 580 21569 5

Amendments issued since publication

Amd. No.	Date	Comments

Contents

	Page
Committees responsible	Inside front cover
Foreword	ii
1 Scope	1
2 References	1
3 Definitions	1
4 Principle	1
5 Apparatus	1
6 Test specimens	2
7 Marking of test specimens	3
8 Conditioning	4
9 Procedure	4
10 Calculation and expression of results	4
11 Test report	4
Figure 1 — Turned dumb-bell test specimens	2
Figure 2 — Punched dumb-bell test specimens (type A)	2
Figure 3 — Test specimen/knife-edged die dimensions for use in the determination of tensile strength and elongation at break (type B)	3
Table 1 — Dimensions of dumb-bell test specimens	3
List of references	Inside back cover