


SPECIFICATION FOR ELECTRICALLY-HEATED CATERING EQUIPMENT

Part 9. Boiling pans

BS 4167 : Part 9 : 1969



BRITISH STANDARDS INSTITUTION

Incorporated by Royal Charter

British Standards House, 2 Park St., London W1Y 4AA

Telegrams: Standards London W1

Telephone: 01-629 9000

THIS BRITISH STANDARD, having been approved by the Electrical Industry Standards Committee, was published under the authority of the Executive Board on 28th November, 1969.

SBN: 580 05863 8

The Institution desires to call attention to the fact that this British Standard does not purport to include all the necessary provisions of a contract.

In order to keep abreast of progress in the industries concerned, British Standards are subject to periodical review. Suggestions for improvements will be recorded and in due course brought to the notice of the committees charged with the revision of the standards to which they refer.

A complete list of British Standards, numbering over 5000, fully indexed and with a note of the contents of each, will be found in the British Standards Yearbook, price 20s. The BS Yearbook may be consulted in many public libraries and similar institutions.

This standard makes reference to the following British Standards:

- BS 729. Zinc coatings on iron and steel articles.
- BS 1224. Electroplated coatings of nickel and chromium.
- BS 1344. Methods of testing vitreous enamel finishes.
- BS 1358. Colours for vitreous enamel finishes.
- BS 1484. 10-gallon tinned steel milk can and lid.
- BS 1872. Electroplated coatings of tin.
- BS 2135. Capacitors for radio interference suppression.
- BS 2660. Colours for building and decorative paints.
- BS 3042. Standard test fingers for checking protection against electric shock and mechanical hazard.
- BS 3535. Safety isolating transformers for industrial and domestic purposes.
- BS 3831. Vitreous enamel finishes for domestic and catering appliances.

BS 4410. The connection of flexible cables and cords to appliances.

BS 6500. Insulated flexible cords.

British Standards are revised, when necessary, by the issue either of amendment slips or of revised editions. It is important that users of British Standards should ascertain that they are in possession of the latest amendments or editions.

The following BSI references relate to the work on this standard:
Committee reference ELE/75. Draft for comment 68/28441

CONTENTS

	Page
Co-operating organizations	6
Foreword	7

SPECIFICATION

1. Scope	7
2. Definitions	8
3. General requirements	9
4. General conditions of tests	9
5. Finish	10
6. Voltage rating	11
7. Marking	11
8. Protection against electric shock	14
9. Input	15
10. Operation under overload conditions	15
11. Temperature rise	16
12. Electrical insulation at operating temperature	18
13. Performance test	19
14. Draining time test	20
15. Protection against spillage	20
16. Insulation resistance and electric strength	20
17. Mechanical strength	21
18. Stability	23
19. Construction	23
20. Thermal controls	25
21. Component parts other than thermal controls	26
22. Supply connections	27
23. Terminals for external conductors	29
24. Provision for earthing	31
25. Screws and connections	32
26. Creepage distances and clearances	34
27. Resistance to rusting	36

APPENDICES

A. General conditions of test	37
B. Indelibility of markings	37

TABLES

1. Temperature rise limits	17
2. Heating-up time	19

	Page
3. Test voltages	21
4. Impact energy and spring compression	22
5. Current rating of flexible cords	28
6. Cable capacity of terminals	30
7. Dimensions of pillar-type terminals	30
8. Torque	33
9. Creepage distances and clearances	35

FIGURES

1. Circuit diagram for leakage current measurement	39
2. Circuit diagram for voltage test	39
3. Impact test apparatus	40
4. Apparatus for testing durability of markings on rating labels	41

CO-OPERATING ORGANIZATIONS

The Electrical Industry Standards Committee, under whose supervision this British Standard was prepared, consists of representatives from the following Government departments and scientific and industrial organizations:

Associated Offices' Technical Committee
 Association of Consulting Engineers
 Association of Mining Electrical and Mechanical Engineers
 *Association of Supervising Electrical Engineers
 *British Electrical and Allied Manufacturers' Association
 British Radio Equipment Manufacturers' Association
 British Railways Board
 Crown Agents for Oversea Governments and Administrations
 *Department of Employment and Productivity
 Electric Cable Makers' Confederation
 Electric Lamp Industry Council
 Electric Light Fittings Association
 Electrical Contractors' Association (Incorporated)
 Electrical Contractors' Association of Scotland
 Electrical Research Association
 *Electricity Council, the Central Electricity Generating Board
 and the Area Boards in England and Wales
 Electronic Engineering Association
 Engineering Equipment Users' Association
 Institution of Electrical Engineers
 Ministry of Defence
 Ministry of Defence, Army Department
 Ministry of Defence, Navy Department
 Ministry of Power
 *Ministry of Public Building and Works
 Ministry of Technology
 Municipal Passenger Transport Association (Incorporated)
 National Inspection Council for Electrical Installation Contracting
 National Physical Laboratory (Ministry of Technology)
 Oil Companies Materials Association
 Post Office
 Public Transport Association (Incorporated)
 South of Scotland Electricity Board

The Government departments and scientific and industrial organizations marked with an asterisk in the above list, together with the following, were directly represented on the committees entrusted with the preparation of this British Standard:

Association of Supervisory Staffs, Executives and Technicians
 Caterers' Association of Great Britain
 Catering Equipment Manufacturers' Association
 Cookery and Food Association
 County Councils Association
 Department of Education and Science
 Department of Health and Social Security
 Electrical Association for Women
 Greater London Council
 Hospital Caterers' Association
 Industrial Catering Association
 Institute of Hospital Engineers
 Institutional Management Association
 National Association of Restaurant Engineers
 Tea Bureau

BRITISH STANDARD SPECIFICATION FOR ELECTRICALLY-HEATED CATERING EQUIPMENT

Part 9. Boiling pans

FOREWORD

This British Standard has been prepared under the authority of the Electrical Industry Standards Committee.

Users of this standard should satisfy themselves that the installation of equipment conforming to the standard meets the requirements of any byelaws issued by the Ministry of Housing and Local Government and the Department of Health for Scotland. Pressure generating appliances shall additionally comply with the requirements of the Factory Act, 1961, where applicable.

This standard covers appliances for a.c. and d.c., but as appliances for d.c. are necessarily more complex than for a.c. organizations inviting tenders to this specification should make it clear in their initial enquiry whether the equipment is for use on a.c. or d.c.

The equipment described in this standard is not necessarily suitable for use in ships or road vehicles.

NOTE. The values of force are expressed in this standard in terms of the newton (symbol N). This is the unit for force in the international (SI) system. The newton is that force which, when acting on a body of mass one kilogramme, gives it an acceleration of one metre per second squared.

SPECIFICATION

1. SCOPE

This Part of BS 4167 specifies the general requirements and tests for the following appliances:

Single purpose, dual purpose and jacketed pans for cooking vegetables and making milk puddings or foods of similar consistency.

Specific constructional requirements for pressure jacketed appliances are also laid down.

The standard applies to equipment for operation on either single-phase or polyphase supplies where the voltage to earth does not exceed 250 V a.c. or d.c.

It establishes a satisfactory standard of safety and performance when the equipment is used under normal conditions.

2. DEFINITIONS

For the purposes of this Part of this British Standard the following definitions apply:

NOTE. The terms 'voltage' and 'current' imply the r.m.s. values, unless otherwise specified.

(1) *Rated voltage*. The voltage (for a 3-phase appliance, the line to line voltage) assigned to the equipment and marked on it.

(2) *Rated current or input*. The current or input assigned to the appliance by the maker and marked on it.

(3) *Rated voltage range*. The voltage limits assigned to the appliance by the maker and marked on it.

(4) *Maximum rated input*. The maximum rated input, when an input range is marked on the appliance, is the highest input of the range. When the mean input is marked, the maximum rated input is given by the formula:

$$\text{Mean rated input} \times \left[\frac{\text{maximum rated voltage}}{\text{mean rated voltage}} \right]^2$$

(5) *Extra low voltage*. Voltage normally not exceeding 50 V a.c. with a maximum voltage to earth of 30 V, or 50 V d.c.

(6) *Non-detachable flexible cord or cable*. A flexible cord, or cable, so connected to the equipment that it can only be removed with the use of tools.

(7) *Thermostat*. A preset or adjustable device which, in normal use, keeps the temperature of the appliance, or of parts of it, between certain limits by automatically opening and closing the circuit or by varying the current.

(8) *Thermal cut-out*. A safety device limiting the temperature of an appliance under abnormal conditions by automatically opening the circuit or by reducing the current. The device may be reset by hand or be self-resetting and is so constructed that there is no provision for adjustment of the setting by the user.

(9) *Energy regulator*. A device which provides a variable rate of energy transmitted to an electrically-heated appliance by changing the ratio of the ON and OFF periods in a progressive manner between the minimum and maximum setting.

(10) *Float switch*. A liquid level float operated electrical switch.

(11) *Transportable appliance*. An appliance which can readily be removed from one place to another.

(12) *Stationary appliance*. An appliance intended to be fixed to its supporting surface or used in one place.

(13) *Capacity*. The amount of liquid capable of being drawn from the draw-off taps when the appliance is filled to a level of 75 mm below overflow.

(14) *Indicated level*. The maximum level to which an appliance may be filled for correct operation.

(15) *Safe working pressure.* The operating pressure assigned to the appliance by the maker.

(16) *Test pressure.* Twice the safe working pressure.

3. GENERAL REQUIREMENTS

3.1 The appliance shall be so designed and constructed that in normal use it is reliable and will operate without danger to the user or surroundings.

3.2 Where the boiling pan is part of an appliance incorporating more than one heating unit the whole appliance shall comply with the relevant Parts of this standard.

3.3 TEST. Compliance shall be checked by carrying out the relevant tests specified.

3.4 Instructions for connecting, maintaining and operating the equipment shall be available for each appliance.

4. GENERAL CONDITIONS OF TESTS

4.1 The tests are type tests and are made on a single sample as delivered which shall pass all the relevant tests and specific requirements.

4.2 Unless otherwise specified, the tests shall be carried out in the order of the clauses.

4.3 The tests shall be carried out at an ambient temperature of $20 \pm 5^{\circ}\text{C}$, unless otherwise specified. Details of the test room and of the preparation of the appliance before testing are given in Appendix A.

4.4 The temperature of the liquid shall be measured by means of a mercury-in-glass thermometer. Surface, floor and wall temperature shall be measured by fine wire thermocouples which are positioned so that they have the minimum effect on the temperature of the part under test.

4.5 Appliances designed for both a.c. and d.c. operation shall be tested using the system of supply which will prove most exacting to the appliance.

When testing with d.c. the possible influence of polarity on the operation of switching devices shall be taken into account.

4.6 When it is specified that the appliance shall be connected to a test voltage so that the input is greater than the rated input, the test voltage as defined in the relevant clauses applies only to heating elements without appreciable positive temperature coefficient of resistance (in general the temperature coefficient is deemed to be appreciable if, at rated voltage, the input of the

equipment in the cold condition differs by more than 25 % from the input at operating temperature).

For the other heating elements the test voltage shall be determined in the following manner:

The rated voltage shall be applied until the heating element reaches its operating temperature. The voltage shall then be rapidly increased to the value necessary to give the required test loading, and the tests are made as specified, this value of the voltage being maintained throughout.

4.7 Where it is stipulated that equipment shall be operated at extra low voltage from a particular transformer supplied with it the test shall be made with this transformer.

5. FINISH

5.1 Finishes shall not be subject to excessive deterioration in normal use and shall adequately protect against corrosion at the temperature and in the humidity conditions to which they will be subjected in normal use.

Surfaces in contact with comestible liquid being heated shall be of such a material or so protected as to avoid contamination of the contents.

The finish of parts which are liable to come in contact with liquid shall be capable of being kept hygienically clean.

5.1.1 TEST. Compliance shall be checked by visual examination for signs of pin holes, blistering, peeling roughness or exposed untreated areas and for paint finishes by the tests of 5.2 and 5.3.

5.2 The appliance shall be filled with water to the indicated level and operated at its rated input, with all controls used in normal operation set at maximum, for a continuous period of 5 h topping up with water as required. Afterwards there shall be no appreciable change of colour on any part of the appliance and the finish shall not become tacky or show other signs of deterioration.

After the initial burning-off period, there shall be no detectable odour from the paint when the appliance is operated normally.

5.3 Paint films shall be subjected to a scratch test with a steel ball 1 mm in diameter. The ball shall be mounted in an apparatus in such a way that it shall be pressed against the surface with a force of 16 N (1.63 kgf) and it shall be caused to move once over the surface for a distance of approximately 65 mm at a speed of 30 mm/s to 40 mm/s. The design of the apparatus shall be such that the ball shall be applied to the surface gently, e.g. by allowing the ball carrier to run down a ramp.

The ball shall not penetrate completely through the film and if flakes are lifted from the edge of the scratch the major dimension of every flake shall be less than 1 mm. For electrically conducting paints penetration shall be

determined by visual observation. For other paints penetration shall be shown by an electrical contact indicator, the voltage applied between the ball and the metal surface to which the paint shall be applied being not greater than 6 V.

The ball shall be cleaned after each test and inspected frequently to ensure that it has not worn significantly.

5.4 The colour of paint and similar finishes on exterior surfaces shall be in accordance with BS 1358* or BS 2660†.

5.4.1 TEST. Compliance shall be checked by inspection.

5.5 Finishes other than painted finishes shall comply with one of the following British Standards as appropriate:

BS 729, 'Zinc coatings on iron and steel articles'.

BS 1224, 'Electroplated coatings of nickel and chromium', (Service condition no. 2).

BS 1344, 'Methods of testing vitreous enamel finishes'.

BS 1484, '10-gallon tinned steel milk can and lid'.

BS 1872, 'Electroplated coating of tin', (classification 12S or 12C).

BS 3831, 'Vitreous enamel finishes for domestic and catering appliances'.

5.5.1 TEST. Compliance shall be checked as detailed in the appropriate standard.

6. VOLTAGE RATING

6.1 The highest rated voltage shall be 250 V for single-phase a.c. or d.c. or 440 V for 3 phase-4 wire a.c. No individual component other than the contact assembly of switching devices shall have a rated voltage exceeding 250 V.

6.1.1 TEST. Compliance shall be checked by inspection of the marking.

7. MARKING

7.1 The equipment shall be marked with the following particulars:

- (1) The number of this British Standard, i.e. BS 4167 : Part 9.
- (2) Rated voltage or voltage range in volts.
- (3) Nature of supply, if necessary for the correct operation of the appliance (single-phase a.c. or 3 phase-4 wire a.c. or d.c.).
- (4) Rated input in watts or kilowatts.
- (5) Safe working pressure.
- (6) Maker's name or trade mark.
- (7) Maker's model or serial number.

* BS 1358, 'Colour for vitreous enamel finishes'.

† BS 2660, 'Colours for building and decorative paints'.

7.2 Heating elements shall be marked with the rated voltage in volts, and the rated input in watts or kilowatts.

7.3 Any cover giving access to live parts at a voltage exceeding 250 V shall be marked with the word **WARNING** and the appropriate voltage. This marking shall not be incorporated with the markings prescribed in 7.1.

7.4 If the appliance can be set to different rated voltages, the voltage to which the appliance is set shall be easily and clearly discernible.

It shall be sufficient if the rated voltage to which the appliance is set is determined from instructions given on the appliance.

7.5 For an appliance where the difference between the limits of the rated voltage range is more than 10 % of the mean value of the range, the upper and lower limits of the rated input shall be marked on the equipment so that the relation between input and voltage appears distinctly.

If the difference between the limits of the rated voltage range is not more than 10 % of the mean value of the range, the marking of rated input shall relate to the mean of the voltage range (alternatively, the upper and lower limits of the rated input may be marked).

If the input of the appliance in the cold condition differs by more than 25 % from the input at operating temperature, the input in cold condition shall be marked in addition and shall be placed between brackets.

7.6 Appliances shall have the maximum level to which they may be filled, i.e. the 'indicated level', marked in such a position as to be easily visible to the operator when being filled by hand. The indicated level shall be at least 75 mm below the overflow.

7.7 For water-jacketed appliances the maximum and minimum water level in the jacket shall be indicated.

7.8 If abbreviations are employed the following letters shall be used:

- | | |
|------------------------|---------|
| (1) Volts | V |
| (2) Amperes | A |
| (3) Watts or kilowatts | W or kW |
| (4) Pressure | P |

7.9 The symbols for the nature of supply shall be as follows:

- | | |
|-------------------------|---------------|
| (1) Alternating current | ~ or a.c. |
| (2) A.C. 3 phase-4 wire | 3N~ |
| (3) Direct current | ----- or d.c. |

7.10 Regulating devices shall have indications for their different positions by figures, letters or other visual means.

7.11 Adjustable thermostats, energy regulator or the like shall be provided with an indication of the direction of adjustment to increase or decrease the temperature.

NOTE. An indication of + and - is deemed to be sufficient.

7.12 Switches shall be marked or placed so as to indicate their function unless this is obvious. There shall be a clear indication of the OFF position on manually operated switches unless this also is obvious.

7.13 TEST. Compliance with the requirements of 7.1 to 7.12 shall be checked by inspection.

7.14 Marking of the appliance shall be durable, resistant to heat and easily legible, and shall be placed on the main part of the appliance so that it is clearly discernible from the outside, if necessary after the removal of a cover. This cover shall be removable without the use of tools, except in the case of stationary appliances, and then only if the cover has also to be removed for servicing. Marking shall not be placed on any removable part which can be replaced in such a way that the marking is misleading.

7.15 Marking of heating elements shall be easily legible and shall be placed on a main part of the element in such a way that it is clearly discernible when the element is removed from the appliance. The marking of the element shall be durable and resistant to heat.

7.16 TEST. Compliance with requirements of 7.14 and 7.15 shall be checked at the conclusion of all the tests in this specification by inspection, and by the tests described in Appendix B.

NOTE. The mark BS 4167 : Part 9 on or in relation to the product is a claim by the manufacturer that it complies with the requirements of the standard.

The British Standards Institution is the owner of a registered certification trade mark. It is usually associated with the words 'approved to British Standard' as shown below, the number of the relevant British Standard being added. This mark may be used only by those licensed under the certification mark scheme operated by BSI. The presence of this mark on or in relation to a product is an assurance that the goods have been produced under a system of supervision, control and testing, operated during manufacture and including periodical inspection of the manufacturer's works in accordance with the certification mark scheme of BSI designed to ensure compliance with a British Standard.

Further particulars of the terms of licence may be obtained from the Certification Marks Section, British Standards Institution, 2 Park Street, London W1Y 4AA.

