

Recommendations for

The presentation of plastics design data —

Part 2: Electrical properties —

Section 2.3 Volume resistivity

IMPORTANT NOTE. Before reading this Section it is essential to read the General Introduction to this series of Recommendations, issued separately.

UDC 001.8:678.5/.8:537.311.3

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW



Document Sharing Hub

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, pages 1 to 7 and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.

Amendments issued since publication

Amd. No.	Date	Comments

© BSI 11-1999

The following BSI references relate to work on this section

Committee reference PLC/36/4

Draft for comment 72/52522

ISBN 0 580 08923 9

Contents

	Page
0 Introduction	1
1 Definitions	1
2 Procedure	1
3 Form of presentation	2
Appendix A Information to accompany each of Figure 1, Figure 2 and Figure 3, as examples of layout of data sheets	4
Figure 1 — Layout of data sheet for volume resistivity as a function of time of electrification, at a number of temperatures	5
Figure 2 — Layout of data sheet for volume resistivity as a function of temperature	6
Figure 3 — Layout of data sheet for volume resistivity as a function of temperature and time of electrification	7

